

1. Main Program.

Here is a relatively robust command line utility that shows how the iad and ad subroutines might be called. It suffers because it is written in CWEB and I used the macro expansion feature instead of creating separate functions. Oh well.

I create an empty file `iad_main.h` to simplify the Makefile

```
<iad_main.h 1> ≡
```

2. All the actual output for this web file goes into `iad_main.c`

```
<iad_main.c 2> ≡
```

```
<Include files for main 3><print version function 17><print usage function 18><stringdup together
  function 24><seconds elapsed function 25><print error legend function 23><print dot
  function 27><calculate coefficients function 19><parse string into array function 26><print
  results header function 21><Print results function 22>int main(int argc, char **argv) {
  <Declare variables for main 4><Handle options 5>Initialize_Measure(&m);
  <Command-line changes to m 15>Initialize_Result(m, &r); <Command-line changes to r 10>
if (cl_forward_calc ≠ UNINITIALIZED) {
  <Calculate and Print the Forward Calculation 6>return 0;
}
if (process_command_line) {
  <Count command-line measurements 16><Calculate and write optical properties 8>return 0;
}
<prepare file for reading 7>if (Read_Header(stdin, &m, &params) ≡ 0) { start_time = clock();
  <Command-line changes to m 15>
while (Read_Data_Line(stdin, &m, params) ≡ 0) {
  <Calculate and write optical properties 8>first_line = 0;
}
}
if (cl_verbosity > 0) fprintf(stderr, "\n\n");
if (any_error ∧ cl_verbosity > 1) print_error_legend();
return 0; }
```

3. The first two defines are to stop Visual C++ from silly complaints

```

< Include files for main 3 > ≡
#define _CRT_SECURE_NO_WARNINGS
#define _CRT_NONSTDC_NO_WARNINGS
#define NO_SLIDES 0
#define ONE_SLIDE_ON_TOP 1
#define TWO_IDENTICAL_SLIDES 2
#define ONE_SLIDE_ON_BOTTOM 3
#define ONE_SLIDE_NEAR_SPHERE 4
#define ONE_SLIDE_NOT_NEAR_SPHERE 5
#define MR_IS_ONLY_RD 1
#define MT_IS_ONLY_TD 2
#define NO_UNSCATTERED_LIGHT 3
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <time.h>
#include <math.h>
#include <ctype.h>
#include "ad_globl.h"
#include "ad_prime.h"
#include "iad_type.h"
#include "iad_pub.h"
#include "iad_io.h"
#include "iad_calc.h"
#include "iad_util.h"
#include "mygetopt.h"
#include "version.h"
#include "mc_lost.h"
#include "ad_frsl.h"
    extern char *optarg;
    extern int optind;

```

This code is used in section 2.

4. \langle Declare variables for *main* 4 $\rangle \equiv$

```

struct measure_type m;
struct invert_type r;
double m_r, m_t;
char *g_out_name =  $\Lambda$ ;
char c;
int first_line = 1;
long n_photons = 100000;
int MC_iterations = 19;
int any_error = 0;
int process_command_line = 0;
int params = 0;
int cl_quadrature_points = UNINITIALIZED;
int cl_verbosity = 2;
double cl_forward_calc = UNINITIALIZED;
double cl_default_a = UNINITIALIZED;
double cl_default_g = UNINITIALIZED;
double cl_default_b = UNINITIALIZED;
double cl_default_mua = UNINITIALIZED;
double cl_default_mus = UNINITIALIZED;
double cl_tolerance = UNINITIALIZED;
double cl_slide_OD = UNINITIALIZED;
double cl_cos_angle = UNINITIALIZED;
double cl_beam_d = UNINITIALIZED;
double cl_sample_d = UNINITIALIZED;
double cl_sample_n = UNINITIALIZED;
double cl_slide_d = UNINITIALIZED;
double cl_slide_n = UNINITIALIZED;
double cl_slides = UNINITIALIZED;
double cl_default_fr = UNINITIALIZED;
double cl_rstd_t = UNINITIALIZED;
double cl_rstd_r = UNINITIALIZED;
double cl_rc_fraction = UNINITIALIZED;
double cl_tc_fraction = UNINITIALIZED;
double cl_mus0 = UNINITIALIZED;
double cl_musp0 = UNINITIALIZED;
double cl_mus0_pwr = UNINITIALIZED;
double cl_mus0_lambda = UNINITIALIZED;
double cl_UR1 = UNINITIALIZED;
double cl_UT1 = UNINITIALIZED;
double cl_Tc = UNINITIALIZED;
double cl_method = UNINITIALIZED;
double cl_num_spheres = UNINITIALIZED;
double cl_sphere_one[5] = {UNINITIALIZED, UNINITIALIZED, UNINITIALIZED, UNINITIALIZED,
    UNINITIALIZED};
double cl_sphere_two[5] = {UNINITIALIZED, UNINITIALIZED, UNINITIALIZED, UNINITIALIZED,
    UNINITIALIZED};
clock_t start_time = clock();

```

This code is used in section 2.

5. use the *mygetopt* to process options. We only handle help at the moment

```

(Handle options 5) ≡
while ((c = my_getopt(argc, argv,
    "?1:2:a:A:b:B:c:C:d:D:e:E:f:F:g:G:hi:n:N:M:o:p:q:r:R:S:t:T:u:vV:x:Xz")) ≠ EOF) {
    int n;
    char cc;
    switch (c) {
    case '1': parse_string_into_array(optarg, cl_sphere_one, 5);
        break;
    case '2': parse_string_into_array(optarg, cl_sphere_two, 5);
        break;
    case 'a': cl_default_a = strtod(optarg, Λ);
        break;
    case 'A': cl_default_mua = strtod(optarg, Λ);
        break;
    case 'b': cl_default_b = strtod(optarg, Λ);
        break;
    case 'B': cl_beam_d = strtod(optarg, Λ);
        break;
    case 'c': cl_rc_fraction = strtod(optarg, Λ);
        if (cl_rc_fraction < 0.0 ∨ cl_rc_fraction > 1.0) {
            fprintf(stderr, "required: 0 ≤ fraction of unscattered refl. in M_R ≤ 1\n");
            exit(0);
        }
        break;
    case 'C': cl_tc_fraction = strtod(optarg, Λ);
        if (cl_tc_fraction < 0.0 ∨ cl_tc_fraction > 1.0) {
            fprintf(stderr, "required: 0 ≤ fraction of unscattered trans. in M_T ≤ 1\n");
            exit(0);
        }
        break;
    case 'd': cl_sample_d = strtod(optarg, Λ);
        break;
    case 'D': cl_slide_d = strtod(optarg, Λ);
        break;
    case 'e': cl_tolerance = strtod(optarg, Λ);
        break;
    case 'E': cl_slide_OD = strtod(optarg, Λ);
        break;
    case 'f': cl_default_fr = strtod(optarg, Λ);
        break;
    case 'F': /* initial digit means this is mus is constant */
        if (isdigit(optarg[0])) {
            cl_default_mus = strtod(optarg, Λ);
            break;
        } /* should be a string like 'R 1000 1.2 -1.8' */
        n = sscanf(optarg, "%c%lf%lf%lf", &cc, &cl_mus0_lambda, &cl_mus0, &cl_mus0_pwr);
        if (n ≠ 4) {
            fprintf(stderr, "Screwy argument for -F option\n");
            exit(1);
        }
        if (cc ≡ 'R' ∨ cc ≡ 'r') {

```

```

    cl_musp0 = cl_mus0;
    cl_mus0 = UNINITIALIZED;
}
break;
case 'g': cl_default_g = strtod(optarg, &);
    break;
case 'G':
    if (optarg[0] == '0') cl_slides = NO_SLIDES;
    else if (optarg[0] == '2') cl_slides = TWO_IDENTICAL_SLIDES;
    else if (optarg[0] == 't' ∨ optarg[0] == 'T') cl_slides = ONE_SLIDE_ON_TOP;
    else if (optarg[0] == 'b' ∨ optarg[0] == 'B') cl_slides = ONE_SLIDE_ON_BOTTOM;
    else if (optarg[0] == 'n' ∨ optarg[0] == 'N') cl_slides = ONE_SLIDE_NEAR_SPHERE;
    else if (optarg[0] == 'f' ∨ optarg[0] == 'F') cl_slides = ONE_SLIDE_NOT_NEAR_SPHERE;
    else {
        fprintf(stderr, "Argument for -G option must be\n");
        fprintf(stderr, "      't' --- light always hits top slide first\n");
        fprintf(stderr, "      'b' --- light always hits bottom slide first\n");
        fprintf(stderr, "      'n' --- slide always closest to sphere\n");
        fprintf(stderr, "      'f' --- slide always farthest from sphere\n");
        exit(1);
    }
    break;
case 'i': cl_cos_angle = strtod(optarg, &);
    if (cl_cos_angle < 0 ∨ cl_cos_angle > 90)
        fprintf(stderr, "Incident angle must be between 0 and 90 degrees\n");
    else cl_cos_angle = cos(cl_cos_angle * 3.1415926535/180.0);
    break;
case 'M': MC_iterations = (int) strtod(optarg, &);
    break;
case 'n': cl_sample_n = strtod(optarg, &);
    break;
case 'N': cl_slide_n = strtod(optarg, &);
    break;
case 'o': g_out_name = strdup(optarg);
    break;
case 'p': n_photons = (int) strtod(optarg, &);
    break;
case 'q': cl_quadrature_points = (int) strtod(optarg, &);
    if (cl_quadrature_points % 4 != 0) {
        fprintf(stderr, "Number of quadrature points must be a multiple of 4\n");
        exit(1);
    }
    if ((cl_cos_angle != UNINITIALIZED) ∧ (cl_quadrature_points % 12 != 0)) {
        fprintf(stderr, "Quadrature must be 12, 24, 36, ... for oblique incidence\n");
        exit(1);
    }
    break;
case 'r': cl_UR1 = strtod(optarg, &);
    process_command_line = 1;
    break;
case 'R': cl_rstd_r = strtod(optarg, &);
    break;

```

```

    case 'S': cl_num_spheres = (int) strtod(optarg, &);
        break;
    case 't': cl_UT1 = strtod(optarg, &);
        process_command_line = 1;
        break;
    case 'T': cl_rstd_t = strtod(optarg, &);
        break;
    case 'u': cl_Tc = strtod(optarg, &);
        process_command_line = 1;
        break;
    case 'v': print_version();
        break;
    case 'V': cl_verbosity = strtod(optarg, &);
        break;
    case 'x': Set_Debugging((int) strtod(optarg, &));
        break;
    case 'X': cl_method = COMPARISON;
        break;
    case 'z': cl_forward_calc = 1;
        process_command_line = 1;
        break;
    default: fprintf(stderr, "unknown_option_%c'\n", c); /* fall through */
    case 'h': case '?': print_usage();
        break;
}
}
argc -= optind;
argv += optind;

```

This code is used in section 2.

```

6.  ⟨ Calculate and Print the Forward Calculation 6 ⟩ ≡
{
  double mu_sp, mu_a;
  if (cl_default_a ≡ UNINITIALIZED) {
    if (cl_default_mus ≡ UNINITIALIZED) r.a = 0;
    else if (cl_default_mua ≡ UNINITIALIZED) r.a = 1;
    else r.a = cl_default_mus / (cl_default_mua + cl_default_mus);
  }
  else r.a = cl_default_a;
  if (cl_default_b ≡ UNINITIALIZED) {
    if (cl_sample_d ≡ UNINITIALIZED) r.b = HUGE_VAL;
    else if (r.a ≡ 0) {
      if (cl_default_mua ≡ UNINITIALIZED) r.b = HUGE_VAL;
      else r.b = cl_default_mua * cl_sample_d;
    }
    else {
      if (cl_default_mus ≡ UNINITIALIZED) r.b = HUGE_VAL;
      else r.b = cl_default_mus / r.a * cl_sample_d;
    }
  }
  else r.b = cl_default_b;
  if (cl_default_g ≡ UNINITIALIZED) r.g = 0;
  else r.g = cl_default_g;
  r.slab.a = r.a;
  r.slab.b = r.b;
  r.slab.g = r.g;
  Calculate_MR_MT(m, r, MC_iterations, &m_r, &m_t);
  Calculate_Mua_Musp(m, r, &mu_sp, &mu_a);
  if (cl_verbosity > 0) {
    Write_Header(m, r, -1);
    print_results_header(stdout);
  }
  print_optical_property_result(stdout, m, r, m_r, m_t, mu_a, mu_sp, 0, 0);
}

```

This code is used in section 2.

7. Make sure that the file is not named '-' and warn about too many files

(prepare file for reading 7) \equiv

```

if (argc > 1) {
    fprintf(stderr, "Only a single file can be processed at a time\n");
    fprintf(stderr, "try 'apply_iad_file1_file2..._fileN'\n");
    exit(1);
}
if (argc  $\equiv$  1  $\wedge$  strcmp(argv[0], "-")  $\neq$  0) { /* filename exists and != "-" */
    int n;
    char *base_name, *rt_name;
    base_name = strdup(argv[0]);
    n = (int)(strlen(base_name) - strlen(".rxt"));
    if (n > 0  $\wedge$  strstr(base_name + n, ".rxt")  $\neq$   $\Lambda$ ) base_name[n] = '\0';
    rt_name = strdup_together(base_name, ".rxt");
    if (freopen(argv[0], "r", stdin)  $\equiv$   $\Lambda$   $\wedge$  freopen(rt_name, "r", stdin)  $\equiv$   $\Lambda$ ) {
        fprintf(stderr, "Could not open either '%s' or '%s'\n", argv[0], rt_name);
        exit(1);
    }
    if (g_out_name  $\equiv$   $\Lambda$ ) g_out_name = strdup_together(base_name, ".txt");
    free(rt_name);
    free(base_name);
}
if (g_out_name  $\neq$   $\Lambda$ ) {
    if (freopen(g_out_name, "w", stdout)  $\equiv$   $\Lambda$ ) {
        fprintf(stderr, "Could not open file '%s' for output\n", g_out_name);
        exit(1);
    }
}
}

```

This code is used in section 2.

8. Need to explicitly reset *r.search* each time through the loop, because it will get altered by the calculation process. We want to be able to let different lines have different constraints. In particular consider the file *newton.tst*. In that file the first two rows contain three real measurements and the last two have the collimated transmission explicitly set to zero — in other words there are really only two measurements.

```

< Calculate and write optical properties 8 > ≡
{ < Local Variables for Calculation 9 >
  Initialize_Result(m, &r);
  < Command-line changes to r 10 >
  if (cl_method ≡ COMPARISON ∧ m.d_sphere_r ≠ 0 ∧ m.as_r ≡ 0) {
    fprintf(stderr, "A dual-beam measurement is specified, but no port sizes.\n");
    fprintf(stderr, "You might forsake the -X option and use zero spheres (which gives\n");
    fprintf(stderr, "the same result except lost light is not taken into account).\n");
    fprintf(stderr, "Alternatively, bite the bullet and enter your sphere parameters,\n");
    fprintf(stderr, "with the knowledge that only the beam diameter and sample port\n");
    fprintf(stderr, "diameter are worth obsessing over.\n");
    exit(0);
  }
  < Write Header 11 >
  Inverse_RT(m, &r);
  calculate_coefficients(m, r, &LR, &LT, &mu_sp, &mu_a);
  < Improve result using Monte Carlo 12 >
  print_optical_property_result(stdout, m, r, LR, LT, mu_a, mu_sp, mc_iter, rt_total);
  if (Debug(DEBUG_LOST_LIGHT)) fprintf(stderr, "\n");
  else print_dot (start_time, r . error , mc_total, rt_total, 99, cl_verbosity, &any_error ); }

```

This code is used in section 2.

9.

```

< Local Variables for Calculation 9 > ≡
static int rt_total = 0;
static int mc_total = 0;
int mc_iter = 0;
double ur1 = 0;
double ut1 = 0;
double uru = 0;
double utu = 0;
double mu_a = 0;
double mu_sp = 0;
double LR = 0;
double LT = 0;
rt_total++;

```

This code is used in section 8.

```

10.  { Command-line changes to r 10 } ≡
    if (cl_quadrature_points ≠ UNINITIALIZED) r.method.quad_pts = cl_quadrature_points;
    else r.method.quad_pts = 8;
    if (cl_default_a ≠ UNINITIALIZED) r.default_a = cl_default_a;
    if (cl_default_mua ≠ UNINITIALIZED) {
        r.default_mua = cl_default_mua;
        if (cl_sample_d ≠ UNINITIALIZED) r.default_ba = cl_default_mua * cl_sample_d;
        else r.default_ba = cl_default_mua * m.slab_thickness;
    }
    if (cl_default_b ≠ UNINITIALIZED) r.default_b = cl_default_b;
    if (cl_default_g ≠ UNINITIALIZED) r.default_g = cl_default_g;
    if (cl_tolerance ≠ UNINITIALIZED) {
        r.tolerance = cl_tolerance;
        r.MC_tolerance = cl_tolerance;
    }
    if (cl_musp0 ≠ UNINITIALIZED)
        cl_mus0 = (r.default_g ≠ UNINITIALIZED) ? cl_musp0 / (1 - r.default_g) : cl_musp0;
    if (cl_mus0 ≠ UNINITIALIZED ∧ m.lambda ≠ 0)
        cl_default_mus = cl_mus0 * pow(m.lambda / cl_mus0_lambda, cl_mus0_pwr);
    if (cl_default_mus ≠ UNINITIALIZED) {
        r.default_mus = cl_default_mus;
        if (cl_sample_d ≠ UNINITIALIZED) r.default_bs = cl_default_mus * cl_sample_d;
        else r.default_bs = cl_default_mus * m.slab_thickness;
    }

```

This code is used in sections 2 and 8.

```

11.  { Write Header 11 } ≡
    if (rt_total ≡ 1 ∧ cl_verbosity > 0) {
        Write_Header(m, r, params);
        if (MC_iterations > 0) {
            if (n_photons ≥ 0)
                fprintf(stdout, "#_Photons_used_to_estimate_lost_light_=%ld\n", n_photons);
            else fprintf(stdout, "#_Time_used_to_estimate_lost_light_=%ldms\n", -n_photons);
        }
        else fprintf(stdout, "#_Photons_used_to_estimate_lost_light_=%ld0\n");
        fprintf(stdout, "#\n");
        print_results_header(stdout);
    }

```

This code is used in section 8.

12. Use Monte Carlo to figure out how much light leaks out. We use the sphere corrected values as the starting values and only do try Monte Carlo when spheres are used, the albedo unknown or non-zero, and there has been no error. The sphere parameters must be known because otherwise the beam size and the port size are unknown.

⟨Improve result using Monte Carlo 12⟩ ≡

```

if ( $m.as\_r \neq 0 \wedge r.default\_a \neq 0 \wedge m.num\_spheres > 0$ ) { double  $mu\_sp\_last = mu\_sp$ ;
double  $mu\_a\_last = mu\_a$ ;
if (Debug(DEBUG_LOST_LIGHT)) {
    print_results_header(stderr);
    print_optical_property_result(stderr,  $m, r, LR, LT, mu\_a, mu\_sp, mc\_iter, rt\_total$ );
}
while ( $mc\_iter < MC\_iterations$ ) { MC_Lost( $m, r, -1000, \&ur1, \&ut1, \&uru, \&utu, \&m.ur1\_lost,$ 
     $\&m.ut1\_lost, \&m.uru\_lost, \&m.utu\_lost$ );
 $mc\_total++$ ;
 $mc\_iter++$ ;
Inverse_RT( $m, \&r$ );
calculate_coefficients( $m, r, \&LR, \&LT, \&mu\_sp, \&mu\_a$ );
if ( $(fabs(mu\_a\_last - mu\_a) / (mu\_a + 0.0001) < r.MC\_tolerance \wedge fabs(mu\_sp\_last - mu\_sp) / (mu\_sp + 0.0001) <$ 
     $r.MC\_tolerance)$  break;
 $mu\_a\_last = mu\_a$ ;
 $mu\_sp\_last = mu\_sp$ ;
if (Debug(DEBUG_LOST_LIGHT))
    print_optical_property_result(stderr,  $m, r, LR, LT, mu\_a, mu\_sp, mc\_iter, rt\_total$ );
else print_dot (start_time,  $r . error, mc\_total, rt\_total, mc\_iter, cl\_verbosity, \&any\_error$  ) ; if (  $r .$ 
     $error \neq IAD\_NO\_ERROR$  ) break; } }
```

This code is used in section 8.

```

struct AD_slab_type s;
double ur1, ut1, uru, utu;
double adur1, adut1, aduru, adutu;

s.a = 0.0;
s.b = 0.5;
s.g = 0.0;
s.phase_function = HENYEY_GREENSTEIN;
s.n_slab = 1.0;
s.n_top_slide = 1.0;
s.n_bottom_slide = 1.0;
s.b_top_slide = 0;
s.b_bottom_slide = 0;
MC_RT(s,&ur1,&ut1,&uru,&utu);
RT(32,&s,&adur1,&adut1,&aduru,&adutu);
fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
s.n_top_slide);
fprintf(stderr, "UUUR1UUUUUUUUUUUUUT1UUUUUUUUUUUUURUUUUUUUUUUUUUUTU\n");
fprintf(stderr, "UUADUUUUCUUUUUUUUUUADUUUUCUUUUUUUUUUADUUUUCUUUUUUUUUUADUUUUCUU\n");
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4fUUU", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4f\n", aduru, uru, adutu, utu);
s.b = 100.0;
s.n_slab = 1.5;
fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
s.n_top_slide);
MC_RT(s,&ur1,&ut1,&uru,&utu);
RT(32,&s,&adur1,&adut1,&aduru,&adutu);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4fUUU", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4f\n", aduru, uru, adutu, utu);
s.n_slab = 2.0;
fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
s.n_top_slide);
MC_RT(s,&ur1,&ut1,&uru,&utu);
RT(32,&s,&adur1,&adut1,&aduru,&adutu);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4fUUU", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4f\n", aduru, uru, adutu, utu);
s.n_slab = 1.5;
s.n_top_slide = 1.5;
s.n_bottom_slide = 1.5;
fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
s.n_top_slide);
MC_RT(s,&ur1,&ut1,&uru,&utu);
RT(32,&s,&adur1,&adut1,&aduru,&adutu);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4fUUU", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f_%5.4fUUU%5.4f_%5.4f\n", aduru, uru, adutu, utu);
s.n_slab = 1.3;
s.n_top_slide = 1.5;
s.n_bottom_slide = 1.5;
fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
s.n_top_slide);
MC_RT(s,&ur1,&ut1,&uru,&utu);

```

```

RT(32, &s, &adur1, &adut1, &aduru, &adutu);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□□□", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□\n", aduru, uru, adutu, utu);
s.a = 0.5;
s.b = 1.0;
s.n_slab = 1.0;
s.n_top_slide = 1.0;
s.n_bottom_slide = 1.0;
fprintf(stderr, "\na=%5.4f□b=%5.4f□g=%5.4f□n=%5.4f□ns=%5.4f□\n", s.a, s.b, s.g, s.n_slab,
    s.n_top_slide);
MC_RT(s, &ur1, &ut1, &uru, &utu);
RT(32, &s, &adur1, &adut1, &aduru, &adutu);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□□□", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□\n", aduru, uru, adutu, utu);
s.g = 0.5;
fprintf(stderr, "\na=%5.4f□b=%5.4f□g=%5.4f□n=%5.4f□ns=%5.4f□\n", s.a, s.b, s.g, s.n_slab,
    s.n_top_slide);
MC_RT(s, &ur1, &ut1, &uru, &utu);
RT(32, &s, &adur1, &adut1, &aduru, &adutu);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□□□", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□\n", aduru, uru, adutu, utu);
s.n_slab = 1.5;
fprintf(stderr, "\na=%5.4f□b=%5.4f□g=%5.4f□n=%5.4f□ns=%5.4f□\n", s.a, s.b, s.g, s.n_slab,
    s.n_top_slide);
MC_RT(s, &ur1, &ut1, &uru, &utu);
RT(32, &s, &adur1, &adut1, &aduru, &adutu);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□□□", adur1, ur1, adut1, ut1);
fprintf(stderr, "%5.4f□%5.4f□□□%5.4f□%5.4f□\n", aduru, uru, adutu, utu);

```

```

14.  ⟨old formatting 14⟩ ≡
    if (cl_verbosity > 0 ∧ count % 100 ≡ 0) fprintf(stderr, "\n");
    if (cl_verbosity > 0) printf(format2, m.m_r, m.m_t, m.m_u, r.a, r.b, r.g, r.final_distance);
    else printf("%9.5f\t%9.5f\t%9.5f\t%9.5f\n", r.a, r.b, r.g, r.final_distance);

```

15. Stuff the command line arguments that should be constant over the entire inversion process into the measurement record and set up the result record to handle the arguments properly so that the optical properties can be determined.

⟨ Command-line changes to *m* 15 ⟩ ≡

```

if (cl_cos_angle ≠ UNINITIALIZED) {
    m_slab_cos_angle = cl_cos_angle;
    if (cl_quadrature_points ≡ UNINITIALIZED) cl_quadrature_points = 12;
    if (cl_quadrature_points ≠ 12 * (cl_quadrature_points/12)) {
        fprintf(stderr,
            "If you use the -i option to specify an oblique incidence angle, then\n");
        fprintf(stderr, "the number of quadrature points must be a multiple of 12\n");
        exit(0);
    }
}
if (cl_sample_n ≠ UNINITIALIZED) m_slab_index = cl_sample_n;
if (cl_slide_n ≠ UNINITIALIZED) {
    m_slab_bottom_slide_index = cl_slide_n;
    m_slab_top_slide_index = cl_slide_n;
}
if (cl_slide_OD ≠ UNINITIALIZED) {
    m_slab_bottom_slide_b = cl_slide_OD;
    m_slab_top_slide_b = cl_slide_OD;
}
if (cl_sample_d ≠ UNINITIALIZED) m_slab_thickness = cl_sample_d;
if (cl_beam_d ≠ UNINITIALIZED) m_d_beam = cl_beam_d;
if (cl_slide_d ≠ UNINITIALIZED) {
    m_slab_bottom_slide_thickness = cl_slide_d;
    m_slab_top_slide_thickness = cl_slide_d;
}
if (cl_slides ≡ NO_SLIDES) {
    m_slab_bottom_slide_index = 1.0;
    m_slab_bottom_slide_thickness = 0.0;
    m_slab_top_slide_index = 1.0;
    m_slab_top_slide_thickness = 0.0;
}
if (cl_slides ≡ ONE_SLIDE_ON_TOP ∨ cl_slides ≡ ONE_SLIDE_NEAR_SPHERE) {
    m_slab_bottom_slide_index = 1.0;
    m_slab_bottom_slide_thickness = 0.0;
}
if (cl_slides ≡ ONE_SLIDE_ON_BOTTOM ∨ cl_slides ≡ ONE_SLIDE_NOT_NEAR_SPHERE) {
    m_slab_top_slide_index = 1.0;
    m_slab_top_slide_thickness = 0.0;
}
if (cl_slides ≡ ONE_SLIDE_NEAR_SPHERE ∨ cl_slides ≡ ONE_SLIDE_NOT_NEAR_SPHERE) m_flip_sample = 1;
else m_flip_sample = 0;
if (cl_method ≠ UNINITIALIZED) m_method = (int) cl_method;
if (cl_rstd_t ≠ UNINITIALIZED) m_rstd_t = cl_rstd_t;
if (cl_rstd_r ≠ UNINITIALIZED) m_rstd_r = cl_rstd_r;
if (cl_sphere_one[4] ≠ UNINITIALIZED) {
    double d_sample_r, d_entrance_r, d_detector_r;
    m_d_sphere_r = cl_sphere_one[0];
    d_sample_r = cl_sphere_one[1];

```

```

    d_entrance_r = cl_sphere_one[2];
    d_detector_r = cl_sphere_one[3];
    m.rw_r = cl_sphere_one[4];
    m.as_r = (d_sample_r/m.d_sphere_r/2) * (d_sample_r/m.d_sphere_r/2);
    m.ae_r = (d_entrance_r/m.d_sphere_r/2) * (d_entrance_r/m.d_sphere_r/2);
    m.ad_r = (d_detector_r/m.d_sphere_r/2) * (d_detector_r/m.d_sphere_r/2);
    m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
    m.d_sphere_t = m.d_sphere_r;
    m.as_t = m.as_r;
    m.ae_t = m.ae_r;
    m.ad_t = m.ad_r;
    m.aw_t = m.aw_r;
    m.rw_t = m.rw_r;
    if (cl_num_spheres == UNINITIALIZED) m.num_spheres = 1;
}
if (cl_sphere_two[4] != UNINITIALIZED) {
    double d_sample_t, d_entrance_t, d_detector_t;
    m.d_sphere_t = cl_sphere_two[0];
    d_sample_t = cl_sphere_two[1];
    d_entrance_t = cl_sphere_two[2];
    d_detector_t = cl_sphere_two[3];
    m.rw_t = cl_sphere_two[4];
    m.as_t = (d_sample_t/m.d_sphere_t/2) * (d_sample_t/m.d_sphere_t/2);
    m.ae_t = (d_entrance_t/m.d_sphere_t/2) * (d_entrance_t/m.d_sphere_t/2);
    m.ad_t = (d_detector_t/m.d_sphere_t/2) * (d_detector_t/m.d_sphere_t/2);
    m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
    if (cl_num_spheres == UNINITIALIZED) m.num_spheres = 2;
}
if (cl_num_spheres != UNINITIALIZED) m.num_spheres = (int) cl_num_spheres;
if (cl_rc_fraction != UNINITIALIZED) m.fraction_of_rc_in_mr = cl_rc_fraction;
if (cl_tc_fraction != UNINITIALIZED) m.fraction_of_tc_in_mt = cl_tc_fraction;
if (cl_UR1 != UNINITIALIZED) m.m_r = cl_UR1;
if (cl_UT1 != UNINITIALIZED) m.m_t = cl_UT1;
if (cl_Tc != UNINITIALIZED) m.m_u = cl_Tc;
if (cl_default_fr != UNINITIALIZED) m.f_r = cl_default_fr;

```

This code is used in section 2.

16. put the values for command line reflection and transmission into the measurement record.

⟨ Count command-line measurements 16 ⟩ ≡

```

    m.num_measures = 3;
    if (m.m_t ≡ 0) m.num_measures--;
    if (m.m_u ≡ 0) m.num_measures--;
    params = m.num_measures;
    if (m.num_measures ≡ 3) { /* need to fill slab entries to calculate the optical thickness */
        struct AD_slab_type s;
        s.n_slab = m.slabs_index;
        s.n_top_slide = m.slabs_top_slide_index;
        s.n_bottom_slide = m.slabs_bottom_slide_index;
        s.b_top_slide = m.slabs_top_slide_b;
        s.b_bottom_slide = m.slabs_bottom_slide_b;
        s.cos_angle = m.slabs_cos_angle;
        cl_default_b = What_Is_B(s, m.m_u);
    }

```

This code is used in section 2.

17. ⟨ print version function 17 ⟩ ≡

```

static void print_version(void)
{
    fprintf(stderr, "iad_%s\n", Version);
    fprintf(stderr, "Copyright_2011_Scott_Prahl, prahls@ohsu.edu\n");
    fprintf(stderr, "see_Applied_Optics, 32:559-568, 1993\n");
    exit(0);
}

```

This code is used in section 2.

18. `<print usage function 18> ≡`

```
static void print_usage(void)
{
    fprintf(stderr, "iad_%s\n\n", Version);
    fprintf(stderr, "iad_finds_optical_properties_from_measurements\n\n");
    fprintf(stderr, "Usage: iad [options] input\n\n");
    fprintf(stderr, "Options:\n");
    fprintf(stderr, "    -1 # # # # ' reflection sphere parameters\n");
    fprintf(stderr, "    -2 # # # # ' transmission sphere parameters\n");
    fprintf(stderr, "    ' sphere_d, sample_d, entrance_d, detector_d, wall_r'\n");
    fprintf(stderr, "    -a # use this albedo\n");
    fprintf(stderr, "    -A # use this absorption coefficient\n");
    fprintf(stderr, "    -b # use this optical thickness\n");
    fprintf(stderr, "    -B # beam diameter\n");
    fprintf(stderr, "    -c # fraction of unscattered refl in MR\n");
    fprintf(stderr, "    -C # fraction of unscattered trans in MT\n");
    fprintf(stderr, "    -d # thickness of sample\n");
    fprintf(stderr, "    -D # thickness of slide\n");
    fprintf(stderr, "    -e # error tolerance (default 0.0001)\n");
    fprintf(stderr, "    -E # optical depth (=mu*D) for slides\n");
    fprintf(stderr,
        "    -f # allow a fraction 0.0-1.0 of light to hit sphere wall first\n");
    fprintf(stderr, "    -F # use this scattering coefficient\n");
    fprintf(stderr, "    -F' P_lambda0 mus0 gamma' mus=mus0*(lambda/lambda0)^gamma\n");
    fprintf(stderr, "    -F' R_lambda0 musp0 gamma' musp=musp0*(lambda/lambda0)^gamma\n");
    fprintf(stderr, "    -g # scattering anisotropy (default 0)\n");
    fprintf(stderr, "    -G # type of boundary '0', '2', 't', 'b', 'n', 'f'\n");
    fprintf(stderr, "    '0' or '2' --- number of slides\n");
    fprintf(stderr, "    't' (top) or 'b' (bottom) --- one slide\n");
    fprintf(stderr, "    that is hit by light first\n");
    fprintf(stderr, "    'n' (near) or 'f' (far) --- one slide\n");
    fprintf(stderr, "    position relative to sphere\n");
    fprintf(stderr, "    -h display help\n");
    fprintf(stderr, "    -i # light is incident at this angle in degrees\n");
    fprintf(stderr, "    -M # number of Monte Carlo iterations\n");
    fprintf(stderr, "    -n # specify index of refraction of slab\n");
    fprintf(stderr, "    -N # specify index of refraction of slides\n");
    fprintf(stderr, "    -o filename explicitly specify filename for output\n");
    fprintf(stderr, "    -p # of Monte Carlo photons (default 100000)\n");
    fprintf(stderr, "    a negative number is max MC time in milliseconds\n");
    fprintf(stderr, "    -q # number of quadrature points (default=8)\n");
    fprintf(stderr, "    -r # total reflection measurement\n");
    fprintf(stderr, "    -R # actual reflectance for 100% measurement\n");
    fprintf(stderr, "    -S # number of spheres used\n");
    fprintf(stderr, "    -t # total transmission measurement\n");
    fprintf(stderr, "    -T # actual transmission for 100% measurement\n");
    fprintf(stderr, "    -u # unscattered transmission measurement\n");
    fprintf(stderr, "    -v version information\n");
    fprintf(stderr, "    -V0 verbosity low --- no output to stderr\n");
    fprintf(stderr, "    -V1 verbosity moderate\n");
    fprintf(stderr, "    -V2 verbosity high\n");
    fprintf(stderr, "    -x # set debugging level\n");
}
```

```

fprintf(stderr, "\n-X dual beam configuration\n");
fprintf(stderr, "\n-Z do forward calculation\n");
fprintf(stderr, "Examples:\n");
fprintf(stderr, "\n_iad_data Optical values put in data.txt\n");
fprintf(stderr, "\n_iad-c0.9_data Assume M_R includes 90% of uns\
cattered reflectance\n");
fprintf(stderr, "\n_iad-C0.8_data Assume M_T includes 80% of uns\
cattered transmittance\n");
fprintf(stderr, "\n_iad-e0.0001_data Better convergence to R_&T values\n");
fprintf(stderr,
"\n_iad-f1.0_data All light hits reflectance sphere wall first\n");
fprintf(stderr, "\n_iad-o_out_data Calculated values in/out\n");
fprintf(stderr, "\n_iad-r0.3 R_total=0.3, b=inf, find albedo\n");
fprintf(stderr, "\n_iad-r0.3-t0.4 R_total=0.3, T_total=0.4, find a,b,g\n");
fprintf(stderr, "\n_iad-r0.3-t0.4-n1.5 R_total=0.3, T_total=0.4, n=1.5, find a,b\n");
fprintf(stderr, "\n_iad-r0.3-t0.4 R_total=0.3, T_total=0.4, find a,b\n");
fprintf(stderr, "\n_iad-p1000_data Only 1000 photons\n");
fprintf(stderr, "\n_iad-p-100_data Allow only 100ms per iteration\n");
fprintf(stderr, "\n_iad-q4_data Four quadrature points\n");
fprintf(stderr, "\n_iad-M0_data No MC(iad)\n");
fprintf(stderr, "\n_iad-M1_data MC once (iad->MC->iad)\n");
fprintf(stderr, "\n_iad-M2_data MC twice (iad->MC->iad->MC->iad)\n");
fprintf(stderr, "\n_iad-M0-q4_data Fast and crude conversion\n");
fprintf(stderr,
"\n_iad-G_t_data One top slide with properties from data.rxt\n");
fprintf(stderr,
"\n_iad-G_b-N1.5-D1_data Use 1 bottom slide with n=1.5 and thickness=1\n");
fprintf(stderr, "\n_iad-x1_data Show sphere and MC effects\n");
fprintf(stderr, "\n_iad-x2_data DEBUG_GRID\n");
fprintf(stderr, "\n_iad-x4_data DEBUG_ITERATIONS\n");
fprintf(stderr, "\n_iad-x8_data DEBUG_LOST_LIGHT\n");
fprintf(stderr, "\n_iad-x16_data DEBUG_SPHERE_EFFECTS\n");
fprintf(stderr, "\n_iad-x32_data DEBUG_BEST_GUESS\n");
fprintf(stderr, "\n_iad-x64_data DEBUG_EVERY_CALC\n");
fprintf(stderr, "\n_iad-x128_data DEBUG_SEARCH\n");
fprintf(stderr, "\n_iad-x255_data All debugging output\n");
fprintf(stderr,
"\n_iad-X-i8_data Dual beam spectrometer with 8 degree incidence\n\n");
fprintf(stderr,
"\n_iad-Z-a0.9-b1-i45 Forward calc assuming 45 degree incidence\n\n");
fprintf(stderr, "\n_apply_iad_data1_data2 Process multiple files\n\n");
fprintf(stderr, "Report bugs to <prahls@ohsu.edu>\n\n");
exit(0);
}

```

This code is used in section 2.

19. Just figure out the damn scattering and absorption

⟨calculate coefficients function 19⟩ ≡

```
static void Calculate_Mua_Musp(struct measure_type m, struct invert_type r, double *musp, double
    *mua)
{
    if (r.default_b ≡ HUGE_VAL ∨ r.b ≡ HUGE_VAL) {
        if (r.a ≡ 0) {
            *musp = 0.0;
            *mua = 1.0;
            return;
        }
        *musp = 1.0 - r.g;
        *mua = (1.0 - r.a)/r.a;
        return;
    }
    *musp = r.a * r.b / m.slab_thickness * (1.0 - r.g);
    *mua = (1 - r.a) * r.b / m.slab_thickness;
}
```

See also section 20.

This code is used in section 2.

20. This can only be called immediately after *Invert_RT* You have been warned! Notice that *Calculate_Distance* does not pass any slab properties.

⟨calculate coefficients function 19⟩ +≡

```
static void calculate_coefficients(struct measure_type m, struct invert_type r, double *LR, double
    *LT, double *musp, double *mua)
{
    double delta;
    *LR = 0;
    *LT = 0;
    Calculate_Distance(LR, LT, &delta);
    Calculate_Mua_Musp(m, r, musp, mua);
}
```

```
static void print_results_header(FILE *fp)
```

This code is used in section 2.

22. When debugging lost light, it is handy to see how each iteration changes the calculated values for the optical properties. We do that here if we are debugging, otherwise we just print a number or something to keep the user from wondering what is going on.

```

void print_optical_property_result (FILE *fp, struct measure_type m, struct invert_type r, double
    LR, double LT, double mu_a, double mu_sp, int mc_iter, int line ) {
if (m.lambda != 0) fprintf(fp, "%.1f\t", m.lambda);
else fprintf(fp, "%6d\t", line );
if (mu_a > 200) mu_a = 199.9999;
if (mu_sp > 1000) mu_sp = 999.9999;
fprintf(fp, "%0.3e\t%0.3e\t", m.m_r, LR);
fprintf(fp, "%0.3e\t%0.3e\t", m.m_t, LT);
fprintf(fp, "%0.3e\t", mu_a);
fprintf(fp, "%0.3e\t", mu_sp);
fprintf(fp, "%0.3e\t", r.g);
if (Debug(DEBUG_LOST_LIGHT)) {
    fprintf(fp, "%0.3e\t%0.3e\t", m.ur1_lost, m.uru_lost);
    fprintf(fp, "%0.3e\t%0.3e\t", m.ut1_lost, m.utu_lost);
    fprintf(fp, "%2d\t", mc_iter);
    fprintf(fp, "%4d\t", r.iterations);
}
fprintf(fp, "#\xc\n", what_char ( r . error ) );
fflush(fp); }

```

This code is used in section 2.

23. \langle print error legend function 23 $\rangle \equiv$

```
static void print_error_legend(void)
{
    fprintf(stderr, "-----_Sorry,_but_..._errors_encountered_-----\n");
    fprintf(stderr, "___*___=>_Success_____");
    fprintf(stderr, "___0-9__=>_Monte_Carlo_Iteration\n");
    fprintf(stderr, "___R__=>_M_R_is_too_big___");
    fprintf(stderr, "___r__=>_M_R_is_too_small\n");
    fprintf(stderr, "___T__=>_M_T_is_too_big___");
    fprintf(stderr, "___t__=>_M_T_is_too_small\n");
    fprintf(stderr, "___U__=>_M_U_is_too_big___");
    fprintf(stderr, "___u__=>_M_U_is_too_small\n");
    fprintf(stderr, "___!__=>_M_R+_M_T>_1_____");
    fprintf(stderr, "___+__=>_Did_not_converge\n\n");
}
```

This code is used in section 2.

24. returns a new string consisting of s+t

\langle stringdup together function 24 $\rangle \equiv$

```
static char *strdup_together(char *s, char *t)
{
    char *both;
    if (s  $\equiv$   $\Lambda$ ) {
        if (t  $\equiv$   $\Lambda$ ) return  $\Lambda$ ;
        return strdup(t);
    }
    if (t  $\equiv$   $\Lambda$ ) return strdup(s);
    both = malloc(strlen(s) + strlen(t) + 1);
    if (both  $\equiv$   $\Lambda$ ) fprintf(stderr, "Could_not_allocate_memory_for_both_strings.\n");
    strcpy(both, s);
    strcat(both, t);
    return both;
}
```

This code is used in section 2.

25. assume that start time has already been set

\langle seconds elapsed function 25 $\rangle \equiv$

```
static double seconds_elapsed(clock_t start_time)
{
    clock_t finish_time = clock();
    return (double)(finish_time - start_time)/CLOCKS_PER_SEC;
}
```

This code is used in section 2.

26. given a string and an array, this fills the array with numbers from the string. The numbers should be separated by spaces.

Returns 0 upon successfully filling n entries, returns 1 for any error.

⟨parse string into array function 26⟩ ≡

```
static int parse_string_into_array(char *s, double *a, int n)
{
    char *t, *last, *r;
    int i = 0;

    t = s;
    last = s + strlen(s);
    while (t < last) { /* a space should mark the end of number */
        r = t;
        while (*r ≠ ' ' ∧ *r ≠ '\0') r++;
        *r = '\0'; /* parse the number and save it */
        if (sscanf(t, "%lf", &(a[i])) ≠ 0) return 1;
        i++; /* are we done ? */
        if (i ≡ n) return 0; /* move pointer just after last number */
        t = r + 1;
    }
    return 1;
}
```

This code is used in section 2.

27. \langle print dot function 27 $\rangle \equiv$

```
static char what_char(int err)
{
    if (err == IAD_NO_ERROR) return '*';
    if (err == IAD_TOO_MANY_ITERATIONS) return '+';
    if (err == IAD_MR_TOO_BIG) return 'R';
    if (err == IAD_MR_TOO_SMALL) return 'r';
    if (err == IAD_MT_TOO_BIG) return 'T';
    if (err == IAD_MT_TOO_SMALL) return 't';
    if (err == IAD_MU_TOO_BIG) return 'U';
    if (err == IAD_MU_TOO_SMALL) return 'u';
    if (err == IAD_TOO_MUCH_LIGHT) return '!';
    return '?';
}

static void print_dot(clock_t start_time, int err, int count, int points, int final, int verbosity, int
                    *any_error)
{
    static int counter = 0;
    counter++;
    if (err != IAD_NO_ERROR) *any_error = err;
    if (verbosity == 0) return;
    if (final == 99) fprintf(stderr, "%c", what_char(err));
    else {
        counter--;
        fprintf(stderr, "%1d\b", final % 10);
    }
    if (final == 99) {
        if (counter % 50 == 0) {
            double rate = (seconds_elapsed(start_time)/points);
            fprintf(stderr, "\u003d\u003done\u0020(%5.2f\u00s/pt)\n", points, rate);
        }
        else if (counter % 10 == 0) fprintf(stderr, "\u0020");
    }
    fflush(stderr);
}
```

This code is used in section 2.

28. IAD Types. This file has no routines. It is responsible for creating the header file `iad_type.h` and nothing else. Altered 3/3/95 to change the version number below. Change June 95 to improve cross referencing using CTwill. Change August 97 to add root finding with known absorption

29. These are the various optical properties that can be found with this program. `FIND_AUTO` allows one to let the computer figure out what it should be looking for.

These determine what metric is used in the minimization process.

These give the two different types of illumination allowed.

Finally, for convenience I create a Boolean type.

```
<iad_type.h 29> ≡
#undef FALSE
#undef TRUE
  <Preprocessor definitions>
  <Structs to export from IAD Types 32>
```

30.

```
#define FIND_A 0
#define FIND_B 1
#define FIND_AB 2
#define FIND_AG 3
#define FIND_AUTO 4
#define FIND_BG 5
#define FIND_BaG 6
#define FIND_BsG 7
#define FIND_Ba 8
#define FIND_Bs 9
#define FIND_G 10
#define FIND_B_WITH_NO_ABSORPTION 11
#define FIND_B_WITH_NO_SCATTERING 12
#define RELATIVE 0
#define ABSOLUTE 1
#define COLLIMATED 0
#define DIFFUSE 1
#define FALSE 0
#define TRUE 1
#define IAD_MAX_ITERATIONS 500
```


31. Need error codes for this silly program

```
#define IAD_NO_ERROR 0
#define IAD_TOO_MANY_ITERATIONS 1
#define IAD_AS_NOT_VALID 16
#define IAD_AE_NOT_VALID 17
#define IAD_AD_NOT_VALID 18
#define IAD_RW_NOT_VALID 19
#define IAD_RD_NOT_VALID 20
#define IAD_RSTD_NOT_VALID 21
#define IAD_GAMMA_NOT_VALID 22
#define IAD_F_NOT_VALID 23
#define IAD_BAD_PHASE_FUNCTION 24
#define IAD_QUAD_PTS_NOT_VALID 25
#define IAD_BAD_G_VALUE 26
#define IAD_TOO_MANY_LAYERS 27
#define IAD_MEMORY_ERROR 28
#define IAD_FILE_ERROR 29
#define IAD_EXCESSIVE_LIGHT_LOSS 30
#define IAD_RT_LT_MINIMUM 31
#define IAD_MR_TOO_SMALL 32
#define IAD_MR_TOO_BIG 33
#define IAD_MT_TOO_SMALL 34
#define IAD_MT_TOO_BIG 35
#define IAD_MU_TOO_SMALL 36
#define IAD_MU_TOO_BIG 37
#define IAD_TOO_MUCH_LIGHT 38
#define IAD_TSTD_NOT_VALID 39
#define UNINITIALIZED -99
#define DEBUG_A_LITTLE 1
#define DEBUG_GRID 2
#define DEBUG_ITERATIONS 4
#define DEBUG_LOST_LIGHT 8
#define DEBUG_SPHERE_EFFECTS 16
#define DEBUG_BEST_GUESS 32
#define DEBUG_EVERY_CALC 64
#define DEBUG_SEARCH 128
#define DEBUG_RD_ONLY 256
#define DEBUG_ANY #FFFFFFF
#define UNKNOWN 0
#define COMPARISON 1
#define SUBSTITUTION 2
```

32. The idea of the structure *measure_type* is collect all the information regarding a single measurement together in one spot. No information regarding how the inversion procedure is supposed to be done is contained in this structure, unlike in previous incarnations of this program.

⟨Structs to export from IAD Types 32⟩ ≡

```
typedef struct measure_type {
    double slab_index;
    double slab_thickness;
    double slab_top_slide_index;
    double slab_top_slide_b;
    double slab_top_slide_thickness;
    double slab_bottom_slide_index;
    double slab_bottom_slide_b;
    double slab_bottom_slide_thickness;
    double slab_cos_angle;
    int num_spheres;
    int num_measures;
    int method;
    int flip_sample;
    double d_beam;
    double fraction_of_rc_in_mr;
    double fraction_of_tc_in_mt;
    double m_r, m_t, m_u;
    double lambda;
    double as_r, ad_r, ae_r, aw_r, rd_r, rw_r, rstd_r, f_r;
    double as_t, ad_t, ae_t, aw_t, rd_t, rw_t, rstd_t, f_t;
    double ur1_lost, uru_lost, ut1_lost, utu_lost;
    double d_sphere_r, d_sphere_t;
} IAD_measure_type;
```

See also sections 33 and 34.

This code is used in section 29.

33. This describes how the inversion process should proceed and also contains the results of that inversion process.

```

⟨Structs to export from IAD Types 32⟩ +=
typedef struct invert_type { double a;      /* the calculated albedo */
double b;      /* the calculated optical depth */
double g;      /* the calculated anisotropy */
int found;
int search;
int metric;
double tolerance;
double MC_tolerance;
double final_distance;
int iterations; int error ;
struct AD_slab_type slab;
struct AD_method_type method;
double default_a;
double default_b;
double default_g;
double default_ba;
double default_bs;
double default_mua;
double default_mus; } IAD_invert_type;

```

34. A few types that used to be enum's are now int's.

```

⟨Structs to export from IAD Types 32⟩ +=
typedef int search_type;
typedef int boolean_type;
typedef int illumination_type;
typedef struct guess_t {
    double distance;
    double a;
    double b;
    double g;
} guess_type;
extern double FRACTION;

```

35. IAD Public.

This contains the routine *Inverse_RT* that should generally be the basic entry point into this whole mess. Call this routine with the proper values and true happiness is bound to be yours.

Altered accuracy of the standard method of root finding from 0.001 to 0.00001. Note, it really doesn't help to change the method from ABSOLUTE to RELATIVE, but I did anyway. (3/3/95)

```
<iad_pub.c 35> ≡
#include <stdio.h>
#include <math.h>
#include "nr_util.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#include "iad_find.h"
#include "iad_pub.h"
#include "iad_io.h"
#include "mc_lost.h"
  <Definition for Inverse_RT 39>
  <Definition for measure_OK 44>
  <Definition for determine_search 51>
  <Definition for Initialize_Result 55>
  <Definition for Initialize_Measure 63>
  <Definition for ez_Inverse_RT 61>
  <Definition for Spheres_Inverse_RT 65>
  <Definition for Calculate_MR_MT 72>
  <Definition for MinMax_MR_MT 76>
  <Definition for Calculate_Minimum_MR 74>
```

36. All the information that needs to be written to the header file *iad_pub.h*. This eliminates the need to maintain a set of header files as well.

```
<iad_pub.h 36> ≡
  <Prototype for Inverse_RT 38>;
  <Prototype for measure_OK 43>;
  <Prototype for determine_search 50>;
  <Prototype for Initialize_Result 54>;
  <Prototype for ez_Inverse_RT 60>;
  <Prototype for Initialize_Measure 62>;
  <Prototype for Calculate_MR_MT 71>;
  <Prototype for MinMax_MR_MT 75>;
  <Prototype for Calculate_Minimum_MR 73>;
```

37. Here is the header file needed to access one interesting routine in the *libiad.so* library.

```
<lib_iad.h 37> ≡
  <Prototype for ez_Inverse_RT 60>;
  <Prototype for Spheres_Inverse_RT 64>;
```

38. Inverse RT. *Inverse_RT* is the main function in this whole package. You pass the variable *m* containing your experimentally measured values to the function *Inverse_RT*. It hopefully returns the optical properties in *r* that are appropriate for your experiment.

⟨Prototype for *Inverse_RT* 38⟩ ≡

```
void Inverse_RT(struct measure_type m, struct invert_type *r)
```

This code is used in sections 36 and 39.

39. ⟨Definition for *Inverse_RT* 39⟩ ≡

⟨Prototype for *Inverse_RT* 38⟩

```
{
  if (0 ∧ Debug(DEBUG_LOST_LIGHT)) {
    fprintf(stderr, "**_Inverse_RT_(%d_spheres)_**\n", m.num_spheres);
    fprintf(stderr, "M_R= %.5f, MT= %.5f\n", m.m_r, m.m_t);
    fprintf(stderr, "UR1_lost= %.5f, UT1_lost= %.5f\n", m.ur1_lost, m.ut1_lost);
  }
  r→found = FALSE;
  ⟨Exit with bad input data 40⟩
  r→search = determine_search(m, *r);
  if (r→search ≡ FIND_B_WITH_NO_ABSORPTION) {
    r→default_a = 1;
    r→search = FIND_B;
  }
  if (r→search ≡ FIND_B_WITH_NO_SCATTERING) {
    r→default_a = 0;
    r→search = FIND_B;
  }
  ⟨Find the optical properties 41⟩
  if (r→final_distance ≤ r→tolerance) r→found = TRUE;
}
```

This code is used in section 35.

40. There is no sense going to all the trouble to try a multivariable minimization if the input data is bogus. So I wrote a single routine *measure_OK* to do just this.

⟨Exit with bad input data 40⟩ ≡

```
r → error = measure_OK(m, *r); if (r→method.quad_pts < 4) r → error = IAD_QUAD_PTS_NOT_VALID; if
( 0 ∧ ( r → error ≠ IAD_NO_ERROR ) ) return;
```

This code is used in section 39.

41. Now I fob the real work off to the unconstrained minimization routines. Ultimately, I would like to replace all these by constrained minimization routines. Actually the first five already are constrained. The real work will be improving the last five because these are 2-D minimization routines.

```

⟨Find the optical properties 41⟩ ≡
  switch (r-search) {
  case FIND_A: U_Find_A(m,r);
    break;
  case FIND_B: U_Find_B(m,r);
    break;
  case FIND_G: U_Find_G(m,r);
    break;
  case FIND_Ba: U_Find_Ba(m,r);
    break;
  case FIND_Bs: U_Find_Bs(m,r);
    break;
  case FIND_AB: U_Find_AB(m,r);
    break;
  case FIND_AG: U_Find_AG(m,r);
    break;
  case FIND_BG: U_Find_BG(m,r);
    break;
  case FIND_BsG: U_Find_BsG(m,r);
    break;
  case FIND_BaG: U_Find_BaG(m,r);
    break;
  }
  if (r-iterations ≡ IAD_MAX_ITERATIONS) r → error = IAD_TOO_MANY_ITERATIONS;

```

This code is used in section 39.

42. Validation.

43. Now the question is — just what is bad data? Here's the prototype.

```

⟨Prototype for measure_OK 43⟩ ≡
  int measure_OK(struct measure_type m, struct invert_type r)

```

This code is used in sections 36 and 44.

44. It would just be nice to stop computing with bad data. This does not work in practice because it turns out that there is often bogus data in a full wavelength scan. Often the reflectance is too low for short wavelengths and at long wavelengths the detector (photomultiplier tube) does not work worth a damn.

The two sphere checks are more complicated. For example, we can no longer categorically state that the transmittance is less than one or that the sum of the reflectance and transmittance is less than one. Instead we use the transmittance to bound the values for the reflectance — see the routine *MinMax_MR_MT* below.

```

⟨ Definition for measure_OK 44 ⟩ ≡
  ⟨ Prototype for measure_OK 43 ⟩ { double ru, tu;
    if (m.num_spheres ≠ 2) {
      ⟨ Check MR for zero or one spheres 45 ⟩
      ⟨ Check MT for zero or one spheres 46 ⟩
    }
    else { int error = MinMax_MR_MT(m, r); if ( error ≠ IAD_NO_ERROR ) return error ; } ⟨ Check
      MU 47 ⟩
    if (m.num_spheres ≠ 0) {
      ⟨ Check sphere parameters 48 ⟩
    }
    return IAD_NO_ERROR; }

```

This code is used in section 35.

45. The reflectance is constrained by the index of refraction of the material and the transmission. The upper bound for the reflectance is just one minus the transmittance. The specular (unscattered) reflectance from the boundaries imposes minimum for the reflectance. Obviously, the reflected light cannot be less than that from the first boundary. This might be calculated by assuming an infinite layer thickness. But we can do better.

There is a definite bound on the minimum reflectance from a sample. If you have a sample with a given transmittance *m.t*, the minimum reflectance possible is found by assuming that the sample does not scatter any light.

Knowledge of the indices of refraction makes it a relatively simple matter to determine the optical thickness $b = \mu_a * d$ of the slab. The minimum reflection is obtained by including all the specular reflectances from all the surfaces.

If the default albedo has been specified as zero, then there is really no need to check MR because it is ignored.

```

⟨ Check MR for zero or one spheres 45 ⟩ ≡
  if (r.default_a ≡ UNINITIALIZED ∨ r.default_a > 0) {
    double mr, mt;
    Calculate_Minimum_MR(m, r, &mr, &mt);
    if (m.m_r < mr) return IAD_MR_TOO_SMALL;
  }

```

This code is used in section 44.

46. The transmittance is also constrained by the index of refraction of the material. The minimum transmittance is zero, but the maximum transmittance cannot exceed the total light passing through the sample when there is no scattering or absorption. This is calculated by assuming an infinitely thin (to eliminate any scattering or absorption effects).

There is a problem when spheres are present. The estimated values for the transmittance using *Sp_mu_RT* are not actually limiting cases. This will require a bit of fixing, but for now that test is omitted if the number of spheres is more than zero.

```

< Check MT for zero or one spheres 46 > ≡
  if (m.m_t < 0) return IAD_MT_TOO_SMALL;
  Sp_mu_RT_Flip(m.flip_sample, r.slab.n_top_slide, r.slab.n_slab, r.slab.n_bottom_slide, r.slab.b_top_slide, 0,
    r.slab.b_bottom_slide, r.slab.cos_angle, &ru, &tu);
  if (m.num_spheres ≡ 0 ∧ m.m_t > tu) {
    fprintf(stderr, "ntop=%7.5f, nslab=%7.5f, nbottom=%7.5f\n", r.slab.n_top_slide, r.slab.n_slab,
      r.slab.n_bottom_slide);
    fprintf(stderr, "tu_max=%7.5f, m_t=%7.5f, t_std=%7.5f\n", tu, m.m_t, m.rstd_t);
    return IAD_MT_TOO_BIG;
  }

```

This code is used in section 44.

47. The unscattered transmission is now always included in the total transmittance. Therefore the unscattered transmittance must fall between zero and *M_T*

```

< Check MU 47 > ≡
  if (m.m_u < 0) return IAD_MU_TOO_SMALL;
  if (m.m_u > m.m_t) return IAD_MU_TOO_BIG;

```

This code is used in section 44.

48. Make sure that reflection sphere parameters are reasonable

```

< Check sphere parameters 48 > ≡
  if (m.as_r < 0 ∨ m.as_r ≥ 0.2) return IAD_AS_NOT_VALID;
  if (m.ad_r < 0 ∨ m.ad_r ≥ 0.2) return IAD_AD_NOT_VALID;
  if (m.ae_r < 0 ∨ m.ae_r ≥ 0.2) return IAD_AE_NOT_VALID;
  if (m.rw_r < 0 ∨ m.rw_r > 1.0) return IAD_RW_NOT_VALID;
  if (m.rd_r < 0 ∨ m.rd_r > 1.0) return IAD_RD_NOT_VALID;
  if (m.rstd_r < 0 ∨ m.rstd_r > 1.0) return IAD_RSTD_NOT_VALID;
  if (m.rstd_t < 0 ∨ m.rstd_t > 1.0) return IAD_TSTD_NOT_VALID;
  if (m.f_r < 0 ∨ m.f_r > 1) return IAD_F_NOT_VALID;

```

See also section 49.

This code is used in section 44.

49. Make sure that transmission sphere parameters are reasonable

```

< Check sphere parameters 48 > +≡
  if (m.as_t < 0 ∨ m.as_t ≥ 0.2) return IAD_AS_NOT_VALID;
  if (m.ad_t < 0 ∨ m.ad_t ≥ 0.2) return IAD_AD_NOT_VALID;
  if (m.ae_t < 0 ∨ m.ae_t ≥ 0.2) return IAD_AE_NOT_VALID;
  if (m.rw_t < 0 ∨ m.rw_r > 1.0) return IAD_RW_NOT_VALID;
  if (m.rd_t < 0 ∨ m.rd_t > 1.0) return IAD_RD_NOT_VALID;
  if (m.rstd_t < 0 ∨ m.rstd_t > 1.0) return IAD_TSTD_NOT_VALID;
  if (m.f_t < 0 ∨ m.f_t > 1) return IAD_F_NOT_VALID;

```


50. Searching Method.

The original idea was that this routine would automatically determine what optical parameters could be figured out from the input data. This worked fine for a long while, but I discovered that often it was convenient to constrain the optical properties in various ways. Consequently, this routine got more and more complicated.

What should be done is to figure out whether the search will be 1D or 2D and split this routine into two parts.

It would be nice to enable the user to constrain two parameters, but the infrastructure is missing at this point.

⟨Prototype for *determine_search* 50⟩ ≡

search_type *determine_search*(**struct measure_type** *m*, **struct invert_type** *r*)

This code is used in sections 36 and 51.

51. This routine is responsible for selecting the appropriate optical properties to determine.

```

⟨Definition for determine_search 51⟩ ≡
⟨Prototype for determine_search 50⟩
{
    double rt, tt, rd, td, tc, rc;
    int search = 0;
    int independent = m.num_measures;
    Estimate_RT(m, r, &rt, &tt, &rd, &rc, &td, &tc);
    if (m.m_u ≡ 0 ∧ independent ≡ 3) /* no information in tc */
        independent--;
    if (rd ≡ 0 ∧ independent ≡ 2) /* no information in rd */
        independent--;
    if (td ≡ 0 ∧ independent ≡ 2) /* no information in td */
        independent--;
    if (independent ≡ 1) {
        ⟨One parameter search 52⟩
    }
    else if (independent ≡ 2) {
        ⟨Two parameter search 53⟩
    } /* three real parameters with information! */
    else {
        search = FIND_AG;
    }
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "\n***_Determine_Search()\n");
        fprintf(stderr, "UUUUindependent_measurements_U=%3d\n", independent);
        fprintf(stderr, "UUUU_m_r=%8.5f_m_t=%8.5f_(rd_U=%8.5f_td=%8.5f)\n", m.m_r, m.m_t, rd, td);
        if (search ≡ FIND_A) fprintf(stderr, "UUUUsearch_U=FIND_A\n");
        if (search ≡ FIND_B) fprintf(stderr, "UUUUsearch_U=FIND_B\n");
        if (search ≡ FIND_AB) fprintf(stderr, "UUUUsearch_U=FIND_AB\n");
        if (search ≡ FIND_AG) fprintf(stderr, "UUUUsearch_U=FIND_AG\n");
        if (search ≡ FIND_AUTO) fprintf(stderr, "UUUUsearch_U=FIND_AUTO\n");
        if (search ≡ FIND_BG) fprintf(stderr, "UUUUsearch_U=FIND_BG\n");
        if (search ≡ FIND_BaG) fprintf(stderr, "UUUUsearch_U=FIND_BaG\n");
        if (search ≡ FIND_BsG) fprintf(stderr, "UUUUsearch_U=FIND_BsG\n");
        if (search ≡ FIND_Ba) fprintf(stderr, "UUUUsearch_U=FIND_Ba\n");
        if (search ≡ FIND_Bs) fprintf(stderr, "UUUUsearch_U=FIND_Bs\n");
        if (search ≡ FIND_G) fprintf(stderr, "UUUUsearch_U=FIND_G\n");
        if (search ≡ FIND_B_WITH_NO_ABSORPTION)
            fprintf(stderr, "UUUUsearch_U=FIND_B_WITH_NO_ABSORPTION\n");
        if (search ≡ FIND_B_WITH_NO_SCATTERING)
            fprintf(stderr, "UUUUsearch_U=FIND_B_WITH_NO_SCATTERING\n");
    }
    return search;
}

```

This code is used in section 35.

52. The fastest inverse problems are those in which just one measurement is known. This corresponds to a simple one-dimensional minimization problem. The only complexity is deciding exactly what should be allowed to vary. The basic assumption is that the anisotropy has been specified or will be assumed to be zero.

If the anisotropy is assumed known, then one other assumption will allow us to figure out the last parameter to solve for.

Ultimately, if no default values are given, then we look at the value of the total transmittance. If this is zero, then we assume that the optical thickness is infinite and solve for the albedo. Otherwise we will just make a stab at solving for the optical thickness assuming the albedo is one.

⟨ One parameter search 52 ⟩ \equiv

```

if (r.default_a  $\neq$  UNINITIALIZED) {
  if (r.default_a  $\equiv$  0) search = FIND_B_WITH_NO_SCATTERING;
  else if (r.default_a  $\equiv$  1) search = FIND_B_WITH_NO_ABSORPTION;
  else search = FIND_B;
}
else if (r.default_b  $\neq$  UNINITIALIZED) search = FIND_A;
else if (r.default_bs  $\neq$  UNINITIALIZED) search = FIND_Ba;
else if (r.default_ba  $\neq$  UNINITIALIZED) search = FIND_Bs;
else if (td  $\equiv$  0) search = FIND_A;
else if (rd  $\equiv$  0) search = FIND_B_WITH_NO_SCATTERING;
else search = FIND_B_WITH_NO_ABSORPTION;

```

This code is used in section 51.

53. If the absorption depth $\mu_a d$ is constrained return *FIND_BsG*. Recall that I use the bizarre mnemonic $bs = \mu_s d$ here and so this means that the program will search over various values of $\mu_s d$ and g .

If there are just two measurements then I assume that the anisotropy is not of interest and the only thing to calculate is the reduced albedo and optical thickness based on an assumed anisotropy.

⟨ Two parameter search 53 ⟩ \equiv

```

if (r.default_a  $\neq$  UNINITIALIZED) {
  if ((r.default_a  $\equiv$  0)  $\vee$  (r.default_g  $\neq$  UNINITIALIZED)) search = FIND_B;
  else search = FIND_BG;
}
else if (r.default_b  $\neq$  UNINITIALIZED) {
  if (r.default_g  $\neq$  UNINITIALIZED) search = FIND_A;
  else search = FIND_AG;
}
else if (r.default_ba  $\neq$  UNINITIALIZED) {
  if (r.default_g  $\neq$  UNINITIALIZED) search = FIND_Bs;
  else search = FIND_BsG;
}
else if (r.default_bs  $\neq$  UNINITIALIZED) {
  if (r.default_g  $\neq$  UNINITIALIZED) search = FIND_Ba;
  else search = FIND_BaG;
}
else if (rt + tt > 1  $\wedge$  0  $\wedge$  m.num_spheres  $\neq$  2) search = FIND_B_WITH_NO_ABSORPTION;
else search = FIND_AB;

```

This code is used in section 51.

54. This little routine just stuffs reasonable values into the structure we use to return the solution. This does not replace the values for *r.default_g* nor for *r.method.quad_pts*. Presumably these have been set correctly elsewhere.

⟨Prototype for *Initialize_Result* 54⟩ ≡
void *Initialize_Result*(**struct** *measure_type* *m*, **struct** *invert_type* **r*)

This code is used in sections 36 and 55.

55. ⟨Definition for *Initialize_Result* 55⟩ ≡
 ⟨Prototype for *Initialize_Result* 54⟩
 {
 ⟨Fill *r* with reasonable values 56⟩
 }

This code is used in section 35.

56. Start with the optical properties.

⟨Fill *r* with reasonable values 56⟩ ≡
 r→*a* = 0.0;
 r→*b* = 0.0;
 r→*g* = 0.0;

See also sections 57, 58, and 59.

This code is used in section 55.

57. Continue with other useful stuff.

⟨Fill *r* with reasonable values 56⟩ +≡
 r→*found* = FALSE;
 r→*tolerance* = 0.0001;
 r→*MC_tolerance* = 0.01; /* percent */
 r→*search* = FIND_AUTO;
 r→*metric* = RELATIVE;
 r→*final_distance* = 10;
 r→*iterations* = 0; *r*→**error** = IAD_NO_ERROR;

58. The defaults might be handy

⟨Fill *r* with reasonable values 56⟩ +≡
 r→*default_a* = UNINITIALIZED;
 r→*default_b* = UNINITIALIZED;
 r→*default_g* = UNINITIALIZED;
 r→*default_ba* = UNINITIALIZED;
 r→*default_bs* = UNINITIALIZED;
 r→*default_mua* = UNINITIALIZED;
 r→*default_mus* = UNINITIALIZED;

59. It is necessary to set up the slab correctly so, I stuff reasonable values into this record as well.

⟨ Fill *r* with reasonable values 56 ⟩ +≡

```

r→slab.a = 0.5;
r→slab.b = 1.0;
r→slab.g = 0;
r→slab.phase_function = HENYEY_GREENSTEIN;
r→slab.n_slab = m.slabs_index;
r→slab.n_top_slide = m.slabs_top_slide_index;
r→slab.n_bottom_slide = m.slabs_bottom_slide_index;
r→slab.b_top_slide = m.slabs_top_slide_b;
r→slab.b_bottom_slide = m.slabs_bottom_slide_b;
r→slab.cos_angle = m.slabs_cos_angle;
r→method.a_calc = 0.5;
r→method.b_calc = 1;
r→method.g_calc = 0.5;
r→method.quad_pts = 8;
r→method.b_thinnest = 1.0/32.0;

```

60. EZ Inverse RT. *ez_Inverse_RT* is a simple interface to the main function *Inverse_RT* in this package. It eliminates the need for complicated data structures so that the command line interface (as well as those to Perl and Mathematica) will be simpler. This function assumes that the reflection and transmission include specular reflection and that the transmission also include unscattered transmission.

Other assumptions are that the top and bottom slides have the same index of refraction, that the illumination is collimated. Of course no sphere parameters are included.

⟨ Prototype for *ez_Inverse_RT* 60 ⟩ ≡

```

void ez_Inverse_RT (double n, double nslide, double UR1, double UT1, double Tc, double
    *a, double *b, double *g, int *error )

```

This code is used in sections 36, 37, and 61.

61. $\langle \text{Definition for } ez_Inverse_RT \text{ 61} \rangle \equiv$
 $\langle \text{Prototype for } ez_Inverse_RT \text{ 60} \rangle \{$ **struct** **measure_type** *m*;
struct **invert_type** *r*;
**a* = 0;
**b* = 0;
**g* = 0;
Initialize_Measure(&*m*);
m.slab_index = *n*;
m.slab_top_slide_index = *nslide*;
m.slab_bottom_slide_index = *nslide*;
m.slab_cos_angle = 1.0;
m.num_measures = 3;
fprintf(*stderr*, "ut1=%f\n", *UT1*);
fprintf(*stderr*, "Tc=%f\n", *Tc*);
if (*UT1* \equiv 0) *m.num_measures*--;
if (*Tc* \equiv 0) *m.num_measures*--;
m.m_r = UR1;
m.m_t = UT1;
m.m_u = *Tc*;
Initialize_Result(*m*, &*r*);
r.method.quad_pts = 8;
Inverse_RT(*m*, &*r*); * **error** = *r . error* ; **if** (*r . error* \equiv IAD_NO_ERROR)
{
 **a* = *r.a*;
 **b* = *r.b*;
 **g* = *r.g*;
}
}

This code is used in section 35.

62. $\langle \text{Prototype for } Initialize_Measure \text{ 62} \rangle \equiv$
void *Initialize_Measure*(**struct** **measure_type** **m*)

This code is used in sections 36 and 63.

63. \langle Definition for *Initialize_Measure* 63 $\rangle \equiv$
 \langle Prototype for *Initialize_Measure* 62 \rangle
 $\{$
 double *default_sphere_d* = 8.0 * 25.4;
 double *default_sample_d* = 0.0 * 25.4;
 double *default_detector_d* = 0.1 * 25.4;
 double *default_entrance_d* = 0.5 * 25.4;
 double *sphere* = *default_sphere_d* * *default_sphere_d*;
 m-slab_index = 1.0;
 m-slab_top_slide_index = 1.0;
 m-slab_top_slide_b = 0.0;
 m-slab_top_slide_thickness = 0.0;
 m-slab_bottom_slide_index = 1.0;
 m-slab_bottom_slide_b = 0.0;
 m-slab_bottom_slide_thickness = 0.0;
 m-slab_thickness = 1.0;
 m-slab_cos_angle = 1.0;
 m-num_spheres = 0;
 m-num_measures = 1;
 m-method = UNKNOWN;
 m-fraction_of_rc_in_mr = 1.0;
 m-fraction_of_tc_in_mt = 1.0;
 m-flip_sample = 0;
 m-m_r = 0.0;
 m-m_t = 0.0;
 m-m_u = 0.0;
 m-d_sphere_r = *default_sphere_d*;
 m-as_r = *default_sample_d* * *default_sample_d* / *sphere*;
 m-ad_r = *default_detector_d* * *default_detector_d* / *sphere*;
 m-ae_r = *default_entrance_d* * *default_entrance_d* / *sphere*;
 m-aw_r = 1.0 - *m-as_r* - *m-ad_r* - *m-ae_r*;
 m-rd_r = 0.0;
 m-rw_r = 1.0;
 m-rstd_r = 1.0;
 m-f_r = 0.0;
 m-d_sphere_t = *default_sphere_d*;
 m-as_t = *m-as_r*;
 m-ad_t = *m-ad_r*;
 m-ae_t = *m-ae_r*;
 m-aw_t = *m-aw_r*;
 m-rd_t = 0.0;
 m-rw_t = 1.0;
 m-rstd_t = 1.0;
 m-f_t = 0.0;
 m-lambda = 0.0;
 m-d_beam = 0.0;
 m-ur1_lost = 0;
 m-uru_lost = 0;
 m-ut1_lost = 0;
 m-utu_lost = 0;
 $\}$

This code is used in section 35.

64. To avoid interfacing with C-structures it is necessary to pass the information as arrays. Here I have divided the experiment into (1) setup, (2) reflection sphere coefficients, (3) transmission sphere coefficients, (4) measurements, and (5) results.

⟨Prototype for *Spheres_Inverse_RT* 64⟩ ≡

```
void Spheres_Inverse_RT(double *setup, double *analysis, double *sphere_r, double *sphere_t, double
    *measurements, double *results)
```

This code is used in sections 37 and 65.

65. ⟨Definition for *Spheres_Inverse_RT* 65⟩ ≡

⟨Prototype for *Spheres_Inverse_RT* 64⟩{ **struct** *measure_type* *m*;

```
struct invert_type r;
```

```
long num_photons;
```

```
double ur1, ut1, uru, utu;
```

```
int i, mc_runs = 1;
```

```
Initialize_Measure(&m);
```

```
⟨handle setup 66⟩
```

```
⟨handle reflection sphere 69⟩
```

```
⟨handle transmission sphere 70⟩
```

```
⟨handle measurement 68⟩
```

```
Initialize_Result(m, &r);
```

```
results[0] = 0;
```

```
results[1] = 0;
```

```
results[2] = 0;
```

```
⟨handle analysis 67⟩
```

```
Inverse_RT(m, &r);
```

```
for (i = 0; i < mc_runs; i++) {
```

```
    MC_Lost(m, r, num_photons, &ur1, &ut1, &uru, &utu, &m.ur1_lost, &m.ut1_lost, &m.uru_lost,
        &m.utu_lost);
```

```
    Inverse_RT(m, &r);
```

```
}
```

```
if ( r . error ≡ IAD_NO_ERROR )
```

```
{
```

```
    results[0] = (1 - r.a) * r.b / m.slab_thickness;
```

```
    results[1] = (r.a) * r.b / m.slab_thickness;
```

```
    results[2] = r.g;
```

```
}
```

```
    results[3] = r . error ; }
```

This code is used in section 35.

66. These are in exactly the same order as the parameters in the .rxt header

```

⟨ handle setup 66 ⟩ ≡
{
    double d_sample_r, d_entrance_r, d_detector_r;
    double d_sample_t, d_entrance_t, d_detector_t;

    m.slab_index = setup[0];
    m.slab_top_slide_index = setup[1];
    m.slab_thickness = setup[2];
    m.slab_top_slide_thickness = setup[3];
    m.d_beam = setup[4];
    m.rstd_r = setup[5];
    m.num_spheres = (int) setup[6];
    m.d_sphere_r = setup[7];
    d_sample_r = setup[8];
    d_entrance_r = setup[9];
    d_detector_r = setup[10];
    m.rw_r = setup[11];
    m.d_sphere_t = setup[12];
    d_sample_t = setup[13];
    d_entrance_t = setup[14];
    d_detector_t = setup[15];
    m.rw_t = setup[16];
    r.default_g = setup[17];
    num_photons = (long) setup[18];
    m.as_r = (d_sample_r/m.d_sphere_r) * (d_sample_r/m.d_sphere_r);
    m.ae_r = (d_entrance_r/m.d_sphere_r) * (d_entrance_r/m.d_sphere_r);
    m.ad_r = (d_detector_r/m.d_sphere_r) * (d_detector_r/m.d_sphere_r);
    m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
    m.as_t = (d_sample_t/m.d_sphere_t) * (d_sample_t/m.d_sphere_t);
    m.ae_t = (d_entrance_t/m.d_sphere_t) * (d_entrance_t/m.d_sphere_t);
    m.ad_t = (d_detector_t/m.d_sphere_t) * (d_detector_t/m.d_sphere_t);
    m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
    m.slab_bottom_slide_index = m.slab_top_slide_index;
    m.slab_bottom_slide_thickness = m.slab_top_slide_thickness;
    fprintf(stderr, "****_executing_FIXME_****\n");
    m.slab_cos_angle = 1.0; /* FIXME */
}

```

This code is used in section 65.

67. ⟨ handle analysis 67 ⟩ ≡
 r.method.quad_pts = (int) analysis[0];
 mc_runs = (int) analysis[1];

This code is used in section 65.

68.

```

⟨ handle measurement 68 ⟩ ≡
    m.m_r = measurements[0];
    m.m_t = measurements[1];
    m.m_u = measurements[2];
    m.num_measures = 3;
    fprintf(stderr, "m.m_t=%f\n", m.m_t);
    fprintf(stderr, "m.m_u=%f\n", m.m_u);
    if (m.m_t == 0) m.num_measures--;
    if (m.m_u == 0) m.num_measures--;

```

This code is used in section 65.

69.

```

⟨ handle reflection sphere 69 ⟩ ≡
    m.as_r = sphere_r[0];
    m.ae_r = sphere_r[1];
    m.ad_r = sphere_r[2];
    m.rw_r = sphere_r[3];
    m.rd_r = sphere_r[4];
    m.rstd_r = sphere_r[5];
    m.f_r = sphere_r[7];

```

This code is used in section 65.

70.

```

⟨ handle transmission sphere 70 ⟩ ≡
    m.as_t = sphere_t[0];
    m.ae_t = sphere_t[1];
    m.ad_t = sphere_t[2];
    m.rw_t = sphere_t[3];
    m.rd_t = sphere_t[4];
    m.rstd_t = sphere_t[5];
    m.f_t = sphere_t[7];

```

This code is used in section 65.

71. I needed a routine that would calculate the values of M_R and M_T without doing the whole inversion process. It seems odd that this does not exist yet.

The values for the lost light *m.uru.lost* etc., should be calculated before calling this routine.

⟨ Prototype for *Calculate_MR_MT* 71 ⟩ ≡

```

void Calculate_MR_MT(struct measure_type m, struct invert_type r, int include_MC, double
    *M_R, double *M_T)

```

This code is used in sections 36 and 72.

72. \langle Definition for *Calculate_MR_MT* 72 $\rangle \equiv$
 \langle Prototype for *Calculate_MR_MT* 71 \rangle
 $\{$
 double *distance*, *ur1*, *ut1*, *uru*, *utu*;
 struct measure_type *old_mm*;
 struct invert_type *old_rr*;
 if (*include_MC* \wedge *m.num_spheres* > 0) *MC_Lost*(*m*, *r*, -2000, &*ur1*, &*ut1*, &*uru*, &*utu*, &(m.ur1_lost),
 &(m.ut1_lost), &(m.uru_lost), &(m.utu_lost));
 Get_Calc_State(&*old_mm*, &*old_rr*);
 Set_Calc_State(*m*, *r*);
 Calculate_Distance(**M_R**, **M_T**, &*distance*);
 Set_Calc_State(*old_mm*, *old_rr*);
 $\}$

This code is used in section 35.

73. So, it turns out that the minimum measured **M_R** can be less than four percent for black glass! This is because the sphere efficiency is much worse for the glass than for the white standard.

\langle Prototype for *Calculate_Minimum_MR* 73 $\rangle \equiv$
 void *Calculate_Minimum_MR*(**struct measure_type** *m*, **struct invert_type** *r*, **double** **mr*, **double** **mt*)

This code is used in sections 36 and 74.

74. \langle Definition for *Calculate_Minimum_MR* 74 $\rangle \equiv$
 \langle Prototype for *Calculate_Minimum_MR* 73 \rangle
 $\{$
 if (*r.default_b* \equiv UNINITIALIZED) *r.slab.b* = 999;
 else *r.slab.b* = *r.default_b*;
 if (*r.default_a* \equiv UNINITIALIZED) *r.slab.a* = 0;
 else *r.slab.a* = *r.default_a*;
 if (*r.default_g* \equiv UNINITIALIZED) *r.slab.g* = 0;
 else *r.slab.g* = *r.default_g*;
 r.a = *r.slab.a*;
 r.b = *r.slab.b*;
 r.g = *r.slab.g*;
 Calculate_MR_MT(*m*, *r*, 0, *mr*, *mt*);
 $\}$

This code is used in section 35.

75. The minimum possible value of **MR** for a given **MT** will be when the albedo is zero and the maximal value will be when the albedo is unity. In the first case there will be light loss and in the second we will assume that light loss is negligible (to maximize **MR**).

The problem is that to calculate these values one must know the optical thickness. Fortunately with the recent addition of constrained minimization, we can do exactly this.

The only thing that remains is to sort out the light lost effect.

\langle Prototype for *MinMax_MR_MT* 75 $\rangle \equiv$
 int *MinMax_MR_MT*(**struct measure_type** *m*, **struct invert_type** *r*)

This code is used in sections 36 and 76.

76. \langle Definition for *MinMax_MR_MT* 76 $\rangle \equiv$
 \langle Prototype for *MinMax_MR_MT* 75 \rangle
 $\{$
 double *distance*, *m_r*, *x*, *min*, *max*;
 if (*m.m_r* < 0) **return** IAD_MR_TOO_SMALL;
 if (*m.m_r* * *m.rstd_r* > 1) **return** IAD_MR_TOO_BIG;
 if (*m.m_t* < 0) **return** IAD_MT_TOO_SMALL;
 if (*m.m_t* \equiv 0) **return** IAD_NO_ERROR;
 m_r = *m.m_r*;
 m.m_r = 0;
 r.search = FIND_B;
 r.default_a = 0;
 U_Find_B(*m*, &*r*);
 Calculate_Distance(&*min*, &*x*, &*distance*);
 if (*m_r* < *min*) **return** IAD_MR_TOO_SMALL;
 r.default_a = 1.0;
 U_Find_B(*m*, &*r*);
 Calculate_Distance(&*max*, &*x*, &*distance*);
 if (*m_r* > *max*) **return** IAD_MR_TOO_BIG;
 return IAD_NO_ERROR;
 $\}$

This code is used in section 35.

77. IAD Input Output.

The special define below is to get Visual C to suppress silly warnings.

```

<iad_io.c 77> ≡
#define _CRT_SECURE_NO_WARNINGS
#include <string.h>
#include <stdio.h>
#include <ctype.h>
#include <math.h>
#include "ad_globl.h"
#include "iad_type.h"
#include "iad_io.h"
#include "iad_pub.h"
#include "version.h"
  <Definition for skip_white 87>
  <Definition for read_number 89>
  <Definition for check_magic 91>
  <Definition for Read_Header 81>
  <Definition for Write_Header 93>
  <Definition for Read_Data_Line 85>

```

```

78. <iad_io.h 78> ≡
  <Prototype for Read_Header 80>;
  <Prototype for Write_Header 92>;
  <Prototype for Read_Data_Line 84>;

```

79. Reading the file header.

```

80. <Prototype for Read_Header 80> ≡
  int Read_Header(FILE *fp, struct measure_type *m, int *params)

```

This code is used in sections 78 and 81.

81. Pretty straightforward stuff. The only thing that needs to be commented on is that only one slide thickness/index is specified in the file. This must be applied to both the top and bottom slides. Finally, to specify no slide, then either setting the slide index to 1.0 or the thickness to 0.0 should do the trick.

```

⟨Definition for Read_Header 81⟩ ≡
⟨Prototype for Read_Header 80⟩
{
    double x;
    Initialize_Measure(m);
    if (check_magic(fp)) return 1;
    if (read_number(fp, &m-slab_index)) return 1;
    if (read_number(fp, &m-slab_top_slide_index)) return 1;
    if (read_number(fp, &m-slab_thickness)) return 1;
    if (read_number(fp, &m-slab_top_slide_thickness)) return 1;
    if (read_number(fp, &m-d_beam)) return 1;
    if (m-slab_top_slide_thickness ≡ 0.0) m-slab_top_slide_index = 1.0;
    if (m-slab_top_slide_index ≡ 1.0) m-slab_top_slide_thickness = 0.0;
    if (m-slab_top_slide_index ≡ 0.0) {
        m-slab_top_slide_thickness = 0.0;
        m-slab_top_slide_index = 1.0;
    }
    m-slab_bottom_slide_index = m-slab_top_slide_index;
    m-slab_bottom_slide_thickness = m-slab_top_slide_thickness;
    if (read_number(fp, &m-rstd_r)) return 1;
    if (read_number(fp, &x)) return 1;
    m-num_spheres = (int) x;
    m-method = SUBSTITUTION;
    ⟨Read coefficients for reflection sphere 82⟩
    ⟨Read coefficients for transmission sphere 83⟩
    if (read_number(fp, &x)) return 1;
    *params = (int) x;
    m-num_measures = (*params ≥ 3) ? 3 : *params;
    return 0;
}

```

This code is used in section 77.

```

82. ⟨Read coefficients for reflection sphere 82⟩ ≡
{
    double d_sample_r, d_entrance_r, d_detector_r;
    if (read_number(fp, &m-d_sphere_r)) return 1;
    if (read_number(fp, &d_sample_r)) return 1;
    if (read_number(fp, &d_entrance_r)) return 1;
    if (read_number(fp, &d_detector_r)) return 1;
    if (read_number(fp, &m-rw_r)) return 1;
    m-as_r = (d_sample_r/m-d_sphere_r) * (d_sample_r/m-d_sphere_r)/4.0;
    m-ae_r = (d_entrance_r/m-d_sphere_r) * (d_entrance_r/m-d_sphere_r)/4.0;
    m-ad_r = (d_detector_r/m-d_sphere_r) * (d_detector_r/m-d_sphere_r)/4.0;
    m-aw_r = 1.0 - m-as_r - m-ae_r - m-ad_r;
}

```

This code is used in section 81.

83. \langle Read coefficients for transmission sphere 83 $\rangle \equiv$

```
{
    double d_sample_t, d_entrance_t, d_detector_t;
    if (read_number(fp, &m-d_sphere_t)) return 1;
    if (read_number(fp, &d_sample_t)) return 1;
    if (read_number(fp, &d_entrance_t)) return 1;
    if (read_number(fp, &d_detector_t)) return 1;
    if (read_number(fp, &m-rw_t)) return 1;
    m-as_t = (d_sample_t/m-d_sphere_t) * (d_sample_t/m-d_sphere_t)/4.0;
    m-ae_t = (d_entrance_t/m-d_sphere_t) * (d_entrance_t/m-d_sphere_t)/4.0;
    m-ad_t = (d_detector_t/m-d_sphere_t) * (d_detector_t/m-d_sphere_t)/4.0;
    m-aw_t = 1.0 - m-as_t - m-ae_t - m-ad_t;
}
```

This code is used in section 81.

84. Reading just one line of a data file.

This reads a line of data based on the value of *params*.

If the first number is greater than one then it is assumed to be the wavelength and is ignored. test on the first value of the line.

A non-zero value is returned upon a failure.

\langle Prototype for *Read_Data_Line* 84 $\rangle \equiv$

```
int Read_Data_Line(FILE *fp, struct measure_type *m, int params)
```

This code is used in sections 78 and 85.

85. \langle Definition for *Read_Data_Line* 85 $\rangle \equiv$

```
 $\langle$  Prototype for Read_Data_Line 84  $\rangle$ 
{
    if (read_number(fp, &m-m_r)) return 1;
    if (m-m_r > 1) {
        m-lambda = m-m_r;
        if (read_number(fp, &m-m_r)) return 1;
    }
    if (params  $\equiv$  1) return 0;
    if (read_number(fp, &m-m_t)) return 1;
    if (params  $\equiv$  2) return 0;
    if (read_number(fp, &m-m_u)) return 1;
    if (params  $\equiv$  3) return 0;
    if (read_number(fp, &m-rw_r)) return 1;
    m-rw_t = m-rw_r;
    if (params  $\equiv$  4) return 0;
    if (read_number(fp, &m-rw_t)) return 1;
    if (params  $\equiv$  5) return 0;
    if (read_number(fp, &m-rstd_r)) return 1;
    if (params  $\equiv$  6) return 0;
    if (read_number(fp, &m-rstd_t)) return 1;
    return 0;
}
```

This code is used in section 77.

86. Skip over white space and comments. It is assumed that `#` starts all comments and continues to the end of a line. This routine should work on files with nearly any line ending CR, LF, CRLF.

Failure is indicated by a non-zero return value.

⟨Prototype for *skip_white* 86⟩ ≡

```
int skip_white(FILE *fp)
```

This code is used in section 87.

87. ⟨Definition for *skip_white* 87⟩ ≡

⟨Prototype for *skip_white* 86⟩

```
{
    int c = fgetc(fp);
    while (!feof(fp)) {
        if (isspace(c)) c = fgetc(fp);
        else if (c == '#') do c = fgetc(fp); while (!feof(fp) & c != '\n' & c != '\r');
        else break;
    }
    if (feof(fp)) return 1;
    ungetc(c, fp);
    return 0;
}
```

This code is used in section 77.

88. Read a single number. Return 0 if there are no problems, otherwise return 1.

⟨Prototype for *read_number* 88⟩ ≡

```
int read_number(FILE *fp, double *x)
```

This code is used in section 89.

89. ⟨Definition for *read_number* 89⟩ ≡

⟨Prototype for *read_number* 88⟩

```
{
    if (skip_white(fp)) return 1;
    if (fscanf(fp, "%lf", x)) return 0;
    else return 1;
}
```

This code is used in section 77.

90. Ensure that the data file is actually in the right form. Return 0 if the file has the right starting characters. Return 1 if on a failure.

⟨Prototype for *check_magic* 90⟩ ≡

```
int check_magic(FILE *fp)
```

This code is used in section 91.

91. \langle Definition for *check_magic* 91 $\rangle \equiv$

```

 $\langle$  Prototype for check_magic 90  $\rangle$ 
{
    char magic[] = "IAD1";
    int i, c;
    for (i = 0; i < 4; i++) {
        c = fgetc(fp);
        if (feof(fp)  $\vee$  c  $\neq$  magic[i]) {
            fprintf(stderr, "Sorry, but iad input files must begin with IAD1\n");
            fprintf(stderr, "as the first four characters of the file.\n");
            fprintf(stderr, "Perhaps you are using an old iad format?\n");
            return 1;
        }
    }
    return 0;
}

```

This code is used in section 77.

92. **Formatting the header information.**

\langle Prototype for *Write_Header* 92 $\rangle \equiv$

```
void Write_Header(struct measure_type m, struct invert_type r, int params)
```

This code is used in sections 78 and 93.

93. \langle Definition for *Write_Header* 93 $\rangle \equiv$

```

 $\langle$  Prototype for Write_Header 92  $\rangle$ 
{
     $\langle$  Write slab info 94  $\rangle$ 
     $\langle$  Write irradiation info 95  $\rangle$ 
     $\langle$  Write general sphere info 96  $\rangle$ 
     $\langle$  Write first sphere info 97  $\rangle$ 
     $\langle$  Write second sphere info 98  $\rangle$ 
     $\langle$  Write measure and inversion info 99  $\rangle$ 
}

```

This code is used in section 77.

94. \langle Write slab info 94 $\rangle \equiv$

```

double xx;
printf("#_Inverse_Adding-Doubling_%s_\n", Version);
printf("#_\n");
printf("#_Beam_diameter_=%7.1f_mm\n", m.d_beam);
printf("#_Sample_thickness_=%7.3f_mm\n", m.slab_thickness);
printf("#_Top_slide_thickness_=%7.3f_mm\n", m.slab_top_slide_thickness);
printf("#_Bottom_slide_thickness_=%7.3f_mm\n", m.slab_bottom_slide_thickness);
printf("#_Sample_index_of_refraction_=%7.4f\n", m.slab_index);
printf("#_Top_slide_index_of_refraction_=%7.4f\n", m.slab_top_slide_index);
printf("#_Bottom_slide_index_of_refraction_=%7.4f\n", m.slab_bottom_slide_index);

```

This code is used in section 93.

95. \langle Write irradiation info 95 $\rangle \equiv$

```
printf("#_\n");
```

This code is used in section 93.

96. { Write general sphere info 96 } \equiv

```
printf("#Fraction_unscattered_refl.in_M_R=%7.1f%%\n", m.fraction_of_rc_in_mr * 100);
printf("#Fraction_unscattered_trans.in_M_T=%7.1f%%\n", m.fraction_of_tc_in_mt * 100);
printf("#\n");
```

This code is used in section 93.

97. { Write first sphere info 97 } \equiv

```
printf("#Reflection_sphere\n");
printf("#sphere_diameter=%7.1fmm\n", m.d_sphere_r);
printf("#sample_port_diameter=%7.1fmm\n", 2 * m.d_sphere_r * sqrt(m.as_r));
printf("#entrance_port_diameter=%7.1fmm\n", 2 * m.d_sphere_r * sqrt(m.ae_r));
printf("#detector_port_diameter=%7.1fmm\n", 2 * m.d_sphere_r * sqrt(m.ad_r));
printf("#wall_reflectance=%7.1f%%\n", m.rw_r * 100);
printf("#standard_reflectance=%7.1f%%\n", m.rstd_r * 100);
printf("#detector_reflectance=%7.1f%%\n", m.rd_r * 100);
printf("#\n");
```

This code is used in section 93.

98. { Write second sphere info 98 } \equiv

```
printf("#Transmission_sphere\n");
printf("#sphere_diameter=%7.1fmm\n", m.d_sphere_t);
printf("#sample_port_diameter=%7.1fmm\n", 2 * m.d_sphere_r * sqrt(m.as_t));
printf("#entrance_port_diameter=%7.1fmm\n", 2 * m.d_sphere_r * sqrt(m.ae_t));
printf("#detector_port_diameter=%7.1fmm\n", 2 * m.d_sphere_r * sqrt(m.ad_t));
printf("#wall_reflectance=%7.1f%%\n", m.rw_t * 100);
printf("#standard_transmittance=%7.1f%%\n", m.rstd_t * 100);
printf("#detector_reflectance=%7.1f%%\n", m.rd_t * 100);
```

This code is used in section 93.

99. \langle Write measure and inversion info 99 $\rangle \equiv$

```

printf("#\n");
switch (params) {
case -1: printf("#No_M_R_or_M_T--_forward_calculation.\n");
        break;
case 1: printf("#Just_M_R_was_measured");
        break;
case 2: printf("#M_R_and_M_T_were_measured");
        break;
case 3: printf("#M_R,_M_T,_and_M_U_were_measured");
        break;
case 4: printf("#M_R,_M_T,_M_U,_and_r_w_were_measured");
        break;
case 5: printf("#M_R,_M_T,_M_U,_r_w,_and_t_w_were_measured");
        break;
case 6: printf("#M_R,_M_T,_M_U,_r_w,_t_w,_and_r_std_were_measured");
        break;
case 7: printf("#M_R,_M_T,_M_U,_r_w,_t_w,_r_std_and_t_std_were_measured");
        break;
default: printf("#Something_went_wrong..._measures_should_be_1_to_5!\n");
        break;
}
if (1 ≤ params ∧ params ≤ 7) {
    if (m.flip_sample) printf("_sample_flipped_");
    switch (m.method) {
    case UNKNOWN: printf("_using_an_unknown_method.\n");
        break;
    case SUBSTITUTION: printf("_using_the_substitution_(single-beam)_method.\n");
        break;
    case COMPARISON: printf("_using_the_comparison_(dual-beam)_method.\n");
        break;
    }
}
switch (m.num_spheres) {
case 0: printf("#No_sphere_corrections_were_used");
        break;
case 1: printf("#Single_sphere_corrections_were_used");
        break;
case 2: printf("#Double_sphere_corrections_were_used");
        break;
}
printf("_with_light_incident_at_%d_degrees_from_the_normal",
      (int)(acos(m.slab_cos_angle) * 57.2958));
printf(".\n");
switch (r.search) {
case FIND_AB: printf("#The_inverse_routine_varied_the_albedo_and_optical_depth.\n");
    printf("#\n");
    xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
    printf("#Default_single_scattering_anisotropy_=%7.3f\n", xx);
    break;
case FIND_AG: printf("#The_inverse_routine_varied_the_albedo_and_anisotropy.\n");
    printf("#\n");
}

```

```

    if (r.default_b ≠ UNINITIALIZED)
        printf("#_Default(mu_t*d)=%7.3g\n", r.default_b);
    else printf("#_\n");
    break;
case FIND_AUTO: printf("#_The_inverse_routine_adapted_to_the_input_data.\n");
    printf("#_\n");
    printf("#_\n");
    break;
case FIND_A: printf("#_The_inverse_routine_varied_only_the_albedo.\n");
    printf("#_\n");
    xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
    printf("#_Default_single_scattering_anisotropy_is_%7.3f\n", xx);
    xx = (r.default_b ≠ UNINITIALIZED) ? r.default_b : HUGE_VAL;
    printf("_and(mu_t*d)=%7.3g\n", xx);
    break;
case FIND_B: printf("#_The_inverse_routine_varied_only_the_optical_depth.\n");
    printf("#_\n");
    xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
    printf("#_Default_single_scattering_anisotropy_is_%7.3f\n", xx);
    if (r.default_a ≠ UNINITIALIZED) printf("and_default_albedo=%7.3g\n", r.default_a);
    else printf("\n");
    break;
case FIND_Ba: printf("#_The_inverse_routine_varied_only_the_absorption.\n");
    printf("#_\n");
    xx = (r.default_bs ≠ UNINITIALIZED) ? r.default_bs : 0;
    printf("#_Default(mu_s*d)=%7.3g\n", xx);
    break;
case FIND_Bs: printf("#_The_inverse_routine_varied_only_the_scattering.\n");
    printf("#_\n");
    xx = (r.default_ba ≠ UNINITIALIZED) ? r.default_ba : 0;
    printf("#_Default(mu_a*d)=%7.3g\n", xx);
    break;
default: printf("#_\n");
    printf("#_\n");
    printf("#_\n");
    break;
}
printf("#_AD_quadrature_points=%3d\n", r.method.quad_pts);
printf("#_AD_tolerance_for_success=%9.5f\n", r.tolerance);
printf("#_MC_tolerance_for_mu_a_and_mu_s'=%7.3f%%\n", r.MC_tolerance);

```

This code is used in section 93.

100. IAD Calculation.

```

<iad_calc.c 100> ≡
#include <math.h>
#include <string.h>
#include <stdio.h>
#include <stdlib.h>
#include "nr_util.h"
#include "nr_zbrent.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "ad_prime.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#define ABIT 1 · 10-6
#define A_COLUMN 1
#define B_COLUMN 2
#define G_COLUMN 3
#define URU_COLUMN 4
#define UTU_COLUMN 5
#define UR1_COLUMN 6
#define UT1_COLUMN 7
#define REFLECTION_SPHERE 1
#define TRANSMISSION_SPHERE 0
#define GRID_SIZE 101
#define T_TRUST_FACTOR 2
static int CALCULATING_GRID = 1;
static struct measure_type MM;
static struct invert_type RR;
static struct measure_type MGRID;
static struct invert_type RGRID;
static double **The_Grid = Λ;
static double GG_a;
static double GG_b;
static double GG_g;
static double GG_bs;
static double GG_ba;
static boolean_type The_Grid_Initialized = FALSE;
static boolean_type The_Grid_Search = -1;
<Definition for Set_Calc_State 116>
<Definition for Get_Calc_State 118>
<Definition for Same_Calc_State 120>
<Prototype for Fill_AB_Grid 138>;
<Prototype for Fill_AG_Grid 143>;
<Definition for RT_Flip 136>
<Definition for Allocate_Grid 122>
<Definition for Valid_Grid 126>
<Definition for fill_grid_entry 137>
<Definition for Fill_Grid 153>
<Definition for Near_Grid_Points 134>
<Definition for Fill_AB_Grid 139>
<Definition for Fill_AG_Grid 144>

```

⟨ Definition for *Fill_BG_Grid* 147 ⟩
 ⟨ Definition for *Fill_BaG_Grid* 149 ⟩
 ⟨ Definition for *Fill_BsG_Grid* 151 ⟩
 ⟨ Definition for *Grid_ABG* 124 ⟩
 ⟨ Definition for *Gain* 105 ⟩
 ⟨ Definition for *Gain_11* 107 ⟩
 ⟨ Definition for *Gain_22* 109 ⟩
 ⟨ Definition for *Two_Sphere_R* 111 ⟩
 ⟨ Definition for *Two_Sphere_T* 113 ⟩
 ⟨ Definition for *Calculate_Distance_With_Corrections* 159 ⟩
 ⟨ Definition for *Calculate_Grid_Distance* 157 ⟩
 ⟨ Definition for *Calculate_Distance* 155 ⟩
 ⟨ Definition for *abg_distance* 132 ⟩
 ⟨ Definition for *Find_AG_fn* 169 ⟩
 ⟨ Definition for *Find_AB_fn* 171 ⟩
 ⟨ Definition for *Find_Ba_fn* 173 ⟩
 ⟨ Definition for *Find_Bs_fn* 175 ⟩
 ⟨ Definition for *Find_A_fn* 177 ⟩
 ⟨ Definition for *Find_B_fn* 179 ⟩
 ⟨ Definition for *Find_G_fn* 181 ⟩
 ⟨ Definition for *Find_BG_fn* 183 ⟩
 ⟨ Definition for *Find_BaG_fn* 185 ⟩
 ⟨ Definition for *Find_BsG_fn* 187 ⟩
 ⟨ Definition for *maxloss* 189 ⟩
 ⟨ Definition for *Max_Light_Loss* 191 ⟩

101.

```

< iad_calc.h 101 > ≡
  < Prototype for Gain 104 >;
  < Prototype for Gain_11 106 >;
  < Prototype for Gain_22 108 >;
  < Prototype for Two_Sphere_R 110 >;
  < Prototype for Two_Sphere_T 112 >;
  < Prototype for Set_Calc_State 115 >;
  < Prototype for Get_Calc_State 117 >;
  < Prototype for Same_Calc_State 119 >;
  < Prototype for Valid_Grid 125 >;
  < Prototype for Allocate_Grid 121 >;
  < Prototype for Fill_Grid 152 >;
  < Prototype for Near_Grid_Points 133 >;
  < Prototype for Grid_ABG 123 >;
  < Prototype for Find_AG_fn 168 >;
  < Prototype for Find_AB_fn 170 >;
  < Prototype for Find_Ba_fn 172 >;
  < Prototype for Find_Bs_fn 174 >;
  < Prototype for Find_A_fn 176 >;
  < Prototype for Find_B_fn 178 >;
  < Prototype for Find_G_fn 180 >;
  < Prototype for Find_BG_fn 182 >;
  < Prototype for Find_BsG_fn 186 >;
  < Prototype for Find_BaG_fn 184 >;
  < Prototype for Fill_BG_Grid 146 >;
  < Prototype for Fill_BsG_Grid 150 >;
  < Prototype for Fill_BaG_Grid 148 >;
  < Prototype for Calculate_Distance_With_Corrections 158 >;
  < Prototype for Calculate_Distance 154 >;
  < Prototype for Calculate_Grid_Distance 156 >;
  < Prototype for abg_distance 131 >;
  < Prototype for maxloss 188 >;
  < Prototype for Max_Light_Loss 190 >;

```

102. Initialization.

The functions in this file assume that the local variables **MM** and **RR** have been initialized appropriately. The variable **MM** contains all the information about how a particular experiment was done. The structure **RR** contains the data structure that is passed to the adding-doubling routines as well as the number of quadrature points.

history 6/8/94 changed error output to *stderr*.

103. Gain.

Assume that a sphere is illuminated with diffuse light having a power P . This light can reach all parts of sphere — specifically, light from this source is not blocked by a baffle. Multiple reflections in the sphere will increase the power falling on non-white areas in the sphere (e.g., the sample, detector, and entrance) To find the total we need to sum all the total of all incident light at a point. The first incidence is

$$P_w^{(1)} = a_w P, \quad P_s^{(1)} = a_s P, \quad P_d^{(1)} = a_d P$$

The light from the detector and sample is multiplied by $(1 - a_e)$ and not by a_w because the light from the detector (and sample) is not allowed to hit either the detector or sample. The second incidence on the wall is

$$P_w^{(2)} = a_w r_w P_w^{(1)} + (1 - a_e) r_d P_d^{(1)} + (1 - a_e) r_s P_s^{(1)}$$

The light that hits the walls after k bounces has the same form as above

$$P_w^{(k)} = a_w r_w P_w^{(k-1)} + (1 - a_e) r_d P_d^{(k-1)} + (1 - a_e) r_s P_s^{(k-1)}$$

Since the light falling on the sample and detector must come from the wall

$$P_s^{(k)} = a_s r_w P_w^{(k-1)} \quad \text{and} \quad P_d^{(k)} = a_d r_w P_w^{(k-1)},$$

Therefore,

$$P_w^{(k)} = a_w r_w P_w^{(k-1)} + (1 - a_e) r_w (a_d r_d + a_s r_s) P_w^{(k-2)}$$

The total power falling on the walls is just

$$P_w = \sum_{k=1}^{\infty} P_w^{(k)} = \frac{a_w + (1 - a_e)(a_d r_d + a_s r_s)}{1 - a_w r_w - (1 - a_e) r_w (a_d r_d + a_s r_s)} P$$

The total power falling the detector is

$$P_d = a_d P + \sum_{k=2}^{\infty} a_d r_w P_w^{(k-1)} = a_d P + a_d r_w P_w$$

The gain $G(r_s)$ on the irradiance on the detector (relative to a black sphere),

$$G(r_s) \equiv \frac{P_d/A_d}{P/A}$$

in terms of the sphere parameters

$$G(r_s) = 1 + \frac{1}{a_w} \cdot \frac{a_w r_w + (1 - a_e) r_w (a_d r_d + a_s r_s)}{1 - a_w r_w - (1 - a_e) r_w (a_d r_d + a_s r_s)}$$

The gain for a detector in a transmission sphere is similar, but with primed parameters to designate a second potential sphere that is used. For a black sphere the gain $G(0) = 1$, which is easily verified by setting $r_w = 0$, $r_s = 0$, and $r_d = 0$. Conversely, when the sphere walls and sample are perfectly white, the irradiance at the entrance port, the sample port, and the detector port must increase so that the total power leaving via these ports is equal to the incident diffuse power P . Thus the gain should be the ratio of the sphere wall area over the area of the ports through which light leaves or $G(1) = A/(A_e + A_d)$ which follows immediately from the gain formula with $r_w = 1$, $r_s = 1$, and $r_d = 0$.

104. The gain $G(r_s)$ on the irradiance on the detector (relative to a black sphere),

$$G(r_s) \equiv \frac{P_d/A_d}{P/A}$$

in terms of the sphere parameters

$$G(r_s) = 1 + \frac{a_w r_w + (1 - a_e) r_w (a_d r_d + a_s r_s)}{1 - a_w r_w - (1 - a_e) r_w (a_d r_d + a_s r_s)}$$

⟨Prototype for *Gain* 104⟩ ≡

double *Gain*(**int** *sphere*, **struct** *measure_type* *m*, **double** URU)

This code is used in sections 101 and 105.

105. ⟨Definition for *Gain* 105⟩ ≡

⟨Prototype for *Gain* 104⟩

```
{
  double G, tmp;
  if (sphere == REFLECTION_SPHERE) {
    tmp = m.rw_r * (m.aw_r + (1 - m.ae_r) * (m.ad_r * m.rd_r + m.as_r * URU));
    if (tmp == 1.0) G = 1;
    else G = 1.0 + tmp / (1.0 - tmp);
  }
  else {
    tmp = m.rw_t * (m.aw_t + (1 - m.ae_t) * (m.ad_t * m.rd_t + m.as_t * URU));
    if (tmp == 1.0) G = 1;
    else G = 1.0 + tmp / (1.0 - tmp);
  }
  return G;
}
```

This code is used in section 100.

106. The gain for light on the detector in the first sphere for diffuse light starting in that same sphere is defined as

$$G_{1 \rightarrow 1}(r_s, t_s) \equiv \frac{P_{1 \rightarrow 1}(r_s, t_s)/A_d}{P/A}$$

then the full expression for the gain is

$$G_{1 \rightarrow 1}(r_s, t_s) = \frac{G(r_s)}{1 - a_s a'_s r_w r'_w (1 - a_e) (1 - a'_e) G(r_s) G'(r_s) t_s^2}$$

⟨Prototype for *Gain_11* 106⟩ ≡

double *Gain_11*(**struct** *measure_type* *m*, **double** URU, **double** *tdiffuse*)

This code is used in sections 101 and 107.

107. $\langle \text{Definition for } \textit{Gain_11} \text{ } 107 \rangle \equiv$
 $\langle \text{Prototype for } \textit{Gain_11} \text{ } 106 \rangle$
 $\{$
 $\quad \text{double } G, \text{ GP, G11};$
 $\quad G = \textit{Gain}(\text{REFLECTION_SPHERE}, m, \text{URU});$
 $\quad \text{GP} = \textit{Gain}(\text{TRANSMISSION_SPHERE}, m, \text{URU});$
 $\quad \text{G11} = G / (1 - m.as_r * m.as_t * m.aw_r * m.aw_t * (1 - m.ae_r) * (1 - m.ae_t) * G * \text{GP} * tdiffuse * tdiffuse);$
 $\quad \text{return G11};$
 $\}$

This code is used in section 100.

108. Similarly, when the light starts in the second sphere, the gain for light on the detector in the second sphere $G_{2 \rightarrow 2}$ is found by switching all primed variables to unprimed. Thus $G_{2 \rightarrow 1}(r_s, t_s)$ is

$$G_{2 \rightarrow 2}(r_s, t_s) = \frac{G'(r_s)}{1 - a_s a'_s r_w r'_w (1 - a_e)(1 - a'_e) G(r_s) G'(r_s) t_s^2}$$

$\langle \text{Prototype for } \textit{Gain_22} \text{ } 108 \rangle \equiv$
 $\text{double } \textit{Gain_22}(\text{struct measure_type } m, \text{double URU}, \text{double } tdiffuse)$

This code is used in sections 101 and 109.

109. $\langle \text{Definition for } \textit{Gain_22} \text{ } 109 \rangle \equiv$
 $\langle \text{Prototype for } \textit{Gain_22} \text{ } 108 \rangle$
 $\{$
 $\quad \text{double } G, \text{ GP, G22};$
 $\quad G = \textit{Gain}(\text{REFLECTION_SPHERE}, m, \text{URU});$
 $\quad \text{GP} = \textit{Gain}(\text{TRANSMISSION_SPHERE}, m, \text{URU});$
 $\quad \text{G22} = \text{GP} / (1 - m.as_r * m.as_t * m.aw_r * m.aw_t * (1 - m.ae_r) * (1 - m.ae_t) * G * \text{GP} * tdiffuse * tdiffuse);$
 $\quad \text{return G22};$
 $\}$

This code is used in section 100.

110. The reflected power for two spheres makes use of the formulas for *Gain_11* above.

The light on the detector in the reflection (first) sphere arises from three sources: the fraction of light directly reflected off the sphere wall $f r_w^2 (1 - a_e) P$, the fraction of light reflected by the sample $(1 - f) r_s^{\text{direct}} r_w^2 (1 - a_e) P$, and the light transmitted through the sample $(1 - f) t_s^{\text{direct}} r'_w (1 - a'_e) P$,

$$\begin{aligned} R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= G_{1 \rightarrow 1}(r_s, t_s) \cdot a_d (1 - a_e) r_w^2 f P \\ &\quad + G_{1 \rightarrow 1}(r_s, t_s) \cdot a_d (1 - a_e) r_w (1 - f) r_s^{\text{direct}} P \\ &\quad + G_{2 \rightarrow 1}(r_s, t_s) \cdot a_d (1 - a'_e) r'_w (1 - f) t_s^{\text{direct}} P \end{aligned}$$

which simplifies slightly to

$$\begin{aligned} R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= a_d (1 - a_e) r_w P \cdot G_{1 \rightarrow 1}(r_s, t_s) \\ &\quad \times \left[(1 - f) r_s^{\text{direct}} + f r_w + (1 - f) a'_s (1 - a'_e) r'_w t_s^{\text{direct}} t_s G'(r_s) \right] \end{aligned}$$

$\langle \text{Prototype for } \textit{Two_Sphere_R} \text{ } 110 \rangle \equiv$
 $\text{double } \textit{Two_Sphere_R}(\text{struct measure_type } m, \text{double UR1}, \text{double URU}, \text{double UT1}, \text{double UTU})$

This code is used in sections 101 and 111.

111. \langle Definition for *TwoSphere_R* 111 $\rangle \equiv$

\langle Prototype for *TwoSphere_R* 110 \rangle

```
{
  double x, GP;
  GP = Gain(TRANSMISSION_SPHERE, m, URU);
  x = m.ad_r * (1 - m.ae_r) * m.rw_r * Gain_11(m, URU, UTU);
  x *= (1 - m.f_r) * UR1 + m.rw_r * m.f_r + (1 - m.f_r) * m.as_t * (1 - m.ae_t) * m.rw_t * UT1 * UTU * GP;
  return x;
}
```

This code is used in section 100.

112. For the power on the detector in the transmission (second) sphere we have the same three sources. The only difference is that the subscripts on the gain terms now indicate that the light ends up in the second sphere

$$\begin{aligned} T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= G_{1 \rightarrow 2}(r_s, t_s) \cdot a'_d(1 - a_e)r_w^2 f P \\ &\quad + G_{1 \rightarrow 2}(r_s, t_s) \cdot a'_d(1 - a_e)r_w(1 - f)r_s^{\text{direct}} P \\ &\quad + G_{2 \rightarrow 2}(r_s, t_s) \cdot a'_d(1 - a'_e)r'_w(1 - f)t_s^{\text{direct}} P \end{aligned}$$

or

$$\begin{aligned} T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= a'_d(1 - a'_e)r'_w P \cdot G_{2 \rightarrow 2}(r_s, t_s) \\ &\quad \times \left[(1 - f)t_s^{\text{direct}} + (1 - a_e)r_w a_s t_s (f r_w + (1 - f)r_s^{\text{direct}}) G(r_s) \right] \end{aligned}$$

\langle Prototype for *TwoSphere_T* 112 $\rangle \equiv$

double *TwoSphere_T*(**struct** *measure_type* m, **double** UR1, **double** URU, **double** UT1, **double** UTU)

This code is used in sections 101 and 113.

113. \langle Definition for *TwoSphere_T* 113 $\rangle \equiv$

\langle Prototype for *TwoSphere_T* 112 \rangle

```
{
  double x, G;
  G = Gain(REFLECTION_SPHERE, m, URU);
  x = m.ad_t * (1 - m.ae_t) * m.rw_t * Gain_22(m, URU, UTU);
  x *= (1 - m.f_r) * UT1 + (1 - m.ae_r) * m.rw_r * m.as_r * UTU * (m.f_r * m.rw_r + (1 - m.f_r) * UR1) * G;
  return x;
}
```

This code is used in section 100.

114. Grid Routines. There is a long story associated with these routines. I spent a lot of time trying to find an empirical function to allow a guess at a starting value for the inversion routine. Basically nothing worked very well. There were too many special cases and what not. So I decided to calculate a whole bunch of reflection and transmission values and keep their associated optical properties linked nearby.

I did the very simplest thing. I just allocate a matrix that is five columns wide. Then I fill every row with a calculated set of optical properties and observables. The distribution of values that I use could certainly use some work, but they currently work.

SO... how does this thing work anyway? There are two possible grids one for calculations requiring the program to find the albedo and the optical depth (*a* and *b*) and one to find the albedo and anisotropy (*a* and *g*). These grids must be allocated and initialized before use.

115. This is a pretty important routine that should have some explanation. The reason that it exists, is that we need some ‘out-of-band’ information during the minimization process. Since the light transport calculation depends on all sorts of stuff (e.g., the sphere parameters) and the minimization routines just vary one or two parameters this information needs to be put somewhere.

I chose the global variables **MM** and **RR** to save things in.

The bottom line is that you cannot do a light transport calculation without calling this routine first.

⟨Prototype for *Set_Calc_State* 115⟩ ≡

```
void Set_Calc_State(struct measure_type m, struct invert_type r)
```

This code is used in sections 101 and 116.

116. ⟨Definition for *Set_Calc_State* 116⟩ ≡

⟨Prototype for *Set_Calc_State* 115⟩

```
{
    memcpy(&MM, &m, sizeof(struct measure_type));
    memcpy(&RR, &r, sizeof(struct invert_type));
    if (Debug(DEBUG_ITERATIONS) ^ !CALCULATING_GRID) {
        fprintf(stderr, "UR1_loss=%g, UT1_loss=%g\n", m.ur1_lost, m.ut1_lost);
        fprintf(stderr, "URU_loss=%g, UTU_loss=%g\n", m.uru_lost, m.utu_lost);
    }
}
```

This code is used in section 100.

117. The inverse of the previous routine. Note that you must have space for the parameters *m* and *r* already allocated.

⟨Prototype for *Get_Calc_State* 117⟩ ≡

```
void Get_Calc_State(struct measure_type *m, struct invert_type *r)
```

This code is used in sections 101 and 118.

118. ⟨Definition for *Get_Calc_State* 118⟩ ≡

⟨Prototype for *Get_Calc_State* 117⟩

```
{
    memcpy(m, &MM, sizeof(struct measure_type));
    memcpy(r, &RR, sizeof(struct invert_type));
}
```

This code is used in section 100.

119. The inverse of the previous routine. Note that you must have space for the parameters *m* and *r* already allocated.

⟨Prototype for *Same_Calc_State* 119⟩ ≡

```
boolean_type Same_Calc_State(struct measure_type m, struct invert_type r)
```

This code is used in sections 101 and 120.

120. $\langle \text{Definition for } \textit{Same_Calc_State} \text{ 120} \rangle \equiv$
 $\langle \text{Prototype for } \textit{Same_Calc_State} \text{ 119} \rangle$
 {
 if ($\textit{The_Grid} \equiv \Lambda$) **return** FALSE;
 if ($\neg \textit{The_Grid_Initialized}$) **return** FALSE;
 if ($r.\textit{search} \neq \textit{RR.search}$) **return** FALSE;
 if ($r.\textit{method.quad_pts} \neq \textit{RR.method.quad_pts}$) **return** FALSE;
 if ($r.\textit{slab.a} \neq \textit{RR.slab.a}$) **return** FALSE;
 if ($r.\textit{slab.b} \neq \textit{RR.slab.b}$) **return** FALSE;
 if ($r.\textit{slab.g} \neq \textit{RR.slab.g}$) **return** FALSE;
 if ($r.\textit{slab.phase_function} \neq \textit{RR.slab.phase_function}$) **return** FALSE;
 if ($r.\textit{slab.n_slab} \neq \textit{RR.slab.n_slab}$) **return** FALSE;
 if ($r.\textit{slab.n_top_slide} \neq \textit{RR.slab.n_top_slide}$) **return** FALSE;
 if ($r.\textit{slab.n_bottom_slide} \neq \textit{RR.slab.n_bottom_slide}$) **return** FALSE;
 if ($r.\textit{slab.b_top_slide} \neq \textit{RR.slab.b_top_slide}$) **return** FALSE;
 if ($r.\textit{slab.b_bottom_slide} \neq \textit{RR.slab.b_bottom_slide}$) **return** FALSE;
 if ($r.\textit{slab.cos_angle} \neq \textit{RR.slab.cos_angle}$) **return** FALSE;
 if ($(m.\textit{num_measures} \equiv 3) \wedge (m.\textit{m_u} \neq \textit{MGRID.m_u})$) **return** (FALSE);
 return TRUE;
 }

This code is used in section 100.

121. $\langle \text{Prototype for } \textit{Allocate_Grid} \text{ 121} \rangle \equiv$
 void *Allocate_Grid*(**search_type** *s*)

This code is used in sections 101 and 122.

122. $\langle \text{Definition for } \textit{Allocate_Grid} \text{ 122} \rangle \equiv$
 $\langle \text{Prototype for } \textit{Allocate_Grid} \text{ 121} \rangle$
 {
 The_Grid = *dmatrix*(0, GRID_SIZE * GRID_SIZE, 1, 7);
 if ($\textit{The_Grid} \equiv \Lambda$) *AD_error*("unable to allocate the grid matrix");
 The_Grid_Initialized = FALSE;
 }

This code is used in section 100.

123. This routine will return the *a*, *b*, and *g* values for a particular row in the grid.

$\langle \text{Prototype for } \textit{Grid_ABG} \text{ 123} \rangle \equiv$
 void *Grid_ABG*(**int** *i*, **int** *j*, **guess_type** **guess*)

This code is used in sections 101 and 124.

124. $\langle \text{Definition for } Grid_ABG \text{ 124} \rangle \equiv$
 $\langle \text{Prototype for } Grid_ABG \text{ 123} \rangle$
 $\{$
 if $(0 \leq i \wedge i < GRID_SIZE \wedge 0 \leq j \wedge j < GRID_SIZE)$ $\{$
 $guess \rightarrow a = The_Grid[GRID_SIZE * i + j][A_COLUMN];$
 $guess \rightarrow b = The_Grid[GRID_SIZE * i + j][B_COLUMN];$
 $guess \rightarrow g = The_Grid[GRID_SIZE * i + j][G_COLUMN];$
 $guess \rightarrow distance = Calculate_Grid_Distance(i, j);$
 $\}$
 else $\{$
 $guess \rightarrow a = 0.5;$
 $guess \rightarrow b = 0.5;$
 $guess \rightarrow g = 0.5;$
 $guess \rightarrow distance = 999;$
 $\}$
 $\}$

This code is used in section 100.

125. This routine is used to figure out if the current grid is valid. This can fail for several reasons. First the grid may not have been allocated. Or it may not have been initialized. The boundary conditions may have changed. The number or values of the sphere parameters may have changed. It is tedious, but straightforward to check these cases out.

If this routine returns true, then it is a pretty good bet that the values in the current grid can be used to guess the next starting set of values.

$\langle \text{Prototype for } Valid_Grid \text{ 125} \rangle \equiv$
boolean_type *Valid_Grid*(**struct measure_type** *m*, **search_type** *s*)

This code is used in sections 101 and 126.

126. $\langle \text{Definition for } Valid_Grid \text{ 126} \rangle \equiv$
 $\langle \text{Prototype for } Valid_Grid \text{ 125} \rangle$
 $\{$
 $\langle \text{Tests for invalid grid 127} \rangle$
 return (TRUE);
 $\}$

This code is used in section 100.

127. First check are to test if the grid has ever been filled

$\langle \text{Tests for invalid grid 127} \rangle \equiv$
 if $(The_Grid \equiv \Lambda)$ **return** (FALSE);
 if $(\neg The_Grid_Initialized)$ **return** (FALSE);

See also sections 128, 129, and 130.

This code is used in section 126.

128. If the type of search has changed then report the grid as invalid

$\langle \text{Tests for invalid grid 127} \rangle + \equiv$
 if $(The_Grid_Search \neq s)$ **return** (FALSE);

129. Compare the *m.m_u* value only if there are three measurements

$\langle \text{Tests for invalid grid 127} \rangle + \equiv$
 if $((m.num_measures \equiv 3) \wedge (m.m_u \neq MGRID.m_u))$ **return** (FALSE);

130. Make sure that the boundary conditions have not changed.

⟨ Tests for invalid grid 127 ⟩ +≡

```

if (m.slab_index ≠ MGRID.slab_index) return (FALSE);
if (m.slab_cos_angle ≠ MGRID.slab_cos_angle) return (FALSE);
if (m.slab_top_slide_index ≠ MGRID.slab_top_slide_index) return (FALSE);
if (m.slab_bottom_slide_index ≠ MGRID.slab_bottom_slide_index) return (FALSE);

```

131. Routine to just figure out the distance to a particular a, b, g point

⟨ Prototype for *abg_distance* 131 ⟩ ≡

```

void abg_distance(double a, double b, double g, guess_type *guess)

```

This code is used in sections 101 and 132.

132. ⟨ Definition for *abg_distance* 132 ⟩ ≡

```

⟨ Prototype for abg_distance 131 ⟩
{
    double m_r, m_t, distance;
    struct measure_type old_mm;
    struct invert_type old_rr;
    Get_Calc_State(&old_mm, &old_rr);
    RR.slab.a = a;
    RR.slab.b = b;
    RR.slab.g = g;
    Calculate_Distance(&m_r, &m_t, &distance);
    Set_Calc_State(old_mm, old_rr);
    guess-a = a;
    guess-b = b;
    guess-g = g;
    guess-distance = distance;
}

```

This code is used in section 100.

133. This just searches through the grid to find the minimum entry and returns the optical properties of that entry. The smallest, the next smallest, and the third smallest values are returned.

This has been rewritten to use *Calculate_Distance_With_Corrections* so that changes in sphere parameters won't necessitate recalculating the grid.

⟨ Prototype for *Near_Grid_Points* 133 ⟩ ≡

```

void Near_Grid_Points(double r, double t, search_type s, int *i_min, int *j_min)

```

This code is used in sections 101 and 134.

134. \langle Definition for *Near_Grid_Points* 134 $\rangle \equiv$
 \langle Prototype for *Near_Grid_Points* 133 \rangle

```

{
    int i, j;
    double fval;
    double smallest = 10.0;
    struct measure_type old_mm;
    struct invert_type old_rr;
    Get_Calc_State(&old_mm, &old_rr);
    *i_min = 0;
    *j_min = 0;
    for (i = 0; i < GRID_SIZE; i++) {
        for (j = 0; j < GRID_SIZE; j++) {
            CALCULATING_GRID = 1;
            fval = Calculate_Grid_Distance(i, j);
            CALCULATING_GRID = 0;
            if (fval < smallest) {
                *i_min = i;
                *j_min = j;
                smallest = fval;
            }
        }
    }
    Set_Calc_State(old_mm, old_rr);
}

```

This code is used in section 100.

135. Routine to incorporate flipping of sample if needed. This is pretty simple. The assumption is that flipping is handled relative to the reflection side of the sphere. Thus even when flipping is needed, the usual call to `RT()` will result in the correct values for the reflectances. The transmission values can then be calculated by swapping the top and bottom slides.

Technically, the value of `slab` should be `const` but it is not so that we don't pay a copying overhead whenever `flip` is false (the usual case).

\langle Prototype for *RT_Flip* 135 $\rangle \equiv$

```

void RT_Flip(int flip, int n, struct AD_slab_type *slab, double *UR1, double *UT1, double
             *URU, double *UTU)

```

This code is used in section 136.

136. \langle Definition for *RT_Flip* 136 $\rangle \equiv$
 \langle Prototype for *RT_Flip* 135 \rangle
 {
 double *swap*, *correct_UR1*, *correct_URU*;
 RT(*n*, *slab*, UR1, UT1, URU, UTU);
 if (*flip*) {
 correct_UR1 = *UR1;
 correct_URU = *URU;
 swap = *slab-n_top_slide*;
 slab-n_top_slide = *slab-n_bottom_slide*;
 slab-n_bottom_slide = *swap*;
 swap = *slab-b_top_slide*;
 slab-b_top_slide = *slab-b_bottom_slide*;
 slab-b_bottom_slide = *swap*;
 RT(*n*, *slab*, UR1, UT1, URU, UTU);
 swap = *slab-n_top_slide*;
 slab-n_top_slide = *slab-n_bottom_slide*;
 slab-n_bottom_slide = *swap*;
 swap = *slab-b_top_slide*;
 slab-b_top_slide = *slab-b_bottom_slide*;
 slab-b_bottom_slide = *swap*;
 *UR1 = *correct_UR1*;
 *URU = *correct_URU*;
 }
 }

This code is used in section 100.

137. Simple routine to put values into the grid

Presumes that *RR.slab* is properly set up.

⟨ Definition for *fill_grid_entry* 137 ⟩ ≡

```
static void fill_grid_entry(int i, int j)
{
    double ur1, ut1, uru, utu;
    if (RR.slab.b ≤ 1 · 10-6) RR.slab.b = 1 · 10-6;
    if (Debug(DEBUG_EVERY_CALC))
        fprintf(stderr, "a=%8.5f b=%10.5f g=%8.5f", RR.slab.a, RR.slab.b, RR.slab.g);
    RT_Flip(MM.flip_sample, RR.method.quad_pts, &RR.slab, &ur1, &ut1, &uru, &utu);
    if (Debug(DEBUG_EVERY_CALC)) fprintf(stderr, "ur1=%8.5f ut1=%8.5f\n", ur1, ut1);
    The_Grid[GRID_SIZE * i + j][A_COLUMN] = RR.slab.a;
    The_Grid[GRID_SIZE * i + j][B_COLUMN] = RR.slab.b;
    The_Grid[GRID_SIZE * i + j][G_COLUMN] = RR.slab.g;
    The_Grid[GRID_SIZE * i + j][UR1_COLUMN] = ur1;
    The_Grid[GRID_SIZE * i + j][UT1_COLUMN] = ut1;
    The_Grid[GRID_SIZE * i + j][URU_COLUMN] = uru;
    The_Grid[GRID_SIZE * i + j][UTU_COLUMN] = utu;
    if (Debug(DEBUG_GRID)) {
        fprintf(stderr, "+_2d_2d", i, j);
        fprintf(stderr, "%10.5f %10.5f %10.5f |", RR.slab.a, RR.slab.b, RR.slab.g);
        fprintf(stderr, "%10.5f %10.5f |", MM.m_r, uru);
        fprintf(stderr, "%10.5f %10.5f\n", MM.m_t, utu);
    }
}
```

This code is used in section 100.

138. This routine fills the grid with a proper set of values. With a little work, this routine could be made much faster by (1) only generating the phase function matrix once, (2) Making only one pass through the array for each albedo value, i.e., using the matrix left over from $b = 1$ to generate the solution for $b = 2$. Unfortunately this would require a complete revision of the *Calculate_Distance* routine. Fortunately, this routine should only need to be calculated once at the beginning of each run.

⟨ Prototype for *Fill_AB_Grid* 138 ⟩ ≡

```
void Fill_AB_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 100 and 139.

139. \langle Definition for *Fill_AB_Grid* 139 $\rangle \equiv$
 \langle Prototype for *Fill_AB_Grid* 138 \rangle

```

{
  int i, j;
  double a;
  double min_b = -8; /* exp(-10) is smallest thickness */
  double max_b = +8; /* exp(+8) is greatest thickness */
  if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling_AB_grid\n");
  if (The_Grid  $\equiv$   $\Lambda$ ) Allocate_Grid(r.search);
   $\langle$  Zero GG 145  $\rangle$ 
  Set_Calc_State(m, r);
  GG_g = RR.slab.g;
  for (i = 0; i < GRID_SIZE; i++) {
    double x = (double) i / (GRID_SIZE - 1.0);
    RR.slab.b = exp(min_b + (max_b - min_b) * x);
    for (j = 0; j < GRID_SIZE; j++) {
       $\langle$  Generate next albedo using j 141  $\rangle$ 
      fill_grid_entry(i, j);
    }
  }
  The_Grid_Initialized = TRUE;
  The_Grid_Search = FIND_AB;
}

```

This code is used in section 100.

140. Now it seems that I must be a bit more subtle in choosing the range of albedos to use in the grid. Originally I just spaced them according to

$$a = 1 - \left[\frac{j-1}{n-1} \right]^3$$

where $1 \leq j \leq n$. Long ago it seems that I based things only on the square of the bracketed term, but I seem to remember that I was forced to change it from a square to a cube to get more global convergence.

So why am I rewriting this? Well, because it works very poorly for samples with small albedos. For example, when $n = 11$ then the values chosen for a are (1, .999, .992, .973, .936, .875, .784, .657, .488, .271, 0). Clearly very skewed towards high albedos.

I am considering a two part division. I'm not too sure how it should go. Let the first half be uniformly divided and the last half follow the cubic scheme given above. The list of values should then be (1, .996, .968, .892, 0.744, .5, .4, .3, .2, .1, 0).

Maybe it would be best if I just went back to a quadratic term. Who knows?

In the **if** statement below, note that it could read $j \geq k$ and still generate the same results.

\langle Nonworking code 140 $\rangle \equiv$

```

k = floor((GRID_SIZE - 1)/2);
if (j > k) {
  a = 0.5 * (1 - (j - k - 1)/(GRID_SIZE - k - 1));
  RR.slab.a = a;
}
else {
  a = (j - 1.0)/(GRID_SIZE - k - 1);
  RR.slab.a = 1.0 - a * a * a/2;
}

```

141. Well, the above code did not work well. So I futzed around and sort of empirically ended up using the very simple method below. The only real difference from the previous method what that the method is now quadratic and not cubic.

```

⟨ Generate next albedo using j 141 ⟩ ≡
  a = (double) j/(GRID_SIZE - 1.0);
  if (a < 0.25) RR.slabs.a = 1.0 - a * a;
  else if (a > 0.75) RR.slabs.a = (1.0 - a) * (1.0 - a);
  else RR.slabs.a = 1 - a;

```

See also section 142.

This code is used in sections 139 and 144.

142. Well, the above code has gaps. Here is an attempt to eliminate the gaps

```

⟨ Generate next albedo using j 141 ⟩ +≡
  a = (double) j/(GRID_SIZE - 1.0);
  RR.slabs.a = (1.0 - a * a) * (1.0 - a) + (1.0 - a) * (1.0 - a) * a;

```

143. This is quite similar to *Fill_AB_Grid*, with the exception of the little shuffle I do at the beginning to figure out the optical thickness to use. The problem is that the optical thickness may not be known. If it is known then the only way that we could have gotten here is if the user dictated **FIND_AG** and specified *b* and only provided two measurements. Otherwise, the user must have made three measurements and the optical depth can be figured out from *m.m.u*.

This routine could also be improved by not recalculating the anisotropy matrix for every point. But this would only end up being a minor performance enhancement if it were fixed.

```

⟨ Prototype for Fill_AG_Grid 143 ⟩ ≡
  void Fill_AG_Grid(struct measure_type m, struct invert_type r)

```

This code is used in sections 100 and 144.

```

144.  ⟨ Definition for Fill_AG_Grid 144 ⟩ ≡
  ⟨ Prototype for Fill_AG_Grid 143 ⟩
  {
    int i, j;
    double a;
    if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling_AG_grid\n");
    if (The_Grid ≡ Λ) Allocate_Grid(r.search);
    ⟨ Zero GG 145 ⟩
    Set_Calc_State(m, r);
    GG_b = r.slabs.b;
    for (i = 0; i < GRID_SIZE; i++) {
      RR.slabs.g = 0.9999 * (2.0 * i/(GRID_SIZE - 1.0) - 1.0);
      for (j = 0; j < GRID_SIZE; j++) {
        ⟨ Generate next albedo using j 141 ⟩
        fill_grid_entry(i, j);
      }
    }
    The_Grid_Initialized = TRUE;
    The_Grid_Search = FIND_AG;
  }

```

This code is used in section 100.

145.

```

⟨Zero GG 145⟩ ≡
    GG_a = 0.0;
    GG_b = 0.0;
    GG_g = 0.0;
    GG_bs = 0.0;
    GG_ba = 0.0;

```

This code is used in sections 139, 144, 147, 149, and 151.

146. This is quite similar to *Fill_AB_Grid*, with the exception of the that the albedo is held fixed while b and g are varied.

This routine could also be improved by not recalculating the anisotropy matrix for every point. But this would only end up being a minor performance enhancement if it were fixed.

```

⟨Prototype for Fill_BG_Grid 146⟩ ≡
    void Fill_BG_Grid(struct measure_type m, struct invert_type r)

```

This code is used in sections 101 and 147.

147. ⟨Definition for *Fill_BG_Grid* 147⟩ ≡

```

⟨Prototype for Fill_BG_Grid 146⟩
{
    int i, j;
    if (The_Grid ≡ Λ) Allocate_Grid(r.search);
    ⟨Zero GG 145⟩
    if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling_BG_grid\n");
    Set_Calc_State(m, r);
    RR.slab.b = 1.0/32.0;
    RR.slab.a = RR.default_a;
    GG_a = RR.slab.a;
    for (i = 0; i < GRID_SIZE; i++) {
        RR.slab.b *= 2;
        for (j = 0; j < GRID_SIZE; j++) {
            RR.slab.g = 0.9999 * (2.0 * j / (GRID_SIZE - 1.0) - 1.0);
            fill_grid_entry(i, j);
        }
    }
    The_Grid_Initialized = TRUE;
    The_Grid_Search = FIND_BG;
}

```

This code is used in section 100.

148. This is quite similar to *Fill_BG_Grid*, with the exception of the that the $b_s = \mu_s d$ is held fixed. Here b and g are varied on the usual grid, but the albedo is forced to take whatever value is needed to ensure that the scattering constant remains fixed.

```

⟨Prototype for Fill_BaG_Grid 148⟩ ≡
    void Fill_BaG_Grid(struct measure_type m, struct invert_type r)

```

This code is used in sections 101 and 149.

149. $\langle \text{Definition for } \textit{Fill_BaG_Grid} \text{ 149} \rangle \equiv$
 $\langle \text{Prototype for } \textit{Fill_BaG_Grid} \text{ 148} \rangle$

```

{
  int i, j;
  double bs, ba;
  if (The_Grid  $\equiv \Lambda$ ) Allocate_Grid(r.search);
   $\langle \text{Zero GG 145} \rangle$ 
  if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling_BaG_grid\n");
  Set_Calc_State(m, r);
  ba = 1.0/32.0;
  bs = RR.default_bs;
  GG_bs = bs;
  for (i = 0; i < GRID_SIZE; i++) {
    ba *= 2;
    ba = exp(((double) i / (GRID_SIZE - 1.0) * log(1024.0)) / 16.0);
    RR.slab.b = ba + bs;
    if (RR.slab.b > 0) RR.slab.a = bs / RR.slab.b;
    else RR.slab.a = 0;
    for (j = 0; j < GRID_SIZE; j++) {
      RR.slab.g = 0.9999 * (2.0 * j / (GRID_SIZE - 1.0) - 1.0);
      fill_grid_entry(i, j);
    }
  }
  The_Grid_Initialized = TRUE;
  The_Grid_Search = FIND_BaG;
}

```

This code is used in section 100.

150. Very similiar to the above routine. The value of $b_a = \mu_a d$ is held constant.

$\langle \text{Prototype for } \textit{Fill_BsG_Grid} \text{ 150} \rangle \equiv$
void *Fill_BsG_Grid*(**struct** *measure_type m*, **struct** *invert_type r*)

This code is used in sections 101 and 151.

151. \langle Definition for *Fill_BsG_Grid* 151 $\rangle \equiv$
 \langle Prototype for *Fill_BsG_Grid* 150 \rangle
{
 int *i*, *j*;
 double *bs*, *ba*;
 if (*The_Grid* $\equiv \Lambda$) *Allocate_Grid*(*r.search*);
 \langle Zero **GG** 145 \rangle
 Set_Calc_State(*m*, *r*);
 bs = 1.0/32.0;
 ba = *RR.default_ba*;
 GG_ba = *ba*;
 for (*i* = 0; *i* < **GRID_SIZE**; *i*++) {
 bs *= 2;
 RR.slab.b = *ba* + *bs*;
 if (*RR.slab.b* > 0) *RR.slab.a* = *bs*/*RR.slab.b*;
 else *RR.slab.a* = 0;
 for (*j* = 0; *j* < **GRID_SIZE**; *j*++) {
 RR.slab.g = 0.9999 * (2.0 * *j* / (**GRID_SIZE** - 1.0) - 1.0);
 fill_grid_entry(*i*, *j*);
 }
 }
 The_Grid_Initialized = **TRUE**;
 The_Grid_Search = *FIND_BsG*;
}

This code is used in section 100.

152. \langle Prototype for *Fill_Grid* 152 $\rangle \equiv$
void *Fill_Grid*(**struct** *measure_type* *m*, **struct** *invert_type* *r*)

This code is used in sections 101 and 153.

153. \langle Definition for *Fill_Grid* 153 $\rangle \equiv$
 \langle Prototype for *Fill_Grid* 152 \rangle

```

{
  if ( $\neg$ Same_Calc_State(m,r)) {
    switch (r.search) {
      case FIND_AB:
        if (Debug(DEBUG_SEARCH)) fprintf(stderr,"filling_AB_Grid\n");
        Fill_AB_Grid(m,r);
        break;
      case FIND_AG:
        if (Debug(DEBUG_SEARCH)) fprintf(stderr,"filling_AG_Grid\n");
        Fill_AG_Grid(m,r);
        break;
      case FIND_BG:
        if (Debug(DEBUG_SEARCH)) fprintf(stderr,"filling_BG_Grid\n");
        Fill_BG_Grid(m,r);
        break;
      case FIND_BaG:
        if (Debug(DEBUG_SEARCH)) fprintf(stderr,"filling_BaG_Grid\n");
        Fill_BaG_Grid(m,r);
        break;
      case FIND_BsG:
        if (Debug(DEBUG_SEARCH)) fprintf(stderr,"filling_BsG_Grid\n");
        Fill_BsG_Grid(m,r);
        break;
      default: AD_error("Attempt_to_fill_grid_for_unusual_search_case.");
    }
  }
  Get_Calc_State(&MGRID, &RGRID);
}

```

This code is used in section 100.

154. Calculating R and T.

Calculate_Distance returns the distance between the measured values in MM and the calculated values for the current guess at the optical properties. It assumes that the everything in the local variables MM and RR have been set appropriately.

\langle Prototype for *Calculate_Distance* 154 $\rangle \equiv$

```

void Calculate_Distance(double *M_R, double *M_T, double *deviation)

```

This code is used in sections 101 and 155.

155. \langle Definition for *Calculate_Distance* 155 $\rangle \equiv$
 \langle Prototype for *Calculate_Distance* 154 \rangle
 $\{$
 double *Rc, Tc, ur1, ut1, uru, utu*;
 if (*RR.slab.b* $\leq 1 \cdot 10^{-6}$) *RR.slab.b* = $1 \cdot 10^{-6}$;
 if (*Debug*(*DEBUG_EVERY_CALC*))
 fprintf(*stderr*, "a=%8.5f b=%10.5f g=%8.5f", *RR.slab.a*, *RR.slab.b*, *RR.slab.g*);
 RT_Flip(*MM.flip_sample*, *RR.method.quad_pts*, &*RR.slab*, &*ur1*, &*ut1*, &*uru*, &*utu*);
 if (*Debug*(*DEBUG_EVERY_CALC*))
 fprintf(*stderr*, "ur1=%8.5f ut1=%8.5f (not M_R and M_T!) \n", *ur1*, *ut1*);
 Sp_mu_RT_Flip(*MM.flip_sample*, *RR.slab.n_top_slide*, *RR.slab.n_slab*, *RR.slab.n_bottom_slide*,
 RR.slab.b_top_slide, *RR.slab.b*, *RR.slab.b_bottom_slide*, *RR.slab.cos_angle*, &*Rc*, &*Tc*);
 if ((\neg *CALCULATING_GRID* \wedge *Debug*(*DEBUG_ITERATIONS*)) \vee (*CALCULATING_GRID* \wedge *Debug*(*DEBUG_GRID*)))
 fprintf(*stderr*, "UUUUUUUU");
 Calculate_Distance_With_Corrections(*ur1*, *ut1*, *Rc*, *Tc*, *uru*, *utu*, *M_R*, *M_T*, *deviation*);
 $\}$

This code is used in section 100.

156. \langle Prototype for *Calculate_Grid_Distance* 156 $\rangle \equiv$
 double *Calculate_Grid_Distance*(**int** *i*, **int** *j*)

This code is used in sections 101 and 157.

157. \langle Definition for *Calculate_Grid_Distance* 157 $\rangle \equiv$
 \langle Prototype for *Calculate_Grid_Distance* 156 \rangle
 $\{$
 double *ur1, ut1, uru, utu, Rc, Tc, b, dev, LR, LT*;
 if (*Debug*(*DEBUG_GRID*)) *fprintf*(*stderr*, "g_%2d_%2d", *i*, *j*);
 b = *The_Grid*[*GRID_SIZE* * *i* + *j*][*B_COLUMN*];
 ur1 = *The_Grid*[*GRID_SIZE* * *i* + *j*][*UR1_COLUMN*];
 ut1 = *The_Grid*[*GRID_SIZE* * *i* + *j*][*UT1_COLUMN*];
 uru = *The_Grid*[*GRID_SIZE* * *i* + *j*][*URU_COLUMN*];
 utu = *The_Grid*[*GRID_SIZE* * *i* + *j*][*UTU_COLUMN*];
 RR.slab.a = *The_Grid*[*GRID_SIZE* * *i* + *j*][*A_COLUMN*];
 RR.slab.b = *The_Grid*[*GRID_SIZE* * *i* + *j*][*B_COLUMN*];
 RR.slab.g = *The_Grid*[*GRID_SIZE* * *i* + *j*][*G_COLUMN*];
 Sp_mu_RT_Flip(*MM.flip_sample*, *RR.slab.n_top_slide*, *RR.slab.n_slab*, *RR.slab.n_bottom_slide*,
 RR.slab.b_top_slide, *b*, *RR.slab.b_bottom_slide*, *RR.slab.cos_angle*, &*Rc*, &*Tc*);
 CALCULATING_GRID = 1;
 Calculate_Distance_With_Corrections(*ur1*, *ut1*, *Rc*, *Tc*, *uru*, *utu*, &*LR*, &*LT*, &*dev*);
 CALCULATING_GRID = 0;
 return *dev*;
 $\}$

This code is used in section 100.

158. This is the routine that actually finds the distance. I have factored this part out so that it can be used in the *Near_Grid_Point* routine.

Rc and *Tc* refer to the unscattered (collimated) reflection and transmission.

The only tricky part is to remember that the we are trying to match the measured values. The measured values are affected by sphere parameters and light loss. Since the values *UR1* and *UT1* are for an infinite slab sample with no light loss, the light loss out the edges must be subtracted. It is these values that are used with the sphere formulas to convert the modified *UR1* and *UT1* to values for **M_R* and **M_T*.

⟨Prototype for *Calculate_Distance_With_Corrections* 158⟩ ≡

```
void Calculate_Distance_With_Corrections(double UR1,double UT1,double Rc,double Tc,double
    URU,double UTU,double *M_R,double *M_T,double *dev)
```

This code is used in sections 101 and 159.

159. ⟨Definition for *Calculate_Distance_With_Corrections* 159⟩ ≡

⟨Prototype for *Calculate_Distance_With_Corrections* 158⟩

```
{
    double R_direct, T_direct, R_diffuse, T_diffuse;
    R_diffuse = URU - MM.uru_lost;
    T_diffuse = UTU - MM.utu_lost;
    R_direct = UR1 - MM.ur1_lost - (1.0 - MM.fraction_of_rc_in_mr) * Rc;
    T_direct = UT1 - MM.ut1_lost - (1.0 - MM.fraction_of_tc_in_mt) * Tc;
    switch (MM.num_spheres) {
    case 0: ⟨Calc M_R and M_T for no spheres 160⟩
        break;
    case 1: case -2:
        if (MM.method ≡ COMPARISON) ⟨Calc M_R and M_T for dual beam sphere 162⟩
        else ⟨Calc M_R and M_T for single beam sphere 161⟩
            break;
    case 2: ⟨Calc M_R and M_T for two spheres 163⟩
        break;
    }
    ⟨Calculate the deviation 164⟩
    ⟨Print diagnostics 167⟩
}
```

This code is used in section 100.

160. If no spheres were used in the measurement, then presumably the measured values are the reflection and transmission. Consequently, we just ascertain what the irradiance was and whether the specular reflection ports were blocked and proceed accordingly. Note that blocking the ports does not have much meaning unless the light is collimated, and therefore the reflection and transmission is only modified for collimated irradiance.

⟨Calc M_R and M_T for no spheres 160⟩ ≡

```
*M_R = R_direct;
*M_T = T_direct;
```

This code is used in section 159.

161. The direct incident power is $(1 - f)P$. The reflected power will be $(1 - f)r_s^{\text{direct}}P$. Since baffles ensure that the light cannot reach the detector, we must bounce the light off the sphere walls to use to above gain formulas. The contribution will then be $(1 - f)r_s^{\text{direct}}(1 - a_e)r_wP$. The measured power will be

$$P_d = a_d(1 - a_e)r_w[(1 - f)r_s^{\text{direct}} + fr_w]P \cdot G(r_s)$$

Similarly the power falling on the detector measuring transmitted light is

$$P'_d = a'_d t_s^{\text{direct}} r'_w (1 - a'_e) P \cdot G'(r_s)$$

when the ‘entrance’ port in the transmission sphere is closed, $a'_e = 0$.

The normalized sphere measurements are

$$M_R = r_{\text{std}} \cdot \frac{R(r_s^{\text{direct}}, r_s) - R(0, 0)}{R(r_{\text{std}}, r_{\text{std}}) - R(0, 0)}$$

and

$$M_T = t_{\text{std}} \cdot \frac{T(t_s^{\text{direct}}, r_s) - T(0, 0)}{T(t_{\text{std}}, r_{\text{std}}) - T(0, 0)}$$

⟨ Calc M_R and M_T for single beam sphere 161 ⟩ ≡

```
{
  double P_std, P_d, P_0;
  double G, G_0, G_std, GP_std, GP;
  G_0 = Gain(REFLECTION_SPHERE, MM, 0.0);
  G = Gain(REFLECTION_SPHERE, MM, R_diffuse);
  G_std = Gain(REFLECTION_SPHERE, MM, MM.rstd_r);
  P_d = G * (R_direct * (1 - MM.f_r) + MM.f_r * MM.rw_r);
  P_std = G_std * (MM.rstd_r * (1 - MM.f_r) + MM.f_r * MM.rw_r);
  P_0 = G_0 * (MM.f_r * MM.rw_r);
  *M_R = MM.rstd_r * (P_d - P_0) / (P_std - P_0);
  GP = Gain(TRANSMISSION_SPHERE, MM, R_diffuse);
  GP_std = Gain(TRANSMISSION_SPHERE, MM, 0.0);
  *M_T = T_direct * GP / GP_std;
}
```

This code is used in section 159.

162. The dual beam case is different because the sphere efficiency is equivalent for measurement of light hitting the sample first or hitting the reference standard first. The dual beam measurement should report the ratio of these two reflectance measurements, thereby eliminating the need to calculate the gain completely. The same holds when no sample is present.

The normalized reflectance measurement (the difference between dual beam measurement for a port with the sample and with nothing) is

$$M_R = r_{\text{std}} \cdot \frac{(1-f)r_s^{\text{direct}} + fr_w}{(1-f')r_{\text{std}} - f'r_w} - r_{\text{std}} \cdot \frac{(1-f)(0) + fr_w}{(1-f')r_{\text{std}} - f'r_w}$$

or

$$M_R = \frac{(1-f)r_s^{\text{direct}}}{(1-f') - f'r_w/r_{\text{std}}}$$

When $f = f' = 1$, then $M_R = 1$ no matter what the reflectance is. (Leave it in this form to avoid division by zero when $f = 1$.)

The normalized transmittance is simply t_s^{direct} .

When $f = 0$ then this result is essentially the same as the no spheres result (because no sphere corrections are needed). However if the number of spheres is zero, then no lost light calculations are made and therefore that is a potential error.

```
< Calc M_R and M_T for dual beam sphere 162 > ≡
{
  *M_R = (1 - MM.f_r) * R_direct / ((1 - MM.f_r) + MM.f_r * MM.rw_r / MM.rstd_r);
  *M_T = T_direct;
}
```

This code is used in section 159.

163. When two integrating spheres are present then the double integrating sphere formulas are slightly more complicated.

I am not sure what it means when r_{std_t} is not unity.

The normalized sphere measurements for two spheres are

$$M_R = \frac{R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) - R(0, 0, 0, 0)}{R(r_{\text{std}}, r_{\text{std}}, 0, 0) - R(0, 0, 0, 0)}$$

and

$$M_T = \frac{T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) - T(0, 0, 0, 0)}{T(0, 0, 1, 1) - T(0, 0, 0, 0)}$$

Note that R_0 and T_0 will be zero unless one has explicitly set the fraction $m.f_r$ or $m.f_t$ to be non-zero.

```
< Calc M_R and M_T for two spheres 163 > ≡
{
  double R_0, T_0;
  R_0 = Two_Sphere_R(MM, 0, 0, 0, 0);
  T_0 = Two_Sphere_T(MM, 0, 0, 0, 0);
  *M_R = (Two_Sphere_R(MM, R_direct, R_diffuse, T_direct, T_diffuse) - R_0) / (Two_Sphere_R(MM,
    MM.rstd_r, MM.rstd_r, 0, 0) - R_0);
  *M_T = (Two_Sphere_T(MM, R_direct, R_diffuse, T_direct, T_diffuse) - T_0) / (Two_Sphere_T(MM, 0, 0, 1,
    1) - T_0);
}
```

This code is used in section 159.

164. There are at least three things that need to be considered here. First, the number of measurements. Second, is the metric is relative or absolute. And third, is the albedo fixed at zero which means that the transmission measurement should be used instead of the reflection measurement.

```

⟨ Calculate the deviation 164 ⟩ ≡
  if (RR.search ≡ FIND_A ∨ RR.search ≡ FIND_G ∨ RR.search ≡ FIND_B ∨ RR.search ≡ FIND_Bs ∨ RR.search ≡
      FIND_Ba) {
    ⟨ One parameter deviation 165 ⟩
  }
  else {
    ⟨ Two parameter deviation 166 ⟩
  }

```

This code is used in section 159.

165. This part was slightly tricky. The crux of the problem was to decide if the transmission or the reflection was trustworthy. After looking a bunches of measurements, I decided that the transmission measurement was almost always more reliable. So when there is just a single measurement known, then use the total transmission if it exists.

```

⟨ One parameter deviation 165 ⟩ ≡
  if (MM.m_t > 0) {
    if (RR.metric ≡ RELATIVE) *dev = fabs(MM.m_t - *M_T)/(MM.m_t + ABIT);
    else *dev = fabs(MM.m_t - *M_T);
  }
  else {
    if (RR.metric ≡ RELATIVE) *dev = fabs(MM.m_r - *M_R)/(MM.m_r + ABIT);
    else *dev = fabs(MM.m_r - *M_R);
  }

```

This code is used in section 164.

166. This stuff happens when we are doing two parameter searches. In these cases there should be information in both R and T. The distance should be calculated using the deviation from both. The albedo stuff might be able to be take out. We'll see.

```

⟨ Two parameter deviation 166 ⟩ ≡
  if (RR.metric ≡ RELATIVE) {
    *dev = 0;
    if (MM.m_t > ABIT) *dev = T_TRUST_FACTOR * fabs(MM.m_t - *M_T)/(MM.m_t + ABIT);
    if (RR.default_a ≠ 0) *dev += fabs(MM.m_r - *M_R)/(MM.m_r + ABIT);
  }
  else {
    *dev = T_TRUST_FACTOR * fabs(MM.m_t - *M_T);
    if (RR.default_a ≠ 0) *dev += fabs(MM.m_r - *M_R);
  }

```

This code is used in section 164.

```

⟨Print diagnostics 167⟩ ≡
  if ((Debug(DEBUG_ITERATIONS) ∧ ¬CALCULATING_GRID) ∨ (Debug(DEBUG_GRID) ∧ CALCULATING_GRID)) {
    static int once = 0;
    if (once ≡ 0) {
      fprintf(stderr, "%10s□%10s□%10s□|%10s□%10s□%10s□%10s□\n", "a", "b", "g", "m_r", "fit",
        "m_t", "fit", "delta");
      once = 1;
    }
    fprintf(stderr, "%10.5f□%10.5f□%10.5f□| ", RR.slab.a, RR.slab.b, RR.slab.g);
    fprintf(stderr, "%10.5f□%10.5f□| ", MM.m_r, *M_R);
    fprintf(stderr, "%10.5f□%10.5f□| ", MM.m_t, *M_T);
    fprintf(stderr, "%10.5f□\n", *dev);
  }

```

```
168.  ⟨Prototype for Find_AG_fn 168⟩ ≡
      double Find_AG_fn(double x[])
```

```

169.  ⟨ Definition for Find_AG_fn 169 ⟩ ≡
    ⟨ Prototype for Find_AG_fn 168 ⟩
    {
      double m_r, m_t, deviation;
      RR.slab.a = acalc2a(x[1]);
      RR.slab.g = gcalc2g(x[2]);
      Calculate_Distance(&m_r, &m_t, &deviation);
      return deviation;
    }

```

```
170.  ⟨Prototype for Find_AB_fn 170⟩ ≡
      double Find_AB_fn(double x[])
```

```

171.    ⟨ Definition for Find_AB_fn 171 ⟩ ≡
    ⟨ Prototype for Find_AB_fn 170 ⟩
    {
        double m_r, m_t, deviation;
        RR.slab.a = acalc2a(x[1]);
        RR.slab.b = bcalc2b(x[2]);
        Calculate_Distance(&m_r, &m_t, &deviation);
        return deviation;
    }

```

172. $\langle \text{Prototype for } Find_Ba_fn \text{ 172} \rangle \equiv$
 double *Find_Ba_fn*(**double** *x*)

This code is used in sections 101 and 173.

173. This is tricky only because the value in `RR.slab.b` is used to hold the value of bs or $d \cdot \mu_s$. It must be switched to the correct value for the optical thickness and then switched back at the end of the routine.

```

⟨Definition for Find_Ba_fn 173⟩ ≡
⟨Prototype for Find_Ba_fn 172⟩
{
  double m_r, m_t, deviation, ba, bs;
  bs = RR.slab.b;
  ba = bcalc2b(x);
  RR.slab.b = ba + bs;    /* unswindle */
  RR.slab.a = bs/(ba + bs);
  Calculate_Distance(&m_r, &m_t, &deviation);
  RR.slab.b = bs;        /* swindle */
  return deviation;
}

```

This code is used in section 100.

174. See the comments for the *Find_Ba_fn* routine above. Play the same trick but use ba .

```

⟨Prototype for Find_Bs_fn 174⟩ ≡
double Find_Bs_fn(double x)

```

This code is used in sections 101 and 175.

```

175. ⟨Definition for Find_Bs_fn 175⟩ ≡
⟨Prototype for Find_Bs_fn 174⟩
{
  double m_r, m_t, deviation, ba, bs;
  ba = RR.slab.b;    /* unswindle */
  bs = bcalc2b(x);
  RR.slab.b = ba + bs;
  RR.slab.a = bs/(ba + bs);
  Calculate_Distance(&m_r, &m_t, &deviation);
  RR.slab.b = ba;    /* swindle */
  return deviation;
}

```

This code is used in section 100.

```

176. ⟨Prototype for Find_A_fn 176⟩ ≡
double Find_A_fn(double x)

```

This code is used in sections 101 and 177.

```

177. ⟨Definition for Find_A_fn 177⟩ ≡
⟨Prototype for Find_A_fn 176⟩
{
  double m_r, m_t, deviation;
  RR.slab.a = acalc2a(x);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}

```

This code is used in section 100.

178. \langle Prototype for *Find_B_fn* 178 $\rangle \equiv$
double *Find_B_fn*(**double** *x*)

This code is used in sections 101 and 179.

179. \langle Definition for *Find_B_fn* 179 $\rangle \equiv$
 \langle Prototype for *Find_B_fn* 178 \rangle
 {
 double *m_r*, *m_t*, *deviation*;
 RR.slab.b = *bcalc2b*(*x*);
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 100.

180. \langle Prototype for *Find_G_fn* 180 $\rangle \equiv$
double *Find_G_fn*(**double** *x*)

This code is used in sections 101 and 181.

181. \langle Definition for *Find_G_fn* 181 $\rangle \equiv$
 \langle Prototype for *Find_G_fn* 180 \rangle
 {
 double *m_r*, *m_t*, *deviation*;
 RR.slab.g = *gcalc2g*(*x*);
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 100.

182. \langle Prototype for *Find_BG_fn* 182 $\rangle \equiv$
double *Find_BG_fn*(**double** *x*[])

This code is used in sections 101 and 183.

183. \langle Definition for *Find_BG_fn* 183 $\rangle \equiv$
 \langle Prototype for *Find_BG_fn* 182 \rangle
 {
 double *m_r*, *m_t*, *deviation*;
 RR.slab.b = *bcalc2b*(*x*[1]);
 RR.slab.g = *gcalc2g*(*x*[2]);
 RR.slab.a = RR.default_a;
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 100.

184. For this function the first term *x*[1] will contain the value of $\mu_s d$, the second term will contain the anisotropy. Of course the first term is in the bizarre calculation space and needs to be translated back into normal terms before use. We just at the scattering back on and voilà we have a useable value for the optical depth.

\langle Prototype for *Find_BaG_fn* 184 $\rangle \equiv$
double *Find_BaG_fn*(**double** *x*[])

This code is used in sections 101 and 185.

185. $\langle \text{Definition for } Find_BaG_fn \text{ 185} \rangle \equiv$
 $\langle \text{Prototype for } Find_BaG_fn \text{ 184} \rangle$
 $\{$
 double $m_r, m_t, deviation;$
 $RR.slab.b = bcalc2b(x[1]) + RR.default_bs;$
 if ($RR.slab.b \leq 0$) $RR.slab.a = 0;$
 else $RR.slab.a = RR.default_bs/RR.slab.b;$
 $RR.slab.g = gcalc2g(x[2]);$
 $Calculate_Distance(\&m_r, \&m_t, \&deviation);$
 return $deviation;$
 $\}$

This code is used in section 100.

186. $\langle \text{Prototype for } Find_BsG_fn \text{ 186} \rangle \equiv$
 double $Find_BsG_fn(\text{double } x[])$

This code is used in sections 101 and 187.

187. $\langle \text{Definition for } Find_BsG_fn \text{ 187} \rangle \equiv$
 $\langle \text{Prototype for } Find_BsG_fn \text{ 186} \rangle$
 $\{$
 double $m_r, m_t, deviation;$
 $RR.slab.b = bcalc2b(x[1]) + RR.default_ba;$
 if ($RR.slab.b \leq 0$) $RR.slab.a = 0;$
 else $RR.slab.a = 1.0 - RR.default_ba/RR.slab.b;$
 $RR.slab.g = gcalc2g(x[2]);$
 $Calculate_Distance(\&m_r, \&m_t, \&deviation);$
 return $deviation;$
 $\}$

This code is used in section 100.

188. Routine to figure out if the light loss exceeds what is physically possible. Returns the discrepancy between the current values and the maximum possible values for the the measurements m_r and m_t .

$\langle \text{Prototype for } maxloss \text{ 188} \rangle \equiv$
 double $maxloss(\text{double } f)$

This code is used in sections 101 and 189.

189. \langle Definition for *maxloss* 189 $\rangle \equiv$
 \langle Prototype for *maxloss* 188 \rangle
 {
 struct **measure_type** *m_old*;
 struct **invert_type** *r_old*;
 double *m_r*, *m_t*, *deviation*;
 Get_Calc_State(&*m_old*, &*r_old*);
 RR.*slab.a* = 1.0;
 MM.*ur1_lost* *= *f*;
 MM.*ut1_lost* *= *f*;
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 Set_Calc_State(*m_old*, *r_old*);
 deviation = ((MM.*m_r* + MM.*m_t*) - (*m_r* + *m_t*));
 return *deviation*;
 }

This code is used in section 100.

190. This checks the two light loss values *ur1_loss* and *ut1_loss* to see if they exceed what is physically possible. If they do, then these values are replaced by a couple that are the maximum possible for the current values in *m* and *r*.

\langle Prototype for *Max_Light_Loss* 190 $\rangle \equiv$
 void *Max_Light_Loss*(**struct** **measure_type** *m*, **struct** **invert_type** *r*, **double** **ur1_loss*, **double** **ut1_loss*)

This code is used in sections 101 and 191.

191. \langle Definition for *Max_Light_Loss* 191 $\rangle \equiv$
 \langle Prototype for *Max_Light_Loss* 190 \rangle
 {
 struct **measure_type** *m_old*;
 struct **invert_type** *r_old*;
 **ur1_loss* = *m.ur1_lost*;
 **ut1_loss* = *m.ut1_lost*;
 if (*Debug*(DEBUG_LOST_LIGHT))
 fprintf(*stderr*, "\nlost before ur1=%7.5f, ut1=%7.5f\n", **ur1_loss*, **ut1_loss*);
 Get_Calc_State(&*m_old*, &*r_old*);
 Set_Calc_State(*m*, *r*);
 if (*maxloss*(1.0) * *maxloss*(0.0) < 0) {
 double *frac*;
 frac = *zbrent*(*maxloss*, 0.00, 1.0, 0.001);
 **ur1_loss* = *m.ur1_lost* * *frac*;
 **ut1_loss* = *m.ut1_lost* * *frac*;
 }
 Set_Calc_State(*m_old*, *r_old*);
 if (*Debug*(DEBUG_LOST_LIGHT))
 fprintf(*stderr*, "\nlost after ur1=%7.5f, ut1=%7.5f\n", **ur1_loss*, **ut1_loss*);
 }

This code is used in section 100.

192. this is currently unused

⟨ Unused diffusion fragment 192 ⟩ ≡

```
static void DE_RT(int nfluxes, AD_slab_type slab, double *UR1, double *UT1, double *URU, double
    *UTU)
{
    slabtype s;
    double rp, tp, rs, ts;
    s.f = slab.g * slab.g;
    s.gprime = slab.g / (1 + slab.g);
    s.aprime = (1 - s.f) * slab.a / (1 - slab.a * s.f);
    s.bprime = (1 - slab.a * s.f) * slab.b;
    s.boundary_method = Egan;
    s.n_top = slab.n_slab;
    s.n_bottom = slab.n_slab;
    s.slide_top = slab.n_top_slide;
    s.slide_bottom = slab.n_bottom_slide;
    s.F0 = 1/pi;
    s.depth = 0.0;
    s.Exact_coll_flag = false;
    if (MM.illumination ≡ collimated) {
        compute_R_and_T(&s, 1.0, &rp, &rs, &tp, &ts);
        *UR1 = rp + rs;
        *UT1 = tp + ts;
        *URU = 0.0;
        *UTU = 0.0;
        return;
    }
    quad_Dif_Calc_R_and_T(&s, &rp, &rs, &tp, &ts);
    *URU = rp + rs;
    *UTU = tp + ts;
    *UR1 = 0.0;
    *UT1 = 0.0;
}
```

193. IAD Find. March 1995. Incorporated the *quick_guess* algorithm for low albedos.

```

<iad_find.c 193> ≡
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include "ad_globl.h"
#include "nr_util.h"
#include "nr_mnbrk.h"
#include "nr_brent.h"
#include "nr_amoeb.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#include "iad_find.h"
#define NUMBER_OF_GUESSES 10
guess_type guess[NUMBER_OF_GUESSES];
int compare_guesses(const void *p1, const void *p2)
{
    guess_type *g1 = (guess_type *) p1;
    guess_type *g2 = (guess_type *) p2;
    if (g1->distance < g2->distance) return -1;
    else if (g1->distance ≡ g2->distance) return 0;
    else return 1;
}
<Definition for U_Find_Ba 207>
<Definition for U_Find_Bs 205>
<Definition for U_Find_A 209>
<Definition for U_Find_B 213>
<Definition for U_Find_G 211>
<Definition for U_Find_AG 216>
<Definition for U_Find_AB 196>
<Definition for U_Find_BG 221>
<Definition for U_Find_BaG 227>
<Definition for U_Find_BsG 232>

```

194. All the information that needs to be written to the header file `iad_find.h`. This eliminates the need to maintain a set of header files as well.

```

<iad_find.h 194> ≡
<Prototype for U_Find_Ba 206>;
<Prototype for U_Find_Bs 204>;
<Prototype for U_Find_A 208>;
<Prototype for U_Find_B 212>;
<Prototype for U_Find_G 210>;
<Prototype for U_Find_AG 215>;
<Prototype for U_Find_AB 195>;
<Prototype for U_Find_BG 220>;
<Prototype for U_Find_BaG 226>;
<Prototype for U_Find_BsG 231>;

```

195. Fixed Anisotropy.

This is the most common case.

⟨Prototype for *U_Find_AB* 195⟩ ≡

```
void U_Find_AB(struct measure_type m, struct invert_type *r)
```

This code is used in sections 194 and 196.

196. ⟨Definition for *U_Find_AB* 196⟩ ≡

⟨Prototype for *U_Find_AB* 195⟩

```
{
  ⟨Allocate local simplex variables 197⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In_U_Find_AB");
    fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
    if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, " default_g = %8.5f", r→default_g);
    fprintf(stderr, "\n");
  }
  r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
  Set_Calc_State(m, *r);
  ⟨Get the initial a, b, and g 198⟩
  ⟨Initialize the nodes of the a and b simplex 199⟩
  ⟨Evaluate the a and b simplex at the nodes 200⟩
  amoeba(p, y, 2, r→tolerance, Find_AB_fn, &r→iterations);
  ⟨Choose the best node of the a and b simplex 201⟩
  ⟨Free simplex data structures 203⟩
  ⟨Put final values in result 202⟩
}
```

This code is used in section 193.

197. To use the simplex algorithm, we need to vectors and a matrix.

⟨Allocate local simplex variables 197⟩ ≡

```
int i, i_best, j_best;
double *x, *y, **p;
x = dvector(1, 2);
y = dvector(1, 3);
p = dmatrix(1, 3, 1, 2);
```

This code is used in sections 196, 216, 221, 227, and 232.

198. Just get the optimal optical properties to start the search process.

I had to add the line that tests to make sure the albedo is greater than 0.2 because the grid just does not work so well in this case. The problem is that for low albedos there is really very little information about the anisotropy available. This change was also made in the analogous code for a and b .

```

⟨ Get the initial  $a$ ,  $b$ , and  $g$  198 ⟩ ≡
{
    /* double a3,b3,g3; */
    size_t count = NUMBER_OF_GUESSES; /* distance to last result */
    abg_distance(r→slab.a, r→slab.b, r→slab.g, &(guess[0]));
    if (¬ Valid_Grid(m, r→search)) Fill_Grid(m, *r); /* distance to nearest grid point */
    Near_Grid_Points(m.m_r, m.m_t, r→search, &i_best, &j_best);
    Grid_ABG(i_best, j_best, &(guess[1]));
    Grid_ABG(i_best + 1, j_best, &(guess[2]));
    Grid_ABG(i_best - 1, j_best, &(guess[3]));
    Grid_ABG(i_best, j_best + 1, &(guess[4]));
    Grid_ABG(i_best, j_best - 1, &(guess[5]));
    Grid_ABG(i_best + 1, j_best + 1, &(guess[6]));
    Grid_ABG(i_best - 1, j_best - 1, &(guess[7]));
    Grid_ABG(i_best + 1, j_best - 1, &(guess[8]));
    Grid_ABG(i_best - 1, j_best + 1, &(guess[9]));
    qsort((void *) guess, count, sizeof(guess_type), compare_guesses);
    if (Debug(DEBUG_BEST_GUESS)) {
        int k;
        fprintf(stderr, "after\n");
        for (k = 0; k ≤ 6; k++) {
            fprintf(stderr, "%3d□", k);
            fprintf(stderr, "%10.5f□", guess[k].a);
            fprintf(stderr, "%10.5f□", guess[k].b);
            fprintf(stderr, "%10.5f□", guess[k].g);
            fprintf(stderr, "%10.5f\n", guess[k].distance);
        }
    }
}

```

This code is used in sections 196, 216, 221, 227, and 232.

199. \langle Initialize the nodes of the a and b simplex 199 $\rangle \equiv$

```

{
  int k, kk;
  p[1][1] = a2acalc(guess[0].a);
  p[1][2] = b2bcalc(guess[0].b);
  for (k = 1; k < 7; k++) {
    if (guess[0].a  $\neq$  guess[k].a) break;
  }
  p[2][1] = a2acalc(guess[k].a);
  p[2][2] = b2bcalc(guess[k].b);
  for (kk = 1; kk < 7; kk++) {
    if (guess[0].b  $\neq$  guess[kk].b  $\wedge$  guess[k].b  $\neq$  guess[kk].b) break;
  }
  p[3][1] = a2acalc(guess[kk].a);
  p[3][2] = b2bcalc(guess[kk].b);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "guess_1");
    fprintf(stderr, "%10.5f_", guess[0].a);
    fprintf(stderr, "%10.5f_", guess[0].b);
    fprintf(stderr, "%10.5f_", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "guess_2");
    fprintf(stderr, "%10.5f_", guess[k].a);
    fprintf(stderr, "%10.5f_", guess[k].b);
    fprintf(stderr, "%10.5f_", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "guess_3");
    fprintf(stderr, "%10.5f_", guess[kk].a);
    fprintf(stderr, "%10.5f_", guess[kk].b);
    fprintf(stderr, "%10.5f_", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
  }
}

```

This code is used in section 196.

200. \langle Evaluate the a and b simplex at the nodes 200 $\rangle \equiv$

```

for (i = 1; i  $\leq$  3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_AB_fn(x);
}

```

This code is used in section 196.

201. \langle Choose the best node of the a and b simplex 201 $\rangle \equiv$

```

r-final_distance = 10;
for (i = 1; i ≤ 3; i++) {
    if (y[i] < r-final_distance) {
        r-slab.a = acalc2a(p[i][1]);
        r-slab.b = bcalc2b(p[i][2]);
        r-final_distance = y[i];
    }
}

```

This code is used in section 196.

202. \langle Put final values in result 202 $\rangle \equiv$

```

r-a = r-slab.a;
r-b = r-slab.b;
r-g = r-slab.g;
r-found = (r-tolerance ≤ r-final_distance);

```

This code is used in sections 196, 205, 207, 209, 211, 213, 216, 221, 227, and 232.

203. Since we allocated these puppies, we got to get rid of them.

\langle Free simplex data structures 203 $\rangle \equiv$

```

free_dvector(x, 1, 2);
free_dvector(y, 1, 3);
free_dmatrix(p, 1, 3, 1, 2);

```

This code is used in sections 196, 216, 221, 227, and 232.

204. Fixed Absorption and Anisotropy. Typically, this routine is called when the absorption coefficient is known, the anisotropy is known, and the physical thickness of the sample is known. This routine calculates the varies the scattering coefficient until the measurements are matched.

This was written for Ted Moffitt to analyze some intralipid data. We wanted to know what the scattering coefficient of the Intralipid was and made total transmission measurements through a sample with a fixed physical thickness. We did not make reflection measurements because the light source diverged too much, and we could not make reflection measurements easily.

In retrospect, we could have made URU measurements by illuminating the wall of the integrating sphere. However, these diffuse type of measurements are very difficult to make accurately.

This is tricky only because the value in *slab.b* is used to hold the value of ba or $d \cdot \mu_a$ when the *Find_Bs_fn* is used.

\langle Prototype for *U_Find_Bs* 204 $\rangle \equiv$

```

void U_Find_Bs(struct measure_type m, struct invert_type *r)

```

This code is used in sections 194 and 205.

205. $\langle \text{Definition for } U_Find_Bs \text{ 205} \rangle \equiv$
 $\langle \text{Prototype for } U_Find_Bs \text{ 204} \rangle$

```

{
  double ax, bx, cx, fa, fb, fc, bs;
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In_U_Find_Bs");
    fprintf(stderr, "\u(mu=%6.4f)", r_slab.cos_angle);
    if (r_default_ba  $\neq$  UNINITIALIZED) fprintf(stderr, "\u\udefault_ba=\u%8.5f", r_default_ba);
    if (r_default_g  $\neq$  UNINITIALIZED) fprintf(stderr, "\u\udefault_g=\u%8.5f", r_default_g);
    fprintf(stderr, "\n");
  }
  r_slab.a = 0;
  r_slab.g = (r_default_g  $\equiv$  UNINITIALIZED) ? 0 : r_default_g;
  r_slab.b = (r_default_ba  $\equiv$  UNINITIALIZED) ? HUGE_VAL : r_default_ba;
  Set_Calc_State(m, *r); /* store ba in RR.slab.b */
  ax = b2bcalc(0.1); /* first try for bs */
  bx = b2bcalc(1.0);
  mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_Bs_fn);
  r_final_distance = brent(ax, bx, cx, Find_Bs_fn, r_tolerance, &bs); /* recover true values */
  r_slab.a = bcalc2b(bs)/(bcalc2b(bs) + r_slab.b);
  r_slab.b = bcalc2b(bs) + r_slab.b;
  Set_Calc_State(m, *r);
   $\langle \text{Put final values in result 202} \rangle$ 
}

```

This code is used in section 193.

206. Fixed Absorption and Scattering. Typically, this routine is called when the scattering coefficient is known, the anisotropy is known, and the physical thickness of the sample is known. This routine calculates the varies the absorption coefficient until the measurements are matched.

This is tricky only because the value in *slab.b* is used to hold the value of *bs* or $d \cdot \mu_s$ when the *Find_Ba_fn* is used.

$\langle \text{Prototype for } U_Find_Ba \text{ 206} \rangle \equiv$
void *U_Find_Ba*(**struct measure_type** *m*, **struct invert_type** **r*)

This code is used in sections 194 and 207.

207. $\langle \text{Definition for } U_Find_Ba \text{ 207} \rangle \equiv$
 $\langle \text{Prototype for } U_Find_Ba \text{ 206} \rangle$

```

{
  double ax, bx, cx, fa, fb, fc, ba;
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In_U_Find_Bs");
    fprintf(stderr, "\u(mu=%6.4f)", r_slab.cos_angle);
    if (r_default_bs  $\neq$  UNINITIALIZED) fprintf(stderr, "\u\udefault_bs=\u%8.5f", r_default_bs);
    if (r_default_g  $\neq$  UNINITIALIZED) fprintf(stderr, "\u\udefault_g=\u%8.5f", r_default_g);
    fprintf(stderr, "\n");
  }
  r_slab.a = 0;
  r_slab.g = (r_default_g  $\equiv$  UNINITIALIZED) ? 0 : r_default_g;
  r_slab.b = (r_default_bs  $\equiv$  UNINITIALIZED) ? HUGE_VAL : r_default_bs;
  Set_Calc_State(m, *r); /* store bs in RR.slabs.b */
  ax = b2bcalc(0.1); /* first try for ba */
  bx = b2bcalc(1.0);
  mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_Ba_fn);
  r_final_distance = brent(ax, bx, cx, Find_Ba_fn, r_tolerance, &ba); /* recover true values */
  r_slab.a = (r_slab.b)/(bcalc2b(ba) + r_slab.b);
  r_slab.b = bcalc2b(ba) + r_slab.b; /* actual value of b */
  Set_Calc_State(m, *r);
   $\langle \text{Put final values in result 202} \rangle$ 
}

```

This code is used in section 193.

208. Fixed Optical Depth and Anisotropy. Typically, this routine is called when the optical thickness is assumed infinite. However, it may also be called when the optical thickness is assumed to be fixed at a particular value. Typically the only reasonable situation for this to occur is when the diffuse transmission is non-zero but the collimated transmission is zero. If this is the case then there is no information in the collimated transmission measurement and there is no sense even using it because the slab is not infinitely thick.

$\langle \text{Prototype for } U_Find_A \text{ 208} \rangle \equiv$
void *U_Find_A*(**struct** *measure_type* *m*, **struct** *invert_type* **r*)

This code is used in sections 194 and 209.

209. $\langle \text{Definition for } U_Find_A \text{ 209} \rangle \equiv$

$\langle \text{Prototype for } U_Find_A \text{ 208} \rangle$

```
{
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_A");
        fprintf(stderr, "\n(mu=%6.4f)", r_slab.cos_angle);
        if (r_default_b  $\neq$  UNINITIALIZED) fprintf(stderr, "\n\ndefault_b=%8.5f", r_default_b);
        if (r_default_g  $\neq$  UNINITIALIZED) fprintf(stderr, "\n\ndefault_g=%8.5f", r_default_g);
        fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r_slab.g = (r_default_g  $\equiv$  UNINITIALIZED) ? 0 : r_default_g;
    r_slab.b = (r_default_b  $\equiv$  UNINITIALIZED) ? HUGE_VAL : r_default_b;
    r_slab.a = 0.0;
    r_final_distance = 0.0;
    Set_Calc_State(m, *r);
    if (Rt > 0.99999) r_final_distance = Find_A_fn(a2acalc(1.0));
    else {
        double x, ax, bx, cx, fa, fb, fc;
        ax = a2acalc(0.3);
        bx = a2acalc(0.5);
        mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_A_fn);
        r_final_distance = brent(ax, bx, cx, Find_A_fn, r_tolerance, &x);
        r_slab.a = acalc2a(x);
    }
     $\langle \text{Put final values in result 202} \rangle$ 
}
```

This code is used in section 193.

210. Fixed Optical Depth and Albedo.

$\langle \text{Prototype for } U_Find_G \text{ 210} \rangle \equiv$

void *U_Find_G*(**struct** *measure_type* *m*, **struct** *invert_type* **r*)

This code is used in sections 194 and 211.

This code is used in section 193.

This code is used in sections 194 and 213.

213. $\langle \text{Definition for } U_Find_B \text{ 213} \rangle \equiv$

$\langle \text{Prototype for } U_Find_B \text{ 212} \rangle$

```
{
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_B");
        fprintf(stderr, "\n(mu=%6.4f)", r->slab.cos_angle);
        if (r->default_a != UNINITIALIZED) fprintf(stderr, "\n\ndefault_a=%8.5f", r->default_a);
        if (r->default_g != UNINITIALIZED) fprintf(stderr, "\n\ndefault_g=%8.5f", r->default_g);
        fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r->slab.g = (r->default_g == UNINITIALIZED) ? 0 : r->default_g;
    r->slab.a = (r->default_a == UNINITIALIZED) ? 0 : r->default_a;
    r->slab.b = 0.5;
    r->final_distance = 0.0;
    Set_Calc_State(m, *r);
     $\langle \text{Iteratively solve for } b \text{ 214} \rangle$ 
     $\langle \text{Put final values in result 202} \rangle$ 
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_B\nfinal\n(a,b,g)\n");
        fprintf(stderr, "(%8.5f,%8.5f,%8.5f)\n", r->a, r->b, r->g);
    }
}
```

This code is used in section 193.

214. This could be improved tremendously. I just don't want to mess with it at the moment.

$\langle \text{Iteratively solve for } b \text{ 214} \rangle \equiv$

```
{
    double x, ax, bx, cx, fa, fb, fc;
    ax = b2bcalc(0.1);
    bx = b2bcalc(10);
    mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_B_fn);
    r->final_distance = brent(ax, bx, cx, Find_B_fn, r->tolerance, &x);
    r->slab.b = bcalc2b(x);
    Set_Calc_State(m, *r);
}
```

This code is used in section 213.

215. Fixed Optical Depth.

We can get here a couple of different ways.

First there can be three real measurements, i.e., t_c is not zero, in this case we want to fix b based on the t_c measurement.

Second, we can get here if a default value for b has been set.

Otherwise, we really should not be here. Just set $b = 1$ and calculate away.

$\langle \text{Prototype for } U_Find_AG \text{ 215} \rangle \equiv$

void *U_Find_AG*(**struct** *measure_type* *m*, **struct** *invert_type* **r*)

This code is used in sections 194 and 216.

This code is used in section 193.

217. $\langle \text{Initialize the nodes of the } a \text{ and } g \text{ simplex } 217 \rangle \equiv$

```

{
  int k, kk;
  p[1][1] = a2acalc(guess[0].a);
  p[1][2] = g2gcalc(guess[0].g);
  for (k = 1; k < 7; k++) {
    if (guess[0].a ≠ guess[k].a) break;
  }
  p[2][1] = a2acalc(guess[k].a);
  p[2][2] = g2gcalc(guess[k].g);
  for (kk = 1; kk < 7; kk++) {
    if (guess[0].g ≠ guess[kk].g ∧ guess[k].g ≠ guess[kk].g) break;
  }
  p[3][1] = a2acalc(guess[kk].a);
  p[3][2] = g2gcalc(guess[kk].g);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "guess_1");
    fprintf(stderr, "%10.5f_", guess[0].a);
    fprintf(stderr, "%10.5f_", guess[0].b);
    fprintf(stderr, "%10.5f_", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "guess_2");
    fprintf(stderr, "%10.5f_", guess[k].a);
    fprintf(stderr, "%10.5f_", guess[k].b);
    fprintf(stderr, "%10.5f_", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "guess_3");
    fprintf(stderr, "%10.5f_", guess[kk].a);
    fprintf(stderr, "%10.5f_", guess[kk].b);
    fprintf(stderr, "%10.5f_", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
  }
}

```

This code is used in section 216.

218. $\langle \text{Evaluate the } a \text{ and } g \text{ simplex at the nodes } 218 \rangle \equiv$

```

for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_AG_fn(x);
}

```

This code is used in section 216.

219. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

⟨ Choose the best node of the a and g simplex 219 ⟩ \equiv

```

    r→final_distance = 10;
    for (i = 1; i ≤ 3; i++) {
        if (y[i] < r→final_distance) {
            r→slab.a = acalc2a(p[i][1]);
            r→slab.g = gcalc2g(p[i][2]);
            r→final_distance = y[i];
        }
    }

```

This code is used in section 216.

220. Fixed Albedo. Here the optical depth and the anisotropy are varied (for a fixed albedo).

⟨ Prototype for U_Find_BG 220 ⟩ \equiv

```

void U_Find_BG(struct measure_type m, struct invert_type *r)

```

This code is used in sections 194 and 221.

221. ⟨ Definition for U_Find_BG 221 ⟩ \equiv

```

⟨ Prototype for  $U\_Find\_BG$  220 ⟩
{
    ⟨ Allocate local simplex variables 197 ⟩
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_BG");
        fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
        if (r→default_a ≠ UNINITIALIZED) fprintf(stderr, " default_a=%8.5f", r→default_a);
        fprintf(stderr, "\n");
    }
    r→slab.a = (r→default_a ≡ UNINITIALIZED) ? 0 : r→default_a;
    Set_Calc_State(m, *r);
    ⟨ Get the initial  $a$ ,  $b$ , and  $g$  198 ⟩
    ⟨ Initialize the nodes of the  $b$  and  $g$  simplex 223 ⟩
    ⟨ Evaluate the  $bg$  simplex at the nodes 224 ⟩
    amoeba(p, y, 2, r→tolerance, Find_BG_fn, &r→iterations);
    ⟨ Choose the best node of the  $b$  and  $g$  simplex 225 ⟩
    ⟨ Free simplex data structures 203 ⟩
    ⟨ Put final values in result 202 ⟩
}

```

This code is used in section 193.

222. A very simple start for variation of b and g . This should work fine for the cases in which the absorption or scattering are fixed.

223. \langle Initialize the nodes of the b and g simplex 223 $\rangle \equiv$

```

{
  int k, kk;
  p[1][1] = b2bcalc(guess[0].b);
  p[1][2] = g2gcalc(guess[0].g);
  for (k = 1; k < 7; k++) {
    if (guess[0].b  $\neq$  guess[k].b) break;
  }
  p[2][1] = b2bcalc(guess[k].b);
  p[2][2] = g2gcalc(guess[k].g);
  for (kk = 1; kk < 7; kk++) {
    if (guess[0].g  $\neq$  guess[kk].g  $\wedge$  guess[k].g  $\neq$  guess[kk].g) break;
  }
  p[3][1] = b2bcalc(guess[kk].b);
  p[3][2] = g2gcalc(guess[kk].g);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "guess_1");
    fprintf(stderr, "%10.5f_", guess[0].a);
    fprintf(stderr, "%10.5f_", guess[0].b);
    fprintf(stderr, "%10.5f_", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "guess_2");
    fprintf(stderr, "%10.5f_", guess[k].a);
    fprintf(stderr, "%10.5f_", guess[k].b);
    fprintf(stderr, "%10.5f_", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "guess_3");
    fprintf(stderr, "%10.5f_", guess[kk].a);
    fprintf(stderr, "%10.5f_", guess[kk].b);
    fprintf(stderr, "%10.5f_", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
  }
}

```

This code is used in section 221.

224. \langle Evaluate the bg simplex at the nodes 224 $\rangle \equiv$

```

for (i = 1; i  $\leq$  3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_BG_fn(x);
}

```

This code is used in section 221.

225. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

```

⟨ Choose the best node of the b and g simplex 225 ⟩ ≡
  r-final_distance = 10;
  for (i = 1; i ≤ 3; i++) {
    if (y[i] < r-final_distance) {
      r-slab.b = bcalc2b(p[i][1]);
      r-slab.g = gcalc2g(p[i][2]);
      r-final_distance = y[i];
    }
  }

```

This code is used in section 221.

226. Fixed Scattering. Here I assume that a constant b_s ,

$$b_s = \mu_s d$$

where d is the physical thickness of the sample and μ_s is of course the absorption coefficient. This is just like *U-Find-BG* except that $b_a = \mu_a d$ is varied instead of b .

```

⟨ Prototype for U-Find-BaG 226 ⟩ ≡
  void U-Find-BaG(struct measure_type m, struct invert_type *r)

```

This code is used in sections 194 and 227.

```

227. ⟨ Definition for U-Find-BaG 227 ⟩ ≡
  ⟨ Prototype for U-Find-BaG 226 ⟩
  {
    ⟨ Allocate local simplex variables 197 ⟩
    Set_Calc_State(m, *r);
    ⟨ Get the initial a, b, and g 198 ⟩
    ⟨ Initialize the nodes of the ba and g simplex 228 ⟩
    ⟨ Evaluate the BaG simplex at the nodes 229 ⟩
    amoeba(p, y, 2, r-tolerance, Find-BaG_fn, &r-iterations);
    ⟨ Choose the best node of the ba and g simplex 230 ⟩
    ⟨ Free simplex data structures 203 ⟩
    ⟨ Put final values in result 202 ⟩
  }

```

This code is used in section 193.

228. \langle Initialize the nodes of the *ba* and *g* simplex 228 $\rangle \equiv$

```

if (guess[0].b > r-default_bs) {
    p[1][1] = b2bcalc(guess[0].b - r-default_bs);
    p[2][1] = b2bcalc(2 * (guess[0].b - r-default_bs));
    p[3][1] = p[1][1];
}
else {
    p[1][1] = b2bcalc(0.0001);
    p[2][1] = b2bcalc(0.001);
    p[3][1] = p[1][1];
}
p[1][2] = g2gcalc(guess[0].g);
p[2][2] = p[1][2];
p[3][2] = g2gcalc(0.9 * guess[0].g + 0.05);

```

This code is used in section 227.

229. \langle Evaluate the *BaG* simplex at the nodes 229 $\rangle \equiv$

```

for (i = 1; i ≤ 3; i++) {
    x[1] = p[i][1];
    x[2] = p[i][2];
    y[i] = Find_BaG_fn(x);
}

```

This code is used in section 227.

230. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

\langle Choose the best node of the *ba* and *g* simplex 230 $\rangle \equiv$

```

r-final_distance = 10;
for (i = 1; i ≤ 3; i++) {
    if (y[i] < r-final_distance) {
        r-slab.b = bcalc2b(p[i][1]) + r-default_bs;
        r-slab.a = r-default_bs / r-slab.b;
        r-slab.g = gcalc2g(p[i][2]);
        r-final_distance = y[i];
    }
}

```

This code is used in section 227.

231. Fixed Absorption. Here I assume that a constant b_a ,

$$b_a = \mu_a d$$

where d is the physical thickness of the sample and μ_a is of course the absorption coefficient. This is just like *U-Find_BG* except that $b_s = \mu_s d$ is varied instead of b .

\langle Prototype for *U-Find_BsG* 231 $\rangle \equiv$

```

void U-Find_BsG(struct measure_type m, struct invert_type *r)

```

This code is used in sections 194 and 232.

232. $\langle \text{Definition for } U_Find_BsG \text{ 232} \rangle \equiv$
 $\langle \text{Prototype for } U_Find_BsG \text{ 231} \rangle$
 $\{$
 $\quad \langle \text{Allocate local simplex variables 197} \rangle$
 $\quad \text{if } (Debug(DEBUG_SEARCH)) \{$
 $\quad \quad fprintf(stderr, "In_U_Find_BsG");$
 $\quad \quad fprintf(stderr, "_(\mu=\%6.4f)", r\text{-}slab.cos_angle);$
 $\quad \quad \text{if } (r\text{-}default_ba \neq UNINITIALIZED) \quad fprintf(stderr, "__default_ba=_ \%8.5f", r\text{-}default_ba);$
 $\quad \quad fprintf(stderr, "_n");$
 $\quad \}$
 $\quad Set_Calc_State(m, *r);$
 $\quad \langle \text{Get the initial } a, b, \text{ and } g \text{ 198} \rangle$
 $\quad \langle \text{Initialize the nodes of the } bs \text{ and } g \text{ simplex 233} \rangle$
 $\quad \langle \text{Evaluate the } BsG \text{ simplex at the nodes 234} \rangle$
 $\quad amoeba(p, y, 2, r\text{-}tolerance, Find_BsG_fn, \&r\text{-}iterations);$
 $\quad \langle \text{Choose the best node of the } bs \text{ and } g \text{ simplex 235} \rangle$
 $\quad \langle \text{Free simplex data structures 203} \rangle$
 $\quad \langle \text{Put final values in result 202} \rangle$
 $\}$

This code is used in section 193.

233. $\langle \text{Initialize the nodes of the } bs \text{ and } g \text{ simplex 233} \rangle \equiv$
 $p[1][1] = b2bcalc(guess[0].b - r\text{-}default_ba);$
 $p[1][2] = g2gcalc(guess[0].g);$
 $p[2][1] = b2bcalc(2 * guess[0].b - 2 * r\text{-}default_ba);$
 $p[2][2] = p[1][2];$
 $p[3][1] = p[1][1];$
 $p[3][2] = g2gcalc(0.9 * guess[0].g + 0.05);$

This code is used in section 232.

234. $\langle \text{Evaluate the } BsG \text{ simplex at the nodes 234} \rangle \equiv$
 $\text{for } (i = 1; i \leq 3; i++) \{$
 $\quad x[1] = p[i][1];$
 $\quad x[2] = p[i][2];$
 $\quad y[i] = Find_BsG_fn(x);$
 $\}$

This code is used in section 232.

235. $\langle \text{Choose the best node of the } bs \text{ and } g \text{ simplex 235} \rangle \equiv$
 $r\text{-}final_distance = 10;$
 $\text{for } (i = 1; i \leq 3; i++) \{$
 $\quad \text{if } (y[i] < r\text{-}final_distance) \{$
 $\quad \quad r\text{-}slab.b = bcalc2b(p[i][1]) + r\text{-}default_ba;$
 $\quad \quad r\text{-}slab.a = 1 - r\text{-}default_ba / r\text{-}slab.b;$
 $\quad \quad r\text{-}slab.g = gcalc2g(p[i][2]);$
 $\quad \quad r\text{-}final_distance = y[i];$
 $\quad \}$
 $\}$

This code is used in section 232.

236. IAD Utilities.

March 1995. Reincluded *quick_guess* code.

```

< iad_util.c 236 > ≡
#include <math.h>
#include <float.h>
#include <stdio.h>
#include "nr_util.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "ad_bound.h"
#include "iad_type.h"
#include "iad_calc.h"
#include "iad_pub.h"
#include "iad_util.h"
    unsigned long g_util.debugging = 0;
    < Preprocessor definitions >
    < Definition for What_Is_B 239 >
    < Definition for Estimate_RT 245 >
    < Definition for a2acalc 251 >
    < Definition for acalc2a 253 >
    < Definition for g2gcalc 255 >
    < Definition for gcalc2g 257 >
    < Definition for b2bcalc 259 >
    < Definition for bcalc2b 261 >
    < Definition for twoprime 263 >
    < Definition for twounprime 265 >
    < Definition for abgg2ab 267 >
    < Definition for abgb2ag 269 >
    < Definition for quick_guess 276 >
    < Definition for Set_Debugging 289 >
    < Definition for Debug 291 >
    < Definition for Print_Invert_Type 293 >
    < Definition for Print_Measure_Type 295 >

```

237. `<iad_util.h 237> ≡`
`<Prototype for What_Is_B 238>;`
`<Prototype for Estimate_RT 244>;`
`<Prototype for a2acalc 250>;`
`<Prototype for acalc2a 252>;`
`<Prototype for g2gcalc 254>;`
`<Prototype for gcalc2g 256>;`
`<Prototype for b2bcalc 258>;`
`<Prototype for bcalc2b 260>;`
`<Prototype for twoprime 262>;`
`<Prototype for twounprime 264>;`
`<Prototype for abgg2ab 266>;`
`<Prototype for abgb2ag 268>;`
`<Prototype for quick_guess 275>;`
`<Prototype for Set_Debugging 288>;`
`<Prototype for Debug 290>;`
`<Prototype for Print_Invert_Type 292>;`
`<Prototype for Print_Measure_Type 294>;`

238. Finding optical thickness.

This routine figures out what the optical thickness of a slab based on the index of refraction of the slab and the amount of collimated light that gets through it.

It should be pointed out right here in the front that this routine does not work for diffuse irradiance, but then the whole concept of estimating the optical depth for diffuse irradiance is bogus anyway.

In version 1.3 changed all error output to *stderr*. Version 1.4 included cases involving absorption in the boundaries.

```
#define BIG_A_VALUE 999999.0
#define SMALL_A_VALUE 0.000001
<Prototype for What_Is_B 238> ≡
    double What_Is_B(struct AD_slab_type slab, double Tc)
```

This code is used in sections 237 and 239.

239. `<Definition for What_Is_B 239> ≡`
`<Prototype for What_Is_B 238>`
`{`
 `double r1, r2, t1, t2;`
 `<Calculate specular reflection and transmission 240>`
 `<Check for bad values of Tc 241>`
 `<Solve if multiple internal reflections are not present 242>`
 `<Find thickness when multiple internal reflections are present 243>`
`}`

This code is used in section 236.

240. The first thing to do is to find the specular reflection for light interacting with the top and bottom air-glass-sample interfaces. I make a simple check to ensure that the the indices are different before calculating the bottom reflection. Most of the time the $r1 \equiv r2$, but there are always those annoying special cases.

```
<Calculate specular reflection and transmission 240> ≡
    Absorbing_Glass_RT(1.0, slab.n_top_slide, slab.n_slab, slab.cos_angle, slab.b_top_slide, &r1, &t1);
    Absorbing_Glass_RT(slab.n_slab, slab.n_bottom_slide, 1.0, slab.cos_angle, slab.b_bottom_slide, &r2, &t2);
```

This code is used in section 239.

241. Bad values for the unscattered transmission are those that are non-positive, those greater than one, and those greater than are possible in a non-absorbing medium, i.e.,

$$T_c > \frac{t_1 t_2}{1 - r_1 r_2}$$

Since this routine has no way to report errors, I just set the optical thickness to the natural values in these cases.

```

⟨ Check for bad values of  $T_c$  241 ⟩ ≡
  if ( $T_c \leq 0$ ) return (HUGE_VAL);
  if ( $T_c \geq t_1 * t_2 / (1 - r_1 * r_2)$ ) return (0.001);

```

This code is used in section 239.

242. If either r_1 or $r_2 \equiv 0$ then things are very simple because the sample does not sustain multiple internal reflections and the unscattered transmission is

$$T_c = t_1 t_2 \exp(-b/\nu)$$

where b is the optical thickness and ν is *slab.cos_angle*. Clearly,

$$b = -\nu \ln \left(\frac{T_c}{t_1 t_2} \right)$$

```

⟨ Solve if multiple internal reflections are not present 242 ⟩ ≡
  if ( $r_1 \equiv 0 \vee r_2 \equiv 0$ ) return ( $-slab.cos\_angle * \log(T_c/t_1/t_2)$ );

```

This code is used in section 239.

243. Well I kept putting it off, but now comes the time to solve the following equation for b

$$T_c = \frac{t_1 t_2 \exp(-b)}{1 - r_1 r_2 \exp(-2b)}$$

We note immediately that this is a quadratic equation in $x = \exp(-b)$.

$$r_1 r_2 T_c x^2 + t_1 t_2 x - T_c = 0$$

Sufficient tests have been made above to ensure that none of the coefficients are exactly zero. However, it is clear that the leading quadratic term has a much smaller coefficient than the other two. Since r_1 and r_2 are typically about four percent the product is roughly 10^{-3} . The collimated transmission can be very small and this makes things even worse. A further complication is that we need to choose the only positive root.

Now the roots of $ax^2 + bx + c = 0$ can be found using the standard quadratic formula,

$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

This is very bad for small values of a . Instead I use

$$q = -\frac{1}{2} \left[b + \operatorname{sgn}(b) \sqrt{b^2 - 4ac} \right]$$

with the two roots

$$x = \frac{q}{a} \quad \text{and} \quad x = \frac{c}{q}$$

Substituting our coefficients

$$q = -\frac{1}{2} \left[t_1 t_2 + \sqrt{t_1^2 t_2^2 + 4r_1 r_2 T_c^2} \right]$$

With some algebra, this can be shown to be

$$q = -t_1 t_2 \left[1 + \frac{r_1 r_2 T_c^2}{t_1^2 t_2^2} + \dots \right]$$

The only positive root is $x = -T_c/q$. Therefore

$$x = \frac{2T_c}{t_1 t_2 + \sqrt{t_1^2 t_2^2 + 4r_1 r_2 T_c^2}}$$

(Not very pretty, but straightforward enough.)

⟨ Find thickness when multiple internal reflections are present [243](#) ⟩ ≡

```
{
  double B;
  B = t1 * t2;
  return (-slab.cos_angle * log(2 * Tc / (B + sqrt(B * B + 4 * Tc * Tc * r1 * r2))));
}
```

This code is used in section [239](#).

244. Estimating R and T.

In several places, it is useful to know an *estimate* for the values of the reflection and transmission of the sample based on the measurements. This routine provides such an estimate, but it currently ignores anything corrections that might be made for the integrating spheres.

Good values are only really obtainable when *num_measures* \equiv 3, otherwise we need to make pretty strong assumptions about the reflection and transmission values. If *num_measures* < 3, then we will assume that no collimated light makes it all the way through the sample. The specular reflection is then just that for a semi-infinite sample and *Tc* = 0. If *num_measures* \equiv 1, then *Td* is also set to zero.

rt total reflection
rc primary or specular reflection
rd diffuse or scattered reflection
tt total transmission
tp primary or unscattered transmission
td diffuse or scattered transmission

⟨Prototype for *Estimate_RT* 244⟩ \equiv

```
void Estimate_RT(struct measure_type m, struct invert_type r, double *rt, double *tt, double
                 *rd, double *rc, double *td, double *tc)
```

This code is used in sections 237 and 245.

245. ⟨Definition for *Estimate_RT* 245⟩ \equiv

```
⟨Prototype for Estimate_RT 244⟩
{
    ⟨Calculate the unscattered transmission and reflection 246⟩
    ⟨Estimate the backscattered reflection 247⟩
    ⟨Estimate the scattered transmission 248⟩
}
```

This code is used in section 236.

246. If there are three measurements then the specular reflection can be calculated pretty well. If there are fewer then the unscattered transmission is assumed to be zero. This is not necessarily the case, but after all, this routine only makes estimates of the various reflection and transmission quantities.

If there are three measurements, the optical thickness of the sample is required. Of course if there are three measurements then the illumination must be collimated and we can call *What_Is_B* to find out the optical thickness. We pass this value to a routine in the **fresnel.h** unit and sit back and wait.

All the above is true if sphere corrections are not needed. Now, we just fob this off on another function.

⟨Calculate the unscattered transmission and reflection 246⟩ \equiv

```
Calculate_Minimum_MR(m, r, rc, tc);
```

This code is used in section 245.

247. Finding the diffuse reflection is now just a matter of checking whether V1% contains the specular reflection from the sample or not and then just adding or subtracting the specular reflection as appropriate.

⟨ Estimate the backscattered reflection 247 ⟩ ≡

```

if (m.fraction_of_rc_in_mr) {
    *rt = m.m_r;
    *rd = *rt - m.fraction_of_rc_in_mr * (*rc);
    if (*rd < 0) {
        *rd = 0;
        *rc = *rt;
    }
}
else {
    *rd = m.m_r;
    *rt = *rd + *rc;
}

```

This code is used in section 245.

248. The transmission values follow in much the same way as the diffuse reflection values — just subtract the specular transmission from the total transmission.

⟨ Estimate the scattered transmission 248 ⟩ ≡

```

if (m.num_measures ≡ 1) {
    *tt = 0.0;
    *td = 0.0;
}
else if (m.fraction_of_tc_in_mt) {
    *tt = m.m_t;
    *td = *tt - *tc;
    if (*td < 0) {
        *tc = *tt;
        *td = 0;
    }
}
else {
    *td = m.m_t;
    *tt = *td + *tc;
}

```

This code is used in section 245.

249. Transforming properties. Routines to convert optical properties to calculation space and back.

250. *a2acalc* is used for the albedo transformations according to

$$a_{calc} = \frac{2a - 1}{a(1 - a)}$$

Care is taken to avoid division by zero. Why was this function chosen? Well mostly because it maps the region between $[0, 1] \rightarrow (-\infty, +\infty)$.

⟨ Prototype for *a2acalc* 250 ⟩ ≡

```

double a2acalc(double a)

```

This code is used in sections 237 and 251.

251. $\langle \text{Definition for } a2acalc \text{ 251} \rangle \equiv$
 $\langle \text{Prototype for } a2acalc \text{ 250} \rangle$
 $\{$
 $\quad \text{if } (a \leq 0) \text{ return } -\text{BIG_A_VALUE};$
 $\quad \text{if } (a \geq 1) \text{ return } \text{BIG_A_VALUE};$
 $\quad \text{return } ((2 * a - 1)/a/(1 - a));$
 $\}$

This code is used in section 236.

252. $acalc2a$ is used for the albedo transformations Now when we solve

$$a_{calc} = \frac{2a - 1}{a(1 - a)}$$

we obtain the quadratic equation

$$a_{calc}a^2 + (2 - a_{calc})a - 1 = 0$$

The only root of this equation between zero and one is

$$a = \frac{-2 + a_{calc} + \sqrt{a_{calc}^2 + 4}}{2a_{calc}}$$

I suppose that I should spend the time to recast this using the more appropriate numerical solutions of the quadratic equation, but this worked and I will leave it as it is for now.

$\langle \text{Prototype for } acalc2a \text{ 252} \rangle \equiv$
 $\text{double } acalc2a(\text{double } acalc)$

This code is used in sections 237 and 253.

253. $\langle \text{Definition for } acalc2a \text{ 253} \rangle \equiv$
 $\langle \text{Prototype for } acalc2a \text{ 252} \rangle$
 $\{$
 $\quad \text{if } (acalc \equiv \text{BIG_A_VALUE}) \text{ return } 1.0;$
 $\quad \text{else if } (acalc \equiv -\text{BIG_A_VALUE}) \text{ return } 0.0;$
 $\quad \text{else if } (fabs(acalc) < \text{SMALL_A_VALUE}) \text{ return } 0.5;$
 $\quad \text{else return } ((-2 + acalc + \text{sqrt}(acalc * acalc + 4))/(2 * acalc));$
 $\}$

This code is used in section 236.

254. $g2gcalc$ is used for the anisotropy transformations according to

$$g_{calc} = \frac{g}{1 + |g|}$$

which maps $(-1, 1) \rightarrow (-\infty, +\infty)$.

$\langle \text{Prototype for } g2gcalc \text{ 254} \rangle \equiv$
 $\text{double } g2gcalc(\text{double } g)$

This code is used in sections 237 and 255.

255. $\langle \text{Definition for } g2gcalc \text{ 255} \rangle \equiv$
 $\langle \text{Prototype for } g2gcalc \text{ 254} \rangle$
 $\{$
 $\quad \text{if } (g \leq -1) \text{ return } (-\text{HUGE_VAL});$
 $\quad \text{if } (g \geq 1) \text{ return } (\text{HUGE_VAL});$
 $\quad \text{return } (g/(1 - fabs(g)));$
 $\}$

This code is used in section 236.

256. $gcalc2g$ is used for the anisotropy transformations it is the inverse of $g2gcalc$. The relation is

$$g = \frac{g_{calc}}{1 + |g_{calc}|}$$

$\langle \text{Prototype for } gcalc2g \text{ 256} \rangle \equiv$
 $\text{double } gcalc2g(\text{double } gcalc)$

This code is used in sections 237 and 257.

257. $\langle \text{Definition for } gcalc2g \text{ 257} \rangle \equiv$
 $\langle \text{Prototype for } gcalc2g \text{ 256} \rangle$
 $\{$
 $\quad \text{if } (gcalc \equiv -\text{HUGE_VAL}) \text{ return } -1.0;$
 $\quad \text{if } (gcalc \equiv \text{HUGE_VAL}) \text{ return } 1.0;$
 $\quad \text{return } (gcalc/(1 + fabs(gcalc)));$
 $\}$

This code is used in section 236.

258. $b2bcalc$ is used for the optical depth transformations it is the inverse of $bcalc2b$. The relation is

$$b_{calc} = \ln(b)$$

The only caveats are to ensure that I don't take the logarithm of something big or non-positive.

$\langle \text{Prototype for } b2bcalc \text{ 258} \rangle \equiv$
 $\text{double } b2bcalc(\text{double } b)$

This code is used in sections 237 and 259.

259. $\langle \text{Definition for } b2bcalc \text{ 259} \rangle \equiv$
 $\langle \text{Prototype for } b2bcalc \text{ 258} \rangle$
 $\{$
 $\quad \text{if } (b \equiv \text{HUGE_VAL}) \text{ return } \text{HUGE_VAL};$
 $\quad \text{if } (b \leq 0) \text{ return } 0.0;$
 $\quad \text{return } (\log(b));$
 $\}$

This code is used in section 236.

260. *bcalc2b* is used for the anisotropy transformations it is the inverse of *b2bcalc*. The relation is

$$b = \exp(b_{calc})$$

The only tricky part is to ensure that I don't exponentiate something big and get an overflow error. In ANSI C the maximum value for x such that 10^x is in the range of representable finite floating point numbers (for doubles) is given by `DBL_MAX_10_EXP`. Thus if we want to know if

$$e^{b_{calc}} > 10^x$$

or

$$b_{calc} > x \ln(10) \approx 2.3x$$

and this is the criterion that I use.

\langle Prototype for *bcalc2b* 260 $\rangle \equiv$
double bcalc2b(double bcalc)

This code is used in sections 237 and 261.

261. \langle Definition for *bcalc2b* 261 $\rangle \equiv$
 \langle Prototype for *bcalc2b* 260 \rangle
 $\{$
 if (*bcalc* \equiv HUGE_VAL) **return** HUGE_VAL;
 if (*bcalc* $>$ 2.3 * DBL_MAX_10_EXP) **return** HUGE_VAL;
 return (*exp*(*bcalc*));
 $\}$

This code is used in section 236.

262. *twoprime* converts the true albedo a , optical depth b to the reduced albedo ap and reduced optical depth bp that correspond to $g = 0$.

\langle Prototype for *twoprime* 262 $\rangle \equiv$
void twoprime(double a, double b, double g, double *ap, double *bp)

This code is used in sections 237 and 263.

263. \langle Definition for *twoprime* 263 $\rangle \equiv$
 \langle Prototype for *twoprime* 262 \rangle
 $\{$
 if ($a \equiv 1 \wedge g \equiv 1$) **ap* = 0.0;
 else **ap* = $(1 - g) * a / (1 - a * g)$;
 if (*b* \equiv HUGE_VAL) **bp* = HUGE_VAL;
 else **bp* = $(1 - a * g) * b$;
 $\}$

This code is used in section 236.

264. *twounprime* converts the reduced albedo ap and reduced optical depth bp (for $g = 0$) to the true albedo a and optical depth b for an anisotropy g .

\langle Prototype for *twounprime* 264 $\rangle \equiv$
void twounprime(double ap, double bp, double g, double *a, double *b)

This code is used in sections 237 and 265.

265. $\langle \text{Definition for } twounprime \text{ 265} \rangle \equiv$
 $\langle \text{Prototype for } twounprime \text{ 264} \rangle$
 $\{$
 $\quad *a = ap / (1 - g + ap * g);$
 $\quad \text{if } (bp \equiv \text{HUGE_VAL}) *b = \text{HUGE_VAL};$
 $\quad \text{else } *b = (1 + ap * g / (1 - g)) * bp;$
 $\}$

This code is used in section 236.

266. *abgg2ab* assume a , b , g , and $g1$ are given this does the similarity translation that you would expect it should by converting it to the reduced optical properties and then transforming back using the new value of g

$\langle \text{Prototype for } abgg2ab \text{ 266} \rangle \equiv$
 $\text{void } abgg2ab(\text{double } a1, \text{double } b1, \text{double } g1, \text{double } g2, \text{double } *a2, \text{double } *b2)$

This code is used in sections 237 and 267.

267. $\langle \text{Definition for } abgg2ab \text{ 267} \rangle \equiv$
 $\langle \text{Prototype for } abgg2ab \text{ 266} \rangle$
 $\{$
 $\quad \text{double } a, b;$
 $\quad twoprime(a1, b1, g1, \&a, \&b);$
 $\quad twounprime(a, b, g2, a2, b2);$
 $\}$

This code is used in section 236.

268. *abgb2ag* translates reduced optical properties to unreduced values assuming that the new optical thickness is given i.e., $a1$ and $b1$ are a' and b' for $g = 0$. This routine then finds the appropriate anisotropy and albedo which correspond to an optical thickness $b2$.

If both $b1$ and $b2$ are zero then just assume $g = 0$ for the unreduced values.

$\langle \text{Prototype for } abgb2ag \text{ 268} \rangle \equiv$
 $\text{void } abgb2ag(\text{double } a1, \text{double } b1, \text{double } b2, \text{double } *a2, \text{double } *g2)$

This code is used in sections 237 and 269.

269. $\langle \text{Definition for } abgb2ag \text{ 269} \rangle \equiv$
 $\langle \text{Prototype for } abgb2ag \text{ 268} \rangle$

```

{
  if ( $b1 \equiv 0 \vee b2 \equiv 0$ ) {
    *a2 = a1;
    *g2 = 0;
  }
  if ( $b2 < b1$ )  $b2 = b1$ ;
  if ( $a1 \equiv 0$ ) *a2 = 0.0;
  else {
    if ( $a1 \equiv 1$ ) *a2 = 1.0;
    else {
      if ( $b1 \equiv 0 \vee b2 \equiv \text{HUGE\_VAL}$ ) *a2 = a1;
      else *a2 =  $1 + b1/b2 * (a1 - 1)$ ;
    }
  }
  if ( $*a2 \equiv 0 \vee b2 \equiv 0 \vee b2 \equiv \text{HUGE\_VAL}$ ) *g2 = 0.5;
  else *g2 =  $(1 - b1/b2)/(a2)$ ;
}

```

This code is used in section 236.

270. Guessing an inverse.

This routine is not used anymore.

$\langle \text{Prototype for } slow_guess \text{ 270} \rangle \equiv$

```

void slow_guess(struct measure_type m, struct invert_type *r, double *a, double *b, double *g)

```

This code is used in section 271.

271. $\langle \text{Definition for } slow_guess \text{ 271} \rangle \equiv$
 $\langle \text{Prototype for } slow_guess \text{ 270} \rangle$

```

{
  double fmin = 10.0;
  double fval;
  double *x;
  x = dvector(1, 2);
  switch (r->search) {
  case FIND_A:  $\langle \text{Slow guess for } a \text{ alone 272} \rangle$ 
    break;
  case FIND_B:  $\langle \text{Slow guess for } b \text{ alone 273} \rangle$ 
    break;
  case FIND_AB: case FIND_AG:  $\langle \text{Slow guess for } a \text{ and } b \text{ or } a \text{ and } g \text{ 274} \rangle$ 
    break;
  }
  *a = r->slab.a;
  *b = r->slab.b;
  *g = r->slab.g;
  free_dvector(x, 1, 2);
}

```

272. $\langle \text{Slow guess for } a \text{ alone } 272 \rangle \equiv$

```

r→slab.b = HUGE_VAL;
r→slab.g = r→default_g;
Set_Calc_State(m, *r);
for (r→slab.a = 0.0; r→slab.a ≤ 1.0; r→slab.a += 0.1) {
    fval = Find_A_fn(a2acalc(r→slab.a));
    if (fval < fmin) {
        r→a = r→slab.a;
        fmin = fval;
    }
}
r→slab.a = r→a;

```

This code is used in section 271.

273. Presumably the only time that this will need to be called is when the albedo is fixed or is one. For now, I'll just assume that it is one.

$\langle \text{Slow guess for } b \text{ alone } 273 \rangle \equiv$

```

r→slab.a = 1;
r→slab.g = r→default_g;
Set_Calc_State(m, *r);
for (r→slab.b = 1/32.0; r→slab.b ≤ 32; r→slab.b *= 2) {
    fval = Find_B_fn(b2bcalc(r→slab.b));
    if (fval < fmin) {
        r→b = r→slab.b;
        fmin = fval;
    }
}
r→slab.b = r→b;

```

This code is used in section 271.

274. $\langle \text{Slow guess for } a \text{ and } b \text{ or } a \text{ and } g \text{ } 274 \rangle \equiv$

```

{
    double min_a, min_b, min_g;
    if (¬Valid_Grid(m, r→search)) Fill_Grid(m, *r);
    Near_Grid_Points(m.m_r, m.m_t, r→search, &min_a, &min_b, &min_g);
    r→slab.a = min_a;
    r→slab.b = min_b;
    r→slab.g = min_g;
}

```

This code is used in section 271.

275. $\langle \text{Prototype for } \text{quick_guess } 275 \rangle \equiv$

```

void quick_guess(struct measure_type m, struct invert_type r, double *a, double *b, double *g)

```

This code is used in sections 237 and 276.

276. $\langle \text{Definition for } \textit{quick_guess} \text{ 276} \rangle \equiv$
 $\langle \text{Prototype for } \textit{quick_guess} \text{ 275} \rangle$

```

{
    double UR1, UT1, rd, td, tc, rc, bprime, aprime, alpha, beta, logr;
    Estimate_RT(m, r, &UR1, &UT1, &rd, &rc, &td, &tc);
     $\langle \text{Estimate } \textit{aprime} \text{ 277} \rangle$ 
    switch (m.num_measures) {
    case 1:  $\langle \text{Guess when only reflection is known 279} \rangle$ 
        break;
    case 2:  $\langle \text{Guess when reflection and transmission are known 280} \rangle$ 
        break;
    case 3:  $\langle \text{Guess when all three measurements are known 281} \rangle$ 
        break;
    }
     $\langle \text{Clean up guesses 286} \rangle$ 
}

```

This code is used in section 236.

277. $\langle \text{Estimate } \textit{aprime} \text{ 277} \rangle \equiv$

```

if (UT1  $\equiv$  1) aprime = 1.0;
else if (rd/(1 - UT1)  $\geq$  0.1) {
    double tmp = (1 - rd - UT1)/(1 - UT1);
    aprime = 1 - 4.0/9.0 * tmp * tmp;
}
else if (rd < 0.05  $\wedge$  UT1 < 0.4) aprime = 1 - (1 - 10 * rd) * (1 - 10 * rd);
else if (rd < 0.1  $\wedge$  UT1 < 0.4) aprime = 0.5 + (rd - 0.05) * 4;
else {
    double tmp = (1 - 4 * rd - UT1)/(1 - UT1);
    aprime = 1 - tmp * tmp;
}

```

This code is used in section 276.

278. $\langle \text{Estimate } \textit{bprime} \text{ 278} \rangle \equiv$

```

if (rd < 0.01) {
    bprime = What_Is_B(r.slabs, UT1);
    fprintf(stderr, "low rd<0.01! ut1=%f aprime=%f bprime=%f\n", UT1, aprime, bprime);
}
else if (UT1  $\leq$  0) bprime = HUGE_VAL;
else if (UT1 > 0.1) bprime = 2 * exp(5 * (rd - UT1) * log(2.0));
else {
    alpha = 1/log(0.05/1.0);
    beta = log(1.0)/log(0.05/1.0);
    logr = log(UR1);
    bprime = log(UT1) - beta * log(0.05) + beta * logr;
    bprime /= alpha * log(0.05) - alpha * logr - 1;
}

```

This code is used in sections 280, 284, and 285.

279.

⟨ Guess when only reflection is known 279 ⟩ ≡

```
*g = r.default_g;
*a = aprime / (1 - *g + aprime * (*g));
*b = HUGE_VAL;
```

This code is used in section 276.

280. ⟨ Guess when reflection and transmission are known 280 ⟩ ≡

```
⟨ Estimate bprime 278 ⟩
*g = r.default_g;
*a = aprime / (1 - *g + aprime * *g);
*b = bprime / (1 - *a * *g);
```

This code is used in section 276.

281. ⟨ Guess when all three measurements are known 281 ⟩ ≡

```
switch (r.search) {
case FIND_A: ⟨ Guess when finding albedo 282 ⟩
    break;
case FIND_B: ⟨ Guess when finding optical depth 283 ⟩
    break;
case FIND_AB: ⟨ Guess when finding the albedo and optical depth 284 ⟩
    break;
case FIND_AG: ⟨ Guess when finding anisotropy and albedo 285 ⟩
    break;
}
```

This code is used in section 276.

282.

⟨ Guess when finding albedo 282 ⟩ ≡

```
*g = r.default_g;
*a = aprime / (1 - *g + aprime * *g);
*b = What_Is_B(r.slabs, m.m_u);
```

This code is used in section 281.

283.

⟨ Guess when finding optical depth 283 ⟩ ≡

```
*g = r.default_g;
*a = 0.0;
*b = What_Is_B(r.slabs, m.m_u);
```

This code is used in section 281.

284.

⟨ Guess when finding the albedo and optical depth 284 ⟩ ≡

```
*g = r.default_g;
if (*g == 1) *a = 0.0;
else *a = aprime / (1 - *g + aprime * *g);
⟨ Estimate bprime 278 ⟩
if (bprime == HUGE_VAL ∨ *a * *g == 1) *b = HUGE_VAL;
else *b = bprime / (1 - *a * *g);
```

This code is used in section 281.

285.

⟨ Guess when finding anisotropy and albedo 285 ⟩ ≡

```

    *b = What_Is_B(r.slab, m.m_u);
    if (*b ≡ HUGE_VAL ∨ *b ≡ 0) {
        *a = a_prime;
        *g = r.default_g;
    }
    else {
        ⟨ Estimate b_prime 278 ⟩
        *a = 1 + b_prime * (a_prime - 1) / (*b);
        if (*a < 0.1) *g = 0.0;
        else *g = (1 - b_prime / (*b)) / (*a);
    }

```

This code is used in section 281.

286.

⟨ Clean up guesses 286 ⟩ ≡

```

    if (*a < 0) *a = 0.0;
    if (*g < 0) *g = 0.0;
    else if (*g ≥ 1) *g = 0.5;

```

This code is used in section 276.

287. Some debugging stuff.

288. ⟨ Prototype for *Set_Debugging* 288 ⟩ ≡

```

    void Set_Debugging(unsigned long debug_level)

```

This code is used in sections 237 and 289.

289.

⟨ Definition for *Set_Debugging* 289 ⟩ ≡

```

    ⟨ Prototype for Set_Debugging 288 ⟩
    {
        g_util_debugging = debug_level;
    }

```

This code is used in section 236.

290.

⟨ Prototype for *Debug* 290 ⟩ ≡

```

    int Debug(unsigned long mask)

```

This code is used in sections 237 and 291.

291.

⟨ Definition for *Debug* 291 ⟩ ≡

```

    ⟨ Prototype for Debug 290 ⟩
    {
        if (g_util_debugging & mask) return 1;
        else return 0;
    }

```

This code is used in section 236.

292.

⟨ Prototype for *Print_Invert_Type* 292 ⟩ ≡

void *Print_Invert_Type*(**struct** **invert_type** *r*)

This code is used in sections 237 and 293.

293.

⟨ Definition for *Print_Invert_Type* 293 ⟩ ≡

⟨ Prototype for *Print_Invert_Type* 292 ⟩

```
{
    fprintf(stderr, "\n");
    fprintf(stderr, "default_t_ua=%10.5f_ubb=%10.5f_ug=%10.5f\n", r.default_a, r.default_b, r.default_g);
    fprintf(stderr, "slab_ua=%10.5f_ubb=%10.5f_ug=%10.5f\n", r.slab.a, r.slab.b, r.slab.g);
    fprintf(stderr, "n_ua_top=%10.5f_umid=%10.5f_ubot=%10.5f\n", r.slab.n_top_slide, r.slab.n_slab,
        r.slab.n_bottom_slide);
    fprintf(stderr, "thick_ub_top=%10.5f_ucos=%10.5f_ubot=%10.5f\n", r.slab.b_top_slide, r.slab.cos_angle,
        r.slab.b_bottom_slide);
    fprintf(stderr, "search_ua_d_uaquadrature_points_ua=%d\n", r.search, r.method.quad_pts);
}
```

This code is used in section 236.

294.

⟨ Prototype for *Print_Measure_Type* 294 ⟩ ≡

void *Print_Measure_Type*(**struct** **measure_type** *m*)

This code is used in sections 237 and 295.

295.

⟨Definition for *Print_Measure_Type* 295⟩ ≡

⟨Prototype for *Print_Measure_Type* 294⟩

```
{
    fprintf(stderr, "\n");
    fprintf(stderr, "#Beam_diameter=%7.1fµm\n", m.d_beam);
    fprintf(stderr, "#Sample_thickness=%7.1fµm\n", m.slab_thickness);
    fprintf(stderr, "#Top_slide_thickness=%7.1fµm\n",
        m.slab_top_slide_thickness);
    fprintf(stderr, "#Bottom_slide_thickness=%7.1fµm\n",
        m.slab_bottom_slide_thickness);
    fprintf(stderr, "#Sample_index_of_refraction=%7.3f\n", m.slab_index);
    fprintf(stderr, "#Top_slide_index_of_refraction=%7.3f\n", m.slab_top_slide_index);
    fprintf(stderr, "#Bottom_slide_index_of_refraction=%7.3f\n", m.slab_bottom_slide_index);
    fprintf(stderr, "#Fraction_unscattered_light_in_M_R=%7.1f%%\n",
        m.fraction_of_rc_in_mr * 100);
    fprintf(stderr, "#Fraction_unscattered_light_in_M_T=%7.1f%%\n",
        m.fraction_of_tc_in_mt * 100);
    fprintf(stderr, "#\n");
    fprintf(stderr, "#Reflection_sphere\n");
    fprintf(stderr, "#sphere_diameter=%7.1fµm\n", m.d_sphere_r);
    fprintf(stderr, "#sample_port_diameter=%7.1fµm\n",
        2 * m.d_sphere_r * sqrt(m.as_r));
    fprintf(stderr, "#entrance_port_diameter=%7.1fµm\n",
        2 * m.d_sphere_r * sqrt(m.ae_r));
    fprintf(stderr, "#detector_port_diameter=%7.1fµm\n",
        2 * m.d_sphere_r * sqrt(m.ad_r));
    fprintf(stderr, "#wall_reflectance=%7.1f%%\n", m.rw_r * 100);
    fprintf(stderr, "#standard_reflectance=%7.1f%%\n", m.rstd_r * 100);
    fprintf(stderr, "#detector_reflectance=%7.1f%%\n", m.rd_r * 100);
    fprintf(stderr, "#spheres=%7d\n", m.num_spheres);
    fprintf(stderr, "#measures=%7d\n", m.num_measures);
    fprintf(stderr, "#method=%7d\n", m.method);
    fprintf(stderr, "area_r_as=%10.5f ad=%10.5f ae=%10.5f aw=%10.5f\n", m.as_r, m.ad_r,
        m.ae_r, m.aw_r);
    fprintf(stderr, "refl_r_r=%10.5f rw=%10.5f rstd=%10.5f f=%10.5f\n", m.rd_r, m.rw_r,
        m.rstd_r, m.f_r);
    fprintf(stderr, "area_t_as=%10.5f ad=%10.5f ae=%10.5f aw=%10.5f\n", m.as_t, m.ad_t,
        m.ae_t, m.aw_t);
    fprintf(stderr, "refl_t_r=%10.5f rw=%10.5f rstd=%10.5f f=%10.5f\n", m.rd_t, m.rw_t,
        m.rstd_t, m.f_t);
    fprintf(stderr, "lost_ur1=%10.5f ut1=%10.5f uru=%10.5f utu=%10.5f\n", m.ur1_lost,
        m.ut1_lost, m.utu_lost, m.utu_lost);
}
```

This code is used in section 236.

296. Index. Here is a cross-reference table for the inverse adding-doubling program. All sections in which an identifier is used are listed with that identifier, except that reserved words are indexed only when they appear in format definitions, and the appearances of identifiers in section names are not indexed. Underlined entries correspond to where the identifier was declared. Error messages and a few other things like “ASCII code dependencies” are indexed here too.

`_CRT_NONSTDC_NO_WARNINGS`: [3](#).
`_CRT_SECURE_NO_WARNINGS`: [3](#), [77](#).
`a`: [26](#), [33](#), [34](#), [60](#), [131](#), [139](#), [144](#), [250](#), [262](#), [264](#), [267](#), [270](#), [275](#).
`a_calc`: [59](#).
`A_COLUMN`: [100](#), [124](#), [137](#), [157](#).
`abg_distance`: [131](#), [198](#).
`abgb2ag`: [268](#).
`abgg2ab`: [266](#).
`ABIT`: [100](#), [165](#), [166](#).
`ABSOLUTE`: [30](#), [35](#).
`Absorbing-Glass-RT`: [240](#).
`acalc`: [252](#), [253](#).
`acalc2a`: [169](#), [171](#), [177](#), [201](#), [209](#), [219](#), [252](#).
`acos`: [99](#).
`AD_error`: [122](#), [153](#).
`AD_method_type`: [33](#).
`ad_r`: [15](#), [32](#), [48](#), [63](#), [66](#), [69](#), [82](#), [97](#), [105](#), [111](#), [295](#).
`AD_slab_type`: [13](#), [16](#), [33](#), [135](#), [192](#), [238](#).
`ad_t`: [15](#), [32](#), [49](#), [63](#), [66](#), [70](#), [83](#), [98](#), [105](#), [113](#), [295](#).
`aduru`: [13](#).
`adur1`: [13](#).
`adutu`: [13](#).
`adut1`: [13](#).
`ae_r`: [15](#), [32](#), [48](#), [63](#), [66](#), [69](#), [82](#), [97](#), [105](#), [107](#), [109](#), [111](#), [113](#), [295](#).
`ae_t`: [15](#), [32](#), [49](#), [63](#), [66](#), [70](#), [83](#), [98](#), [105](#), [107](#), [109](#), [111](#), [113](#), [295](#).
`Allocate_Grid`: [121](#), [139](#), [144](#), [147](#), [149](#), [151](#).
`alpha`: [276](#), [278](#).
`amoeba`: [196](#), [216](#), [221](#), [227](#), [232](#).
`analysis`: [64](#), [67](#).
`any_error`: [2](#), [4](#), [8](#), [12](#), [27](#).
`ap`: [262](#), [263](#), [264](#), [265](#).
`aprime`: [192](#), [276](#), [277](#), [278](#), [279](#), [280](#), [282](#), [284](#), [285](#).
`argc`: [2](#), [5](#), [7](#).
`argv`: [2](#), [5](#), [7](#).
`as_r`: [8](#), [12](#), [15](#), [32](#), [48](#), [63](#), [66](#), [69](#), [82](#), [97](#), [105](#), [107](#), [109](#), [113](#), [295](#).
`as_t`: [15](#), [32](#), [49](#), [63](#), [66](#), [70](#), [83](#), [98](#), [105](#), [107](#), [109](#), [111](#), [295](#).
`aw_r`: [15](#), [32](#), [63](#), [66](#), [82](#), [105](#), [107](#), [109](#), [295](#).
`aw_t`: [15](#), [32](#), [63](#), [66](#), [83](#), [105](#), [107](#), [109](#), [295](#).
`ax`: [205](#), [207](#), [209](#), [211](#), [214](#).
`a1`: [266](#), [267](#), [268](#), [269](#).
`a2`: [266](#), [267](#), [268](#), [269](#).
`a2acalc`: [199](#), [209](#), [217](#), [250](#), [272](#).
`B`: [243](#).
`b`: [33](#), [34](#), [60](#), [131](#), [157](#), [258](#), [262](#), [264](#), [267](#), [270](#), [275](#).
`b_bottom_slide`: [13](#), [16](#), [46](#), [59](#), [120](#), [136](#), [155](#), [157](#), [240](#), [293](#).
`b_calc`: [59](#).
`B_COLUMN`: [100](#), [124](#), [137](#), [157](#).
`b_thinnest`: [59](#).
`b_top_slide`: [13](#), [16](#), [46](#), [59](#), [120](#), [136](#), [155](#), [157](#), [240](#), [293](#).
`ba`: [149](#), [151](#), [173](#), [174](#), [175](#), [204](#), [207](#).
`base_name`: [7](#).
`bcalc`: [260](#), [261](#).
`bcalc2b`: [171](#), [173](#), [175](#), [179](#), [183](#), [185](#), [187](#), [201](#), [205](#), [207](#), [214](#), [225](#), [230](#), [235](#), [258](#), [260](#).
`beta`: [276](#), [278](#).
`BIG_A_VALUE`: [238](#), [251](#), [253](#).
`boolean_type`: [34](#), [100](#), [119](#), [125](#).
`both`: [24](#).
`boundary_method`: [192](#).
`bp`: [262](#), [263](#), [264](#), [265](#).
`bprime`: [192](#), [276](#), [278](#), [280](#), [284](#), [285](#).
`brent`: [205](#), [207](#), [209](#), [211](#), [214](#).
`bs`: [149](#), [151](#), [173](#), [175](#), [205](#), [206](#).
`bx`: [205](#), [207](#), [209](#), [211](#), [214](#).
`b1`: [266](#), [267](#), [268](#), [269](#).
`b2`: [266](#), [267](#), [268](#), [269](#).
`b2bcalc`: [199](#), [205](#), [207](#), [214](#), [223](#), [228](#), [233](#), [258](#), [260](#), [273](#).
`c`: [4](#), [87](#), [91](#).
`calculate_coefficients`: [8](#), [12](#), [20](#).
`Calculate_Distance`: [20](#), [72](#), [76](#), [132](#), [138](#), [154](#), [169](#), [171](#), [173](#), [175](#), [177](#), [179](#), [181](#), [183](#), [185](#), [187](#), [189](#).
`Calculate_Distance-With-Corrections`: [133](#), [155](#), [157](#), [158](#).
`Calculate_Grid_Distance`: [124](#), [134](#), [156](#).
`Calculate_Minimum_MR`: [45](#), [73](#), [246](#).
`Calculate_MR_MT`: [6](#), [71](#), [74](#).
`Calculate_Mua_Musp`: [6](#), [19](#), [20](#).
`CALCULATING_GRID`: [100](#), [116](#), [134](#), [155](#), [157](#), [167](#).
`cc`: [5](#).
`check_magic`: [81](#), [90](#).
`cl_beam_d`: [4](#), [5](#), [15](#).
`cl_cos_angle`: [4](#), [5](#), [15](#).
`cl_default_a`: [4](#), [5](#), [6](#), [10](#).
`cl_default_b`: [4](#), [5](#), [6](#), [10](#), [16](#).
`cl_default_fr`: [4](#), [5](#), [15](#).
`cl_default_g`: [4](#), [5](#), [6](#), [10](#).

- cl_default_mua*: [4](#), [5](#), [6](#), [10](#).
- cl_default_mus*: [4](#), [5](#), [6](#), [10](#).
- cl_forward_calc*: [2](#), [4](#), [5](#).
- cl_method*: [4](#), [5](#), [8](#), [15](#).
- cl_musp0*: [4](#), [5](#), [10](#).
- cl_mus0*: [4](#), [5](#), [10](#).
- cl_mus0_lambda*: [4](#), [5](#), [10](#).
- cl_mus0_pwr*: [4](#), [5](#), [10](#).
- cl_num_spheres*: [4](#), [5](#), [15](#).
- cl_quadrature_points*: [4](#), [5](#), [10](#), [15](#).
- cl_rc_fraction*: [4](#), [5](#), [15](#).
- cl_rstd_r*: [4](#), [5](#), [15](#).
- cl_rstd_t*: [4](#), [5](#), [15](#).
- cl_sample_d*: [4](#), [5](#), [6](#), [10](#), [15](#).
- cl_sample_n*: [4](#), [5](#), [15](#).
- cl_slide_d*: [4](#), [5](#), [15](#).
- cl_slide_n*: [4](#), [5](#), [15](#).
- cl_slide_OD*: [4](#), [5](#), [15](#).
- cl_slides*: [4](#), [5](#), [15](#).
- cl_sphere_one*: [4](#), [5](#), [15](#).
- cl_sphere_two*: [4](#), [5](#), [15](#).
- cl_Tc*: [4](#), [5](#), [15](#).
- cl_tc_fraction*: [4](#), [5](#), [15](#).
- cl_tolerance*: [4](#), [5](#), [10](#).
- cl_UR1*: [4](#), [5](#), [15](#).
- cl_UT1*: [4](#), [5](#), [15](#).
- cl_verbosity*: [2](#), [4](#), [5](#), [6](#), [8](#), [11](#), [12](#), [14](#).
- clock*: [2](#), [4](#), [25](#).
- CLOCKS_PER_SEC: [25](#).
- COLLIMATED: [30](#).
- collimated*: [192](#).
- compare_guesses*: [193](#), [198](#).
- COMPARISON: [5](#), [8](#), [31](#), [99](#), [159](#).
- compute_R_and_T*: [192](#).
- correct_URU*: [136](#).
- correct_UR1*: [136](#).
- cos*: [5](#).
- cos_angle*: [16](#), [46](#), [59](#), [120](#), [155](#), [157](#), [196](#), [205](#), [207](#), [209](#), [211](#), [213](#), [216](#), [221](#), [232](#), [240](#), [242](#), [243](#), [293](#).
- count*: [14](#), [27](#), [198](#).
- counter*: [27](#).
- cx*: [205](#), [207](#), [209](#), [211](#), [214](#).
- d_beam*: [15](#), [32](#), [63](#), [66](#), [81](#), [94](#), [295](#).
- d_detector_r*: [15](#), [66](#), [82](#).
- d_detector_t*: [15](#), [66](#), [83](#).
- d_entrance_r*: [15](#), [66](#), [82](#).
- d_entrance_t*: [15](#), [66](#), [83](#).
- d_sample_r*: [15](#), [66](#), [82](#).
- d_sample_t*: [15](#), [66](#), [83](#).
- d_sphere_r*: [8](#), [15](#), [32](#), [63](#), [66](#), [82](#), [97](#), [98](#), [295](#).
- d_sphere_t*: [15](#), [32](#), [63](#), [66](#), [83](#), [98](#).
- DBL_MAX_10_EXP: [260](#), [261](#).
- DE_RT: [192](#).
- Debug*: [8](#), [12](#), [21](#), [22](#), [39](#), [51](#), [116](#), [137](#), [139](#), [144](#), [147](#), [149](#), [153](#), [155](#), [157](#), [167](#), [191](#), [196](#), [198](#), [199](#), [205](#), [207](#), [209](#), [211](#), [213](#), [216](#), [217](#), [221](#), [223](#), [232](#), [290](#).
- DEBUG_A_LITTLE: [31](#).
- DEBUG_ANY: [31](#).
- DEBUG_BEST_GUESS: [31](#), [198](#), [199](#), [217](#), [223](#).
- DEBUG_EVERY_CALC: [31](#), [137](#), [155](#).
- DEBUG_GRID: [31](#), [137](#), [139](#), [144](#), [147](#), [149](#), [155](#), [157](#), [167](#).
- DEBUG_ITERATIONS: [31](#), [116](#), [155](#), [167](#).
- debug_level*: [288](#), [289](#).
- DEBUG_LOST_LIGHT: [8](#), [12](#), [21](#), [22](#), [31](#), [39](#), [191](#).
- DEBUG_RD_ONLY: [31](#).
- DEBUG_SEARCH: [31](#), [51](#), [153](#), [196](#), [205](#), [207](#), [209](#), [211](#), [213](#), [216](#), [221](#), [232](#).
- DEBUG_SPHERE_EFFECTS: [31](#).
- default_a*: [10](#), [12](#), [33](#), [39](#), [45](#), [52](#), [53](#), [58](#), [74](#), [76](#), [99](#), [147](#), [166](#), [183](#), [211](#), [213](#), [221](#), [293](#).
- default_b*: [10](#), [19](#), [33](#), [52](#), [53](#), [58](#), [74](#), [99](#), [209](#), [211](#), [216](#), [293](#).
- default_ba*: [10](#), [33](#), [52](#), [53](#), [58](#), [99](#), [151](#), [187](#), [205](#), [232](#), [233](#), [235](#).
- default_bs*: [10](#), [33](#), [52](#), [53](#), [58](#), [99](#), [149](#), [185](#), [207](#), [228](#), [230](#).
- default_detector_d*: [63](#).
- default_entrance_d*: [63](#).
- default_g*: [10](#), [33](#), [53](#), [54](#), [58](#), [66](#), [74](#), [99](#), [196](#), [205](#), [207](#), [209](#), [213](#), [272](#), [273](#), [279](#), [280](#), [282](#), [283](#), [284](#), [285](#), [293](#).
- default_mua*: [10](#), [33](#), [58](#).
- default_mus*: [10](#), [33](#), [58](#).
- default_sample_d*: [63](#).
- default_sphere_d*: [63](#).
- delta*: [20](#).
- depth*: [192](#).
- determine_search*: [39](#), [50](#).
- dev*: [157](#), [158](#), [165](#), [166](#), [167](#).
- deviation*: [154](#), [155](#), [169](#), [171](#), [173](#), [175](#), [177](#), [179](#), [181](#), [183](#), [185](#), [187](#), [189](#).
- DIFFUSE: [30](#).
- distance*: [34](#), [72](#), [76](#), [124](#), [132](#), [193](#), [198](#), [199](#), [217](#), [223](#).
- dmatrix*: [122](#), [197](#).
- dvector*: [197](#), [271](#).
- Egan*: [192](#).
- EOF: [5](#).
- err*: [27](#).
- Estimate_RT*: [51](#), [209](#), [211](#), [213](#), [244](#), [276](#).
- Exact_coll_flag*: [192](#).
- exit*: [5](#), [7](#), [8](#), [15](#), [17](#), [18](#).

- exp*: 139, 149, 261, 278.
ez_Inverse_RT: 60.
f: 188.
f_r: 15, 32, 48, 63, 69, 111, 113, 161, 162, 163, 295.
f_t: 32, 49, 63, 70, 163, 295.
fa: 205, 207, 209, 211, 214.
fabs: 12, 165, 166, 253, 255, 257.
FALSE: 29, 30, 39, 57, 100, 120, 122, 127, 128, 129, 130.
false: 192.
fb: 205, 207, 209, 211, 214.
fc: 205, 207, 209, 211, 214.
feof: 87, 91.
fflush: 22, 27.
fgetc: 87, 91.
Fill_AB_Grid: 138, 143, 146, 153.
Fill_AG_Grid: 143, 153.
Fill_BaG_Grid: 148, 153.
Fill_BG_Grid: 146, 148, 153.
Fill_BsG_Grid: 150, 153.
Fill_Grid: 152, 198, 274.
fill_grid_entry: 137, 139, 144, 147, 149, 151.
final: 27.
final_distance: 14, 33, 39, 57, 201, 202, 205, 207, 209, 211, 213, 214, 219, 225, 230, 235.
FIND_A: 30, 41, 51, 52, 53, 99, 164, 271, 281.
Find_A_fn: 176, 209, 272.
FIND_AB: 30, 41, 51, 53, 99, 139, 153, 271, 281.
Find_AB_fn: 170, 196, 200.
FIND_AG: 30, 41, 51, 53, 99, 143, 144, 153, 271, 281.
Find_AG_fn: 168, 216, 218.
FIND_AUTO: 29, 30, 51, 57, 99.
FIND_B: 30, 39, 41, 51, 52, 53, 76, 99, 164, 271, 281.
Find_B_fn: 178, 214, 273.
FIND_B_WITH_NO_ABSORPTION: 30, 39, 51, 52, 53.
FIND_B_WITH_NO_SCATTERING: 30, 39, 51, 52.
FIND_Ba: 30, 41, 51, 52, 53, 99, 164.
Find_Ba_fn: 172, 174, 206, 207.
FIND_BaG: 30, 41, 51, 53, 149, 153.
Find_BaG_fn: 184, 227, 229.
FIND_BG: 30, 41, 51, 53, 147, 153.
Find_BG_fn: 182, 221, 224.
FIND_Bs: 30, 41, 51, 52, 53, 99, 164.
Find_Bs_fn: 174, 204, 205.
FIND_BsG: 30, 41, 51, 53, 151, 153.
Find_BsG_fn: 186, 232, 234.
FIND_G: 30, 41, 51, 164.
Find_G_fn: 180, 211.
finish_time: 25.
first_line: 2, 4.
flip: 135, 136.
flip_sample: 15, 32, 46, 63, 99, 137, 155, 157.
floor: 140.
fmin: 271, 272, 273.
format2: 14.
found: 33, 39, 57, 202.
fp: 21, 22, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91.
fprintf: 2, 5, 7, 8, 11, 13, 14, 15, 17, 18, 21, 22, 23, 24, 27, 39, 46, 51, 61, 66, 68, 91, 116, 137, 139, 144, 147, 149, 153, 155, 157, 167, 191, 196, 198, 199, 205, 207, 209, 211, 213, 216, 217, 221, 223, 232, 278, 293, 295.
frac: 191.
FRACTION: 34.
fraction_of_rc_in_mr: 15, 32, 63, 96, 159, 247, 295.
fraction_of_tc_in_mt: 15, 32, 63, 96, 159, 248, 295.
free: 7.
free_dmatrix: 203.
free_dvector: 203, 271.
freopen: 7.
fscanf: 89.
fval: 134, 271, 272, 273.
FO: 192.
G: 105, 107, 109, 113, 161.
g: 33, 34, 60, 131, 254, 262, 264, 270, 275.
g_calc: 59.
G_COLUMN: 100, 124, 137, 157.
g_out_name: 4, 5, 7.
G_std: 161.
g_util_debugging: 236, 289, 291.
G_O: 161.
Gain: 104, 107, 109, 111, 113, 161.
Gain_11: 106, 110, 111.
Gain_22: 108, 113.
gcalc: 256, 257.
gcalc2g: 169, 181, 183, 185, 187, 211, 219, 225, 230, 235, 256.
Get_Calc_State: 72, 117, 132, 134, 153, 189, 191.
GG_a: 100, 145, 147.
GG_b: 100, 144, 145.
GG_ba: 100, 145, 151.
GG_bs: 100, 145, 149.
GG_g: 100, 139, 145.
GP: 107, 109, 111, 161.
GP_std: 161.
gprime: 192.
Grid_ABG: 123, 198.
GRID_SIZE: 100, 122, 124, 134, 137, 139, 140, 141, 142, 144, 147, 149, 151, 157.
guess: 123, 124, 131, 132, 193, 198, 199, 217, 223, 228, 233.
guess_t: 34.
guess_type: 34, 123, 131, 193, 198.

- g1*: [193](#), [266](#), [267](#).
- G11*: [107](#).
- g2*: [193](#), [266](#), [267](#), [268](#), [269](#).
- g2gcalc*: [211](#), [217](#), [223](#), [228](#), [233](#), [254](#), [256](#).
- G22*: [109](#).
- HENVEY_GREENSTEIN*: [13](#), [59](#).
- HUGE_VAL*: [6](#), [19](#), [99](#), [205](#), [207](#), [209](#), [211](#), [241](#), [255](#), [257](#), [259](#), [261](#), [263](#), [265](#), [269](#), [272](#), [278](#), [279](#), [284](#), [285](#).
- i*: [26](#), [65](#), [91](#), [123](#), [134](#), [137](#), [139](#), [144](#), [147](#), [149](#), [151](#), [156](#), [197](#).
- i_best*: [197](#), [198](#).
- i_min*: [133](#), [134](#).
- IAD_AD_NOT_VALID*: [31](#), [48](#), [49](#).
- IAD_AE_NOT_VALID*: [31](#), [48](#), [49](#).
- IAD_AS_NOT_VALID*: [31](#), [48](#), [49](#).
- IAD_BAD_G_VALUE*: [31](#).
- IAD_BAD_PHASE_FUNCTION*: [31](#).
- IAD_EXCESSIVE_LIGHT_LOSS*: [31](#).
- IAD_F_NOT_VALID*: [31](#), [48](#), [49](#).
- IAD_FILE_ERROR*: [31](#).
- IAD_GAMMA_NOT_VALID*: [31](#).
- IAD_invert_type*: [33](#).
- IAD_MAX_ITERATIONS*: [30](#), [41](#).
- IAD_measure_type**: [32](#).
- IAD_MEMORY_ERROR*: [31](#).
- IAD_MR_TOO_BIG*: [27](#), [31](#), [76](#).
- IAD_MR_TOO_SMALL*: [27](#), [31](#), [45](#), [76](#).
- IAD_MT_TOO_BIG*: [27](#), [31](#), [46](#).
- IAD_MT_TOO_SMALL*: [27](#), [31](#), [46](#), [76](#).
- IAD_MU_TOO_BIG*: [27](#), [31](#), [47](#).
- IAD_MU_TOO_SMALL*: [27](#), [31](#), [47](#).
- IAD_NO_ERROR*: [12](#), [27](#), [31](#), [40](#), [44](#), [57](#), [61](#), [65](#), [76](#).
- IAD_QUAD_PTS_NOT_VALID*: [31](#), [40](#).
- IAD_RD_NOT_VALID*: [31](#), [48](#), [49](#).
- IAD_RSTD_NOT_VALID*: [31](#), [48](#).
- IAD_RT_LT_MINIMUM*: [31](#).
- IAD_RW_NOT_VALID*: [31](#), [48](#), [49](#).
- IAD_TOO_MANY_ITERATIONS*: [27](#), [31](#), [41](#).
- IAD_TOO_MANY_LAYERS*: [31](#).
- IAD_TOO_MUCH_LIGHT*: [27](#), [31](#).
- IAD_TSTD_NOT_VALID*: [31](#), [48](#), [49](#).
- illumination*: [192](#).
- illumination_type**: [34](#).
- include_MC*: [71](#), [72](#).
- independent*: [51](#).
- Initialize_Measure*: [2](#), [61](#), [62](#), [65](#), [81](#).
- Initialize_Result*: [2](#), [8](#), [54](#), [61](#), [65](#).
- Inverse_RT*: [8](#), [12](#), [35](#), [38](#), [60](#), [61](#), [65](#).
- Invert_RT*: [20](#).
- invert_type**: [4](#), [19](#), [20](#), [22](#), [33](#), [38](#), [43](#), [50](#), [54](#), [61](#), [65](#), [71](#), [72](#), [73](#), [75](#), [92](#), [100](#), [115](#), [116](#), [117](#), [118](#), [119](#), [132](#), [134](#), [138](#), [143](#), [146](#), [148](#), [150](#), [152](#), [189](#), [190](#), [191](#), [195](#), [204](#), [206](#), [208](#), [210](#), [212](#), [215](#), [220](#), [226](#), [231](#), [244](#), [270](#), [275](#), [292](#).
- isdigit*: [5](#).
- isspace*: [87](#).
- iterations*: [22](#), [33](#), [41](#), [57](#), [196](#), [216](#), [221](#), [227](#), [232](#).
- j*: [123](#), [134](#), [137](#), [139](#), [144](#), [147](#), [149](#), [151](#), [156](#).
- j_best*: [197](#), [198](#).
- j_min*: [133](#), [134](#).
- k*: [198](#), [199](#), [217](#), [223](#).
- kk*: [199](#), [217](#), [223](#).
- lambda*: [10](#), [22](#), [32](#), [63](#), [85](#).
- last*: [26](#).
- log*: [149](#), [242](#), [243](#), [259](#), [278](#).
- logr*: [276](#), [278](#).
- LR*: [8](#), [9](#), [12](#), [20](#), [22](#), [157](#).
- LT*: [8](#), [9](#), [12](#), [20](#), [22](#), [157](#).
- m*: [4](#), [19](#), [20](#), [22](#), [38](#), [43](#), [50](#), [54](#), [61](#), [62](#), [65](#), [71](#), [73](#), [75](#), [80](#), [84](#), [92](#), [104](#), [106](#), [108](#), [110](#), [112](#), [115](#), [117](#), [119](#), [125](#), [138](#), [143](#), [146](#), [148](#), [150](#), [152](#), [190](#), [195](#), [204](#), [206](#), [208](#), [210](#), [212](#), [215](#), [220](#), [226](#), [231](#), [244](#), [270](#), [275](#), [294](#).
- m_old*: [189](#), [191](#).
- M_R*: [71](#), [72](#), [73](#), [154](#), [155](#), [158](#), [160](#), [161](#), [162](#), [163](#), [165](#), [166](#), [167](#).
- m_r*: [4](#), [6](#), [14](#), [15](#), [22](#), [32](#), [39](#), [45](#), [51](#), [61](#), [63](#), [68](#), [76](#), [85](#), [132](#), [137](#), [165](#), [166](#), [167](#), [169](#), [171](#), [173](#), [175](#), [177](#), [179](#), [181](#), [183](#), [185](#), [187](#), [188](#), [189](#), [198](#), [247](#), [274](#).
- M_T*: [47](#), [71](#), [72](#), [154](#), [155](#), [158](#), [160](#), [161](#), [162](#), [163](#), [165](#), [166](#), [167](#).
- m_t*: [4](#), [6](#), [14](#), [15](#), [16](#), [22](#), [32](#), [39](#), [45](#), [46](#), [47](#), [51](#), [61](#), [63](#), [68](#), [76](#), [85](#), [132](#), [137](#), [165](#), [166](#), [167](#), [169](#), [171](#), [173](#), [175](#), [177](#), [179](#), [181](#), [183](#), [185](#), [187](#), [188](#), [189](#), [198](#), [248](#), [274](#).
- m_u*: [14](#), [15](#), [16](#), [32](#), [47](#), [51](#), [61](#), [63](#), [68](#), [85](#), [120](#), [129](#), [143](#), [216](#), [282](#), [283](#), [285](#).
- magic*: [91](#).
- main*: [2](#).
- malloc*: [24](#).
- mask*: [290](#), [291](#).
- max*: [76](#).
- max_b*: [139](#).
- Max_Light_Loss*: [190](#).
- maxloss*: [188](#), [191](#).
- mc_iter*: [8](#), [9](#), [12](#), [22](#).
- MC_iterations*: [4](#), [5](#), [6](#), [11](#), [12](#).
- MC_Lost*: [12](#), [65](#), [72](#).
- MC_RT*: [13](#).
- mc_runs*: [65](#), [67](#).
- MC_tolerance*: [10](#), [12](#), [33](#), [57](#), [99](#).
- mc_total*: [8](#), [9](#), [12](#).

- measure_OK*: [40](#), [43](#).
measure_type: [4](#), [19](#), [20](#), [22](#), [32](#), [38](#), [43](#), [50](#), [54](#),
[61](#), [62](#), [65](#), [71](#), [72](#), [73](#), [75](#), [80](#), [84](#), [92](#), [100](#), [104](#),
[106](#), [108](#), [110](#), [112](#), [115](#), [116](#), [117](#), [118](#), [119](#), [125](#),
[132](#), [134](#), [138](#), [143](#), [146](#), [148](#), [150](#), [152](#), [189](#),
[190](#), [191](#), [195](#), [204](#), [206](#), [208](#), [210](#), [212](#), [215](#),
[220](#), [226](#), [231](#), [244](#), [270](#), [275](#), [294](#).
measurements: [64](#), [68](#).
memcpy: [116](#), [118](#).
method: [10](#), [15](#), [32](#), [33](#), [40](#), [54](#), [59](#), [61](#), [63](#), [67](#), [81](#),
[99](#), [120](#), [137](#), [155](#), [159](#), [293](#), [295](#).
metric: [33](#), [57](#), [165](#), [166](#).
MGRID: [100](#), [120](#), [129](#), [130](#), [153](#).
min: [76](#).
min_a: [274](#).
min_b: [139](#), [274](#).
min_g: [274](#).
MinMax_MR_MT: [44](#), [75](#).
MM: [100](#), [102](#), [115](#), [116](#), [118](#), [137](#), [154](#), [155](#), [157](#),
[159](#), [161](#), [162](#), [163](#), [165](#), [166](#), [167](#), [189](#), [192](#).
mnbrak: [205](#), [207](#), [209](#), [211](#), [214](#).
mr: [45](#), [73](#), [74](#).
MR: [45](#), [75](#).
MR_IS_ONLY_RD: [3](#).
mt: [45](#), [73](#), [74](#).
MT: [75](#).
MT_IS_ONLY_TD: [3](#).
mu_a: [6](#), [8](#), [9](#), [12](#), [22](#), [45](#).
mu_a_last: [12](#).
mu_sp: [6](#), [8](#), [9](#), [12](#), [22](#).
mu_sp_last: [12](#).
mua: [19](#), [20](#).
musp: [19](#), [20](#).
my-getopt: [5](#).
mygetop: [5](#).
n: [5](#), [7](#), [26](#), [60](#), [135](#).
n_bottom: [192](#).
n_bottom_slide: [13](#), [16](#), [46](#), [59](#), [120](#), [136](#), [155](#),
[157](#), [192](#), [240](#), [293](#).
n_photons: [4](#), [5](#), [11](#).
n_slab: [13](#), [16](#), [46](#), [59](#), [120](#), [155](#), [157](#), [192](#), [240](#), [293](#).
n_top: [192](#).
n_top_slide: [13](#), [16](#), [46](#), [59](#), [120](#), [136](#), [155](#), [157](#),
[192](#), [240](#), [293](#).
Near_Grid_Point: [158](#).
Near_Grid_Points: [133](#), [198](#), [274](#).
newton: [8](#).
nfluxes: [192](#).
NO_SLIDES: [3](#), [5](#), [15](#).
NO_UNSCATTERED_LIGHT: [3](#).
nslide: [60](#), [61](#).
num_measures: [16](#), [32](#), [51](#), [61](#), [63](#), [68](#), [81](#), [120](#),
[129](#), [216](#), [244](#), [248](#), [276](#), [295](#).
num_photons: [65](#), [66](#).
num_spheres: [12](#), [15](#), [32](#), [39](#), [44](#), [46](#), [53](#), [63](#), [66](#),
[72](#), [81](#), [99](#), [159](#), [295](#).
NUMBER_OF_GUESSES: [193](#), [198](#).
old_mm: [72](#), [132](#), [134](#).
old_rr: [72](#), [132](#), [134](#).
once: [167](#).
ONE_SLIDE_NEAR_SPHERE: [3](#), [5](#), [15](#).
ONE_SLIDE_NOT_NEAR_SPHERE: [3](#), [5](#), [15](#).
ONE_SLIDE_ON_BOTTOM: [3](#), [5](#), [15](#).
ONE_SLIDE_ON_TOP: [3](#), [5](#), [15](#).
optarg: [3](#), [5](#).
optind: [3](#), [5](#).
p: [197](#).
P_d: [161](#).
P_std: [161](#).
P_0: [161](#).
params: [2](#), [4](#), [11](#), [16](#), [80](#), [81](#), [84](#), [85](#), [92](#), [99](#).
parse_string_into_array: [5](#), [26](#).
phase_function: [13](#), [59](#), [120](#).
pi: [192](#).
points: [27](#).
pow: [10](#).
print_dot: [8](#), [12](#), [27](#).
print_error_legend: [2](#), [23](#).
Print_Invert_Type: [292](#).
Print_Measure_Type: [294](#).
print_optical_property_result: [6](#), [8](#), [12](#), [22](#).
print_results_header: [6](#), [11](#), [12](#), [21](#).
print_usage: [5](#), [18](#).
print_version: [5](#), [17](#).
printf: [14](#), [94](#), [95](#), [96](#), [97](#), [98](#), [99](#).
process_command_line: [2](#), [4](#), [5](#).
p1: [193](#).
p2: [193](#).
qsort: [198](#).
quad_Dif_Calc_R_and_T: [192](#).
quad_pts: [10](#), [40](#), [54](#), [59](#), [61](#), [67](#), [99](#), [120](#), [137](#),
[155](#), [293](#).
quick_guess: [193](#), [236](#), [275](#).
r: [4](#), [19](#), [20](#), [22](#), [26](#), [38](#), [43](#), [50](#), [54](#), [61](#), [65](#), [71](#), [73](#),
[75](#), [92](#), [115](#), [117](#), [119](#), [133](#), [138](#), [143](#), [146](#), [148](#),
[150](#), [152](#), [190](#), [195](#), [204](#), [206](#), [208](#), [210](#), [212](#), [215](#),
[220](#), [226](#), [231](#), [244](#), [270](#), [275](#), [292](#).
R_diffuse: [159](#), [161](#), [163](#).
R_direct: [159](#), [160](#), [161](#), [162](#), [163](#).
r_old: [189](#), [191](#).
R_0: [163](#).
rate: [27](#).
rc: [51](#), [244](#), [246](#), [247](#), [276](#).

- Rc*: [155](#), [157](#), [158](#), [159](#), [209](#), [211](#), [213](#).
rd: [51](#), [52](#), [244](#), [247](#), [276](#), [277](#), [278](#).
Rd: [209](#), [211](#), [213](#).
rd_r: [32](#), [48](#), [63](#), [69](#), [97](#), [105](#), [295](#).
rd_t: [32](#), [49](#), [63](#), [70](#), [98](#), [105](#), [295](#).
Read_Data_Line: [2](#), [84](#).
Read_Header: [2](#), [80](#).
read_number: [81](#), [82](#), [83](#), [85](#), [88](#).
REFLECTION_SPHERE: [100](#), [105](#), [107](#), [109](#), [113](#), [161](#).
RELATIVE: [30](#), [35](#), [57](#), [165](#), [166](#).
results: [64](#), [65](#).
RGRID: [100](#), [153](#).
rp: [192](#).
RR: [100](#), [102](#), [115](#), [116](#), [118](#), [120](#), [132](#), [137](#), [139](#),
[140](#), [141](#), [142](#), [144](#), [147](#), [149](#), [151](#), [154](#), [155](#),
[157](#), [164](#), [165](#), [166](#), [167](#), [169](#), [171](#), [173](#), [175](#),
[177](#), [179](#), [181](#), [183](#), [185](#), [187](#), [189](#).
rs: [192](#).
rstd_r: [15](#), [32](#), [48](#), [63](#), [66](#), [69](#), [76](#), [81](#), [85](#), [97](#),
[161](#), [162](#), [163](#), [295](#).
rstd_t: [15](#), [32](#), [46](#), [48](#), [49](#), [63](#), [70](#), [85](#), [98](#), [163](#), [295](#).
rt: [51](#), [53](#), [244](#), [247](#).
Rt: [209](#), [211](#), [213](#).
RT: [13](#), [135](#), [136](#).
RT_Flip: [135](#), [137](#), [155](#).
rt_name: [7](#).
rt_total: [8](#), [9](#), [11](#), [12](#).
ru: [44](#), [46](#).
rw_r: [15](#), [32](#), [48](#), [49](#), [63](#), [66](#), [69](#), [82](#), [85](#), [97](#), [105](#),
[111](#), [113](#), [161](#), [162](#), [295](#).
rw_t: [15](#), [32](#), [49](#), [63](#), [66](#), [70](#), [83](#), [85](#), [98](#), [105](#),
[111](#), [113](#), [295](#).
r1: [239](#), [240](#), [241](#), [242](#), [243](#).
r2: [239](#), [240](#), [241](#), [242](#), [243](#).
s: [13](#), [16](#), [24](#), [26](#), [121](#), [125](#), [133](#).
Same_Calc_State: [119](#), [153](#).
search: [8](#), [33](#), [39](#), [41](#), [51](#), [52](#), [53](#), [57](#), [76](#), [99](#),
[120](#), [139](#), [144](#), [147](#), [149](#), [151](#), [153](#), [164](#), [198](#),
[271](#), [274](#), [281](#), [293](#).
search_type: [34](#), [50](#), [121](#), [125](#), [133](#).
seconds_elapsed: [25](#), [27](#).
Set_Calc_State: [72](#), [115](#), [132](#), [134](#), [139](#), [144](#), [147](#),
[149](#), [151](#), [189](#), [191](#), [196](#), [205](#), [207](#), [209](#), [211](#), [213](#),
[214](#), [216](#), [221](#), [227](#), [232](#), [272](#), [273](#).
Set_Debugging: [5](#), [288](#).
setup: [64](#), [66](#).
skip_white: [86](#), [89](#).
slab: [6](#), [33](#), [46](#), [59](#), [74](#), [120](#), [132](#), [135](#), [136](#), [137](#),
[139](#), [140](#), [141](#), [142](#), [144](#), [147](#), [149](#), [151](#), [155](#), [157](#),
[167](#), [169](#), [171](#), [173](#), [175](#), [177](#), [179](#), [181](#), [183](#), [185](#),
[187](#), [189](#), [192](#), [196](#), [198](#), [201](#), [202](#), [204](#), [205](#), [206](#),
[207](#), [209](#), [211](#), [213](#), [214](#), [216](#), [219](#), [221](#), [225](#),
[230](#), [232](#), [235](#), [238](#), [240](#), [242](#), [243](#), [271](#), [272](#),
[273](#), [274](#), [278](#), [282](#), [283](#), [285](#), [293](#).
slab_bottom_slide_b: [15](#), [16](#), [32](#), [59](#), [63](#).
slab_bottom_slide_index: [15](#), [16](#), [32](#), [59](#), [61](#), [63](#),
[66](#), [81](#), [94](#), [130](#), [295](#).
slab_bottom_slide_thickness: [15](#), [32](#), [63](#), [66](#), [81](#),
[94](#), [295](#).
slab_cos_angle: [15](#), [16](#), [32](#), [59](#), [61](#), [63](#), [66](#), [99](#), [130](#).
slab_index: [15](#), [16](#), [32](#), [59](#), [61](#), [63](#), [66](#), [81](#), [94](#),
[130](#), [295](#).
slab_thickness: [10](#), [15](#), [19](#), [32](#), [63](#), [65](#), [66](#), [81](#),
[94](#), [295](#).
slab_top_slide_b: [15](#), [16](#), [32](#), [59](#), [63](#).
slab_top_slide_index: [15](#), [16](#), [32](#), [59](#), [61](#), [63](#), [66](#),
[81](#), [94](#), [130](#), [295](#).
slab_top_slide_thickness: [15](#), [32](#), [63](#), [66](#), [81](#), [94](#), [295](#).
slabtype: [192](#).
slide_bottom: [192](#).
slide_top: [192](#).
slow_guess: [270](#).
SMALL_A_VALUE: [238](#), [253](#).
smallest: [134](#).
Sp_mu_RT: [46](#).
Sp_mu_RT_Flip: [46](#), [155](#), [157](#).
sphere: [63](#), [104](#), [105](#).
sphere_r: [64](#), [69](#).
sphere_t: [64](#), [70](#).
Spheres_Inverse_RT: [64](#).
sqrt: [97](#), [98](#), [243](#), [253](#), [295](#).
sscanf: [5](#), [26](#).
start_time: [2](#), [4](#), [8](#), [12](#), [25](#), [27](#).
stderr: [2](#), [5](#), [7](#), [8](#), [12](#), [13](#), [14](#), [15](#), [17](#), [18](#), [23](#), [24](#), [27](#),
[39](#), [46](#), [51](#), [61](#), [66](#), [68](#), [91](#), [102](#), [116](#), [137](#), [139](#),
[144](#), [147](#), [149](#), [153](#), [155](#), [157](#), [167](#), [191](#), [196](#),
[198](#), [199](#), [205](#), [207](#), [209](#), [211](#), [213](#), [216](#), [217](#),
[221](#), [223](#), [232](#), [238](#), [278](#), [293](#), [295](#).
stdin: [2](#), [7](#).
stdout: [6](#), [7](#), [8](#), [11](#).
strcat: [24](#).
strcmp: [7](#).
strcpy: [24](#).
strdup: [5](#), [7](#), [24](#).
strdup_together: [7](#), [24](#).
strlen: [7](#), [24](#), [26](#).
strstr: [7](#).
strtod: [5](#).
SUBSTITUTION: [31](#), [81](#), [99](#).
swap: [136](#).
t: [24](#), [26](#), [133](#).
T_diffuse: [159](#), [163](#).
T_direct: [159](#), [160](#), [161](#), [162](#), [163](#).
T_TRUST_FACTOR: [100](#), [166](#).

- T_O:** [163](#).
tc: [51](#), [244](#), [246](#), [248](#), [276](#).
Tc: [60](#), [61](#), [155](#), [157](#), [158](#), [159](#), [209](#), [211](#), [213](#), [238](#), [241](#), [242](#), [243](#).
td: [51](#), [52](#), [244](#), [248](#), [276](#).
Td: [209](#), [211](#), [213](#), [244](#).
tdiffuse: [106](#), [107](#), [108](#), [109](#).
The_Grid: [100](#), [120](#), [122](#), [124](#), [127](#), [137](#), [139](#), [144](#), [147](#), [149](#), [151](#), [157](#).
The_Grid_Initialized: [100](#), [120](#), [122](#), [127](#), [139](#), [144](#), [147](#), [149](#), [151](#).
The_Grid_Search: [100](#), [128](#), [139](#), [144](#), [147](#), [149](#), [151](#).
tmp: [105](#), [277](#).
tolerance: [10](#), [33](#), [39](#), [57](#), [99](#), [196](#), [202](#), [205](#), [207](#), [209](#), [211](#), [214](#), [216](#), [221](#), [227](#), [232](#).
tp: [192](#), [244](#).
TRANSMISSION_SPHERE: [100](#), [107](#), [109](#), [111](#), [161](#).
TRUE: [29](#), [30](#), [39](#), [120](#), [126](#), [139](#), [144](#), [147](#), [149](#), [151](#).
ts: [192](#).
tst: [8](#).
tt: [51](#), [53](#), [244](#), [248](#).
Tt: [209](#), [211](#), [213](#).
tu: [44](#), [46](#).
TWO_IDENTICAL_SLIDES: [3](#), [5](#).
Two_Sphere_R: [110](#), [163](#).
Two_Sphere_T: [112](#), [163](#).
twoprime: [262](#), [267](#).
twounprime: [264](#), [267](#).
t1: [239](#), [240](#), [241](#), [242](#), [243](#).
t2: [239](#), [240](#), [241](#), [242](#), [243](#).
U_Find_A: [41](#), [208](#).
U_Find_AB: [41](#), [195](#).
U_Find_AG: [41](#), [215](#).
U_Find_B: [41](#), [76](#), [212](#).
U_Find_Ba: [41](#), [206](#).
U_Find_BaG: [41](#), [226](#).
U_Find_BG: [41](#), [220](#), [226](#), [231](#).
U_Find_Bs: [41](#), [204](#).
U_Find_BsG: [41](#), [231](#).
U_Find_G: [41](#), [210](#).
ungetc: [87](#).
UNINITIALIZED: [2](#), [4](#), [5](#), [6](#), [10](#), [15](#), [31](#), [45](#), [52](#), [53](#), [58](#), [74](#), [99](#), [196](#), [205](#), [207](#), [209](#), [211](#), [213](#), [216](#), [221](#), [232](#).
UNKNOWN: [31](#), [63](#), [99](#).
URU: [104](#), [105](#), [106](#), [107](#), [108](#), [109](#), [110](#), [111](#), [112](#), [113](#), [135](#), [136](#), [158](#), [159](#), [192](#).
uru: [9](#), [12](#), [13](#), [65](#), [72](#), [137](#), [155](#), [157](#).
URU_COLUMN: [100](#), [137](#), [157](#).
uru_lost: [12](#), [22](#), [32](#), [63](#), [65](#), [71](#), [72](#), [116](#), [159](#).
UR1: [60](#), [61](#), [110](#), [111](#), [112](#), [113](#), [135](#), [136](#), [158](#), [159](#), [192](#), [276](#), [278](#).
ur1: [9](#), [12](#), [13](#), [65](#), [72](#), [137](#), [155](#), [157](#).
UR1_COLUMN: [100](#), [137](#), [157](#).
ur1_loss: [190](#), [191](#).
ur1_lost: [12](#), [22](#), [32](#), [39](#), [63](#), [65](#), [72](#), [116](#), [159](#), [189](#), [191](#), [295](#).
UTU: [110](#), [111](#), [112](#), [113](#), [135](#), [136](#), [158](#), [159](#), [192](#).
utu: [9](#), [12](#), [13](#), [65](#), [72](#), [137](#), [155](#), [157](#).
UTU_COLUMN: [100](#), [137](#), [157](#).
utu_lost: [12](#), [22](#), [32](#), [63](#), [65](#), [72](#), [116](#), [159](#), [295](#).
UT1: [60](#), [61](#), [110](#), [111](#), [112](#), [113](#), [135](#), [136](#), [158](#), [159](#), [192](#), [276](#), [277](#), [278](#).
ut1: [9](#), [12](#), [13](#), [65](#), [72](#), [137](#), [155](#), [157](#).
UT1_COLUMN: [100](#), [137](#), [157](#).
ut1_loss: [190](#), [191](#).
ut1_lost: [12](#), [22](#), [32](#), [39](#), [63](#), [65](#), [72](#), [116](#), [159](#), [189](#), [191](#), [295](#).
Valid_Grid: [125](#), [198](#), [274](#).
verbosity: [27](#).
Version: [17](#), [18](#), [94](#).
what_char: [22](#), [27](#).
What_Is_B: [16](#), [216](#), [238](#), [246](#), [278](#), [282](#), [283](#), [285](#).
Write_Header: [6](#), [11](#), [92](#).
x: [76](#), [81](#), [88](#), [111](#), [113](#), [139](#), [168](#), [170](#), [172](#), [174](#), [176](#), [178](#), [180](#), [182](#), [184](#), [186](#), [197](#), [209](#), [211](#), [214](#), [271](#).
xx: [94](#), [99](#).
y: [197](#).
zbrent: [191](#).

⟨ Allocate local simplex variables 197 ⟩ Used in sections 196, 216, 221, 227, and 232.
 ⟨ Calc M_R and M_T for dual beam sphere 162 ⟩ Used in section 159.
 ⟨ Calc M_R and M_T for no spheres 160 ⟩ Used in section 159.
 ⟨ Calc M_R and M_T for single beam sphere 161 ⟩ Used in section 159.
 ⟨ Calc M_R and M_T for two spheres 163 ⟩ Used in section 159.
 ⟨ Calculate and Print the Forward Calculation 6 ⟩ Used in section 2.
 ⟨ Calculate and write optical properties 8 ⟩ Used in section 2.
 ⟨ Calculate specular reflection and transmission 240 ⟩ Used in section 239.
 ⟨ Calculate the deviation 164 ⟩ Used in section 159.
 ⟨ Calculate the unscattered transmission and reflection 246 ⟩ Used in section 245.
 ⟨ Check MR for zero or one spheres 45 ⟩ Used in section 44.
 ⟨ Check MT for zero or one spheres 46 ⟩ Used in section 44.
 ⟨ Check MU 47 ⟩ Used in section 44.
 ⟨ Check for bad values of Tc 241 ⟩ Used in section 239.
 ⟨ Check sphere parameters 48, 49 ⟩ Used in section 44.
 ⟨ Choose the best node of the a and b simplex 201 ⟩ Used in section 196.
 ⟨ Choose the best node of the a and g simplex 219 ⟩ Used in section 216.
 ⟨ Choose the best node of the ba and g simplex 230 ⟩ Used in section 227.
 ⟨ Choose the best node of the bs and g simplex 235 ⟩ Used in section 232.
 ⟨ Choose the best node of the b and g simplex 225 ⟩ Used in section 221.
 ⟨ Clean up guesses 286 ⟩ Used in section 276.
 ⟨ Command-line changes to m 15 ⟩ Used in section 2.
 ⟨ Command-line changes to r 10 ⟩ Used in sections 2 and 8.
 ⟨ Count command-line measurements 16 ⟩ Used in section 2.
 ⟨ Declare variables for *main* 4 ⟩ Used in section 2.
 ⟨ Definition for *Allocate_Grid* 122 ⟩ Used in section 100.
 ⟨ Definition for *Calculate_Distance_With_Corrections* 159 ⟩ Used in section 100.
 ⟨ Definition for *Calculate_Distance* 155 ⟩ Used in section 100.
 ⟨ Definition for *Calculate_Grid_Distance* 157 ⟩ Used in section 100.
 ⟨ Definition for *Calculate_MR_MT* 72 ⟩ Used in section 35.
 ⟨ Definition for *Calculate_Minimum_MR* 74 ⟩ Used in section 35.
 ⟨ Definition for *Debug* 291 ⟩ Used in section 236.
 ⟨ Definition for *Estimate_RT* 245 ⟩ Used in section 236.
 ⟨ Definition for *Fill_AB_Grid* 139 ⟩ Used in section 100.
 ⟨ Definition for *Fill_AG_Grid* 144 ⟩ Used in section 100.
 ⟨ Definition for *Fill_BG_Grid* 147 ⟩ Used in section 100.
 ⟨ Definition for *Fill_BaG_Grid* 149 ⟩ Used in section 100.
 ⟨ Definition for *Fill_BsG_Grid* 151 ⟩ Used in section 100.
 ⟨ Definition for *Fill_Grid* 153 ⟩ Used in section 100.
 ⟨ Definition for *Find_AB_fn* 171 ⟩ Used in section 100.
 ⟨ Definition for *Find_AG_fn* 169 ⟩ Used in section 100.
 ⟨ Definition for *Find_A_fn* 177 ⟩ Used in section 100.
 ⟨ Definition for *Find_BG_fn* 183 ⟩ Used in section 100.
 ⟨ Definition for *Find_B_fn* 179 ⟩ Used in section 100.
 ⟨ Definition for *Find_BaG_fn* 185 ⟩ Used in section 100.
 ⟨ Definition for *Find_Ba_fn* 173 ⟩ Used in section 100.
 ⟨ Definition for *Find_BsG_fn* 187 ⟩ Used in section 100.
 ⟨ Definition for *Find_Bs_fn* 175 ⟩ Used in section 100.
 ⟨ Definition for *Find_G_fn* 181 ⟩ Used in section 100.
 ⟨ Definition for *Gain_11* 107 ⟩ Used in section 100.
 ⟨ Definition for *Gain_22* 109 ⟩ Used in section 100.
 ⟨ Definition for *Gain* 105 ⟩ Used in section 100.

⟨ Definition for *Get_Calc_State* 118 ⟩ Used in section 100.
 ⟨ Definition for *Grid_ABG* 124 ⟩ Used in section 100.
 ⟨ Definition for *Initialize_Measure* 63 ⟩ Used in section 35.
 ⟨ Definition for *Initialize_Result* 55 ⟩ Used in section 35.
 ⟨ Definition for *Inverse_RT* 39 ⟩ Used in section 35.
 ⟨ Definition for *Max_Light_Loss* 191 ⟩ Used in section 100.
 ⟨ Definition for *MinMax_MR_MT* 76 ⟩ Used in section 35.
 ⟨ Definition for *Near_Grid_Points* 134 ⟩ Used in section 100.
 ⟨ Definition for *Print_Invert_Type* 293 ⟩ Used in section 236.
 ⟨ Definition for *Print_Measure_Type* 295 ⟩ Used in section 236.
 ⟨ Definition for *RT_Flip* 136 ⟩ Used in section 100.
 ⟨ Definition for *Read_Data_Line* 85 ⟩ Used in section 77.
 ⟨ Definition for *Read_Header* 81 ⟩ Used in section 77.
 ⟨ Definition for *Same_Calc_State* 120 ⟩ Used in section 100.
 ⟨ Definition for *Set_Calc_State* 116 ⟩ Used in section 100.
 ⟨ Definition for *Set_Debugging* 289 ⟩ Used in section 236.
 ⟨ Definition for *Spheres_Inverse_RT* 65 ⟩ Used in section 35.
 ⟨ Definition for *Two_Sphere_R* 111 ⟩ Used in section 100.
 ⟨ Definition for *Two_Sphere_T* 113 ⟩ Used in section 100.
 ⟨ Definition for *U_Find_AB* 196 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_AG* 216 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_A* 209 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_BG* 221 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_BaG* 227 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_Ba* 207 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_BsG* 232 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_Bs* 205 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_B* 213 ⟩ Used in section 193.
 ⟨ Definition for *U_Find_G* 211 ⟩ Used in section 193.
 ⟨ Definition for *Valid_Grid* 126 ⟩ Used in section 100.
 ⟨ Definition for *What_Is_B* 239 ⟩ Used in section 236.
 ⟨ Definition for *Write_Header* 93 ⟩ Used in section 77.
 ⟨ Definition for *a2acalc* 251 ⟩ Used in section 236.
 ⟨ Definition for *abg_distance* 132 ⟩ Used in section 100.
 ⟨ Definition for *abgb2ag* 269 ⟩ Used in section 236.
 ⟨ Definition for *abgg2ab* 267 ⟩ Used in section 236.
 ⟨ Definition for *acalc2a* 253 ⟩ Used in section 236.
 ⟨ Definition for *b2bcalc* 259 ⟩ Used in section 236.
 ⟨ Definition for *bcalc2b* 261 ⟩ Used in section 236.
 ⟨ Definition for *check_magic* 91 ⟩ Used in section 77.
 ⟨ Definition for *determine_search* 51 ⟩ Used in section 35.
 ⟨ Definition for *ez_Inverse_RT* 61 ⟩ Used in section 35.
 ⟨ Definition for *fill_grid_entry* 137 ⟩ Used in section 100.
 ⟨ Definition for *g2gcalc* 255 ⟩ Used in section 236.
 ⟨ Definition for *gcalc2g* 257 ⟩ Used in section 236.
 ⟨ Definition for *maxloss* 189 ⟩ Used in section 100.
 ⟨ Definition for *measure_OK* 44 ⟩ Used in section 35.
 ⟨ Definition for *quick_guess* 276 ⟩ Used in section 236.
 ⟨ Definition for *read_number* 89 ⟩ Used in section 77.
 ⟨ Definition for *skip_white* 87 ⟩ Used in section 77.
 ⟨ Definition for *slow_guess* 271 ⟩
 ⟨ Definition for *twoprime* 263 ⟩ Used in section 236.

- ⟨ Definition for *twounprime* 265 ⟩ Used in section 236.
- ⟨ Estimate the backscattered reflection 247 ⟩ Used in section 245.
- ⟨ Estimate the scattered transmission 248 ⟩ Used in section 245.
- ⟨ Estimate *aprime* 277 ⟩ Used in section 276.
- ⟨ Estimate *bprime* 278 ⟩ Used in sections 280, 284, and 285.
- ⟨ Evaluate the *BaG* simplex at the nodes 229 ⟩ Used in section 227.
- ⟨ Evaluate the *BsG* simplex at the nodes 234 ⟩ Used in section 232.
- ⟨ Evaluate the *a* and *b* simplex at the nodes 200 ⟩ Used in section 196.
- ⟨ Evaluate the *a* and *g* simplex at the nodes 218 ⟩ Used in section 216.
- ⟨ Evaluate the *bg* simplex at the nodes 224 ⟩ Used in section 221.
- ⟨ Exit with bad input data 40 ⟩ Used in section 39.
- ⟨ Fill *r* with reasonable values 56, 57, 58, 59 ⟩ Used in section 55.
- ⟨ Find the optical properties 41 ⟩ Used in section 39.
- ⟨ Find thickness when multiple internal reflections are present 243 ⟩ Used in section 239.
- ⟨ Free simplex data structures 203 ⟩ Used in sections 196, 216, 221, 227, and 232.
- ⟨ Generate next albedo using *j* 141, 142 ⟩ Used in sections 139 and 144.
- ⟨ Get the initial *a*, *b*, and *g* 198 ⟩ Used in sections 196, 216, 221, 227, and 232.
- ⟨ Guess when all three measurements are known 281 ⟩ Used in section 276.
- ⟨ Guess when finding albedo 282 ⟩ Used in section 281.
- ⟨ Guess when finding anisotropy and albedo 285 ⟩ Used in section 281.
- ⟨ Guess when finding optical depth 283 ⟩ Used in section 281.
- ⟨ Guess when finding the albedo and optical depth 284 ⟩ Used in section 281.
- ⟨ Guess when only reflection is known 279 ⟩ Used in section 276.
- ⟨ Guess when reflection and transmission are known 280 ⟩ Used in section 276.
- ⟨ Handle options 5 ⟩ Used in section 2.
- ⟨ Improve result using Monte Carlo 12 ⟩ Used in section 8.
- ⟨ Include files for *main* 3 ⟩ Used in section 2.
- ⟨ Initialize the nodes of the *a* and *b* simplex 199 ⟩ Used in section 196.
- ⟨ Initialize the nodes of the *a* and *g* simplex 217 ⟩ Used in section 216.
- ⟨ Initialize the nodes of the *ba* and *g* simplex 228 ⟩ Used in section 227.
- ⟨ Initialize the nodes of the *bs* and *g* simplex 233 ⟩ Used in section 232.
- ⟨ Initialize the nodes of the *b* and *g* simplex 223 ⟩ Used in section 221.
- ⟨ Iteratively solve for *b* 214 ⟩ Used in section 213.
- ⟨ Local Variables for Calculation 9 ⟩ Used in section 8.
- ⟨ Nonworking code 140 ⟩
- ⟨ One parameter deviation 165 ⟩ Used in section 164.
- ⟨ One parameter search 52 ⟩ Used in section 51.
- ⟨ Print diagnostics 167 ⟩ Used in section 159.
- ⟨ Print results function 22 ⟩ Used in section 2.
- ⟨ Prototype for *Allocate_Grid* 121 ⟩ Used in sections 101 and 122.
- ⟨ Prototype for *Calculate_Distance_With_Corrections* 158 ⟩ Used in sections 101 and 159.
- ⟨ Prototype for *Calculate_Distance* 154 ⟩ Used in sections 101 and 155.
- ⟨ Prototype for *Calculate_Grid_Distance* 156 ⟩ Used in sections 101 and 157.
- ⟨ Prototype for *Calculate_MR_MT* 71 ⟩ Used in sections 36 and 72.
- ⟨ Prototype for *Calculate_Minimum_MR* 73 ⟩ Used in sections 36 and 74.
- ⟨ Prototype for *Debug* 290 ⟩ Used in sections 237 and 291.
- ⟨ Prototype for *Estimate_RT* 244 ⟩ Used in sections 237 and 245.
- ⟨ Prototype for *Fill_AB_Grid* 138 ⟩ Used in sections 100 and 139.
- ⟨ Prototype for *Fill_AG_Grid* 143 ⟩ Used in sections 100 and 144.
- ⟨ Prototype for *Fill_BG_Grid* 146 ⟩ Used in sections 101 and 147.
- ⟨ Prototype for *Fill_BaG_Grid* 148 ⟩ Used in sections 101 and 149.
- ⟨ Prototype for *Fill_BsG_Grid* 150 ⟩ Used in sections 101 and 151.

- ⟨Prototype for *Fill_Grid* 152⟩ Used in sections 101 and 153.
- ⟨Prototype for *Find_AB_fn* 170⟩ Used in sections 101 and 171.
- ⟨Prototype for *Find_AG_fn* 168⟩ Used in sections 101 and 169.
- ⟨Prototype for *Find_A_fn* 176⟩ Used in sections 101 and 177.
- ⟨Prototype for *Find_BG_fn* 182⟩ Used in sections 101 and 183.
- ⟨Prototype for *Find_B_fn* 178⟩ Used in sections 101 and 179.
- ⟨Prototype for *Find_BaG_fn* 184⟩ Used in sections 101 and 185.
- ⟨Prototype for *Find_Ba_fn* 172⟩ Used in sections 101 and 173.
- ⟨Prototype for *Find_BsG_fn* 186⟩ Used in sections 101 and 187.
- ⟨Prototype for *Find_Bs_fn* 174⟩ Used in sections 101 and 175.
- ⟨Prototype for *Find_G_fn* 180⟩ Used in sections 101 and 181.
- ⟨Prototype for *Gain_11* 106⟩ Used in sections 101 and 107.
- ⟨Prototype for *Gain_22* 108⟩ Used in sections 101 and 109.
- ⟨Prototype for *Gain* 104⟩ Used in sections 101 and 105.
- ⟨Prototype for *Get_Calc_State* 117⟩ Used in sections 101 and 118.
- ⟨Prototype for *Grid_ABG* 123⟩ Used in sections 101 and 124.
- ⟨Prototype for *Initialize_Measure* 62⟩ Used in sections 36 and 63.
- ⟨Prototype for *Initialize_Result* 54⟩ Used in sections 36 and 55.
- ⟨Prototype for *Inverse_RT* 38⟩ Used in sections 36 and 39.
- ⟨Prototype for *Max_Light_Loss* 190⟩ Used in sections 101 and 191.
- ⟨Prototype for *MinMax_MR_MT* 75⟩ Used in sections 36 and 76.
- ⟨Prototype for *Near_Grid_Points* 133⟩ Used in sections 101 and 134.
- ⟨Prototype for *Print_Invert_Type* 292⟩ Used in sections 237 and 293.
- ⟨Prototype for *Print_Measure_Type* 294⟩ Used in sections 237 and 295.
- ⟨Prototype for *RT_Flip* 135⟩ Used in section 136.
- ⟨Prototype for *Read_Data_Line* 84⟩ Used in sections 78 and 85.
- ⟨Prototype for *Read_Header* 80⟩ Used in sections 78 and 81.
- ⟨Prototype for *Same_Calc_State* 119⟩ Used in sections 101 and 120.
- ⟨Prototype for *Set_Calc_State* 115⟩ Used in sections 101 and 116.
- ⟨Prototype for *Set_Debugging* 288⟩ Used in sections 237 and 289.
- ⟨Prototype for *Spheres_Inverse_RT* 64⟩ Used in sections 37 and 65.
- ⟨Prototype for *Two_Sphere_R* 110⟩ Used in sections 101 and 111.
- ⟨Prototype for *Two_Sphere_T* 112⟩ Used in sections 101 and 113.
- ⟨Prototype for *U_Find_AB* 195⟩ Used in sections 194 and 196.
- ⟨Prototype for *U_Find_AG* 215⟩ Used in sections 194 and 216.
- ⟨Prototype for *U_Find_A* 208⟩ Used in sections 194 and 209.
- ⟨Prototype for *U_Find_BG* 220⟩ Used in sections 194 and 221.
- ⟨Prototype for *U_Find_BaG* 226⟩ Used in sections 194 and 227.
- ⟨Prototype for *U_Find_Ba* 206⟩ Used in sections 194 and 207.
- ⟨Prototype for *U_Find_BsG* 231⟩ Used in sections 194 and 232.
- ⟨Prototype for *U_Find_Bs* 204⟩ Used in sections 194 and 205.
- ⟨Prototype for *U_Find_B* 212⟩ Used in sections 194 and 213.
- ⟨Prototype for *U_Find_G* 210⟩ Used in sections 194 and 211.
- ⟨Prototype for *Valid_Grid* 125⟩ Used in sections 101 and 126.
- ⟨Prototype for *What_Is_B* 238⟩ Used in sections 237 and 239.
- ⟨Prototype for *Write_Header* 92⟩ Used in sections 78 and 93.
- ⟨Prototype for *a2acalc* 250⟩ Used in sections 237 and 251.
- ⟨Prototype for *abg_distance* 131⟩ Used in sections 101 and 132.
- ⟨Prototype for *abgb2ag* 268⟩ Used in sections 237 and 269.
- ⟨Prototype for *abgg2ab* 266⟩ Used in sections 237 and 267.
- ⟨Prototype for *acalc2a* 252⟩ Used in sections 237 and 253.
- ⟨Prototype for *b2bcalc* 258⟩ Used in sections 237 and 259.

< Prototype for *bcalc2b* 260 > Used in sections 237 and 261.
 < Prototype for *check_magic* 90 > Used in section 91.
 < Prototype for *determine_search* 50 > Used in sections 36 and 51.
 < Prototype for *ez_Inverse_RT* 60 > Used in sections 36, 37, and 61.
 < Prototype for *g2gcalc* 254 > Used in sections 237 and 255.
 < Prototype for *gcalc2g* 256 > Used in sections 237 and 257.
 < Prototype for *maxloss* 188 > Used in sections 101 and 189.
 < Prototype for *measure_OK* 43 > Used in sections 36 and 44.
 < Prototype for *quick_guess* 275 > Used in sections 237 and 276.
 < Prototype for *read_number* 88 > Used in section 89.
 < Prototype for *skip_white* 86 > Used in section 87.
 < Prototype for *slow_guess* 270 > Used in section 271.
 < Prototype for *twoprime* 262 > Used in sections 237 and 263.
 < Prototype for *twounprime* 264 > Used in sections 237 and 265.
 < Put final values in result 202 > Used in sections 196, 205, 207, 209, 211, 213, 216, 221, 227, and 232.
 < Read coefficients for reflection sphere 82 > Used in section 81.
 < Read coefficients for transmission sphere 83 > Used in section 81.
 < Slow guess for *a* alone 272 > Used in section 271.
 < Slow guess for *a* and *b* or *a* and *g* 274 > Used in section 271.
 < Slow guess for *b* alone 273 > Used in section 271.
 < Solve if multiple internal reflections are not present 242 > Used in section 239.
 < Structs to export from IAD Types 32, 33, 34 > Used in section 29.
 < Testing MC code 13 >
 < Tests for invalid grid 127, 128, 129, 130 > Used in section 126.
 < Two parameter deviation 166 > Used in section 164.
 < Two parameter search 53 > Used in section 51.
 < Unused diffusion fragment 192 >
 < Write Header 11 > Used in section 8.
 < Write first sphere info 97 > Used in section 93.
 < Write general sphere info 96 > Used in section 93.
 < Write irradiation info 95 > Used in section 93.
 < Write measure and inversion info 99 > Used in section 93.
 < Write second sphere info 98 > Used in section 93.
 < Write slab info 94 > Used in section 93.
 < Zero GG 145 > Used in sections 139, 144, 147, 149, and 151.
 < calculate coefficients function 19, 20 > Used in section 2.
 < handle analysis 67 > Used in section 65.
 < handle measurement 68 > Used in section 65.
 < handle reflection sphere 69 > Used in section 65.
 < handle setup 66 > Used in section 65.
 < handle transmission sphere 70 > Used in section 65.
 < iad_calc.c 100 >
 < iad_calc.h 101 >
 < iad_find.c 193 >
 < iad_find.h 194 >
 < iad_io.c 77 >
 < iad_io.h 78 >
 < iad_main.c 2 >
 < iad_main.h 1 >
 < iad_pub.c 35 >
 < iad_pub.h 36 >
 < iad_type.h 29 >

`< iad_util.c 236 >`
`< iad_util.h 237 >`
`< lib_iad.h 37 >`
`< old formatting 14 >`
`< parse string into array function 26 >` Used in section 2.
`< prepare file for reading 7 >` Used in section 2.
`< print dot function 27 >` Used in section 2.
`< print error legend function 23 >` Used in section 2.
`< print results header function 21 >` Used in section 2.
`< print usage function 18 >` Used in section 2.
`< print version function 17 >` Used in section 2.
`< seconds elapsed function 25 >` Used in section 2.
`< strdup together function 24 >` Used in section 2.

Inverse Adding-Doubling

(Version 3.6.3)

	Section	Page
Main Program	1	1
IAD Types	28	24
IAD Public	35	28
Inverse RT	38	29
Validation	42	30
Searching Method	50	33
EZ Inverse RT	60	37
IAD Input Output	77	45
Reading the file header	79	45
Reading just one line of a data file	84	47
Formatting the header information	92	49
IAD Calculation	100	53
Initialization	102	55
Gain	103	56
Grid Routines	114	59
Calculating R and T	154	72
IAD Find	193	84
Fixed Anisotropy	195	85
Fixed Absorption and Anisotropy	204	88
Fixed Absorption and Scattering	206	89
Fixed Optical Depth and Anisotropy	208	90
Fixed Optical Depth and Albedo	210	91
Fixed Anisotropy and Albedo	212	92
Fixed Optical Depth	215	93
Fixed Albedo	220	96
Fixed Scattering	226	98
Fixed Absorption	231	99
IAD Utilities	236	101
Finding optical thickness	238	102
Estimating R and T	244	105
Transforming properties	249	106
Guessing an inverse	270	111
Some debugging stuff	287	115
Index	296	118

Copyright © 2010 Scott Prahl

Permission is granted to make and distribute verbatim copies of this document provided that the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this document under the conditions for verbatim copying, provided that the entire resulting derived work is given a different name and distributed under the terms of a permission notice identical to this one.