

The Rust programming language

Paolo Bettelini

Contents

1	Data Types	2
1.1	Primitive Types	2
1.2	Tuples	2
1.3	Arrays	2
1.3.1	Definition	2
1.3.2	Indexing	2
1.3.3	Slices	2
1.4	Struct	3
1.4.1	Definition	3
1.5	Union	3
2	Loops	4
2.1	Loop	4
2.2	While	4
2.3	For	4
2.4	Returning from loops	4
2.5	Labels	4
2.6	Returning from labelled loops	5
3	Pattern Matching	5
3.1	Basic	5
3.2	Destructuring	6
3.3	Ignoring values	6
3.4	Match guards	7
3.5	@ bindings	7
4	Common types	8
4.1	Option	8
4.2	Result	8
4.2.1	Definition	8
4.2.2	? operator	9
4.3	Box	9
4.4	Rc	9
4.5	Arc	9

1 Data Types

1.1 Primitive Types

```
// boolean
bool

// signed integers
i8, i16, i32, i64, i128, isize

// unsigned integers
u8, u16, u32, u64, u128, usize

// floating points
f32, f64

// Text
char, str
```

1.2 Tuples

Tuples are a combination of multiple types. Tuples can contain any number of types and/or other tuples.

```
let coordinates = (101, 3, 4);
let person = ("Paolo", "Bettellini", 18);
let status: (bool, (u128, i32)) = (true, (1u128, 2));
```

1.3 Arrays

1.3.1 Definition

An array is defined by its type and length.

```
let values = [1, 2, 3, 4, 5];
// with explicit type
let values: [i32; 5] = [1, 2, 3, 4, 5];
```

We can also initialize an array by specifying its default value and length

```
let values = [0; 5]; // [0, 0, 0, 0, 0]
```

1.3.2 Indexing

We can index an array element using the square brackets

```
let first = values[0];
let second = values[1];
```

1.3.3 Slices

We can point to a portion of the array using slices

```

let slice = &values[1..5];
let slice = &values[1..=5];
let slice = &values[..5];
let slice = &values[1..];
let slice = &values[..];

```

1.4 Struct

1.4.1 Definition

Structs are a way to group multiple values into a single definition.

```

struct Measurement {
    id: u32,
    weight: f64,
    velocity: f64
}

```

Structs can be initialized as follows

```

let result = Measurement {
    id: 0,
    weight: 55.5,
    velocity: 22.0
};

```

Variables can accessed

```

let id = result.id;
let weight = result.weight;

```

A struct can omit the names of its fields

```

struct MyStruct (i32, f64);

fn main() {
    let result = MyStruct (0, 5.5);
    let a = result.0; // accessing
    let b = result.1;
}

```

1.5 Union

A union allows to store different data types in the same memory location. Every field must have the same size.

```

union Num {
    f: f32,
    i: i32
}

```

2 Loops

2.1 Loop

An infinite loop

```
loop {  
    // ...  
}
```

2.2 While

A while loop

```
while a > 0 {  
    // ...  
}
```

2.3 For

A for loop

```
for i in 0..10 {  
    // ...  
}
```

2.4 Returning from loops

```
let mut counter = 0;  
  
let result = loop {  
    counter += 1;  
  
    if counter == 10 {  
        break counter;  
    }  
};
```

2.5 Labels

```
'outer: loop {  
    'inner: loop {  
        // This breaks the inner loop  
        break;  
        // This breaks the outer loop  
        break 'outer;  
    }  
}
```

2.6 Returning from labelled loops

```
let mut counter = 0;

let result = 'outer: loop {
    counter += 1;

    if counter == 10 {
        break 'outer counter;
    }
};
```

3 Pattern Matching

3.1 Basic

```
let x = 5;

match x {
    // matching literals
    1 => println!("one"),
    // matching multiple patterns
    2 | 3 => println!("two or three"),
    // matching ranges
    4..=9 => println!("within range"),
    // matching named variables
    x => println!("{}", x),
    // default case (ignores value)
    _ => println!("default Case")
}
```

3.2 Destructuring

```
struct Point {
  x: i32,
  y: i32,
}

let p = Point { x: 0, y: 7 };

match p {
  Point { x, y: 0 } => {
    println!("{}", x);
  },
  Point { x, y } => {
    println!("{}", x, y);
  },
}

enum Shape {
  Rectangle { width: i32, height: i32 },
  Circle(i32),
}

let shape = Shape::Circle(10);

match shape {
  Shape::Rectangle { x, y } => //...
  Shape::Circle(radius) => //...
}
```

3.3 Ignoring values

```
struct SemVer(i32, i32, i32);

let version = SemVer(1, 32, 2);

match version {
  SemVer(major, _, _) => {
    println!("{}", major);
  }
}

let numbers = (2, 4, 8, 16, 32);

match numbers {
  (first, .., last) => {
    println!("{}", first, last);
  }
}
```

3.4 Match guards

```
let num = Some(4);

match num {
  Some(x) if x < 5 => println!("less than five: {}", x),
  Some(x) => println!("{}", x),
  None => (),
}
```

3.5 @ bindings

Bind value to a name

```
match beaufort() {
  v @ 0..1    => println!("Calm : {} km/h", v),
  v @ 1..=5   => println!("Light Air : {} km/h", v),
  v @ 5..=11  => println!("Light Breeze : {} km/h", v),
  v @ 11..=19 => println!("Gentle Breeze : {} km/h", v)
}
```

4 Common types

4.1 Option

A function that may fail might enclose its return value in an **Option** enum, to notify whether the action was successful.

```
fn sqrt(v: f64) -> Option<(f64, f64)> {
    if v < 0.0 {
        return None;
    }

    let sqrt = v.sqrt();
    Some((sqrt, -sqrt))
}
```

4.2 Result

4.2.1 Definition

The **Result** enum is similar to **Option** but it specifies why the function has failed.

When the function doesn't really need to return anything other than the **Result** status, `()` can be used.

```
enum ErrorType {
    NegativeBase,
    NegativeArgument,
    BaseOne
}

fn log(base: f64, arg: f64) -> Result<f64, ErrorType> {
    if base <= 0.0 {
        return Err(ErrorType::NegativeBase);
    }

    if base == 1.0 {
        return Err(ErrorType::BaseOne);
    }

    if arg <= 0.0 {
        return Err(ErrorType::NegativeArgument);
    }

    let result = arg.log(base);
    Ok(result)
}
```


4.2.2 ? operator

The ? operator is syntax sugar for **Result** handling.

This operator can be placed at the end of a **Result** type. If the result is an error, the function returns it, otherwise unwraps its value.

```
fn log(base: f64, arg: f64) -> Result<f64, ErrorType> { ... }

fn something() -> Result<f64, ErrorType> {
    let v = match log(2.718, 3.14) {
        Ok(v) => v,
        Err(e) => return Err(e)
    };

    // use `v`
}
```

can be written as

```
fn log(base: f64, arg: f64) -> Result<f64, ErrorType> { ... }

fn something() -> Result<f64, ErrorType> {
    let v = log(2.718, 3.14)?;

    // use `v`
}
```

4.3 Box

`Box<T>` is a smart pointer used for heap allocation. You can dereference a `Box` to access its value.

```
// Moving a value from stack to heap
let boxed = Box::new(num);
// or
let boxed = box num;

let a = *boxed + 42;
```

4.4 Rc

The `Rc<T>` smart pointer (Reference Counted) is a type that provides shared ownership of a heap allocated value. Cloning an `Rc` produces a shallow copy. This data type keeps count of all the owners, and drops the value when there are 0 owners.

```
let foo = Rc::new(value);
let bar = foo.clone();
// both point to `value`
```

4.5 Arc

The `Arc<T>` smart pointer (Atomic Reference Counted) is the same as `Rc<T>` but uses atomic operations to increment the owner counter, so it is thread-safe.