Category Theory

Paolo Bettelini

Contents

1 Category

A category consists of *objects* and *morphism* or *arrows*.
An arrow has a beginning and an ending, and it goes from one object to another.
Objects serve the purpose of marking the beginning and ending of a morphism.

$$\begin{tikzcd} a \arrow[loop left] \arrow[r, bend left=40] \arrow[r, bend left=10] & b \arrow[l, bend left=30] \arrow[loop right] \end{tikzcd}$$ An example of
objects and morphisms

1.1 Composition

Composition is a property that says that if there is an arrow from a to b, and an arrow from b to c, there must exist an arrow from a to c.

$$\begin{tikzcd} a \arrow[r, "f"] \arrow[rr, bend left, "f \circ g"] & b \arrow[r, "g"] & c \end{tikzcd}$$

1.2 Identity

For every object there is an identity arrow.

$$\begin{tikzcd} a \arrow[loop right, "\mathrm{id}_a"] \end{tikzcd}$$

The composition of an arrow with an identity is the arrow itself

$$\begin{tikzcd} a \arrow[r, "f"] & b \arrow[loop right, "\mathrm{id}_b"] \end{tikzcd}$$

$$f \circ \mathrm{id}_b = f$$

and also vice versa

$$\mathrm{id}_b \circ f = f$$

1.3 Associativity

Compositions have the associative property

$$\begin{tikzcd} a \arrow[r, "f"] \arrow[rr, bend left, "g \circ f"] \arrow[rrr, bend left=50, "h \circ (g \circ f)"] \arrow[rrr, bend right=50, "(h \circ g) \circ f"'] & b \arrow[r, "g"] \arrow[rr, bend right, "h \circ g"'] & c \arrow[r, "h"] & d \end{tikzcd}$$

$$h \circ (g \circ f) = (h \circ g) \circ f$$

2 Homomorphism

An Homomorphism is a map between two structures of the same type.

2.1 Isomorphisms

A function f going from a to b

$$f: \quad a \to b$$

is invertible if there is a function g that goes from b to a

$$b: \quad b \to a$$

such that

$$g \circ f = \mathrm{id}_b$$
$$f \circ g = \mathrm{id}_a$$

$$\begin{tikzcd} a \arrow[r, bend left, "f"] & b \arrow[l, bend left, "g"] \end{tikzcd}$$

This is a *bijective* homomorphism and it's called isomorphism. An isomorphism is labelled $\xrightarrow{\sim}$.

2.2 Epimorphisms

$$\begin{tikzcd} a \arrow[r, "f"] & b \arrow[r, shift left, "g_1"] \arrow[r, shift right, "g_2"'] & c \end{tikzcd}$$

2.3 Monomorphisms