

Sorting Algorithms

Paolo Bettelini

Contents

1	Bubble Sort	2
2	Selection Sort	3

1 Bubble Sort

Given a list of numbers a .

We check each pair of adjacent numbers in the list (a_i, a_{i+1}) .

If $a_i > a_{i+1}$, we swap a_i and a_{i+1} .

We repeat this process until we check every tuple without performing the swap operation.

	Best-case	Average-case	Worst-case
comparison	$O(n)$	$O(n^2)$	$O(n^2)$
swap	$O(1)$	$O(n^2)$	$O(n^2)$

Algorithm 1 Bubble Sort

```
swapped  $\leftarrow$  false
do
  swapped  $\leftarrow$  false
  for  $i \leftarrow 0$  to  $\text{length}(a) - 1$  do
    if  $a_i > a_{i+1}$  then
      swapped  $\leftarrow$  true
      swap  $a_i$  and  $a_{i+1}$ 
while swapped
```

2 Selection Sort

Given a list of numbers a .

We find the minimum value in the list starting from an offset of 1.

We swap the minimum value and the value before the offset.

We increment the offset by 1 and repeat this process while the offset is less than the length of the list.

	Best-case	Average-case	Worst-case
comparison	$O(n^2)$	$O(n^2)$	$O(n^2)$
swap	$O(1)$	$O(n)$	$O(n)$

Algorithm 2 Selection Sort

```
for  $i \leftarrow 0$  to  $\text{length}(a) - 1$  do
   $\text{min} \leftarrow i$ 
  for  $j \leftarrow i + 1$  to  $\text{length}(a)$  do
    if  $a_j < a_{\text{min}}$  then
       $\text{min} \leftarrow j$ 
  swap  $a_i$  and  $a_{\text{min}}$ 
```
