Assignment 1

Multi Agent Systems for Smart Machining
ECIU Micro-Module
Offered by INSA Toulouse · Academic Year 2026/27

UNIVERSITÀ DI TRENTO

Paolo Rossi – 277177

27 October 2026

Status: To Be Reviewed

Abstract. Turning power is compared with chapter-based predictions for constant cutting speed and constant spindle speed. Maximum pass-mean deviations are 2.83% and 7.31%, respectively. Mean specific cutting pressures are 2985.64 and 3091.83 N/mm^2. Transferring the final constant-N pass estimate to drilling predicts 1.210 kW for pre-drilling and 3.147 kW for full drilling, with entry ramps and a pilot-bottom power step.

1 Process Parameters and Predictions

An AISI 4135 bar is turned from 48 to 24 mm over an axial length of 40 mm, using a DNMG NC5330 coated carbide tool [1]. Twelve passes machine diameters $D = 46, 44, \ldots, 24$ mm with radial depth $a_p = 1$ mm and feed $f = 0.2$ mm/rev.

The programs maintain either $v_c = 150$ m/min or $N = 1200$ rpm. Subtracting the air-cutting trace at matching timestamps estimates cutting power:

$$P_c = P_m - P_{nc}, \qquad P_c = \frac{K_c v_c f a_p}{60}, \qquad t_c = \frac{60L}{fN}. \tag{1}$$

The smallest-diameter chapter values, $K_c = 3025.6$ and 3230.3 N/mm^2, respectively, are held constant across the prediction passes.

Table 1: Turning predictions. Arrows follow the diameter reduction from 46 to 24 mm.

Mode	v_c (m/min)	N (rpm)	P_c (kW)	t_c/Pass (s)
Constant v_c	150.00	1038 → 1989	1.513	11.56 → 6.03
Constant N	173.42 → 90.48	1200	1.867 → 0.974	10.00

Constant v_c preserves predicted cutting power while spindle speed rises and pass duration decreases. Constant N reduces cutting speed and power while keeping each predicted pass at 10 s. The timing model assumes full engagement over L; entry ramps, return moves and positioning are excluded.

1.1 Timing Comparison

Table 2: Predicted versus threshold-detected cutting time. Gaps are excluded; MAE is the mean absolute error of the 12 pass durations.

Mode	Predicted (s)	Detected (s)	Difference (%)	MAE (s)
Constant v_c	105.56	102.18	-3.20	0.282
Constant N	120.00	120.09	+0.07	0.013

Detected durations use the same windows as the power comparison, including the last sample interval ($T_s = 0.009$ s). The signed total difference is $100(T_{\text{det}} - T_{\text{pred}})/T_{\text{pred}}$. Constant-$N$ timing agrees closely; constant-v_c detection gives a shorter total. Threshold windows do not by themselves establish the physical cause of this difference. Comparison plots align prediction levels to detected windows, so they assess amplitude rather than independently validating timing.

Implementation: `power_prediction_TP.py` and `power_comparison_TP.py`.

2 Turning Power Comparison (Tasks 1 and 2)

2.1 Constant Cutting Speed




Figure 1: Raw idle-subtracted cutting power and predicted levels at constant v_c. The 12 predicted plateaus are aligned to detected cutting intervals; gaps remain on the measured time axis.

Table 3: Constant-v_c results for all passes. The standard deviation (SD) describes raw samples within each detected interval.

Pass	D (mm)	Predicted (kW)	Mean (kW)	SD (kW)	Deviation (%)
1	46	1.513	1.470	0.196	-2.83
2	44	1.513	1.483	0.364	-1.97
3	42	1.513	1.487	0.083	-1.70
4	40	1.513	1.504	0.407	-0.56
5	38	1.513	1.497	0.138	-1.03
6	36	1.513	1.512	0.379	-0.06
7	34	1.513	1.515	0.434	+0.17
8	32	1.513	1.496	0.252	-1.13
9	30	1.513	1.495	0.126	-1.18
10	28	1.513	1.500	0.149	-0.83
11	26	1.513	1.496	0.308	-1.09
12	24	1.513	1.515	0.350	+0.17

$$\text{Deviation} = 100\,\frac{\overline{P}_{\text{exp}} - P_{\text{pred}}}{P_{\text{pred}}}. \tag{2}$$

Measured pass means remain close to the constant 1.513 kW prediction: the maximum absolute deviation is 2.83%, and the mean absolute percentage deviation is 1.06%. Short spikes increase the within-pass SD but have a smaller effect on pass means.

Intervals are continuous segments above 0.5 kW lasting at least 2 s. Detection at constant v_c uses raw power. Means and sample SDs ($n-1$ denominator) also use raw samples, without extra entry/exit trimming. Pass averaging is sufficient for the present power comparison; this does not imply that individual samples are noise-free.

2.2 Constant Spindle Speed




Figure 2: Raw idle-subtracted cutting power and predicted levels at constant $N = 1200$ rpm. Both decrease with diameter; pass numbers identify the chronological pairing with prediction rows.

Table 4: Constant-N results for all passes. Predictions use the chapter's final-pass K_c throughout.

Pass	D (mm)	Predicted (kW)	Mean (kW)	SD (kW)	Deviation (%)
1	46	1.867	1.731	0.341	-7.31
2	44	1.786	1.658	0.340	-7.16
3	42	1.705	1.591	0.341	-6.68
4	40	1.624	1.524	0.338	-6.12
5	38	1.543	1.460	0.331	-5.35
6	36	1.461	1.396	0.331	-4.48
7	34	1.380	1.326	0.331	-3.91
8	32	1.299	1.254	0.328	-3.50
9	30	1.218	1.185	0.327	-2.69
10	28	1.137	1.112	0.329	-2.16
11	26	1.055	1.038	0.330	-1.68
12	24	0.974	0.968	0.332	-0.60

The measured mean decreases from 1.731 to 0.968 kW. Predictions overestimate all pass means, with deviations ranging from -7.31% to -0.60%; the mean absolute percentage deviation is 4.30%.

A short centered median (11 samples, approximately 0.10 s) is used only to detect intervals above 0.5 kW lasting at least 2 s. Statistics are calculated from raw samples within those windows, with no additional trimming. This prevents brief dips from splitting the last passes while preserving their measured variability.

Agreement is with a chapter-based prediction, not independent model validation: the reference K_c values were derived from the same experimental case [1]. Holding the final-pass value fixed also omits the variation of estimated K_c across the constant-N passes.

3 Specific Cutting Pressure (Task 3)

3.1 Constant Cutting Speed

For each retained sample, specific cutting pressure is calculated as

$$K_c[i] = \frac{60 P_c[i]}{v_c f a_p}, \tag{3}$$

using P_c in W. Each pass is summarized by its sample mean and sample SD. The implementation is linked in `kc_estimation_TP.py`.




Figure 3: Constant-v_c selection: orange dashed outlines are nominal windows beginning at detected entries and lasting the predicted duration; blue shading marks the samples retained for K_c. Gray is raw power and blue is the 55-sample moving average.

At constant v_c, a centered 55-sample moving average (0.495 s support) is used. Its width was selected qualitatively and iteratively relative to the shortest cutting interval; filter-tuning steps are omitted. Entries and exits are detected at 1 kW using a 23-sample median (approximately 0.20 s), with intervals shorter than 2 s discarded. The median serves detection only.

Each window ends at the earlier of the predicted end and detected exit. Trimming 27 samples at either boundary keeps the entire centered moving-average support inside the cut. No K_c-based outlier removal is applied. The early passes retain appreciable variation despite smoothing; the later retained traces are steadier.

Across the 12 pass means, the equal-weight mean is 2985.64 N/mm^2. The between-pass sample SD is 37.37 N/mm^2. Table 5 gives all per-pass results.

3.2 Constant Spindle Speed




Figure 4: Constant-N selection: raw cutting power is used for K_c; blue shading marks retained samples. Orange nominal windows last 10 s, while retained windows stop at the earlier of the nominal end and detected exit.

The 0.5 kW threshold, approximately 0.10 s detection median and 2 s minimum duration match the power comparison. The lower threshold retains the late passes as cutting power falls. No moving average, transition margin, clipping or outlier rejection is applied. Averaging reduces random fluctuations but does not remove systematic bias.

Table 5: Specific cutting pressure for both modes, in N/mm^2. SD is within-pass variability: filtered samples at constant v_c and raw samples at constant N.

	Constant v_c		Constant N	
D (mm)	Mean K_c	SD	Mean K_c	SD
46	2949.55	213.87	2995.85	588.45
44	2931.36	246.74	2999.08	615.64
42	2936.72	287.97	3017.39	641.08
40	3010.56	74.97	3031.46	672.23
38	2935.94	382.06	3057.40	693.14
36	3027.59	25.39	3085.70	732.43
34	3029.04	29.26	3104.16	775.63
32	2996.12	15.10	3120.30	812.48
30	2992.02	16.95	3143.35	868.09
28	3001.50	16.74	3160.53	933.89
26	2992.51	18.92	3176.04	1010.40
24	3024.79	20.17	3210.76	1099.91

The equal-weight mean is 3091.83 N/mm^2 at constant N, with 72.48 N/mm^2 sample SD between pass means. Estimated K_c rises as cutting speed decreases, from 2995.85 to 3210.76 N/mm^2. The constant-N mean is 3.56% above the constant-v_c mean.

Within-pass SDs in Table 5 are not confidence intervals or uncertainties on the overall mean. Filtering differs between modes, so their SD magnitudes cannot be compared as equivalent measures of process stability.

4 Drilling Prediction (Task 4)

The final constant-N turning pass ($D = 24$ mm) supplies $K_c = 3210.76$ N/mm^2 and $v_c = 90.48$ m/min. Each drill uses this outer-edge cutting speed, giving different spindle speeds. Feed is the total axial feed per revolution; no extra cutting-lip multiplier is applied [2,3].

Table 6: Drilling inputs and predictions. Duration runs from first material contact to stopping.

Phase	D (mm)	Depth (mm)	Angle	N (rpm)	Duration (s)	Peak (kW)
Pre-Drilling	5	10	120°	5760	0.521	1.210
Drilling	13	20	120°	2215	2.513	3.147

Both tools have a 120° point angle and $f = 0.2$ mm/rev. Tip depths are measured from the original surface: 10 mm for the blind conical pilot and 20 mm for the larger drill. The plotted 0.5 s interstage lag is illustrative; the 0.1 s initial padding is not cutting time.




Figure 5: Predicted rotational cutting power. Entry ramps lead to full engagement. The 13 mm drill first removes an annulus, then reaches the pilot bottom and rises from 2.682 to 3.147 kW as the inner lips engage.

For an engaged radial interval $[r_i, r_o]$ in mm,

$$M_c = \frac{K_c f (r_o^2 - r_i^2)}{2000}, \qquad P_c = M_c \frac{2\pi N}{60}.$$

Equal point angles give simultaneous inner-lip engagement at the pilot bottom, idealized as a power step. The model omits chisel-edge effects, friction, spindle losses and withdrawal. Implementation: `power_prediction_DP.py`.

5 Conclusions

Pass means follow both predicted turning profiles (Tables 3 and 4). Cutting times agree closely at constant N and are shorter than predicted at constant v_c (Table 2).

The transferred final-pass K_c predicts 1.210 kW pre-drilling and 3.147 kW full drilling (Table 6; Figure 5), without experimental drilling validation.

References

[1] A. C. Araujo, *Integrating Environmental Impact into Cutting Speed Decisions in CNC Turning*, course chapter, Tables 1–2. Experimental dataset.

[2] *Introduction – Smart Machining*, INSA Toulouse course slides, 2025.

[3] Sandvik Coromant, *Formulas and Definitions for Drilling – Metric*, p. H81.

Code and reproducibility: PaoloRos/MASSMa, first assignment.

AI Use and Co-Authorship. ChatGPT (GPT-6), AI co-author, generated code, supporting material and this report. The approach and analytical decisions are Paolo Rossi's.