

Report S7L2

ho iniziato cambiando gli ip delle macchine

```
(kali㉿kali)-[~]
$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:be:6f:fd brd ff:ff:ff:ff:ff:ff
    inet 192.168.1.25/24 brd 192.168.1.255 scope global noprefixroute eth0
        valid_lft forever preferred_lft forever
    inet6 fe80::218f:f931:a8ab:b7d7/64 scope link noprefixroute
        valid_lft forever preferred_lft forever

(kali㉿kali)-[~]
```

poi ho aperto metasploit, fatto search per trovare l'auxiliary dell'esercizio, settato i parametri mancanti e l'ho eseguito con run

```
File  Actions  Edit  View  Help
2  auxiliary/scanner/telnet/lantronix_telnet_version .
    normal No Lantronix Telnet Service Banner Detection
3  auxiliary/admin/http/netgear_pnp_getsharefolderlist_auth_bypass 2021-09-06
    normal Yes Netgear PNPX_GetShareFolderList Authentication Bypass
4  auxiliary/admin/http/netgear_r6700_pass_reset 2020-06-15
    normal Yes Netgear R6700v3 Unauthenticated LAN Admin Password Reset
5  auxiliary/admin/http/netgear_r7000_backup_cgi_heap_overflow_rce 2021-04-21
    normal Yes Netgear R7000 backup.cgi Heap Overflow RCE
6  auxiliary/scanner/telnet/telnet_version .
    normal No Telnet Service Banner Detection

Interact with a module by name or index. For example info 6, use 6 or use auxiliary/scanner/telnet/telnet_version

msf6 > use 6
msf6 auxiliary(scanner/telnet/telnet_version) > show options

Module options (auxiliary/scanner/telnet/telnet_version):



| Name     | Current Setting | Required | Description                                                                                                                                                                                         |
|----------|-----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PASSWORD |                 | no       | The password for the specified username                                                                                                                                                             |
| RHOSTS   |                 | yes      | The target host(s), see <a href="https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html">https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html</a> |
| RPORT    | 23              | yes      | The target port (TCP)                                                                                                                                                                               |
| THREADS  | 1               | yes      | The number of concurrent threads (max one per host)                                                                                                                                                 |


```

