

PACE COMMUNICATIONS PLAN

M2 Community Node — Build it. Own it. Control it.



A PACE plan defines four tiers of communication, ordered from most capable to most resilient. The M2 Community Node provides all four tiers in a single deployable rack. Each tier operates independently — losing one does not affect the others below it.

P	PRIMARY Local WiFi Network	Matrix / Element Encrypted group chat, E2E, self-hosted OpenTAK Server Shared tactical map, CoT, GeoChat, voice AdGuard DNS Local DNS resolution, ad blocking	~300m WiFi range Node powered on	FULL CAPABILITY
A	ALTERNATE Clearnet Tunnel	Cloudflare Tunnel Zero-trust encrypted tunnel, no open ports communitynode.capableenough.org Element Web accessible worldwide Headscale VPN Remote operator access, encrypted	Worldwide Internet connection required	INTERNET REQUIRED
C	CONTINGENCY Anonymous Routing	Tor Hidden Services Three .onion addresses, censorship-resistant I2P / i2pd Distributed anonymous network, eepsite No DNS dependency Works when DNS is blocked or compromised	Worldwide Internet + Tor Browser or I2P router	CENSORSHIP RESISTANT
E	EMERGENCY Radio — No Infrastructure	Meshtastic / LoRa 1–5 km range, encrypted, no internet, no WiFi Reticulum / RNode Encrypted mesh backbone, LoRa + TCP transport Heltec V3 LoRa LEFT=RNode/Reticulum RIGHT=Meshtastic	1–5 km per hop No internet. No WiFi. No infrastructure.	NO INFRASTRUCTURE

DEPLOYMENT NOTES

Each tier is independent — failure of a higher tier does not affect lower tiers.

Meshtastic and Reticulum operate from the node's onboard LoRa radios — no external hardware needed by operators.

This PACE plan covers the node's output. Operators still need client devices (phone, laptop, ATAK-compatible).