COMPLETE SYSTEM DOSSIER & SOURCE REPOSITORY

# REAL-WORLD MISSILE IMPACT SIMULATOR

Technical Architecture, Scientific Physics Equations, Geospatial 3D Engine, & Verbatim Full Codebase

Mandatory Tkinter Core GUI | PyView (pywebview 6.2+) | CesiumJS 3D Earth Globe | Glasstone-Dolan Blast Physics | 58-Missile Global Database | Live OpenStreetMap Geocoding | OpenDataSoft Population Engine | SQLite Local Persistence | Python 3.13 Runtime | Public GitHub Repository

This document contains the complete, unabridged architectural design, physical calculations, mathematical equations, interactive features, and verbatim source code of the **Real-World Missile Impact Simulator**. It is explicitly structured for direct upload to **Google Gemini** to analyze the entire application in context, answer questions, and generate precise engineering prompts for further feature extensions and refactorings.

| | |
|---|---|
| **Repository URL:** | https://github.com/Salvius2422/missile-impact-simulator (Public) |
| **Primary Author:** | Vedant Antil (GitHub: **Salvius2422**) & Google DeepMind Antigravity Pair Programming Agent |
| **Core Framework:** | Python Tkinter (Primary Mandatory Window) with embedded PyView CesiumJS 3D viewport |
| **Scientific Standard:** | Glasstone-Dolan (1977) Nuclear & Conventional Blast Overpressure Scaling Laws |
| **Geospatial Data:** | WGS84 Ellipsoid, OpenStreetMap Nominatim, OpenDataSoft GeoNames Worldwide Cities |
| **Weapons Inventory:** | 58 Global Systems across 10 Powers (India, USA, Russia, China, France, UK, Israel, Iran, ROK, DPRK) |
| **Document Date:** | November 1, 2026 • Version 2.5 (Fully Updated & Synchronized) |

# TABLE OF CONTENTS


1. Executive Summary & Project Purpose ..... Section 1

2. System Architecture & Dual-Framework Design ..... Section 2

3. Detailed Module Breakdown & Engineering Specifications ..... Section 3

- 3.1 Tkinter Master Application & Viewport Hosting ..... 3.1
- 3.2 3D CesiumJS Viewport & HUD Command Overlay ..... 3.2
- 3.3 Python-JavaScript Bidirectional IPC Bridge ..... 3.3
- 3.4 Glasstone-Dolan Blast Physics & Casualties ..... 3.4
- 3.5 Live Public Geocoding & Transliteration Engine ..... 3.5
- 3.6 Urban Population & Automatic Density Lookup ..... 3.6
- 3.7 58-Missile Technical Database Catalog ..... 3.7
- 3.8 SQLite Scenario Persistence & Models ..... 3.8
- 3.9 Automated Unit Testing Suite ..... 3.9

4. 58-Missile Master Technical Catalog Table ..... Section 4

5. Verbatim Full Codebase Listing (All 17 Source Files) ..... Section 5

6. Gemini Prompt Engineering Guide & Extension Templates ..... Section 6

# 1. EXECUTIVE SUMMARY & PROJECT PURPOSE

The **Real-World Missile Impact Simulator** is a comprehensive, map-centric desktop software application designed to model ballistic, cruise, and hypersonic missile trajectories, verify physical range envelopes between arbitrary global coordinates, simulate nuclear and conventional detonations based on empirical blast physics, and assess humanitarian casualties using live public urban population databases over Wi-Fi.


> 🎯 **Core Mission Requirements Achieved:**
>
> - **Mandatory Tkinter Core Framework:** Tkinter acts as the root window (`MissileSimulatorApp(tk.Tk)`) hosting top menus, toolbar controls, status bar telemetry, and technical modal dialogs.
> - **Hardware-Accelerated 3D Earth:** Directly embeds CesiumJS running within PyView (`pywebview`) into a native Tkinter frame—completely avoiding separate popup browser windows or disconnected HTML files.
> - **Glasstone-Dolan (1977) Physics:** Models cube-root scaled blast overpressures (20 psi, 5 psi, 1 psi), fireball vaporization, and 3rd-degree thermal burns for arbitrary kiloton yields or conventional explosives.
> - **No Private API Keys Needed:** Operates over Wi-Fi using open public endpoints from OpenStreetMap Nominatim and OpenDataSoft GeoNames datasets.
> - **Extensive 58-Missile Inventory:** Features 58 real-world systems across 10 major world powers (with all Pakistani missiles permanently excluded).
> - **Interactive Dropdown City Search:** Provides live debounced autocomplete for both Launch Site (Origin) and Target (Destination) with single-click pin placement and camera fly-to.
> - **Camera Rotation vs. Pin Placement:** Prevents accidental pin drops while revolving Earth by enforcing a mouse movement travel threshold (≥ 6 pixels).

# 2. SYSTEM ARCHITECTURE & DUAL-FRAMEWORK DESIGN

The simulator utilizes a hybrid architecture combining the reliable native desktop controls of **Python Tkinter** with the WebGL 3D rendering capabilities of **CesiumJS** via **PyView (`pywebview`)**.

## 2.1 High-Level Architecture Diagram

System Architecture Topology — ASCII Block Diagram




## 2.2 Process Lifecycle & Initialization Sequence

1. **Bootstrap:** User runs `python app/main.py` or double-clicks `run_simulator.bat`.
2. **Bridge Server Start:** `GlobeBridgeServer(port=8765)` spins up a background daemon HTTP server serving the CesiumJS web assets.

3. **Tkinter Root Construction:** `MissileSimulatorApp` builds the root window, top menu bar, command toolbar, status bar, and central `tk.Frame`.
4. **PyView Window Creation:** `webview.create_window()` initializes a hardware-accelerated WebView2 window pointing to `http://127.0.0.1:8765/index.html`.
5. **Native OS Embedding:** When the PyView window emits its `shown` event, the Win32 API `SetParent` reparents the window into the Tkinter container frame HWND, stripping popup/caption window styles (`WS_CHILD`), making the 3D globe a seamless sub-view of Tkinter.
6. **Window Resizing Synchronization:** The Tkinter container binds to `<Configure>`, calling `MoveWindow` to resize the embedded WebGL viewport dynamically whenever the user resizes the Tkinter window.

# 3. DETAILED MODULE BREAKDOWN & ENGINEERING SPECIFICATIONS

## 3.1 Tkinter Master Application (`app/ui/main_window.py`)

Serves as the mandatory top-level GUI framework. Key classes:

- `MissileSimulatorApp(tk.Tk)`: Root window hosting menus, action buttons, embedded viewport frame, and status bar.
- `MissileCatalogDialog(tk.Toplevel)`: Interactive searchable catalog using `ttk.Treeview` listing all 58 missiles with filtering by name, country, or classification.
- `ScenarioManagerDialog(tk.Toplevel)`: Scenario persistence manager allowing users to browse, load, or delete saved scenarios from `scenarios.db`.
- `PhysicsInfoDialog(tk.Toplevel)`: Dedicated scientific documentation window explaining the Glasstone-Dolan equations and overpressure thresholds.
- `launch_simulator_app()`: Bootstrapping function that initializes threading, Tkinter root, and PyView embedding.

## 3.2 3D CesiumJS Viewport & HUD Overlay (`app/visualization/globe/index.html`)

A single-page WebGL application running inside the embedded viewport:

- **CesiumJS Viewer:** Utilizes ArcGis World Imagery, WGS84 ellipsoid coordinates, and depth testing for terrain.
- **Camera Drag Threshold:** Differentiates between dragging to rotate the Earth (≥ 6px movement) versus a deliberate stationary click (< 6px) to select pins.
- **Interactive HUD:** Glassmorphism panel featuring Origin/Destination city search inputs with debounced live autocomplete dropdowns, 58-missile system selectors, country filters, and yield controls.
- **Range Circle & Launch Interlock:** Renders a cyan geodesic circle around the launch site. If distance exceeds the missile's maximum range, the banner turns red and launch is locked.
- **Post-Impact Assessment Modal:** Displays concentric glowing blast rings, flight time, distance, verified population, and an animated casualty chart.

## 3.3 Python-JavaScript IPC Bridge (`app/services/webview_api.py`)

Exposes high-level Python methods directly to JavaScript under `window.pywebview.api`:

- `search_city(query)`: Queries geocoding service and returns matching candidates.
- `reverse_geocode(lon, lat)`: Converts clicked coordinates into city/state/country labels.
- `get_population(lon, lat, label)`: Fetches live verified municipal population over Wi-Fi.
- `simulate_launch(origin, dest, missile_id, is_nuclear, yield_kt)`: Verifies range, computes blast effects, and returns the impact assessment.
- `save_scenario(...)` and `list_scenarios()`: Database operations for mission persistence.

## 3.4 Glasstone-Dolan Blast Physics & Casualties (`app/services/impact_physics.py`)

Implements the standard **Glasstone-Dolan (1977)** nuclear and conventional weapons blast equations:

- **Cube-Root Scaling:** Concentric radii scale proportionally to $Y^{1/3}$, where $Y$ is yield in kilotons TNT:

```
r_fireball = 0.048 × Y^0.4 km
r_heavy (20 psi) = 0.28 × Y^1/3 km
r_moderate (5 psi) = 0.65 × Y^1/3 km
r_thermal (3rd deg) = 1.15 × Y^0.41 km
r_light (1 psi) = 1.60 × Y^1/3 km
```

- **Humanitarian Casualties:** Evaluated across annular rings:
  - Fireball Zone: 100% fatalities.
  - 20 psi Zone: 90% fatalities, 10% severe injuries (complete structural collapse).
  - 5 psi Zone: 50% fatalities, 40% injuries (residential structural collapse).
  - Thermal Burn Zone: 15% fatalities, 50% second- and third-degree burn injuries.

## 3.5 Multi-Provider Geocoding & Transliteration (`app/services/mapbox_geocoding.py`)

Ensures global geocoding works seamlessly across all small towns and districts worldwide without requiring private API tokens:

- **Triple-Tier Redundancy:** Mapbox v6 forward/reverse (if configured) → OpenStreetMap Nominatim API (free public Wi-Fi) → OpenDataSoft GeoNames global dataset → Built-in offline major cities catalog.
- **Unicode Transliteration (`clean_label`):** Decomposes and transliterates accented characters (e.g. `Sonīpat` → `Sonipat`) using `unicodedata.normalize('NFKD')` to prevent Windows `cp1252` charmap encoding exceptions.
- **Deduplication:** Coordinates and labels are normalized and deduplicated before rendering in the dropdown list.

## 3.6 Urban Population & SQLite Caching (`app/services/population_service.py`)

Automatically resolves real-world population and density without prompting the user:

- Queries OpenDataSoft / GeoNames worldwide cities database matching coordinates within ±0.35° bounding box.
- Calculates realistic urban population densities per $km^2$ based on city population tiers.
- Maintains an internal SQLite cache (`population_cache` table) to store query results locally for instant sub-millisecond retrieval.

## 3.7 Comprehensive 58-Missile Inventory (`app/data/reference_data.json`)

Contains 58 real-world missile systems across 10 global powers: India, United States, Russia, China, France, United Kingdom, Israel, Iran, South Korea, and North Korea. All Pakistani missiles have been completely removed.

## 3.8 SQLite Scenario Persistence (`app/data/database.py`, `models.py`)

Provides local database storage in `scenarios.db` using Python's built-in `sqlite3` library. Saves mission scenarios with full coordinate tracking, missile configuration, warhead yield, and timestamps.

## 3.9 Unit Verification Suite (`tests/test_all.py`)

Includes 8 automated test cases verifying missile dataset integrity, Haversine distance, range limit interlocks, nuclear blast radii calculations, geocoding fallbacks, SQLite persistence, Python API bridges, and Tkinter Treeview dialog rendering.

# 4. 58-MISSILE MASTER TECHNICAL CATALOG TABLE

The following table provides the complete technical specifications of all 58 missiles currently configured in the database:

| # | Country | Missile System | Classification | Max Range (km) | Speed (Mach) | Warhead Type | Default Yield |
|---|---|---|---|---|---|---|---|
| 1 | **India** | Agni-V | Intercontinental Ballistic Missile (ICBM) | 5,500 km | Mach 24.0 | ☢ Nuclear | 250.0 kt |
| 2 | **India** | Agni-IV | Intermediate-Range Ballistic Missile (IRBM) | 4,000 km | Mach 7.0 | ☢ Nuclear | 40.0 kt |
| 3 | **India** | Agni-III | Intermediate-Range Ballistic Missile (IRBM) | 3,500 km | Mach 5.0 | ☢ Nuclear | 200.0 kt |
| 4 | **India** | Agni-II | Medium-Range Ballistic Missile (MRBM) | 2,000 km | Mach 4.5 | ☢ Nuclear | 150.0 kt |
| 5 | **India** | Agni-Prime (Agni-P) | Medium-Range Ballistic Missile (MRBM) | 2,000 km | Mach 6.0 | ☢ Nuclear | 100.0 kt |
| 6 | **India** | BrahMos Block-III / ER | Supersonic Cruise Missile | 800 km | Mach 2.8 | ☢ Nuclear | 10.0 kt |
| 7 | **India** | BrahMos-II (Hypersonic) | Hypersonic Cruise Missile | 1,000 km | Mach 7.0 | 💥 Conventional | N/A |
| 8 | **India** | Nirbhay | Subsonic Long-Range Cruise Missile | 1,000 km | Mach 0.75 | ☢ Nuclear | 12.0 kt |
| 9 | **India** | Pralay Tactical Ballistic | Quasi-Ballistic Tactical Missile | 500 km | Mach 6.1 | 💥 Conventional | N/A |
| 10 | **India** | Shaurya Hypersonic | Hypersonic Surface-to-Surface Missile | 750 km | Mach 7.5 | ☢ Nuclear | 20.0 kt |
| 11 | **India** | K-4 SLBM | Submarine-Launched Ballistic Missile (SLBM) | 3,500 km | Mach 5.5 | ☢ Nuclear | 200.0 kt |
| 12 | **India** | Prithvi-II | Short-Range Ballistic Missile (SRBM) | 350 km | Mach 3.5 | ☢ Nuclear | 10.0 kt |
| 13 | **United States** | LGM-30G Minuteman III | Intercontinental Ballistic Missile (ICBM) | 13,000 km | Mach 23.0 | ☢ Nuclear | 335.0 kt |
| 14 | **United States** | UGM-133A Trident II D5 (US) | Submarine-Launched Ballistic Missile (SLBM) | 12,000 km | Mach 24.0 | ☢ Nuclear | 455.0 kt |
| 15 | **United States** | BGM-109 Tomahawk Block V | Long-Range Subsonic Cruise Missile | 1,600 km | Mach 0.74 | 💥 Conventional | N/A |
| 16 | **United States** | AGM-158B JASSM-ER | Air-Launched Stealth Cruise Missile | 925 km | Mach 0.82 | 💥 Conventional | N/A |
| 17 | **United States** | AGM-114 Hellfire | Tactical Air-to-Surface Missile | 11 km | Mach 1.3 | 💥 Conventional | N/A |

| # | Country | Missile System | Classification | Max Range (km) | Speed (Mach) | Warhead Type | Default Yield |
|---|---|---|---|---|---|---|---|
| 18 | **United States** | MGM-140 ATACMS | Tactical Ballistic Missile | 300 km | Mach 3.0 | 💥 Conventional | N/A |
| 19 | **United States** | Precision Strike Missile (PrSM) | Next-Gen Tactical Ballistic Missile | 500 km | Mach 4.2 | 💥 Conventional | N/A |
| 20 | **United States** | AGM-86B ALCM | Air-Launched Strategic Cruise Missile | 2,400 km | Mach 0.73 | ☢ Nuclear | 150.0 kt |
| 21 | **United States** | RIM-161 Standard Missile 3 (SM-3) | Exoatmospheric Ballistic Missile Interceptor | 2,500 km | Mach 15.0 | 💥 Conventional | N/A |
| 22 | **United States** | RGM-84 Harpoon Block II | Anti-Ship Cruise Missile | 280 km | Mach 0.71 | 💥 Conventional | N/A |
| 23 | **Russia** | RS-28 Sarmat (Satan II) | Super-Heavy Thermonuclear ICBM | 18,000 km | Mach 20.7 | ☢ Nuclear | 800.0 kt |
| 24 | **Russia** | RS-24 Yars | Road-Mobile Intercontinental Ballistic Missile | 11,000 km | Mach 20.0 | ☢ Nuclear | 500.0 kt |
| 25 | **Russia** | R-36M2 Voyevoda (SS-18 Satan) | Heavy Silo-Based ICBM | 16,000 km | Mach 22.0 | ☢ Nuclear | 1000.0 kt |
| 26 | **Russia** | RSM-56 Bulava | Submarine-Launched Ballistic Missile (SLBM) | 9,300 km | Mach 18.0 | ☢ Nuclear | 150.0 kt |
| 27 | **Russia** | 9M723 Iskander-M | Quasi-Ballistic Tactical Missile | 500 km | Mach 5.9 | ☢ Nuclear | 50.0 kt |
| 28 | **Russia** | Kh-47M2 Kinzhal | Air-Launched Hypersonic Aeroballistic Missile | 2,000 km | Mach 10.0 | ☢ Nuclear | 50.0 kt |
| 29 | **Russia** | 3M22 Zircon | Hypersonic Scramjet Cruise Missile | 1,000 km | Mach 9.0 | ☢ Nuclear | 200.0 kt |
| 30 | **Russia** | 3M-54 Kalibr | Land-Attack / Anti-Ship Cruise Missile | 2,500 km | Mach 0.8 | ☢ Nuclear | 50.0 kt |
| 31 | **Russia** | Kh-101 Stealth Cruise | Long-Range Air-Launched Stealth Cruise Missile | 4,500 km | Mach 0.77 | 💥 Conventional | N/A |
| 32 | **China** | DF-41 (Dongfeng-41) | Road-Mobile Intercontinental Ballistic Missile | 15,000 km | Mach 25.0 | ☢ Nuclear | 1000.0 kt |
| 33 | **China** | DF-31AG | Road-Mobile Intercontinental Ballistic Missile | 11,200 km | Mach 20.0 | ☢ Nuclear | 500.0 kt |
| 34 | **China** | DF-26B (Guam Killer) | Intermediate-Range Ballistic Missile (IRBM) | 4,000 km | Mach 18.0 | ☢ Nuclear | 300.0 kt |
| 35 | **China** | DF-21D (Carrier Killer) | Anti-Ship Ballistic Missile (ASBM) | 1,500 km | Mach 10.0 | 💥 Conventional | N/A |

| # | Country | Missile System | Classification | Max Range (km) | Speed (Mach) | Warhead Type | Default Yield |
|---|---|---|---|---|---|---|---|
| 36 | **China** | DF-17 Hypersonic Glide Vehicle | Hypersonic Boost-Glide Weapon System | 2,500 km | Mach 8.5 | ☢ Nuclear | 50.0 kt |
| 37 | **China** | JL-3 (Julang-3) | Submarine-Launched Ballistic Missile (SLBM) | 10,000 km | Mach 20.0 | ☢ Nuclear | 250.0 kt |
| 38 | **China** | CJ-10 (Changjian-10) | Land-Attack Subsonic Cruise Missile | 2,000 km | Mach 0.75 | ☢ Nuclear | 20.0 kt |
| 39 | **France** | M51 SLBM | Submarine-Launched Ballistic Missile (SLBM) | 10,000 km | Mach 25.0 | ☢ Nuclear | 150.0 kt |
| 40 | **France** | ASMP-A | Air-Launched Supersonic Nuclear Cruise Missile | 500 km | Mach 3.0 | ☢ Nuclear | 300.0 kt |
| 41 | **France** | Storm Shadow / SCALP-EG | Air-Launched Low-Observable Cruise Missile | 560 km | Mach 0.8 | 💥 Conventional | N/A |
| 42 | **France** | Exocet MM40 Block 3 | Anti-Ship Cruise Missile | 200 km | Mach 0.93 | 💥 Conventional | N/A |
| 43 | **United Kingdom** | Trident II D5 (United Kingdom) | Submarine-Launched Ballistic Missile (SLBM) | 12,000 km | Mach 24.0 | ☢ Nuclear | 100.0 kt |
| 44 | **United Kingdom** | Sea Viper / Aster 30 | Naval Surface-to-Air / Anti-Missile | 120 km | Mach 4.5 | 💥 Conventional | N/A |
| 45 | **United Kingdom** | Brimstone 2 | Precision Ground-Attack Tactical Missile | 60 km | Mach 1.3 | 💥 Conventional | N/A |
| 46 | **Israel** | Jericho III | Intercontinental Ballistic Missile (ICBM) | 6,500 km | Mach 20.0 | ☢ Nuclear | 400.0 kt |
| 47 | **Israel** | Popeye Turbo SLCM | Submarine-Launched Long-Range Cruise Missile | 1,500 km | Mach 0.8 | ☢ Nuclear | 200.0 kt |
| 48 | **Israel** | Delilah Standoff | Loitering Standoff Cruise Missile | 250 km | Mach 0.7 | 💥 Conventional | N/A |
| 49 | **Iran** | Khorramshahr-4 (Kheibar) | Medium-Range Ballistic Missile (MRBM) | 2,000 km | Mach 16.0 | 💥 Conventional | N/A |
| 50 | **Iran** | Fattah-1 Hypersonic | Hypersonic Ballistic Missile | 1,400 km | Mach 13.0 | 💥 Conventional | N/A |
| 51 | **Iran** | Sejjil-2 | Medium-Range Ballistic Missile (MRBM) | 2,000 km | Mach 14.0 | 💥 Conventional | N/A |
| 52 | **North Korea** | Hwasong-17 (Monster ICBM) | Heavy Intercontinental Ballistic Missile | 15,000 km | Mach 22.0 | ☢ Nuclear | 500.0 kt |
| 53 | **North Korea** | Hwasong-15 | Intercontinental Ballistic Missile (ICBM) | 13,000 km | Mach 20.0 | ☢ Nuclear | 300.0 kt |
| 54 | **North Korea** | KN-23 (Hwasong-11Ga) | Quasi-Ballistic Tactical Missile | 690 km | Mach 6.0 | ☢ Nuclear | 50.0 kt |

| # | Country | Missile System | Classification | Max Range (km) | Speed (Mach) | Warhead Type | Default Yield |
|---|---|---|---|---|---|---|---|
| 55 | **North Korea** | Taepodong-2 / Unha-3 | Multi-Stage Ballistic Missile / Space Launch | 10,000 km | Mach 21.0 | ☢ Nuclear | 200.0 kt |
| 56 | **South Korea** | Hyunmoo-V (Monster Missile) | Heavy Bunker-Busting Ballistic Missile | 3,000 km | Mach 10.0 | 💥 Conventional | N/A |
| 57 | **Germany** | Taurus KEPD 350 | Air-Launched Standoff Cruise Missile | 500 km | Mach 0.95 | 💥 Conventional | N/A |
| 58 | **India** | Sagarika (K-15) SLBM | Submarine-Launched Ballistic Missile (SLBM) | 750 km | Mach 5.0 | ☢ Nuclear | 25.0 kt |

# 5. VERBATIM FULL CODEBASE LISTING (ALL 17 SOURCE FILES)

Below is the complete, unabridged source code for every file in the project repository. Lines and formatting are strictly preserved.

**app/main.py** — 23 lines • 647 bytes • Primary Application Entry Point (Tkinter Bootstrapper)

```
"""
Real-World Missile Impact Simulator
===================================
A desktop application built mandatorily with Tkinter as the primary GUI framework,
embedding a high-performance PyView (pywebview) 3D CesiumJS Earth geospatial engine.
"""
import sys
from pathlib import Path

PROJECT_ROOT = Path(__file__).resolve().parent.parent
if str(PROJECT_ROOT) not in sys.path:
    sys.path.insert(0, str(PROJECT_ROOT))

from app.ui.main_window import launch_simulator_app


def main() -> None:
    """Launches the Tkinter Master Application embedding the PyView 3D Earth view."""
    launch_simulator_app()


if __name__ == "__main__":
    main()
```

**app/ui/main_window.py** — 630 lines • 25,162 bytes • Tkinter Core Desktop GUI & Embedded Viewport Host

```
import os
import sys
import json
import time
import ctypes
import threading
from ctypes import wintypes
import tkinter as tk
from tkinter import ttk, messagebox, simpledialog
from typing import Optional, Dict, Any, List
from pathlib import Path

import webview

from app.data.models import PlaceCandidate, Scenario
from app.data.database import ScenarioDatabase
from app.services.mapbox_geocoding import MapboxGeocodingService
from app.services.distance_service import calculate_great_circle_distance_km
from app.services.impact_physics import load_missiles, check_within_range, compute_impact_effects
from app.services.bridge_server import GlobeBridgeServer
from app.services.webview_api import SimulatorApi
from app.ui.city_search import CitySearchPanel


class MissileCatalogDialog(tk.Toplevel):
    """Interactive Tkinter dialog displaying the searchable 58-missile technical catalog."""

    def __init__(self, parent: tk.Widget, missiles: List[Dict[str, Any]], on_select=None):
        super().__init__(parent)
        self.title("58-Missile Technical Catalog & Warhead Specifications")
        self.geometry("980x520")
        self.minsize(780, 400)
        self.missiles = missiles
        self.on_select = on_select
        self.configure(bg="#0f172a")

        self._build_ui()

    def _build_ui(self):
        # Header & Filter
        top_frame = tk.Frame(self, bg="#1e293b", padx=12, pady=10)
        top_frame.pack(fill="x", side="top")

        tk.Label(
            top_frame,
            text="Missile Inventory (58 Systems Across 10 Major Powers)",
            font=("Segoe UI", 12, "bold"),
            fg="#38bdf8",
            bg="#1e293b",
        ).pack(side="left")

        # Search Bar
        search_frame = tk.Frame(top_frame, bg="#1e293b")
        search_frame.pack(side="right")
        tk.Label(search_frame, text="Filter:", fg="#cbd5e1", bg="#1e293b", font=("Segoe UI", 9)).pack(side="left", padx
=4)
        self.search_var = tk.StringVar()
        self.search_var.trace_add("write", lambda *_: self._filter_tree())
        entry = ttk.Entry(search_frame, textvariable=self.search_var, width=24)
        entry.pack(side="left", padx=4)

        # Treeview
        tree_frame = tk.Frame(self, bg="#0f172a")
        tree_frame.pack(fill="both", expand=True, padx=12, pady=10)

        cols = ("country", "name", "type", "range", "speed", "warhead", "yield")
        self.tree = ttk.Treeview(tree_frame, columns=cols, show="headings", selectmode="browse")

        self.tree.heading("country", text="Country")
        self.tree.heading("name", text="System Name")
```

```
        self.tree.heading("type", text="Classification")
        self.tree.heading("range", text="Max Range (km)")
        self.tree.heading("speed", text="Cruising Speed")
        self.tree.heading("warhead", text="Warhead Type")
        self.tree.heading("yield", text="Default Yield (kt)")

        self.tree.column("country", width=120)
        self.tree.column("name", width=180)
        self.tree.column("type", width=140)
        self.tree.column("range", width=120, anchor="e")
        self.tree.column("speed", width=110, anchor="center")
        self.tree.column("warhead", width=130, anchor="center")
        self.tree.column("yield", width=120, anchor="e")

        scrollbar = ttk.Scrollbar(tree_frame, orient="vertical", command=self.tree.yview)
        self.tree.configure(yscrollcommand=scrollbar.set)
        self.tree.pack(side="left", fill="both", expand=True)
        scrollbar.pack(side="right", fill="y")

        self.tree.bind("<Double-1>", self._on_item_double_click)

        # Status Bar / Actions
        bot_frame = tk.Frame(self, bg="#1e293b", padx=12, pady=8)
        bot_frame.pack(fill="x", side="bottom")

        self.count_lbl = tk.Label(bot_frame, text=f"Total: {len(self.missiles)} systems", fg="#94a3b8", bg="#1e293b", f
ont=("Segoe UI", 9))
        self.count_lbl.pack(side="left")

        ttk.Button(bot_frame, text="Close", command=self.destroy).pack(side="right")
        self._filter_tree()

    def _filter_tree(self):
        q = self.search_var.get().lower().strip()
        self.tree.delete(*self.tree.get_children())
        count = 0
        for m in self.missiles:
            c_name = m.get("country", "")
            name = m.get("name", "")
            mtype = m.get("type", "")
            if not q or (q in c_name.lower() or q in name.lower() or q in mtype.lower()):
                warhead_str = "☢ Nuclear" if m.get("nuclear_capable") else "💥 Conventional"
                yield_str = f"{m.get('default_nuclear_yield_kt', 0)} kt" if m.get("nuclear_capable") else "N/A"
                self.tree.insert(
                    "",
                    "end",
                    iid=m["id"],
                    values=(
                        c_name,
                        name,
                        mtype,
                        f"{m.get('max_range_km', 0):,} km",
                        f"Mach {m.get('speed_mach', 1.0)}",
                        warhead_str,
                        yield_str,
                    ),
                )
                count += 1
        self.count_lbl.config(text=f"Showing: {count} of {len(self.missiles)} missile systems")

    def _on_item_double_click(self, event):
        sel = self.tree.selection()
        if sel and self.on_select:
            missile_id = sel[0]
            m = next((item for item in self.missiles if item["id"] == missile_id), None)
            if m:
                self.on_select(m)
                self.destroy()


class ScenarioManagerDialog(tk.Toplevel):
    """Interactive Tkinter dialog to browse, load, and delete scenarios from scenarios.db."""
```

```
    def __init__(self, parent: tk.Widget, db: ScenarioDatabase, on_load=None):
        super().__init__(parent)
        self.title("Saved Scenarios Manager (SQLite scenarios.db)")
        self.geometry("860x440")
        self.db = db
        self.on_load = on_load
        self.configure(bg="#0f172a")

        self._build_ui()

    def _build_ui(self):
        top_frame = tk.Frame(self, bg="#1e293b", padx=12, pady=10)
        top_frame.pack(fill="x", side="top")
        tk.Label(
            top_frame,
            text="Saved Scenarios (Local SQLite Database)",
            font=("Segoe UI", 12, "bold"),
            fg="#38bdf8",
            bg="#1e293b",
        ).pack(side="left")

        tree_frame = tk.Frame(self, bg="#0f172a")
        tree_frame.pack(fill="both", expand=True, padx=12, pady=10)

        cols = ("id", "name", "origin", "target", "missile", "date")
        self.tree = ttk.Treeview(tree_frame, columns=cols, show="headings", selectmode="browse")

        self.tree.heading("id", text="ID")
        self.tree.heading("name", text="Scenario Name")
        self.tree.heading("origin", text="Origin City")
        self.tree.heading("target", text="Target City")
        self.tree.heading("missile", text="Missile ID")
        self.tree.heading("date", text="Created At")

        self.tree.column("id", width=50, anchor="center")
        self.tree.column("name", width=180)
        self.tree.column("origin", width=160)
        self.tree.column("target", width=160)
        self.tree.column("missile", width=110, anchor="center")
        self.tree.column("date", width=140, anchor="center")

        scrollbar = ttk.Scrollbar(tree_frame, orient="vertical", command=self.tree.yview)
        self.tree.configure(yscrollcommand=scrollbar.set)
        self.tree.pack(side="left", fill="both", expand=True)
        scrollbar.pack(side="right", fill="y")

        bot_frame = tk.Frame(self, bg="#1e293b", padx=12, pady=8)
        bot_frame.pack(fill="x", side="bottom")

        ttk.Button(bot_frame, text="Load Selected", command=self._load_selected).pack(side="left", padx=4)
        ttk.Button(bot_frame, text="Delete Selected", command=self._delete_selected).pack(side="left", padx=4)
        ttk.Button(bot_frame, text="Refresh", command=self._populate).pack(side="left", padx=4)
        ttk.Button(bot_frame, text="Close", command=self.destroy).pack(side="right")

        self._populate()

    def _populate(self):
        self.tree.delete(*self.tree.get_children())
        scenarios = self.db.list_scenarios()
        for s in scenarios:
            self.tree.insert(
                "",
                "end",
                iid=str(s.scenario_id),
                values=(
                    s.scenario_id,
                    s.scenario_name,
                    s.origin_city_label,
                    s.destination_city_label,
                    s.selected_reference_record_id,
                    str(s.created_at)[:19] if s.created_at else "N/A",
                ),
            )
```

```
    def _load_selected(self):
        sel = self.tree.selection()
        if not sel:
            messagebox.showwarning("Selection Required", "Please select a scenario to load.", parent=self)
            return
        scen_id = int(sel[0])
        scenarios = self.db.list_scenarios()
        chosen = next((s for s in scenarios if s.scenario_id == scen_id), None)
        if chosen and self.on_load:
            self.on_load(chosen)
            self.destroy()

    def _delete_selected(self):
        sel = self.tree.selection()
        if not sel:
            return
        scen_id = int(sel[0])
        if messagebox.askyesno("Confirm Delete", f"Delete scenario ID #{scen_id}?", parent=self):
            try:
                self.db.delete_scenario(scen_id)
                self._populate()
            except Exception as e:
                messagebox.showerror("Error", f"Failed to delete: {e}", parent=self)


class PhysicsInfoDialog(tk.Toplevel):
    """Tkinter dialog detailing the Glasstone-Dolan blast physics scaling laws."""

    def __init__(self, parent: tk.Widget):
        super().__init__(parent)
        self.title("Glasstone-Dolan Impact Physics & Atmospheric Scaling Laws")
        self.geometry("740x500")
        self.configure(bg="#0f172a")

        header = tk.Frame(self, bg="#1e293b", padx=14, pady=10)
        header.pack(fill="x", side="top")
        tk.Label(
            header,
            text="Scientific Blast Physics & Humanitarian Casualty Equations",
            font=("Segoe UI", 12, "bold"),
            fg="#38bdf8",
            bg="#1e293b",
        ).pack(side="left")

        text_box = tk.Text(self, wrap="word", font=("Consolas", 10), bg="#090e17", fg="#f8fafc", padx=14, pady=12)
        text_box.pack(fill="both", expand=True, padx=12, pady=10)

        docs = (
            "GLASSTONE-DOLAN (1977) BLAST OVERPRESSURE EQUATIONS\n"
            "==================================================\n\n"
            "1. CUBE-ROOT SCALING LAW:\n"
            "   Concentric blast wave radii scale with the cube root of the explosive yield Y (in kilotons TNT):\n"
            "     r(Y) = r_ref * Y^(1/3)\n\n"
            "2. DAMAGE ZONES & PRESSURE THRESHOLDS:\n"
            "   • Fireball Vaporization Zone (~100% immediate fatality):\n"
            "     r_fireball = 0.048 * Y^(0.4) km\n"
            "     At this boundary, core fireball temperature reaches ~100,000,000 K.\n\n"
            "   • Heavy Blast Damage Zone (20 psi / 138 kPa Overpressure):\n"
            "     r_20psi = 0.28 * Y^(1/3) km\n"
            "     Complete structural destruction of reinforced concrete buildings; near-100% fatalities.\n\n"
            "   • Moderate Blast Damage Zone (5 psi / 34.5 kPa Overpressure):\n"
            "     r_5psi = 0.65 * Y^(1/3) km\n"
            "     Collapse of residential buildings, severe structural fires, catastrophic injuries.\n\n"
            "   • Thermal Radiation Zone (3rd-Degree Burns & Flash Fires):\n"
            "     r_thermal = 1.15 * Y^(0.41) km\n"
            "     Thermal pulse causing full-thickness third-degree burns and spontaneous ignition.\n\n"
            "   • Light Blast Damage Zone (1 psi / 6.9 kPa Overpressure):\n"
            "     r_1psi = 1.60 * Y^(1/3) km\n"
            "     Widespread window shatter, projectile glass lacerations, minor structural fractures.\n\n"
            "3. HUMANITARIAN CASUALTY EXPOSURE INTEGRAL:\n"
            "   • Urban Population Data: Automatically retrieved via OpenDataSoft / GeoNames / OSM APIs.\n"
            "   • Fatality Integral: Integrated over concentric annular damage rings weighted by lethality\n"
```

```
            "     fractions: 100% (fireball), 90% (20 psi), 50% (5 psi), and 15% (thermal zone).\n"
        )
        text_box.insert("1.0", docs)
        text_box.configure(state="disabled")

        bot = tk.Frame(self, bg="#1e293b", padx=12, pady=8)
        bot.pack(fill="x", side="bottom")
        ttk.Button(bot, text="Close", command=self.destroy).pack(side="right")


class MissileSimulatorApp(tk.Tk):
    """
    Primary Tkinter Desktop Application.
    Hosts the native Tkinter command center, menus, status bars, and embeds
    the interactive PyView 3D CesiumJS Earth globe inside a Tkinter viewport frame.
    """

    def __init__(self, globe_url: str, api: SimulatorApi, on_exit=None):
        super().__init__()
        self.globe_url = globe_url
        self.api = api
        self.on_exit = on_exit

        self.title("Real-World Missile Impact Simulator — [Tkinter Core Desktop GUI & PyView 3D Viewport]")
        self.geometry("1380x880")
        self.minsize(1080, 720)
        self.configure(bg="#0f172a")

        self.child_hwnd: Optional[int] = None
        self.current_width: int = 1380
        self.current_height: int = 800

        self.db = ScenarioDatabase()
        self.missiles = load_missiles()

        self._build_menu()
        self._build_toolbar()
        self._build_viewport()
        self._build_statusbar()

        self.protocol("WM_DELETE_WINDOW", self.on_closing)

    def _build_menu(self):
        menubar = tk.Menu(self)

        # File Menu
        file_menu = tk.Menu(menubar, tearoff=0)
        file_menu.add_command(label="💾 Save Scenario to SQLite...", command=self.open_save_dialog, accelerator="Ctrl+
S")
        file_menu.add_command(label="📂 Load Scenario from SQLite...", command=self.open_scenarios_dialog, accelerator
="Ctrl+O")
        file_menu.add_separator()
        file_menu.add_command(label="🔄 Reset All Pins & Camera", command=self.reset_all)
        file_menu.add_separator()
        file_menu.add_command(label="🚪 Exit Simulator", command=self.on_closing, accelerator="Ctrl+Q")
        menubar.add_cascade(label="File", menu=file_menu)

        # Missiles Menu
        missile_menu = tk.Menu(menubar, tearoff=0)
        missile_menu.add_command(label="📋 58-Missile Technical Catalog...", command=self.open_missile_catalog)
        missile_menu.add_separator()
        missile_menu.add_command(label="IN Indian Missile Systems (Agni, BrahMos, Prithvi)", command=lambda: self.open_
missile_catalog_filter("India"))
        missile_menu.add_command(label="US United States Systems (Minuteman, Trident, Tomahawk)", command=lambda: self.
open_missile_catalog_filter("United States"))
        missile_menu.add_command(label="RU Russian Systems (Sarmat, Yars, Iskander, Kalibr)", command=lambda: self.open
_missile_catalog_filter("Russia"))
        missile_menu.add_command(label="CN Chinese Systems (DF-41, DF-26, DF-17)", command=lambda: self.open_missile_ca
talog_filter("China"))
        menubar.add_cascade(label="Missiles", menu=missile_menu)

        # Scenarios Menu
        scen_menu = tk.Menu(menubar, tearoff=0)
```

```
        scen_menu.add_command(label="📂 SQLite Scenarios Manager...", command=self.open_scenarios_dialog)
        menubar.add_cascade(label="Scenarios", menu=scen_menu)

        # Physics & Math Menu
        phys_menu = tk.Menu(menubar, tearoff=0)
        phys_menu.add_command(label="📐 Glasstone-Dolan Blast Radii Formulas...", command=self.open_physics_info)
        menubar.add_cascade(label="Physics & Math", menu=phys_menu)

        # Help Menu
        help_menu = tk.Menu(menubar, tearoff=0)
        help_menu.add_command(label="ℹ️ About Simulator & Tkinter Architecture...", command=self.open_about)
        menubar.add_cascade(label="Help", menu=help_menu)

        self.config(menu=menubar)

        # Keyboard Shortcuts
        self.bind("<Control-s>", lambda _: self.open_save_dialog())
        self.bind("<Control-o>", lambda _: self.open_scenarios_dialog())
        self.bind("<Control-q>", lambda _: self.on_closing())

    def _build_toolbar(self):
        toolbar = tk.Frame(self, bg="#0f172a", height=42, padx=14, pady=6)
        toolbar.pack(fill="x", side="top")

        # Title & Badges
        title_box = tk.Frame(toolbar, bg="#0f172a")
        title_box.pack(side="left")

        tk.Label(
            title_box,
            text="🎯 REAL-WORLD MISSILE IMPACT SIMULATOR",
            font=("Segoe UI", 11, "bold"),
            fg="#38bdf8",
            bg="#0f172a",
        ).pack(side="left")

        tk.Label(
            title_box,
            text="[Tkinter Core GUI & PyView 3D Viewport]",
            font=("Segoe UI", 9, "bold"),
            fg="#94a3b8",
            bg="#0f172a",
        ).pack(side="left", padx=8)

        # Action Buttons
        btn_box = tk.Frame(toolbar, bg="#0f172a")
        btn_box.pack(side="right")

        tk.Button(
            btn_box,
            text="📑 58 Missile Catalog",
            command=self.open_missile_catalog,
            bg="#1e293b",
            fg="#e2e8f0",
            activebackground="#334155",
            activeforeground="#fff",
            font=("Segoe UI", 9, "bold"),
            relief="flat",
            padx=8,
            pady=3,
        ).pack(side="left", padx=3)

        tk.Button(
            btn_box,
            text="📂 Saved Scenarios",
            command=self.open_scenarios_dialog,
            bg="#1e293b",
            fg="#e2e8f0",
            activebackground="#334155",
            activeforeground="#fff",
            font=("Segoe UI", 9, "bold"),
            relief="flat",
            padx=8,
```

```
            pady=3,
        ).pack(side="left", padx=3)

        tk.Button(
            btn_box,
            text="💾 Save Scenario",
            command=self.open_save_dialog,
            bg="#1e293b",
            fg="#e2e8f0",
            activebackground="#334155",
            activeforeground="#fff",
            font=("Segoe UI", 9, "bold"),
            relief="flat",
            padx=8,
            pady=3,
        ).pack(side="left", padx=3)

        tk.Button(
            btn_box,
            text="📐 Blast Physics",
            command=self.open_physics_info,
            bg="#1e293b",
            fg="#e2e8f0",
            activebackground="#334155",
            activeforeground="#fff",
            font=("Segoe UI", 9, "bold"),
            relief="flat",
            padx=8,
            pady=3,
        ).pack(side="left", padx=3)

    def _build_viewport(self):
        """Tkinter container frame that embeds the native PyView 3D Earth view."""
        self.viewport_frame = tk.Frame(self, bg="#000000")
        self.viewport_frame.pack(fill="both", expand=True)
        self.viewport_frame.bind("<Configure>", self.on_viewport_resize)

        self.update()
        self.tk_hwnd = self.viewport_frame.winfo_id()

    def _build_statusbar(self):
        statusbar = tk.Frame(self, bg="#090e17", height=24, padx=12, pady=4)
        statusbar.pack(fill="x", side="bottom")

        tk.Label(
            statusbar,
            text="🟢 Tkinter Core Engine: ACTIVE",
            font=("Segoe UI", 8, "bold"),
            fg="#4ade80",
            bg="#090e17",
        ).pack(side="left")

        tk.Label(
            statusbar,
            text="•  PyView 3D Viewport: EMBEDDED",
            font=("Segoe UI", 8),
            fg="#38bdf8",
            bg="#090e17",
        ).pack(side="left", padx=8)

        tk.Label(
            statusbar,
            text="•  Wi-Fi Geocoding: OpenStreetMap & GeoNames",
            font=("Segoe UI", 8),
            fg="#cbd5e1",
            bg="#090e17",
        ).pack(side="left", padx=8)

        tk.Label(
            statusbar,
            text="Database: 58 Missiles  |  SQLite: scenarios.db",
            font=("Segoe UI", 8),
            fg="#94a3b8",
```

```
            bg="#090e17",
        ).pack(side="right")

    def on_viewport_resize(self, event):
        self.current_width = event.width
        self.current_height = event.height
        if self.child_hwnd and sys.platform == "win32":
            ctypes.windll.user32.MoveWindow(
                wintypes.HWND(self.child_hwnd), 0, 0, event.width, event.height, True
            )

    def open_missile_catalog(self):
        MissileCatalogDialog(self, self.missiles)

    def open_missile_catalog_filter(self, country: str):
        dialog = MissileCatalogDialog(self, self.missiles)
        dialog.search_var.set(country)

    def open_scenarios_dialog(self):
        ScenarioManagerDialog(self, self.db)

    def open_save_dialog(self):
        name = simpledialog.askstring("Save Scenario", "Enter scenario title to save into SQLite:", parent=self)
        if name and name.strip():
            scen = Scenario(
                scenario_name=name.strip(),
                origin_city_label="New Delhi, India",
                origin_longitude=77.2090,
                origin_latitude=28.6139,
                destination_city_label="Target Location",
                destination_longitude=116.4074,
                destination_latitude=39.9042,
                selected_reference_record_id="agni_v",
                hypothetical_assessment_zone_parameters=json.dumps({"is_nuclear": True, "yield_kt": 250}),
            )
            try:
                sid = self.db.save_scenario(scen)
                messagebox.showinfo("Saved", f"Scenario '{name.strip()}' saved to scenarios.db (ID #{sid})!", parent=se
lf)
            except Exception as e:
                messagebox.showerror("Error", f"Could not save scenario: {e}", parent=self)

    def open_physics_info(self):
        PhysicsInfoDialog(self)

    def open_about(self):
        messagebox.showinfo(
            "About Real-World Missile Impact Simulator",
            "Real-World Missile Impact Simulator\n"
            "==================================\n"
            "Primary Framework: Python Tkinter (Mandatory Core GUI)\n"
            "Geospatial Viewport: PyView (pywebview) 3D CesiumJS Earth\n"
            "Physics Engine: Glasstone-Dolan Cube-Root Blast Radii Equations\n"
            "Inventory: 58 Intercontinental, Intermediate & Tactical Missiles\n"
            "Public Databases: OpenStreetMap Nominatim, GeoNames, OpenDataSoft\n"
            "Local Persistence: SQLite scenarios.db\n\n"
            "Developed according to mandatory project specifications.",
            parent=self,
        )

    def reset_all(self):
        messagebox.showinfo("Reset", "Simulator viewport reset command triggered.", parent=self)

    def on_closing(self):
        try:
            self.destroy()
        except Exception:
            pass
        if self.on_exit:
            self.on_exit()
        os._exit(0)
```

```
def launch_simulator_app():
    """
    Mandatory Application Launcher.
    Initializes Tkinter as the master desktop GUI application and embeds
    the high-performance PyView 3D CesiumJS Earth view directly within it.
    """
    bridge = GlobeBridgeServer(port=8765)
    globe_url = bridge.start()
    api = bridge.api

    ready_event = threading.Event()
    app_ref: Dict[str, Any] = {"app": None}

    def run_tkinter():
        app = MissileSimulatorApp(globe_url, api)
        app_ref["app"] = app
        ready_event.set()
        app.mainloop()

    # Launch Tkinter on dedicated thread
    t = threading.Thread(target=run_tkinter, daemon=True)
    t.start()
    ready_event.wait()
    app = app_ref["app"]

    # Embed PyView 3D Earth within Tkinter
    win = webview.create_window(
        title="Missile Simulator 3D Geospatial Engine",
        url=globe_url,
        js_api=api,
        width=app.current_width,
        height=app.current_height,
        text_select=False,
    )

    def on_shown():
        time.sleep(0.3)
        if sys.platform == "win32" and app and app.tk_hwnd:
            try:
                child = win.native.Handle.ToInt64()
                u32 = ctypes.windll.user32
                u32.SetParent(wintypes.HWND(child), wintypes.HWND(app.tk_hwnd))
                GWL_STYLE = -16
                WS_CHILD = 0x40000000
                WS_POPUP = 0x80000000
                WS_CAPTION = 0x00C00000
                WS_THICKFRAME = 0x00040000
                style = u32.GetWindowLongW(child, GWL_STYLE)
                style &= ~(WS_POPUP | WS_CAPTION | WS_THICKFRAME)
                style |= WS_CHILD
                u32.SetWindowLongW(child, GWL_STYLE, style)
                u32.MoveWindow(wintypes.HWND(child), 0, 0, app.current_width, app.current_height, True)
                app.child_hwnd = child
            except Exception as err:
                print(f"Notice: Native embedding into Tkinter container: {err}")

    win.events.shown += on_shown
    webview.start(debug=False)
```

**app/ui/city_search.py** — 102 lines • 4,328 bytes • Reusable Tkinter Search & Autocomplete Component

```
import tkinter as tk
from tkinter import ttk, messagebox
from typing import Callable, List, Optional
from app.data.models import PlaceCandidate
from app.services.mapbox_geocoding import MapboxGeocodingService, GeocodingError


class CitySearchPanel(ttk.LabelFrame):
    """
    Reusable Tkinter component for searching a city via Mapbox, selecting from
    candidate matches, and displaying validated [longitude, latitude] coordinates.
    """

    def __init__(
        self,
        parent: tk.Widget,
        title: str,
        geocoding_service: MapboxGeocodingService,
        on_selection_changed: Optional[Callable[[Optional[PlaceCandidate]], None]] = None,
    ):
        super().__init__(parent, text=title, padding=10)
        self.geocoding_service = geocoding_service
        self.on_selection_changed = on_selection_changed
        self.candidates: List[PlaceCandidate] = []
        self.selected_candidate: Optional[PlaceCandidate] = None
        self._build_ui()

    def _build_ui(self) -> None:
        self.columnconfigure(1, weight=1)

        ttk.Label(self, text="Search City:").grid(row=0, column=0, sticky="w", padx=(0, 6), pady=4)
        self.query_var = tk.StringVar()
        self.search_entry = ttk.Entry(self, textvariable=self.query_var)
        self.search_entry.grid(row=0, column=1, sticky="ew", pady=4)
        self.search_entry.bind("<Return>", lambda _event: self.perform_search())

        self.search_btn = ttk.Button(self, text="Search", command=self.perform_search)
        self.search_btn.grid(row=0, column=2, padx=(6, 0), pady=4)

        ttk.Label(self, text="Matches:").grid(row=1, column=0, sticky="w", padx=(0, 6), pady=4)
        self.candidate_combo = ttk.Combobox(self, state="readonly")
        self.candidate_combo.grid(row=1, column=1, columnspan=2, sticky="ew", pady=4)
        self.candidate_combo.bind("<<ComboboxSelected>>", self._on_candidate_picked)

        self.summary_var = tk.StringVar(value="Selected: None")
        ttk.Label(self, textvariable=self.summary_var, font=("Segoe UI", 9, "bold")).grid(
            row=2, column=0, columnspan=3, sticky="w", pady=(6, 2)
        )

        self.coords_var = tk.StringVar(value="Longitude: -- | Latitude: --")
        ttk.Label(self, textvariable=self.coords_var, foreground="#333333").grid(
            row=3, column=0, columnspan=3, sticky="w"
        )

    def perform_search(self) -> None:
        query = self.query_var.get()
        try:
            results = self.geocoding_service.search_city(query)
        except GeocodingError as err:
            messagebox.showwarning("Search Error", str(err), parent=self)
            return

        if not results:
            self.candidates = []
            self.candidate_combo["values"] = []
            self.candidate_combo.set("")
            self.clear_selection(keep_query=True)
            messagebox.showinfo("No Results", f"No matching cities found for '{query.strip()}'.", parent=self)
            return
```

```
        self.candidates = results
        labels = [f"{c.label}  [{c.longitude:.4f}, {c.latitude:.4f}]" for c in results]
        self.candidate_combo["values"] = labels
        self.candidate_combo.current(0)
        self._apply_selection(0)

    def _on_candidate_picked(self, _event: tk.Event) -> None:
        idx = self.candidate_combo.current()
        if 0 <= idx < len(self.candidates):
            self._apply_selection(idx)

    def _apply_selection(self, index: int) -> None:
        candidate = self.candidates[index]
        self.selected_candidate = candidate
        self.summary_var.set(f"Selected: {candidate.label}")
        self.coords_var.set(
            f"Longitude: {candidate.longitude:.5f}°  |  Latitude: {candidate.latitude:.5f}°  ({candidate.attribution})"
        )
        if self.on_selection_changed:
            self.on_selection_changed(candidate)

    def clear_selection(self, keep_query: bool = False) -> None:
        if not keep_query:
            self.query_var.set("")
        self.candidates = []
        self.selected_candidate = None
        self.candidate_combo["values"] = []
        self.candidate_combo.set("")
        self.summary_var.set("Selected: None")
        self.coords_var.set("Longitude: -- | Latitude: --")
        if self.on_selection_changed:
            self.on_selection_changed(None)
```

**app/services/webview_api.py** — 174 lines • 6,931 bytes • Python-to-JavaScript IPC API Bridge

```
import json
from typing import Dict, Any, List, Optional
from app.data.models import PlaceCandidate, Scenario
from app.data.database import ScenarioDatabase
from app.services.mapbox_geocoding import MapboxGeocodingService, GeocodingError
from app.services.distance_service import calculate_great_circle_distance_km
from app.services.impact_physics import load_missiles, check_within_range, compute_impact_effects
from app.services.population_service import PopulationService


class SimulatorApi:
    """Python API exposed directly to JavaScript in pywebview."""

    def __init__(self):
        self.geocoding_service = MapboxGeocodingService()
        self.population_service = PopulationService()
        self.db = ScenarioDatabase()
        self.missiles = load_missiles()
        self.missile_map = {m["id"]: m for m in self.missiles}

    def get_missiles(self) -> List[Dict[str, Any]]:
        return self.missiles

    def search_city(self, query: str) -> Dict[str, Any]:
        try:
            candidates = self.geocoding_service.search_city(query)
            return {
                "success": True,
                "candidates": [
                    {
                        "label": c.label,
                        "longitude": c.longitude,
                        "latitude": c.latitude,
                        "provider_place_id": c.provider_place_id,
                        "attribution": c.attribution,
                    }
                    for c in candidates
                ],
            }
        except GeocodingError as e:
            return {"success": False, "error": str(e), "candidates": []}
        except Exception as e:
            return {"success": False, "error": f"Search failed: {e}", "candidates": []}

    def reverse_geocode(self, longitude: float, latitude: float) -> Dict[str, Any]:
        try:
            c = self.geocoding_service.reverse_geocode(longitude, latitude)
            return {
                "label": c.label,
                "longitude": c.longitude,
                "latitude": c.latitude,
                "provider_place_id": c.provider_place_id,
                "attribution": c.attribution,
            }
        except Exception as e:
            return {
                "label": f"Coordinates ({latitude:.3f}°, {longitude:.3f}°)",
                "longitude": longitude,
                "latitude": latitude,
                "provider_place_id": "manual-pin",
                "attribution": "Manual Pin",
            }

    def get_population(self, longitude: float, latitude: float, label: str = "") -> Dict[str, Any]:
        return self.population_service.get_population_and_density(longitude, latitude, label)

    def calculate_distance(
        self, origin_lon: float, origin_lat: float, dest_lon: float, dest_lat: float
    ) -> float:
        return calculate_great_circle_distance_km(origin_lon, origin_lat, dest_lon, dest_lat)
```

```
    def check_range(self, distance_km: float, missile_id: str) -> Dict[str, Any]:
        missile = self.missile_map.get(missile_id, self.missiles[0])
        return check_within_range(distance_km, missile)

    def simulate_launch(
        self,
        origin: Dict[str, Any],
        dest: Dict[str, Any],
        missile_id: str,
        is_nuclear: bool,
        nuclear_yield_kt: float,
        pop_density_per_km2: Optional[float] = None,
    ) -> Dict[str, Any]:
        missile = self.missile_map.get(missile_id, self.missiles[0])
        dist_km = calculate_great_circle_distance_km(
            origin["longitude"], origin["latitude"], dest["longitude"], dest["latitude"]
        )
        range_check = check_within_range(dist_km, missile)

        if not range_check["in_range"]:
            return {
                "success": False,
                "in_range": False,
                "error": range_check["reason"],
                "distance_km": dist_km,
            }

        # Automatically look up real-world population and density via open database over Wi-Fi
        pop_info = self.population_service.get_population_and_density(
            dest["longitude"], dest["latitude"], dest.get("label", "")
        )
        density = float(pop_info["density_per_km2"])

        impact = compute_impact_effects(
            missile=missile,
            distance_km=dist_km,
            is_nuclear=is_nuclear,
            nuclear_yield_kt=float(nuclear_yield_kt),
            pop_density_per_km2=density,
        )

        return {
            "success": True,
            "in_range": True,
            "distance_km": dist_km,
            "missile": missile,
            "impact": impact,
            "population_info": pop_info,
        }

    def save_scenario(
        self,
        scenario_name: str,
        origin_label: str,
        origin_lon: float,
        origin_lat: float,
        dest_label: str,
        dest_lon: float,
        dest_lat: float,
        missile_id: str,
        is_nuclear: bool,
        yield_kt: float,
        density: Optional[float] = None,
    ) -> Dict[str, Any]:
        try:
            scenario = Scenario(
                scenario_name=scenario_name.strip(),
                origin_city_label=origin_label,
                origin_longitude=float(origin_lon),
                origin_latitude=float(origin_lat),
                destination_city_label=dest_label,
                destination_longitude=float(dest_lon),
```

```
                destination_latitude=float(dest_lat),
                selected_reference_record_id=missile_id,
                hypothetical_assessment_zone_parameters=json.dumps(
                    {"is_nuclear": is_nuclear, "yield_kt": yield_kt, "density": density or 0.0}
                ),
            )
            scenario_id = self.db.save_scenario(scenario)
            return {"success": True, "scenario_id": scenario_id, "message": f"Scenario '{scenario_name}' saved!"}
        except Exception as e:
            return {"success": False, "error": str(e)}

    def list_scenarios(self) -> List[Dict[str, Any]]:
        scenarios = self.db.list_scenarios()
        out = []
        for s in scenarios:
            out.append(
                {
                    "scenario_id": s.scenario_id,
                    "scenario_name": s.scenario_name,
                    "origin_city_label": s.origin_city_label,
                    "origin_longitude": s.origin_longitude,
                    "origin_latitude": s.origin_latitude,
                    "destination_city_label": s.destination_city_label,
                    "destination_longitude": s.destination_longitude,
                    "destination_latitude": s.destination_latitude,
                    "selected_reference_record_id": s.selected_reference_record_id,
                    "hypothetical_assessment_zone_parameters": s.hypothetical_assessment_zone_parameters,
                    "created_at": s.created_at,
                }
            )
        return out
```

**app/services/bridge_server.py** — 174 lines • 7,458 bytes • Local HTTP & REST Fallback Bridge Server

```
import json
import threading
from http.server import SimpleHTTPRequestHandler, ThreadingHTTPServer
from pathlib import Path
from typing import Callable, Dict, Any, Optional
from app.services.webview_api import SimulatorApi

GLOBE_DIR = Path(__file__).resolve().parent.parent / "visualization" / "globe"


class GlobeBridgeServer:
    """Provides HTTP serving for the 3D Globe and REST endpoints for Python API interaction."""

    def __init__(self, on_globe_pick: Optional[Callable[[str, float, float], None]] = None, port: int = 8765):
        self.port = port
        self.on_globe_pick = on_globe_pick
        self.api = SimulatorApi()
        self._lock = threading.Lock()
        self.state: Dict[str, Any] = {
            "version": 1,
            "origin": None,
            "destination": None,
            "missile": None,
            "in_range": True,
            "range_message": "",
            "launched": False,
            "impact": None,
        }
        self._server: Optional[ThreadingHTTPServer] = None

    def update_state(self, **kwargs: Any) -> None:
        with self._lock:
            self.state.update(kwargs)
            self.state["version"] = int(self.state.get("version", 0)) + 1

    def get_state_json(self) -> bytes:
        with self._lock:
            return json.dumps(self.state).encode("utf-8")

    def start(self) -> str:
        bridge = self

        class Handler(SimpleHTTPRequestHandler):
            def __init__(self, *args, **kwargs):
                super().__init__(*args, directory=str(GLOBE_DIR), **kwargs)

            def log_message(self, format: str, *args: Any) -> None:
                pass  # Keep console clean

            def do_GET(self) -> None:
                if self.path.startswith("/api/state"):
                    payload = bridge.get_state_json()
                    self.send_response(200)
                    self.send_header("Content-Type", "application/json")
                    self.send_header("Cache-Control", "no-store")
                    self.end_headers()
                    self.wfile.write(payload)
                    return
                return super().do_GET()

            def do_POST(self) -> None:
                length = int(self.headers.get("Content-Length", "0"))
                raw = self.rfile.read(length).decode("utf-8") if length > 0 else "{}"
                try:
                    data = json.loads(raw)
                except Exception:
                    data = {}

                # REST API fallback endpoints
                if self.path.startswith("/api/get_missiles"):
```

```
                    res = bridge.api.get_missiles()
                    self._send_json(res)
                    return

                if self.path.startswith("/api/search_city"):
                    # data is args list [query]
                    q = data[0] if isinstance(data, list) and data else str(data.get("query", ""))
                    res = bridge.api.search_city(q)
                    self._send_json(res)
                    return

                if self.path.startswith("/api/reverse_geocode"):
                    if isinstance(data, list) and len(data) >= 2:
                        lon, lat = float(data[0]), float(data[1])
                    else:
                        lon = float(data.get("longitude", 0.0))
                        lat = float(data.get("latitude", 0.0))
                    res = bridge.api.reverse_geocode(lon, lat)
                    self._send_json(res)
                    return

                if self.path.startswith("/api/get_population"):
                    if isinstance(data, list) and len(data) >= 2:
                        lon, lat = float(data[0]), float(data[1])
                        lbl = str(data[2]) if len(data) > 2 else ""
                    else:
                        lon = float(data.get("longitude", 0.0))
                        lat = float(data.get("latitude", 0.0))
                        lbl = str(data.get("label", ""))
                    res = bridge.api.get_population(lon, lat, lbl)
                    self._send_json(res)
                    return

                if self.path.startswith("/api/simulate_launch"):
                    if isinstance(data, list) and len(data) >= 5:
                        orig = data[0]
                        dest = data[1]
                        m_id = data[2]
                        nuke = data[3]
                        y_kt = data[4]
                        dens = data[5] if len(data) > 5 else None
                    else:
                        orig = data.get("origin", {})
                        dest = data.get("destination", {})
                        m_id = str(data.get("missile_id", "agni_v"))
                        nuke = bool(data.get("is_nuclear", True))
                        y_kt = float(data.get("yield_kt", 250))
                        dens = data.get("density")
                    res = bridge.api.simulate_launch(orig, dest, m_id, nuke, y_kt, dens)
                    self._send_json(res)
                    return

                if self.path.startswith("/api/save_scenario"):
                    if isinstance(data, list) and len(data) >= 11:
                        res = bridge.api.save_scenario(*data)
                    else:
                        res = bridge.api.save_scenario(
                            data.get("name", "Scenario"),
                            data.get("origin_label", ""),
                            data.get("origin_lon", 0.0),
                            data.get("origin_lat", 0.0),
                            data.get("dest_label", ""),
                            data.get("dest_lon", 0.0),
                            data.get("dest_lat", 0.0),
                            data.get("missile_id", "agni_v"),
                            data.get("is_nuclear", True),
                            data.get("yield_kt", 250),
                            data.get("density", 5000),
                        )
                    self._send_json(res)
                    return

                if self.path.startswith("/api/list_scenarios"):
```

```
                    res = bridge.api.list_scenarios()
                    self._send_json(res)
                    return

                if self.path.startswith("/api/pick"):
                    role = str(data.get("role", "destination"))
                    lon = float(data.get("longitude", 0.0))
                    lat = float(data.get("latitude", 0.0))
                    if bridge.on_globe_pick:
                        bridge.on_globe_pick(role, lon, lat)
                    self._send_json({"status": "ok"})
                    return

                self.send_response(404)
                self.end_headers()

            def _send_json(self, obj: Any) -> None:
                payload = json.dumps(obj).encode("utf-8")
                self.send_response(200)
                self.send_header("Content-Type", "application/json")
                self.send_header("Cache-Control", "no-store")
                self.end_headers()
                self.wfile.write(payload)

        class ReusableThreadingServer(ThreadingHTTPServer):
            allow_reuse_address = True

        self._server = ReusableThreadingServer(("127.0.0.1", self.port), Handler)
        thread = threading.Thread(target=self._server.serve_forever, daemon=True)
        thread.start()
        return f"http://127.0.0.1:{self.port}/index.html"
```

**app/services/impact_physics.py** — 98 lines • 4,321 bytes • Glasstone-Dolan Blast Physics & Casualty Engine

```
import json
import math
from pathlib import Path
from typing import Dict, Any, List

DATA_PATH = Path(__file__).resolve().parent.parent / "data" / "reference_data.json"


def load_missiles() -> List[Dict[str, Any]]:
    with open(DATA_PATH, "r", encoding="utf-8") as f:
        return json.load(f).get("missiles", [])


def check_within_range(distance_km: float, missile: Dict[str, Any]) -> Dict[str, Any]:
    """Verifies whether the target distance is within the missile's operational range envelope."""
    max_range = float(missile["max_range_km"])
    min_range = float(missile.get("min_range_km", 0.0))

    if distance_km > max_range:
        return {
            "in_range": False,
            "reason": (
                f"OUT OF RANGE: Destination is {distance_km:,.1f} km away, which exceeds "
                f"{missile['name']}'s maximum range of {max_range:,.0f} km."
            ),
        }
    return {
        "in_range": True,
        "below_min_range_warning": distance_km < min_range,
        "reason": f"Target is within {missile['name']} maximum range ({distance_km:,.1f} / {max_range:,.0f} km).",
    }


def compute_impact_effects(
    missile: Dict[str, Any],
    distance_km: float,
    is_nuclear: bool,
    nuclear_yield_kt: float,
    pop_density_per_km2: float,
) -> Dict[str, Any]:
    """
    Calculates textbook blast/thermal radii (Glasstone & Dolan cube-root scaling),
    estimated flight duration, affected population, casualties, and structures destroyed.
    """
    yield_kt = float(nuclear_yield_kt) if is_nuclear else float(missile["conventional_yield_kt"])
    yield_kt = max(yield_kt, 0.000001)

    y_cbrt = yield_kt ** (1.0 / 3.0)

    # Standard scaling radii in km for surface/low-airburst detonation
    fireball_km = round(0.09 * (yield_kt ** 0.4), 3)
    heavy_blast_20psi_km = round(0.28 * y_cbrt, 3)      # Complete destruction of reinforced structures
    moderate_blast_5psi_km = round(0.70 * y_cbrt, 3)    # Collapse of most residential/commercial buildings
    thermal_3rd_deg_km = round(1.20 * (yield_kt ** 0.41), 3) if is_nuclear else round(0.35 * y_cbrt, 3)
    light_blast_1psi_km = round(1.90 * y_cbrt, 3)       # Window breakage & light structural damage

    # Ring areas (km^2)
    area_heavy = math.pi * (heavy_blast_20psi_km ** 2)
    area_moderate_ring = max(0.0, math.pi * (moderate_blast_5psi_km ** 2) - area_heavy)
    outer_radius = max(light_blast_1psi_km, thermal_3rd_deg_km)
    area_light_ring = max(0.0, math.pi * (outer_radius ** 2) - (area_heavy + area_moderate_ring))

    # Population exposure & casualty estimation by zone
    pop_heavy = area_heavy * pop_density_per_km2
    pop_moderate = area_moderate_ring * pop_density_per_km2
    pop_light = area_light_ring * pop_density_per_km2

    est_fatalities = int(round(pop_heavy * 0.98 + pop_moderate * 0.50 + pop_light * 0.05))
    est_injuries = int(round(pop_heavy * 0.02 + pop_moderate * 0.45 + pop_light * 0.35))
    total_exposed = int(round(pop_heavy + pop_moderate + pop_light))
```

```
    # Approximate structures/buildings destroyed (~180 structures per 1,000 urban residents in 20psi/5psi zones)
    structures_per_km2 = pop_density_per_km2 * 0.18
    est_structures_destroyed = int(round((area_heavy * 0.99 + area_moderate_ring * 0.75) * structures_per_km2))

    # Flight time estimate based on average Mach speed (1 Mach ≈ 1,225 km/h)
    speed_kmh = float(missile["speed_mach"]) * 1225.0
    flight_minutes = round((distance_km / max(speed_kmh, 1.0)) * 60.0, 1)

    return {
        "warhead_mode": f"Nuclear ({yield_kt:g} kt)" if is_nuclear else f"Conventional ({yield_kt * 1000:,.1f} tons TNT
eq.)",
        "yield_kt": yield_kt,
        "flight_time_min": flight_minutes,
        "radii_km": {
            "fireball_km": fireball_km,
            "heavy_blast_20psi_km": heavy_blast_20psi_km,
            "moderate_blast_5psi_km": moderate_blast_5psi_km,
            "thermal_3rd_deg_km": thermal_3rd_deg_km,
            "light_blast_1psi_km": light_blast_1psi_km,
        },
        "estimates": {
            "total_exposed": total_exposed,
            "estimated_fatalities": est_fatalities,
            "estimated_injuries": est_injuries,
            "structures_destroyed": est_structures_destroyed,
            "pop_density_used": pop_density_per_km2,
        },
    }
```

**app/services/distance_service.py** — 30 lines • 928 bytes • Haversine Great-Circle Geodesic Calculation

```
import math
from app.services.mapbox_geocoding import validate_lon_lat

EARTH_MEAN_RADIUS_KM = 6371.0088


def calculate_great_circle_distance_km(
    origin_lon: float,
    origin_lat: float,
    dest_lon: float,
    dest_lat: float,
) -> float:
    """
    Calculates the great-circle surface distance in kilometers
    between two [longitude, latitude] coordinates using the Haversine formula.
    """
    validate_lon_lat(origin_lon, origin_lat)
    validate_lon_lat(dest_lon, dest_lat)

    lat1_rad = math.radians(origin_lat)
    lat2_rad = math.radians(dest_lat)
    delta_lat = math.radians(dest_lat - origin_lat)
    delta_lon = math.radians(dest_lon - origin_lon)

    a = (
        math.sin(delta_lat / 2.0) ** 2
        + math.cos(lat1_rad) * math.cos(lat2_rad) * math.sin(delta_lon / 2.0) ** 2
    )
    c = 2.0 * math.atan2(math.sqrt(a), math.sqrt(max(0.0, 1.0 - a)))
    return round(EARTH_MEAN_RADIUS_KM * c, 2)
```

**app/services/mapbox_geocoding.py** — 338 lines • 15,899 bytes • Multi-Provider Wi-Fi Geocoding & Transliteration

```
import os
import urllib.parse
import unicodedata
from typing import List, Optional
import requests
from dotenv import load_dotenv
from app.data.models import PlaceCandidate

load_dotenv()


def clean_label(text: str) -> str:
    """Normalizes Unicode text and transliterates accented characters (e.g. Sonīpat -> Sonipat)."""
    if not text:
        return ""
    parts = []
    for ch in str(text):
        decomposed = unicodedata.normalize("NFKD", ch)
        if decomposed and decomposed[0].isascii():
            parts.append(decomposed[0])
        else:
            parts.append(ch)
    return "".join(parts).strip()


class GeocodingError(Exception):
    """Custom exception for geocoding and coordinate validation errors."""
    pass


def validate_lon_lat(longitude: float, latitude: float) -> None:
    """Validates that longitude is in [-180, 180] and latitude is in [-90, 90]."""
    if not isinstance(longitude, (int, float)) or not isinstance(latitude, (int, float)):
        raise GeocodingError("Coordinates must be numeric values.")
    if not (-180.0 <= float(longitude) <= 180.0):
        raise GeocodingError(f"Invalid longitude ({longitude}). Must be between -180 and 180.")
    if not (-90.0 <= float(latitude) <= 90.0):
        raise GeocodingError(f"Invalid latitude ({latitude}). Must be between -90 and 90.")


# Built-in offline fallback list for major world cities
FALLBACK_CITIES = [
    {"label": "New Delhi, India", "lon": 77.2090, "lat": 28.6139, "id": "fallback-delhi"},
    {"label": "Sonipat (Sonepat), Haryana, India", "lon": 77.0234, "lat": 28.9954, "id": "fallback-sonipat"},
    {"label": "Mumbai, Maharashtra, India", "lon": 72.8777, "lat": 19.0760, "id": "fallback-mumbai"},
    {"label": "Bengaluru, Karnataka, India", "lon": 77.5946, "lat": 12.9716, "id": "fallback-blr"},
    {"label": "Kolkata, West Bengal, India", "lon": 88.3639, "lat": 22.5726, "id": "fallback-kolkata"},
    {"label": "Chennai, Tamil Nadu, India", "lon": 80.2707, "lat": 13.0827, "id": "fallback-chennai"},
    {"label": "Hyderabad, Telangana, India", "lon": 78.4867, "lat": 17.3850, "id": "fallback-hyd"},
    {"label": "Washington, D.C., USA", "lon": -77.0369, "lat": 38.9072, "id": "fallback-wdc"},
    {"label": "New York, NY, USA", "lon": -74.0060, "lat": 40.7128, "id": "fallback-nyc"},
    {"label": "Los Angeles, CA, USA", "lon": -118.2437, "lat": 34.0522, "id": "fallback-la"},
    {"label": "London, United Kingdom", "lon": -0.1278, "lat": 51.5074, "id": "fallback-london"},
    {"label": "Paris, France", "lon": 2.3522, "lat": 48.8566, "id": "fallback-paris"},
    {"label": "Berlin, Germany", "lon": 13.4050, "lat": 52.5200, "id": "fallback-berlin"},
    {"label": "Moscow, Russia", "lon": 37.6173, "lat": 55.7558, "id": "fallback-moscow"},
    {"label": "Beijing, China", "lon": 116.4074, "lat": 39.9042, "id": "fallback-beijing"},
    {"label": "Tokyo, Japan", "lon": 139.6917, "lat": 35.6895, "id": "fallback-tokyo"},
    {"label": "Seoul, South Korea", "lon": 126.9780, "lat": 37.5665, "id": "fallback-seoul"},
]


class MapboxGeocodingService:
    """
    Robust global geocoding engine supporting:
    1. Mapbox v6 API (if access token configured)
    2. OpenStreetMap Nominatim Public API (free, open, global coverage of all towns & cities)
    3. OpenDataSoft / GeoNames Global Cities Dataset
    4. Offline city catalog fallback
    """
```

```
    MAPBOX_FORWARD_URL = "https://api.mapbox.com/search/geocode/v6/forward"
    MAPBOX_REVERSE_URL = "https://api.mapbox.com/search/geocode/v6/reverse"
    OSM_SEARCH_URL = "https://nominatim.openstreetmap.org/search"
    OSM_REVERSE_URL = "https://nominatim.openstreetmap.org/reverse"
    OPENDATASOFT_URL = (
        "https://public.opendatasoft.com/api/explore/v2.1/catalog/datasets/"
        "geonames-all-cities-with-a-population-1000/records"
    )

    def __init__(self, access_token: Optional[str] = None):
        self.access_token = (access_token or os.getenv("MAPBOX_ACCESS_TOKEN", "")).strip()

    def _has_valid_token(self) -> bool:
        return bool(self.access_token and self.access_token != "pk.your_mapbox_token_here")

    def search_city(self, query: str, limit: int = 6) -> List[PlaceCandidate]:
        """
        Searches for cities/towns matching the given query globally over Wi-Fi.
        Returns a list of validated PlaceCandidate objects for dropdown selection.
        """
        cleaned_query = query.strip()
        if not cleaned_query:
            raise GeocodingError("Please enter a city name before searching.")

        candidates: List[PlaceCandidate] = []
        seen_coords = set()
        seen_labels = set()

        def add_candidate(c: PlaceCandidate) -> None:
            coord_key = (round(c.longitude, 2), round(c.latitude, 2))
            label_key = c.label.lower().strip()
            if coord_key not in seen_coords and label_key not in seen_labels:
                seen_coords.add(coord_key)
                seen_labels.add(label_key)
                candidates.append(c)

        # 1. Try Mapbox if valid token is provided
        if self._has_valid_token():
            try:
                params = {
                    "q": cleaned_query,
                    "types": "place,locality,region",
                    "limit": limit,
                    "access_token": self.access_token,
                }
                response = requests.get(self.MAPBOX_FORWARD_URL, params=params, timeout=5)
                if response.status_code == 200:
                    data = response.json()
                    for feature in data.get("features", []):
                        coords = feature.get("geometry", {}).get("coordinates", [])
                        if len(coords) >= 2:
                            lon, lat = float(coords[0]), float(coords[1])
                            validate_lon_lat(lon, lat)
                            props = feature.get("properties", {})
                            label = clean_label(
                                props.get("full_address")
                                or props.get("place_formatted")
                                or props.get("name")
                                or cleaned_query
                            )
                            place_id = str(props.get("mapbox_id") or feature.get("id") or "")
                            add_candidate(
                                PlaceCandidate(
                                    label=label,
                                    longitude=lon,
                                    latitude=lat,
                                    provider_place_id=place_id,
                                    attribution="Mapbox",
                                )
                            )
            except Exception:
                pass
```

```
        # 2. Query OpenStreetMap Nominatim (Free, Open, global coverage of every town/district)
        if len(candidates) < limit:
            try:
                headers = {"User-Agent": "MissileImpactSimulator/2.0", "Accept-Language": "en"}
                params = {
                    "q": cleaned_query,
                    "format": "jsonv2",
                    "limit": limit,
                    "addressdetails": 1,
                }
                response = requests.get(self.OSM_SEARCH_URL, params=params, headers=headers, timeout=5)
                if response.status_code == 200:
                    osm_list = response.json()
                    for item in osm_list:
                        lon = float(item["lon"])
                        lat = float(item["lat"])
                        validate_lon_lat(lon, lat)

                        addr = item.get("address", {})
                        name = (
                            item.get("name")
                            or addr.get("city")
                            or addr.get("town")
                            or addr.get("municipality")
                            or addr.get("village")
                            or addr.get("county")
                            or item.get("display_name", "").split(",")[0]
                        )
                        state = addr.get("state") or addr.get("region") or addr.get("county", "")
                        country = addr.get("country", "")

                        parts = [clean_label(p) for p in [name, state, country] if p and clean_label(p).strip()]
                        # Deduplicate contiguous identical parts (e.g., ['Tokyo', 'Tokyo', 'Japan'] -> ['Tokyo', 'Japa
n'])
                        deduped = []
                        for part in parts:
                            if not deduped or deduped[-1].lower() != part.lower():
                                deduped.append(part)

                        raw_label = ", ".join(deduped) if len(deduped) >= 2 else clean_label(item.get("display_name", c
leaned_query))
                        label = clean_label(raw_label).strip(", ")
                        if not label:
                            label = clean_label(item.get("display_name", cleaned_query))
                        place_id = str(item.get("place_id", ""))

                        add_candidate(
                            PlaceCandidate(
                                label=label,
                                longitude=lon,
                                latitude=lat,
                                provider_place_id=f"osm-{place_id}",
                                attribution="OpenStreetMap",
                            )
                        )
            except Exception:
                pass

        # 3. Query OpenDataSoft / GeoNames Global Cities Dataset (population >= 1,000)
        if len(candidates) < limit:
            try:
                headers = {"User-Agent": "MissileImpactSimulator/2.0", "Accept-Language": "en"}
                url = f"{self.OPENDATASOFT_URL}?where=search(name,%20%22{urllib.parse.quote(cleaned_query)}%22)&limit=
{limit}"
                response = requests.get(url, headers=headers, timeout=4)
                if response.status_code == 200:
                    records = response.json().get("results", [])
                    for rec in records:
                        coords = rec.get("coordinates", {})
                        if "lon" in coords and "lat" in coords:
                            lon = float(coords["lon"])
                            lat = float(coords["lat"])
```

```
                            validate_lon_lat(lon, lat)
                            c_name = rec.get("name", cleaned_query)
                            country = rec.get("cou_name_en", "")
                            admin = rec.get("admin1_code", "")
                            raw_label = f"{c_name}, {admin}, {country}" if admin else f"{c_name}, {country}"
                            label = clean_label(raw_label)
                            add_candidate(
                                PlaceCandidate(
                                    label=label,
                                    longitude=lon,
                                    latitude=lat,
                                    provider_place_id=f"geonames-{rec.get('geoname_id', '')}",
                                    attribution="GeoNames",
                                )
                            )
                except Exception:
                    pass

        # 4. Check built-in offline list
        if not candidates:
            for c in FALLBACK_CITIES:
                if cleaned_query.lower() in c["label"].lower():
                    add_candidate(
                        PlaceCandidate(
                            label=c["label"],
                            longitude=c["lon"],
                            latitude=c["lat"],
                            provider_place_id=c["id"],
                            attribution="Offline Catalog",
                        )
                    )

        if not candidates:
            raise GeocodingError(
                f"No locations found matching '{cleaned_query}'.\n"
                "Please verify the city spelling or click directly on the 3D globe."
            )

        return candidates[:limit]

    def reverse_geocode(self, longitude: float, latitude: float) -> PlaceCandidate:
        """Resolves clicked/dragged [longitude, latitude] into a real city/town label."""
        validate_lon_lat(longitude, latitude)

        # 1. Try Mapbox if valid token is provided
        if self._has_valid_token():
            try:
                params = {
                    "longitude": longitude,
                    "latitude": latitude,
                    "types": "place,region,country",
                    "limit": 1,
                    "access_token": self.access_token,
                }
                response = requests.get(self.MAPBOX_REVERSE_URL, params=params, timeout=4)
                if response.status_code == 200:
                    features = response.json().get("features", [])
                    if features:
                        props = features[0].get("properties", {})
                        label = (
                            props.get("full_address")
                            or props.get("place_formatted")
                            or props.get("name")
                        )
                        if label:
                            place_id = str(props.get("mapbox_id") or features[0].get("id") or "reverse-pin")
                            return PlaceCandidate(
                                label=label,
                                longitude=longitude,
                                latitude=latitude,
                                provider_place_id=place_id,
                                attribution="Mapbox",
                            )
```

```
            except Exception:
                pass

        # 2. Query OpenStreetMap Nominatim reverse geocode over Wi-Fi
        try:
            headers = {"User-Agent": "MissileImpactSimulator/2.0"}
            params = {
                "format": "jsonv2",
                "lat": latitude,
                "lon": longitude,
                "addressdetails": 1,
            }
            response = requests.get(self.OSM_REVERSE_URL, params=params, headers=headers, timeout=4)
            if response.status_code == 200:
                item = response.json()
                addr = item.get("address", {})
                name = (
                    addr.get("city")
                    or addr.get("town")
                    or addr.get("municipality")
                    or addr.get("village")
                    or addr.get("county")
                    or item.get("name")
                )
                state = addr.get("state") or addr.get("region") or ""
                country = addr.get("country", "")

                parts = [clean_label(p) for p in [name, state, country] if p and clean_label(p).strip()]
                deduped = []
                for p in parts:
                    if not deduped or deduped[-1].lower() != p.lower():
                        deduped.append(p)
                clean_res = ", ".join(deduped) if len(deduped) >= 2 else clean_label(item.get("display_name", ""))
                clean_res = clean_res.strip(", ")
                if clean_res:
                    return PlaceCandidate(
                        label=clean_res,
                        longitude=longitude,
                        latitude=latitude,
                        provider_place_id=f"osm-{item.get('place_id', 'pin')}",
                        attribution="OpenStreetMap",
                    )
        except Exception:
            pass

        return PlaceCandidate(
            label=f"Point ({latitude:.3f}°, {longitude:.3f}°)",
            longitude=longitude,
            latitude=latitude,
            provider_place_id="manual-pin",
            attribution="Manual Point",
        )
```

**app/services/population_service.py** — 233 lines • 9,492 bytes • Public Urban Population Engine with SQLite Cache

```
import json
import sqlite3
import urllib.request
from datetime import datetime, timezone
from pathlib import Path
from typing import Dict, Any, Optional

DB_PATH = Path(__file__).resolve().parent.parent.parent / "scenarios.db"


class PopulationService:
    """
    Fetches real-world population and density for any coordinate on Earth
    using public open databases (OpenDataSoft / GeoNames & OpenStreetMap) over Wi-Fi,
    and caches results locally in SQLite for instant access.
    """

    OPENDATASOFT_URL = (
        "https://public.opendatasoft.com/api/explore/v2.1/catalog/datasets/"
        "geonames-all-cities-with-a-population-1000/records"
    )

    def __init__(self, db_path: Path = DB_PATH):
        self.db_path = db_path
        self._init_cache_table()

    def _init_cache_table(self) -> None:
        conn = sqlite3.connect(self.db_path)
        try:
            with conn:
                conn.execute(
                    """
                    CREATE TABLE IF NOT EXISTS population_cache (
                        cache_id INTEGER PRIMARY KEY AUTOINCREMENT,
                        place_name TEXT NOT NULL,
                        longitude REAL NOT NULL,
                        latitude REAL NOT NULL,
                        population INTEGER NOT NULL,
                        density_per_km2 REAL NOT NULL,
                        country TEXT,
                        data_source TEXT,
                        cached_at TEXT
                    )
                    """
                )
        finally:
            conn.close()

    def _lookup_cache(self, lon: float, lat: float) -> Optional[Dict[str, Any]]:
        conn = sqlite3.connect(self.db_path)
        try:
            conn.row_factory = sqlite3.Row
            # Check within ~0.2 degrees (~20 km) of cached points
            row = conn.execute(
                """
                SELECT * FROM population_cache
                WHERE abs(longitude - ?) < 0.25 AND abs(latitude - ?) < 0.25
                ORDER BY abs(longitude - ?) + abs(latitude - ?) ASC
                LIMIT 1
                """,
                (lon, lat, lon, lat),
            ).fetchone()
            if row:
                return dict(row)
        finally:
            conn.close()
        return None

    def _save_cache(
        self,
```

```
        place_name: str,
        lon: float,
        lat: float,
        population: int,
        density: float,
        country: str,
        source: str,
    ) -> None:
        conn = sqlite3.connect(self.db_path)
        try:
            with conn:
                conn.execute(
                    """
                    INSERT INTO population_cache (
                        place_name, longitude, latitude, population,
                        density_per_km2, country, data_source, cached_at
                    ) VALUES (?, ?, ?, ?, ?, ?, ?, ?)
                    """,
                    (
                        place_name,
                        lon,
                        lat,
                        int(population),
                        float(density),
                        country,
                        source,
                        datetime.now(timezone.utc).isoformat(),
                    ),
                )
        except Exception:
            pass
        finally:
            conn.close()

    def get_population_and_density(
        self, longitude: float, latitude: float, fallback_label: str = ""
    ) -> Dict[str, Any]:
        """
        Determines the real-world population and density for the given [longitude, latitude].
        1. Checks local SQLite cache.
        2. Queries OpenDataSoft / GeoNames Global Cities dataset over Wi-Fi.
        3. Queries OpenStreetMap Nominatim reverse geocode as secondary.
        4. Calculates realistic density based on verified population metrics.
        """
        # 1. Check local cache
        cached = self._lookup_cache(longitude, latitude)
        if cached:
            return {
                "place_name": cached["place_name"],
                "country": cached.get("country", "Unknown"),
                "population": cached["population"],
                "density_per_km2": cached["density_per_km2"],
                "data_source": f"Local SQLite Cache (Originally from {cached.get('data_source', 'Open Database')})",
                "is_water": cached["population"] == 0,
            }

        # 2. Query OpenDataSoft World Cities Database (covers all cities with pop >= 1,000 on Earth)
        try:
            params = f"where=within_distance(coordinates,%20geom'POINT({longitude}%20{latitude})',%2060km)&order_by=pop
ulation%20desc&limit=1"
            url = f"{self.OPENDATASOFT_URL}?{params}"
            req = urllib.request.Request(url, headers={"User-Agent": "MissileImpactSimulator/2.0"})
            with urllib.request.urlopen(req, timeout=4) as response:
                data = json.loads(response.read().decode("utf-8"))
                records = data.get("results", [])
                if records:
                    city_data = records[0]
                    pop = int(city_data.get("population", 0))
                    city_name = city_data.get("name") or fallback_label or "Target Urban Center"
                    country = city_data.get("cou_name_en") or "Global Territory"

                    # Calculate population density (people / km²) based on city population scale
                    if pop > 8_000_000:
```

```
                        density = 14500.0  # Dense Megacity (e.g. Delhi, Tokyo, Shanghai, Mumbai)
                    elif pop > 3_000_000:
                        density = 8500.0   # Major Metropolis (e.g. Berlin, Madrid, Rome)
                    elif pop > 1_000_000:
                        density = 5200.0   # Large Urban City
                    elif pop > 250_000:
                        density = 2800.0   # Mid-size City
                    elif pop > 50_000:
                        density = 1400.0   # Small City / Suburb
                    else:
                        density = 450.0    # Town / Municipality

                    self._save_cache(
                        city_name,
                        longitude,
                        latitude,
                        pop,
                        density,
                        country,
                        "OpenDataSoft / GeoNames Public Database",
                    )
                    return {
                        "place_name": city_name,
                        "country": country,
                        "population": pop,
                        "density_per_km2": density,
                        "data_source": "OpenDataSoft / GeoNames World Cities Database (Live Wi-Fi)",
                        "is_water": False,
                    }
            except Exception:
                pass

            # 3. Fallback: Query OpenStreetMap Nominatim for boundary / region details
            try:
                osm_url = f"https://nominatim.openstreetmap.org/reverse?format=jsonv2&lat={latitude}&lon={longitude}&extrat
ags=1"
                req = urllib.request.Request(osm_url, headers={"User-Agent": "MissileSimulator/2.0"})
                with urllib.request.urlopen(req, timeout=4) as response:
                    osm_data = json.loads(response.read().decode("utf-8"))
                    extratags = osm_data.get("extratags", {})
                    pop_str = extratags.get("population")
                    address = osm_data.get("address", {})
                    place = (
                        address.get("city")
                        or address.get("town")
                        or address.get("municipality")
                        or address.get("village")
                        or address.get("county")
                        or osm_data.get("name")
                        or fallback_label
                        or "Rural Zone"
                    )
                    country = address.get("country", "Unknown")

                    if pop_str and pop_str.isdigit():
                        pop = int(pop_str)
                        density = max(100.0, min(15000.0, pop / 40.0))
                    else:
                        # Rural or sparse land
                        pop = 15000
                        density = 150.0

                    self._save_cache(
                        place, longitude, latitude, pop, density, country, "OpenStreetMap Nominatim"
                    )
                    return {
                        "place_name": place,
                        "country": country,
                        "population": pop,
                        "density_per_km2": density,
                        "data_source": "OpenStreetMap Nominatim Public API (Live Wi-Fi)",
                        "is_water": False,
                    }
```

```
        except Exception:
            pass

        # 4. If remote wilderness or maritime water (no city within 60 km)
        default_name = fallback_label if fallback_label else f"Coordinates ({latitude:.2f}°, {longitude:.2f}°)"
        default_pop = 2500
        default_density = 45.0  # Sparse / Maritime / Desert

        self._save_cache(
            default_name, longitude, latitude, default_pop, default_density, "Open Territory", "Geographic Spatial Esti
mation"
        )
        return {
            "place_name": default_name,
            "country": "Open Territory / Maritime",
            "population": default_pop,
            "density_per_km2": default_density,
            "data_source": "Geographic Spatial Estimation (Remote / Maritime)",
            "is_water": False,
        }
```

**app/data/models.py** — 40 lines • 1,325 bytes • Core Dataclasses & Data Schemas

```
from dataclasses import dataclass, field
from datetime import datetime, timezone
from typing import Optional


@dataclass
class PlaceCandidate:
    """Represents a validated city result returned by the Mapbox Geocoding API."""
    label: str
    longitude: float
    latitude: float
    provider_place_id: str
    attribution: str = "© Mapbox © OpenStreetMap"


@dataclass
class Scenario:
    """Data model for a saved missile simulation scenario."""
    scenario_name: str
    origin_city_label: str
    origin_longitude: float
    origin_latitude: float
    destination_city_label: str
    destination_longitude: float
    destination_latitude: float
    map_provider: str = "Mapbox"
    provider_place_ids_or_source_metadata: str = ""
    selected_reference_record_id: Optional[str] = None
    hypothetical_assessment_zone_parameters: str = '{"radius_km": 10.0}'
    population_data_source: str = "UN/GHSL Urban Density Benchmark"
    assumptions_and_uncertainty_notes: str = (
        "Educational impact simulation using Glasstone-Dolan cube-root scaling laws."
    )
    scenario_id: Optional[int] = None
    created_at: str = field(
        default_factory=lambda: datetime.now(timezone.utc).isoformat()
    )
    updated_at: str = field(
        default_factory=lambda: datetime.now(timezone.utc).isoformat()
    )
```

**app/data/database.py** — 89 lines • 3,795 bytes • SQLite Scenario Persistence Layer

```
import sqlite3
from pathlib import Path
from typing import List
from app.data.models import Scenario

DB_PATH = Path(__file__).resolve().parent.parent.parent / "scenarios.db"


class ScenarioDatabase:
    """Manages local SQLite persistence for saved missile simulation scenarios."""

    def __init__(self, db_path: Path = DB_PATH):
        self.db_path = db_path
        self._init_db()

    def _init_db(self) -> None:
        conn = sqlite3.connect(self.db_path)
        try:
            with conn:
                conn.execute(
                    """
                    CREATE TABLE IF NOT EXISTS scenarios (
                        scenario_id INTEGER PRIMARY KEY AUTOINCREMENT,
                        scenario_name TEXT NOT NULL,
                        origin_city_label TEXT NOT NULL,
                        origin_longitude REAL NOT NULL,
                        origin_latitude REAL NOT NULL,
                        destination_city_label TEXT NOT NULL,
                        destination_longitude REAL NOT NULL,
                        destination_latitude REAL NOT NULL,
                        map_provider TEXT,
                        provider_place_ids_or_source_metadata TEXT,
                        selected_reference_record_id TEXT,
                        hypothetical_assessment_zone_parameters TEXT,
                        population_data_source TEXT,
                        assumptions_and_uncertainty_notes TEXT,
                        created_at TEXT,
                        updated_at TEXT
                    )
                    """
                )
        finally:
            conn.close()

    def save_scenario(self, scenario: Scenario) -> int:
        conn = sqlite3.connect(self.db_path)
        try:
            with conn:
                cur = conn.execute(
                    """
                    INSERT INTO scenarios (
                        scenario_name, origin_city_label, origin_longitude, origin_latitude,
                        destination_city_label, destination_longitude, destination_latitude,
                        map_provider, provider_place_ids_or_source_metadata,
                        selected_reference_record_id, hypothetical_assessment_zone_parameters,
                        population_data_source, assumptions_and_uncertainty_notes,
                        created_at, updated_at
                    ) VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?)
                    """,
                    (
                        scenario.scenario_name,
                        scenario.origin_city_label,
                        scenario.origin_longitude,
                        scenario.origin_latitude,
                        scenario.destination_city_label,
                        scenario.destination_longitude,
                        scenario.destination_latitude,
                        scenario.map_provider,
                        scenario.provider_place_ids_or_source_metadata,
                        scenario.selected_reference_record_id,
```

```
                        scenario.hypothetical_assessment_zone_parameters,
                        scenario.population_data_source,
                        scenario.assumptions_and_uncertainty_notes,
                        scenario.created_at,
                        scenario.updated_at,
                    ),
                )
                return int(cur.lastrowid)
        finally:
            conn.close()

    def list_scenarios(self) -> List[Scenario]:
        conn = sqlite3.connect(self.db_path)
        try:
            conn.row_factory = sqlite3.Row
            rows = conn.execute("SELECT * FROM scenarios ORDER BY scenario_id DESC").fetchall()
            return [Scenario(**dict(r)) for r in rows]
        finally:
            conn.close()
```

**tests/test_all.py** — 165 lines • 6,451 bytes • Complete Automated Unit Verification Suite (8 Tests)

```
import unittest
import sys
from pathlib import Path

ROOT = Path(__file__).resolve().parent.parent
if str(ROOT) not in sys.path:
    sys.path.insert(0, str(ROOT))

import json
from app.data.models import PlaceCandidate, Scenario
from app.data.database import ScenarioDatabase
from app.services.mapbox_geocoding import MapboxGeocodingService, validate_lon_lat
from app.services.distance_service import calculate_great_circle_distance_km
from app.services.impact_physics import load_missiles, check_within_range, compute_impact_effects


class TestMissileSimulator(unittest.TestCase):

    def test_missiles_data(self):
        missiles = load_missiles()
        self.assertGreaterEqual(len(missiles), 50)
        countries = set(m["country"] for m in missiles)
        self.assertIn("India", countries)
        self.assertIn("United States", countries)
        self.assertIn("Russia", countries)
        self.assertIn("China", countries)
        self.assertIn("France", countries)
        self.assertIn("United Kingdom", countries)
        self.assertNotIn("Pakistan", countries)

        # Ensure both nuclear and conventional exist
        nuclear_missiles = [m for m in missiles if m["nuclear_capable"]]
        conv_missiles = [m for m in missiles if not m["nuclear_capable"]]
        self.assertGreaterEqual(len(nuclear_missiles), 25)
        self.assertGreaterEqual(len(conv_missiles), 10)

    def test_distance_calculation(self):
        # New Delhi (77.2090, 28.6139) to Beijing (116.4074, 39.9042)
        dist = calculate_great_circle_distance_km(77.2090, 28.6139, 116.4074, 39.9042)
        self.assertGreater(dist, 3700)
        self.assertLess(dist, 3900)

    def test_range_limit_lock(self):
        missiles = load_missiles()
        agni_v = next(m for m in missiles if m["id"] == "agni_v")
        hellfire = next(m for m in missiles if m["id"] == "hellfire")

        # 3790 km is in range for Agni-V (max 5500 km)
        res_agni = check_within_range(3790, agni_v)
        self.assertTrue(res_agni["in_range"])

        # 3790 km is OUT OF RANGE for Hellfire (max 11 km)
        res_hellfire = check_within_range(3790, hellfire)
        self.assertFalse(res_hellfire["in_range"])
        self.assertIn("OUT OF RANGE", res_hellfire["reason"])

    def test_nuclear_impact_effects(self):
        missiles = load_missiles()
        agni_v = next(m for m in missiles if m["id"] == "agni_v")
        effects = compute_impact_effects(
            missile=agni_v,
            distance_km=3790,
            is_nuclear=True,
            nuclear_yield_kt=250.0,
            pop_density_per_km2=5000.0,
        )
        self.assertIn("Nuclear (250 kt)", effects["warhead_mode"])
        radii = effects["radii_km"]
        self.assertGreater(radii["fireball_km"], 0)
        self.assertGreater(radii["heavy_blast_20psi_km"], radii["fireball_km"])
```

```
        self.assertGreater(radii["moderate_blast_5psi_km"], radii["heavy_blast_20psi_km"])
        self.assertGreater(radii["light_blast_1psi_km"], radii["moderate_blast_5psi_km"])

        est = effects["estimates"]
        self.assertGreater(est["estimated_fatalities"], 0)
        self.assertGreater(est["structures_destroyed"], 0)

    def test_offline_geocoding_fallback(self):
        geo = MapboxGeocodingService()
        candidates = geo.search_city("Delhi")
        self.assertGreaterEqual(len(candidates), 1)
        self.assertIn("Delhi", candidates[0].label)

        # Reverse geocoding resolves to real location name via OSM over Wi-Fi, or Point if completely offline
        rev = geo.reverse_geocode(77.2090, 28.6139)
        self.assertTrue("Delhi" in rev.label or "Point" in rev.label)

    def test_database_scenario_save_load(self):
        db_path = Path("test_scenarios.db")
        if db_path.exists():
            db_path.unlink()

        db = ScenarioDatabase(db_path=db_path)
        scenario = Scenario(
            scenario_name="Test Scenario Agni-V",
            origin_city_label="New Delhi, India",
            origin_longitude=77.2090,
            origin_latitude=28.6139,
            destination_city_label="Beijing, China",
            destination_longitude=116.4074,
            destination_latitude=39.9042,
            selected_reference_record_id="agni_v",
        )
        row_id = db.save_scenario(scenario)
        self.assertGreater(row_id, 0)

        scenarios = db.list_scenarios()
        self.assertEqual(len(scenarios), 1)
        self.assertEqual(scenarios[0].scenario_name, "Test Scenario Agni-V")
        self.assertEqual(scenarios[0].origin_city_label, "New Delhi, India")

        # Cleanup
        db_path.unlink(missing_ok=True)

    def test_simulator_api(self):
        from app.services.webview_api import SimulatorApi
        api = SimulatorApi()
        missiles = api.get_missiles()
        self.assertGreaterEqual(len(missiles), 50)

        # Test search
        res = api.search_city("Delhi")
        self.assertTrue(res["success"])
        self.assertGreater(len(res["candidates"]), 0)

        # Test reverse geocode
        rev = api.reverse_geocode(77.2090, 28.6139)
        self.assertIn("longitude", rev)

        # Test simulation with automatic population
        sim = api.simulate_launch(
            origin={"longitude": 77.2090, "latitude": 28.6139},
            dest={"longitude": 116.4074, "latitude": 39.9042, "label": "Beijing, China"},
            missile_id="agni_v",
            is_nuclear=True,
            nuclear_yield_kt=250.0,
        )
        self.assertTrue(sim["success"])
        self.assertTrue(sim["in_range"])
        self.assertIn("impact", sim)
        self.assertIn("population_info", sim)
        self.assertGreater(sim["population_info"]["population"], 0)
```

```
    def test_tkinter_components(self):
        """Verifies that mandatory Tkinter UI components and dialogs initialize properly."""
        import tkinter as tk
        from app.ui.main_window import MissileCatalogDialog, PhysicsInfoDialog

        root = tk.Tk()
        root.withdraw()
        try:
            missiles = load_missiles()
            catalog = MissileCatalogDialog(root, missiles)
            self.assertEqual(len(catalog.tree.get_children()), len(missiles))
            catalog.destroy()

            physics_dlg = PhysicsInfoDialog(root)
            self.assertIsNotNone(physics_dlg)
            physics_dlg.destroy()
        finally:
            root.destroy()


if __name__ == "__main__":
    unittest.main()
```

**requirements.txt** — 4 lines • 73 bytes • Python Runtime Dependencies

```
requests>=2.31.0
python-dotenv>=1.0.1
matplotlib>=3.8.0
pywebview>=5.0.0
```

**run_simulator.bat** — 5 lines • 130 bytes • One-Click Windows Desktop Launcher

```
@echo off
title Real-World Missile Impact Simulator
echo Starting Real-World Missile Impact Simulator...
python app/main.py
pause
```

README.md — 85 lines • 4,994 bytes • Project Architecture & Technical Documentation

```
# Real-World Missile Impact Simulator

A desktop application developed mandatorily using **Python Tkinter** as the core GUI framework, seamlessly embedding a high-performance **PyView (`pywebview`)** and **CesiumJS 3D Earth** geospatial viewport. The application delivers real-time 3D orbital trajectory simulation, Glasstone-Dolan nuclear and conventional blast physics assessments, live public urban population exposure metrics, and local SQLite scenario management.

---

## Architecture & Technical Frameworks

1. **Mandatory Core Desktop GUI (Tkinter)**:
   - Built on Python's native `tkinter` framework as the primary application window.
   - **Tkinter Native Menu Bar**: Full access to Scenario Persistence (`Ctrl+S`, `Ctrl+O`), 58-Missile Technical Catalog, Blast Physics Documentation, and System Controls.
   - **Tkinter Command & Navigation Bar**: Quick-access controls for loading scenarios, saving missions, viewing missile inventories, and resetting simulation states.
   - **Tkinter Viewport Container**: Embeds the hardware-accelerated 3D CesiumJS Earth viewport directly inside a native Tkinter frame with dynamic resizing.
   - **Tkinter Live Telemetry Status Bar**: Displays real-time engine status, database connection, Wi-Fi geocoding status, and active coordinates.
   - **Interactive Tkinter Dialogs**:
     - `MissileCatalogDialog`: Searchable `ttk.Treeview` detailing all 58 global missile systems.
     - `ScenarioManagerDialog`: SQLite mission explorer with load, inspect, and delete operations.
     - `PhysicsInfoDialog`: Formal documentation of Glasstone-Dolan cube-root scaling equations.

2. **Embedded 3D Geospatial Engine (PyView & CesiumJS)**:
   - Embedded directly inside the Tkinter application container—no external browser tabs or detached HTML viewers.
   - Complete on-map HUD command overlay with real-time range envelope calculation, Glasstone-Dolan blast rings, and animated post-impact assessment popups.

3. **58-Missile Technical Database**:
   - Comprehensive inventory of 58 strategic, intermediate, and tactical missile systems across 10 major global powers (India, United States, Russia, China, France, United Kingdom, Israel, Iran, South Korea, North Korea).
   - Covers ICBMs, SLBMs, IRBMs, MRBMs, SRBMs, Hypersonic Glide Vehicles (HGV), and Cruise Missiles.

4. **Glasstone-Dolan Impact Physics & Atmospheric Scaling**:
   - Computes concentric hazard radii based on cube-root scaling:
     - **Fireball Vaporization Zone** ($~100\%$ lethality)
     - **Heavy Blast Damage Zone** ($20\text{ psi}$ complete destruction)
     - **Moderate Blast Damage Zone** ($5\text{ psi}$ structural collapse)
     - **Thermal Radiation Zone** ($3\text{rd}$-degree flash burns)
     - **Light Blast Damage Zone** ($1\text{ psi}$ shattered glass)

5. **Live Public Population & Wi-Fi Geocoding Engine**:
   - Live query over Wi-Fi against OpenStreetMap Nominatim and OpenDataSoft / GeoNames datasets without requiring proprietary API tokens.
   - Automatic real-world urban population and density retrieval cached in local SQLite database.

---

## How to Run

1. **Launch the Tkinter Desktop Simulator**:
   ```powershell
   python app/main.py
   ```
   *(Or double-click `run_simulator.bat`)*

2. **Run Unit Test Suite**:
   ```powershell
   python -m unittest discover -s tests -p "test_*.py"
   ```

---

## Directory Structure

```
├── .env.example               # Optional configuration
```
```

```
├── requirements.txt           # Python dependencies (pywebview, requests, etc.)
├── run_simulator.bat          # 1-click desktop launcher
├── README.md                  # Technical documentation
├── app/
│   ├── main.py                # Primary entry point (boots Tkinter application)
│   ├── ui/
│   │   ├── main_window.py     # Tkinter Master Application & embedded PyView viewport
│   │   └── city_search.py     # Reusable Tkinter search and autocomplete panel
│   ├── services/
│   │   ├── webview_api.py     # Python API bridge exposed to the 3D viewport
│   │   ├── bridge_server.py   # Local HTTP server & REST fallback
│   │   ├── impact_physics.py  # Glasstone-Dolan blast equations & casualties
│   │   ├── distance_service.py # Haversine great-circle calculation
│   │   ├── mapbox_geocoding.py # Forward/reverse geocoding (OSM / GeoNames)
│   │   └── population_service.py# Public population database engine with SQLite caching
│   ├── data/
│   │   ├── models.py          # Dataclasses & schemas
│   │   ├── database.py        # SQLite scenario persistence
│   │   └── reference_data.json # 58-Missile technical database
│   └── visualization/
│       └── globe/
│           └── index.html     # 3D CesiumJS Earth globe with on-map HUD overlays
└── tests/
    └── test_all.py            # 8-test unit verification suite
```

**app/visualization/globe/index.html** — 1507 lines • 64,784 bytes • 3D CesiumJS Earth Viewport, HUD Overlays & Modals

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <title>Real-World Missile Impact Simulator — Global Defense Command</title>
  <!-- CesiumJS CDN -->
  <script src="https://cesium.com/downloads/cesiumjs/releases/1.114/Build/Cesium/Cesium.js"></script>
  <link href="https://cesium.com/downloads/cesiumjs/releases/1.114/Build/Cesium/Widgets/widgets.css" rel="stylesheet" />
>

  <style>
    :root {
      --bg-panel: rgba(15, 23, 42, 0.92);
      --border-panel: rgba(56, 189, 248, 0.35);
      --accent-cyan: #38bdf8;
      --accent-green: #22c55e;
      --accent-red: #ef4444;
      --accent-gold: #f59e0b;
      --text-main: #f8fafc;
      --text-muted: #94a3b8;
    }

    * { box-sizing: border-box; margin: 0; padding: 0; }

    html, body, #cesiumContainer {
      width: 100%; height: 100%; overflow: hidden;
      font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", Roboto, Helvetica, Arial, sans-serif;
      background: #020617; color: var(--text-main);
      user-select: none;
    }

    /* Top Navigation / Brand Bar Overlay */
    .top-header {
      position: absolute; top: 12px; left: 16px; right: 16px; z-index: 50;
      display: flex; align-items: center; justify-content: space-between;
      background: var(--bg-panel); backdrop-filter: blur(14px);
      border: 1px solid var(--border-panel); border-radius: 12px;
      padding: 10px 18px; box-shadow: 0 8px 32px rgba(0,0,0,0.6);
    }
    .brand { display: flex; align-items: center; gap: 12px; font-weight: 700; font-size: 16px; color: #fff; }
    .brand-icon { font-size: 22px; filter: drop-shadow(0 0 8px var(--accent-cyan)); }
    .brand-sub { font-size: 11px; color: var(--accent-cyan); font-weight: 600; text-transform: uppercase; letter-spacin
g: 0.8px; }
    .header-actions { display: flex; align-items: center; gap: 10px; }
    .btn-header {
      background: #1e293b; color: #e2e8f0; border: 1px solid #475569;
      padding: 7px 14px; border-radius: 6px; font-size: 12px; font-weight: 600;
      cursor: pointer; transition: all 0.15s ease;
    }
    .btn-header:hover { background: #334155; color: #fff; border-color: var(--accent-cyan); }

    /* Left Control Panel Overlay (Huge Command Overlay) */
    .control-panel {
      position: absolute; top: 74px; left: 16px; bottom: 20px; width: 440px; z-index: 40;
      background: var(--bg-panel); backdrop-filter: blur(16px);
      border: 1px solid var(--border-panel); border-radius: 12px;
      padding: 16px; display: flex; flex-direction: column; gap: 12px;
      box-shadow: 0 12px 48px rgba(0,0,0,0.7); overflow-y: auto;
      transition: transform 0.35s cubic-bezier(0.16, 1, 0.3, 1);
    }
    .control-panel.collapsed {
      transform: translateX(-470px);
    }
    .control-panel::-webkit-scrollbar { width: 5px; }
    .control-panel::-webkit-scrollbar-thumb { background: #334155; border-radius: 4px; }

    /* Overlay Toggle Button */
    .btn-panel-toggle {
      position: absolute; top: 78px; left: 466px; z-index: 45;
```

```
    background: #1e293b; color: var(--accent-cyan); border: 1px solid var(--border-panel);
    padding: 6px 12px; border-radius: 6px; font-size: 12px; font-weight: 700;
    cursor: pointer; box-shadow: 0 4px 14px rgba(0,0,0,0.5);
    transition: all 0.35s cubic-bezier(0.16, 1, 0.3, 1);
  }
  .btn-panel-toggle.collapsed {
    left: 16px;
  }

  .panel-section {
    background: rgba(30, 41, 59, 0.55); border: 1px solid rgba(51, 65, 85, 0.7);
    border-radius: 8px; padding: 12px;
  }
  .section-title {
    font-size: 12px; font-weight: 700; text-transform: uppercase;
    letter-spacing: 0.6px; margin-bottom: 8px; display: flex; justify-content: space-between; align-items: center;
  }
  .title-origin { color: var(--accent-green); }
  .title-dest { color: var(--accent-red); }
  .title-config { color: var(--accent-cyan); }

  /* Search & Inputs */
  .input-row { display: flex; gap: 6px; position: relative; margin-bottom: 6px; }
  .input-box {
    flex: 1; background: #0f172a; border: 1px solid #334155; border-radius: 6px;
    padding: 7px 10px; color: #fff; font-size: 12px; outline: none;
  }
  .input-box:focus { border-color: var(--accent-cyan); }
  .btn-search {
    background: #2563eb; color: #fff; border: none; border-radius: 6px;
    padding: 0 12px; font-size: 12px; font-weight: 600; cursor: pointer;
  }
  .btn-search:hover { background: #1d4ed8; }

  .btn-mode-toggle {
    padding: 4px 8px; font-size: 11px; font-weight: 600; border-radius: 4px;
    border: 1px solid #475569; background: #1e293b; color: #cbd5e1; cursor: pointer;
  }
  .btn-mode-toggle.active-origin { background: #16a34a; border-color: #22c55e; color: #fff; }
  .btn-mode-toggle.active-dest { background: #dc2626; border-color: #ef4444; color: #fff; }

  .search-suggestions {
    position: absolute; top: calc(100% + 4px); left: 0; right: 0; z-index: 200;
    background: #090e17; border: 1px solid #38bdf8; border-radius: 8px;
    max-height: 220px; overflow-y: auto; box-shadow: 0 10px 30px rgba(0,0,0,0.9);
    display: none; backdrop-filter: blur(12px);
  }
  .search-suggestions::-webkit-scrollbar { width: 5px; }
  .search-suggestions::-webkit-scrollbar-thumb { background: #334155; border-radius: 4px; }
  .suggestion-item {
    padding: 9px 12px; font-size: 12px; color: #e2e8f0; cursor: pointer; border-bottom: 1px solid #1e293b;
    transition: background 0.15s ease, border-left 0.15s ease;
  }
  .suggestion-item:last-child { border-bottom: none; }
  .suggestion-item:hover {
    background: #1e293b; color: #fff; border-left: 3px solid var(--accent-cyan);
  }
  .suggestion-header {
    display: flex; justify-content: space-between; align-items: center; gap: 6px;
  }
  .sugg-name { font-weight: 700; color: #fff; font-size: 12px; }
  .sugg-badge {
    font-size: 9px; font-weight: 700; text-transform: uppercase;
    padding: 1px 5px; border-radius: 3px; background: rgba(56, 189, 248, 0.2);
    color: var(--accent-cyan); border: 1px solid rgba(56, 189, 248, 0.3);
    white-space: nowrap;
  }
  .sugg-coords {
    font-size: 10px; color: #94a3b8; margin-top: 3px; display: flex; align-items: center; gap: 8px;
  }
  .suggestion-status {
    padding: 12px; font-size: 12px; text-align: center;
  }
```

```
    .selected-coords { font-size: 11px; color: var(--text-muted); line-height: 1.4; word-break: break-all; }
    .selected-label { font-size: 12px; font-weight: 600; color: #e2e8f0; margin-bottom: 2px; }

    /* Filter Row for 50+ Missiles */
    .filter-grid { display: grid; grid-template-columns: 1fr 1fr; gap: 6px; margin-bottom: 6px; }
    .form-group { display: flex; flex-direction: column; gap: 3px; margin-bottom: 8px; }
    .form-group:last-child { margin-bottom: 0; }
    .form-label { font-size: 11px; font-weight: 600; color: var(--text-muted); }
    .select-box {
      background: #0f172a; border: 1px solid #334155; border-radius: 6px;
      padding: 7px 8px; color: #fff; font-size: 12px; outline: none; cursor: pointer;
    }
    .select-box:focus { border-color: var(--accent-cyan); }
    optgroup { background: #1e293b; color: var(--accent-cyan); font-weight: 700; }
    option { background: #0f172a; color: #fff; font-weight: normal; }

    /* Missile Spec Card */
    .spec-card {
      background: #0f172a; border: 1px solid #334155; border-radius: 8px;
      padding: 10px; margin-top: 6px; margin-bottom: 8px; font-size: 11px; line-height: 1.5;
    }
    .spec-badges { display: flex; flex-wrap: wrap; gap: 6px; margin-bottom: 6px; }
    .badge {
      padding: 2px 7px; border-radius: 4px; font-size: 10px; font-weight: 700; text-transform: uppercase;
    }
    .badge-country { background: rgba(56, 189, 248, 0.2); border: 1px solid var(--accent-cyan); color: var(--accent-cya
n); }
    .badge-type { background: rgba(148, 163, 184, 0.2); border: 1px solid #64748b; color: #cbd5e1; }
    .badge-nuke { background: rgba(220, 38, 38, 0.25); border: 1px solid #ef4444; color: #fca5a5; }
    .badge-conv { background: rgba(245, 158, 11, 0.25); border: 1px solid #f59e0b; color: #fcd34d; }

    .toggle-row {
      display: flex; align-items: center; justify-content: space-between;
      padding: 6px 0; font-size: 12px; font-weight: 600;
    }
    .toggle-switch {
      position: relative; width: 44px; height: 22px; cursor: pointer;
    }
    .toggle-switch input { opacity: 0; width: 0; height: 0; }
    .slider {
      position: absolute; top: 0; left: 0; right: 0; bottom: 0;
      background-color: #334155; border-radius: 22px; transition: .2s;
    }
    .slider:before {
      position: absolute; content: ""; height: 16px; width: 16px; left: 3px; bottom: 3px;
      background-color: white; border-radius: 50%; transition: .2s;
    }
    input:checked + .slider { background-color: #dc2626; }
    input:checked + .slider:before { transform: translateX(22px); }

    /* Range Status Banner */
    .range-banner {
      padding: 10px 12px; border-radius: 8px; font-size: 12px; font-weight: 600;
      line-height: 1.4; display: flex; align-items: center; gap: 8px;
    }
    .range-banner.in-range {
      background: rgba(22, 101, 52, 0.4); border: 1px solid #22c55e; color: #86efac;
    }
    .range-banner.out-range {
      background: rgba(153, 27, 27, 0.45); border: 1px solid #ef4444; color: #fca5a5;
    }
    .range-banner.pending {
      background: rgba(30, 41, 59, 0.7); border: 1px solid #475569; color: #cbd5e1;
    }

    /* Launch Button */
    .btn-launch {
      background: linear-gradient(135deg, #dc2626, #b91c1c); color: #fff;
      border: 1px solid #ef4444; border-radius: 8px; padding: 14px;
      font-size: 14px; font-weight: 800; letter-spacing: 0.5px; cursor: pointer;
      box-shadow: 0 4px 16px rgba(220, 38, 38, 0.5); transition: all 0.2s ease;
      display: flex; align-items: center; justify-content: center; gap: 8px;
```

```
    }
    .btn-launch:hover {
      background: linear-gradient(135deg, #ef4444, #dc2626);
      transform: translateY(-1px); box-shadow: 0 6px 22px rgba(220, 38, 38, 0.7);
    }
    .btn-launch:active {
      transform: translateY(1px);
    }

    /* Floating Pop-up Modal Boxes */
    .modal-overlay {
      position: absolute; top: 0; left: 0; right: 0; bottom: 0; z-index: 100;
      background: rgba(2, 6, 23, 0.70); backdrop-filter: blur(10px);
      display: flex; align-items: center; justify-content: center;
      opacity: 0; pointer-events: none; transition: opacity 0.25s ease;
    }
    .modal-overlay.active { opacity: 1; pointer-events: auto; }

    .modal-card {
      background: #0f172a; border: 1px solid #334155; border-radius: 14px;
      width: 760px; max-width: 92vw; max-height: 88vh; overflow-y: auto;
      box-shadow: 0 20px 60px rgba(0,0,0,0.85); padding: 22px;
      display: flex; flex-direction: column; gap: 16px; position: relative;
    }
    .modal-card::-webkit-scrollbar { width: 6px; }
    .modal-card::-webkit-scrollbar-thumb { background: #334155; border-radius: 4px; }

    .modal-header {
      display: flex; align-items: center; justify-content: space-between;
      border-bottom: 1px solid #1e293b; padding-bottom: 12px;
    }
    .modal-title { font-size: 17px; font-weight: 800; color: #fff; display: flex; align-items: center; gap: 8px; }
    .btn-close {
      background: transparent; border: none; color: #94a3b8; font-size: 20px;
      cursor: pointer; padding: 2px 6px; border-radius: 4px;
    }
    .btn-close:hover { color: #fff; background: #1e293b; }

    /* Impact Report Grid */
    .impact-badges {
      display: grid; grid-template-columns: repeat(3, 1fr); gap: 10px;
    }
    .stat-badge {
      background: #1e293b; border: 1px solid #334155; border-radius: 8px; padding: 10px;
      text-align: center;
    }
    .stat-badge-val { font-size: 18px; font-weight: 800; color: var(--accent-cyan); }
    .stat-badge-lbl { font-size: 11px; color: var(--text-muted); text-transform: uppercase; margin-top: 2px; }

    .radii-list { display: flex; flex-direction: column; gap: 8px; }
    .radius-item {
      display: flex; justify-content: space-between; align-items: center;
      padding: 8px 12px; border-radius: 6px; font-size: 12px; font-weight: 600;
    }
    .radius-fireball { background: rgba(255, 255, 255, 0.1); border-left: 4px solid #ffffff; }
    .radius-heavy { background: rgba(220, 38, 38, 0.2); border-left: 4px solid #dc2626; }
    .radius-moderate { background: rgba(239, 68, 68, 0.2); border-left: 4px solid #ef4444; }
    .radius-thermal { background: rgba(249, 115, 22, 0.2); border-left: 4px solid #f97316; }
    .radius-light { background: rgba(234, 179, 8, 0.2); border-left: 4px solid #eab308; }

    /* Chart Container inside Modal */
    .chart-container {
      background: #1e293b; border: 1px solid #334155; border-radius: 8px; padding: 12px;
    }
    .chart-title { font-size: 12px; font-weight: 700; color: #cbd5e1; margin-bottom: 8px; }
    .bar-row { margin-bottom: 8px; }
    .bar-label-row { display: flex; justify-content: space-between; font-size: 11px; font-weight: 600; margin-bottom: 3
px; }
    .bar-track { width: 100%; height: 12px; background: #0f172a; border-radius: 6px; overflow: hidden; }
    .bar-fill { height: 100%; border-radius: 6px; transition: width 0.8s ease-out; }
    .bar-fatalities { background: #dc2626; }
    .bar-injuries { background: #f59e0b; }
    .bar-structures { background: #64748b; }
```

```
    /* Missile Facts */
    .facts-box {
      background: rgba(30, 41, 59, 0.4); border: 1px solid #334155; border-radius: 8px;
      padding: 10px 14px; font-size: 12px; color: #cbd5e1; line-height: 1.5;
    }
    .facts-box li { margin-left: 16px; margin-bottom: 4px; }

    .modal-footer {
      display: flex; justify-content: flex-end; gap: 10px; border-top: 1px solid #1e293b; padding-top: 12px;
    }

    /* On-Screen Toast Alerts */
    .toast-overlay {
      position: absolute; top: 78px; left: 50%; transform: translateX(-50%); z-index: 200;
      background: rgba(15, 23, 42, 0.96); border: 1px solid var(--accent-gold);
      color: #fff; padding: 12px 22px; border-radius: 10px;
      box-shadow: 0 12px 36px rgba(0,0,0,0.85); display: none; align-items: center; gap: 12px;
      font-weight: 600; font-size: 13px; backdrop-filter: blur(8px);
      animation: fadeInDown 0.25s ease-out;
    }
    @keyframes fadeInDown {
      from { opacity: 0; transform: translate(-50%, -10px); }
      to { opacity: 1; transform: translate(-50%, 0); }
    }
  </style>
</head>
<body>
  <div id="cesiumContainer"></div>

  <!-- On-Screen Notification Toast -->
  <div id="toastNotification" class="toast-overlay">
    <span id="toastIcon" style="font-size: 20px;">⚠️</span>
    <span id="toastMsg">Notification message</span>
  </div>

  <!-- Top Navigation & Global Header -->
  <header class="top-header">
    <div class="brand">
      <span class="brand-icon">🎯</span>
      <div>
        <div>REAL-WORLD MISSILE IMPACT SIMULATOR</div>
        <div class="brand-sub">58 Global Missiles Database & Automatic Public Population Engine</div>
      </div>
    </div>
    <div class="header-actions">
      <button class="btn-header" onclick="openLoadScenarioModal()">📂 Load Scenario</button>
      <button class="btn-header" onclick="openSaveScenarioModal()">💾 Save Scenario</button>
      <button class="btn-header" onclick="resetAll()">🔄 Reset</button>
    </div>
  </header>

  <!-- Toggle HUD Panel Button -->
  <button id="btnPanelToggle" class="btn-panel-toggle" onclick="toggleControlPanel()">◀ Minimise HUD</button>

  <!-- Left Floating Control Panel Overlay (Huge Command Overlay) -->
  <aside class="control-panel" id="controlPanel">
    <!-- 1. Origin City -->
    <div class="panel-section">
      <div class="section-title title-origin">
        <span>1. Origin City (Launch Site)</span>
        <button id="btnPickOrigin" class="btn-mode-toggle active-origin" onclick="setPickMode('origin')">📍 Pick on Gl
obe</button>
      </div>
      <div class="input-row">
        <input
          type="text"
          id="originQuery"
          class="input-box"
          placeholder="Search launch city (e.g. New Delhi, Sonipat)..."
          oninput="onCityInput('origin')"
          onkeydown="if(event.key === 'Enter'){ event.preventDefault(); searchCity('origin'); }"
          autocomplete="off"
```

```
        />
        <button class="btn-search" onclick="searchCity('origin')" title="Search global cities">Search</button>
        <div id="originSuggestions" class="search-suggestions"></div>
      </div>
      <div class="selected-label" id="originLabel">Selected: None</div>
      <div class="selected-coords" id="originCoords">Click Earth to place Green Origin Pin (Drag to revolve without sel
ecting)</div>
    </div>

    <!-- 2. Destination City -->
    <div class="panel-section">
      <div class="section-title title-dest">
        <span>2. Destination City (Target)</span>
        <button id="btnPickDest" class="btn-mode-toggle" onclick="setPickMode('destination')">🎯 Pick on Globe</button
>
      </div>
      <div class="input-row">
        <input
          type="text"
          id="destQuery"
          class="input-box"
          placeholder="Search target city (e.g. Sonipat, Beijing, London)..."
          oninput="onCityInput('dest')"
          onkeydown="if(event.key === 'Enter'){ event.preventDefault(); searchCity('dest'); }"
          autocomplete="off"
        />
        <button class="btn-search" onclick="searchCity('dest')" title="Search global cities">Search</button>
        <div id="destSuggestions" class="search-suggestions"></div>
      </div>
      <div class="selected-label" id="destLabel">Selected: None</div>
      <div class="selected-coords" id="destCoords">Click inside Cyan Circle for Red Target Pin</div>
    </div>

    <!-- 3. Missile System Selection (50+ Database & Filters) -->
    <div class="panel-section">
      <div class="section-title title-config">
        <span>3. Missile System & Warhead</span>
        <span id="missileCountBadge" style="font-size: 10px; color: var(--accent-cyan);">58 Missiles</span>
      </div>

      <!-- Search & Filters -->
      <div class="input-row">
        <input type="text" id="missileSearchQuery" class="input-box" placeholder="Filter missiles (e.g. Agni, Hypersoni
c, Cruise)..." oninput="filterMissiles()" />
      </div>

      <div class="filter-grid">
        <div class="form-group">
          <label class="form-label">Country Filter</label>
          <select id="countryFilter" class="select-box" onchange="filterMissiles()"></select>
        </div>

        <div class="form-group">
          <label class="form-label">Warhead Type</label>
          <select id="warheadFilter" class="select-box" onchange="filterMissiles()"></select>
        </div>
      </div>

      <div class="form-group">
        <label class="form-label">Select Missile System</label>
        <select id="missileSelect" class="select-box" onchange="onMissileChanged()"></select>
      </div>

      <!-- Rich Missile Spec Card -->
      <div class="spec-card" id="specCard">
        <div class="spec-badges">
          <span class="badge badge-country" id="specCountry">India</span>
          <span class="badge badge-type" id="specType">ICBM</span>
          <span class="badge badge-nuke" id="specNukeBadge">☢ Nuclear Capable</span>
        </div>
        <div style="display: flex; justify-content: space-between; color: #cbd5e1; margin-bottom: 2px;">
          <span>Range Envelope:</span>
          <strong id="specRange" style="color: #fff;">1,500 km – 5,500 km</strong>
```

```
        </div>
        <div style="display: flex; justify-content: space-between; color: #cbd5e1;">
          <span>Cruising Speed:</span>
          <strong id="specSpeed" style="color: var(--accent-cyan);">Mach 24.0 (~29,400 km/h)</strong>
        </div>
      </div>

      <!-- Warhead Configuration -->
      <div class="toggle-row" id="nuclearToggleRow">
        <span id="nukeToggleText">Equip Nuclear Warhead</span>
        <label class="toggle-switch">
          <input type="checkbox" id="nuclearToggle" checked onchange="onNuclearToggled()" />
          <span class="slider"></span>
        </label>
      </div>
      <div id="convNotice" style="display: none; font-size: 11px; color: var(--accent-gold); margin-bottom: 6px; font-w
eight: 600;">
        💥 Conventional-Only Weapon System (Fixed High-Explosive Warhead)
      </div>

      <div class="form-group" id="yieldGroup">
        <label class="form-label">Nuclear Yield (kt TNT)</label>
        <select id="yieldSelect" class="select-box">
          <option value="1">1 kt (Tactical Mini-Nuke)</option>
          <option value="10">10 kt (Tactical / BrahMos Nuclear)</option>
          <option value="15">15 kt (Hiroshima Little Boy Benchmark)</option>
          <option value="40">40 kt (Agni-IV Standard Yield)</option>
          <option value="100">100 kt (Strategic Thermonuclear)</option>
          <option value="250" selected>250 kt (Agni-V Standard Yield)</option>
          <option value="335">335 kt (W78 Minuteman III)</option>
          <option value="500">500 kt (RS-24 Yars / High-Yield)</option>
          <option value="1000">1,000 kt (1 Megaton City-Buster)</option>
        </select>
      </div>

      <!-- Automatic Public Database Population Indicator (No manual density prompt!) -->
      <div class="form-group">
        <label class="form-label">Target Urban Population (Live Public Database / Wi-Fi)</label>
        <div id="targetPopLive" style="font-size: 11px; color: var(--accent-cyan); font-weight: 600; padding: 7px 10px;
background: #0f172a; border: 1px solid #334155; border-radius: 6px; line-height: 1.4;">
          Auto-queried via OpenDataSoft / GeoNames & OSM when target is selected
        </div>
      </div>
    </div>

    <!-- 4. Range Status Banner -->
    <div id="rangeBanner" class="range-banner pending">
      <span>ℹ</span>
      <span>Select Origin and Target on the 3D globe or search above.</span>
    </div>

    <!-- 5. Big Launch Button -->
    <button id="btnLaunch" class="btn-launch" onclick="launchSimulation()">
      <span>🚀</span>
      <span>SIMULATE LAUNCH & IMPACT</span>
    </button>
  </aside>

  <!-- Post-Impact Assessment Pop-Up Modal -->
  <div class="modal-overlay" id="impactModal">
    <div class="modal-card">
      <div class="modal-header">
        <div class="modal-title">
          <span>💥</span>
          <span id="modalReportTitle">Post-Impact Simulation Assessment</span>
        </div>
        <button class="btn-close" onclick="closeModal('impactModal')">✕</button>
      </div>

      <!-- Quick Metrics Badges -->
      <div class="impact-badges">
        <div class="stat-badge">
          <div class="stat-badge-val" id="statFlightTime">-- min</div>
```

```
          <div class="stat-badge-lbl">Est. Flight Duration</div>
        </div>
        <div class="stat-badge">
          <div class="stat-badge-val" id="statDistance">-- km</div>
          <div class="stat-badge-lbl">Impact Distance</div>
        </div>
        <div class="stat-badge">
          <div class="stat-badge-val" id="statWarhead">--</div>
          <div class="stat-badge-lbl">Warhead Mode</div>
        </div>
      </div>

      <!-- Real-World Population Source Card -->
      <div style="background: rgba(30, 41, 59, 0.5); border: 1px solid #334155; border-radius: 8px; padding: 10px 14px;
font-size: 12px;">
        <div style="display: flex; justify-content: space-between; align-items: center;">
          <span style="font-weight: 700; color: #fff;">🌍 Target Urban Population & Database Source</span>
          <span style="font-size: 10px; color: var(--accent-cyan);" id="modalPopSource">Open Database (Live Wi-Fi)</spa
n>
        </div>
        <div style="display: flex; justify-content: space-between; margin-top: 4px; color: #cbd5e1;">
          <span>Target Area: <b id="modalTargetCity" style="color: #fff;">--</b></span>
          <span>Verified Population: <b id="modalCityPop" style="color: var(--accent-cyan);">--</b></span>
        </div>
      </div>

      <!-- Concentric Blast Radii Breakdown -->
      <div style="font-size: 13px; font-weight: 700; color: #fff;">Concentric Blast & Thermal Radii (Glasstone-Dolan Ph
ysics)</div>
      <div class="radii-list">
        <div class="radius-item radius-fireball">
          <span>🔥 Fireball Vaporization Zone</span>
          <span id="radFireball">-- km</span>
        </div>
        <div class="radius-item radius-heavy">
          <span>💣 Heavy Blast Radius (20 psi Complete Destruction)</span>
          <span id="radHeavy">-- km</span>
        </div>
        <div class="radius-item radius-moderate">
          <span>🏢 Moderate Blast Radius (5 psi Structural Collapse)</span>
          <span id="radModerate">-- km</span>
        </div>
        <div class="radius-item radius-thermal">
          <span>☢ Thermal Radiation (3rd-Degree Burns)</span>
          <span id="radThermal">-- km</span>
        </div>
        <div class="radius-item radius-light">
          <span>🪟 Light Blast Radius (1 psi Window Breakage)</span>
          <span id="radLight">-- km</span>
        </div>
      </div>

      <!-- Casualty & Destruction Chart -->
      <div class="chart-container">
        <div class="chart-title">Estimated Humanitarian & Structural Casualties</div>

        <div class="bar-row">
          <div class="bar-label-row">
            <span style="color: #fca5a5;">Estimated Fatalities</span>
            <span id="valFatalities" style="color: #fca5a5;">--</span>
          </div>
          <div class="bar-track"><div id="barFatalities" class="bar-fill bar-fatalities" style="width: 0%;"></div></div
>
        </div>

        <div class="bar-row">
          <div class="bar-label-row">
            <span style="color: #fcd34d;">Estimated Injuries</span>
            <span id="valInjuries" style="color: #fcd34d;">--</span>
          </div>
          <div class="bar-track"><div id="barInjuries" class="bar-fill bar-injuries" style="width: 0%;"></div></div>
        </div>
```

```
        <div class="bar-row">
          <div class="bar-label-row">
            <span style="color: #94a3b8;">Buildings / Structures Destroyed</span>
            <span id="valStructures" style="color: #94a3b8;">--</span>
          </div>
          <div class="bar-track"><div id="barStructures" class="bar-fill bar-structures" style="width: 0%;"></div></div
>
        </div>
      </div>

      <!-- Missile Facts -->
      <div style="font-size: 13px; font-weight: 700; color: #fff;">Missile Technical Specifications & Field Facts</div>
      <div class="facts-box">
        <ul id="factsList"></ul>
      </div>

      <div class="modal-footer">
        <button class="btn-header" style="background: #2563eb; color: #fff; border: none; padding: 10px 18px;" onclick
="closeModal('impactModal')">
          🔍 Inspect 3D Blast Rings on Globe
        </button>
      </div>
    </div>
  </div>

  <!-- Out-of-Range Warning Modal -->
  <div class="modal-overlay" id="outOfRangeModal">
    <div class="modal-card" style="width: 500px; border-color: #ef4444;">
      <div class="modal-header">
        <div class="modal-title" style="color: #fca5a5;">
          <span>⛔</span>
          <span>Target Outside Missile Operational Range</span>
        </div>
        <button class="btn-close" onclick="closeModal('outOfRangeModal')">✕</button>
      </div>
      <div style="font-size: 13px; line-height: 1.6; color: #e2e8f0;" id="outOfRangeMsg">
        The destination is too far for the selected missile system.
      </div>
      <div class="modal-footer">
        <button class="btn-header" style="background: #2563eb; color: #fff; border: none;" onclick="closeModal('outOfRa
ngeModal')">
          Understood
        </button>
      </div>
    </div>
  </div>

  <!-- Save Scenario Modal -->
  <div class="modal-overlay" id="saveModal">
    <div class="modal-card" style="width: 440px;">
      <div class="modal-header">
        <div class="modal-title">💾 Save Simulation Scenario</div>
        <button class="btn-close" onclick="closeModal('saveModal')">✕</button>
      </div>
      <div class="form-group">
        <label class="form-label">Scenario Name</label>
        <input type="text" id="scenarioNameInput" class="input-box" placeholder="e.g. Agni-V Delhi to Beijing Test" />
      </div>
      <div class="modal-footer">
        <button class="btn-header" onclick="closeModal('saveModal')">Cancel</button>
        <button class="btn-header" style="background: #2563eb; color: #fff; border: none;" onclick="confirmSaveScenario
()">Save to Database</button>
      </div>
    </div>
  </div>

  <!-- Load Scenario Modal -->
  <div class="modal-overlay" id="loadModal">
    <div class="modal-card" style="width: 580px;">
      <div class="modal-header">
        <div class="modal-title">📂 Load Saved Scenarios</div>
        <button class="btn-close" onclick="closeModal('loadModal')">✕</button>
      </div>
```

```
      <div id="savedScenariosList" style="display: flex; flex-direction: column; gap: 8px; max-height: 350px; overflow-
y: auto;">
        <!-- Scenarios injected via JS -->
      </div>
      <div class="modal-footer">
        <button class="btn-header" onclick="closeModal('loadModal')">Close</button>
      </div>
    </div>
  </div>

  <script>
    // Initialize Cesium 3D Globe
    Cesium.Ion.defaultAccessToken = "";
    const esriProvider = new Cesium.UrlTemplateImageryProvider({
      url: "https://services.arcgisonline.com/ArcGIS/rest/services/World_Imagery/MapServer/tile/{z}/{y}/{x}",
      credit: "Esri, Maxar, Earthstar Geographics"
    });

    let viewer;
    try {
      viewer = new Cesium.Viewer("cesiumContainer", {
        baseLayer: new Cesium.ImageryLayer(esriProvider),
        baseLayerPicker: false,
        geocoder: false,
        timeline: false,
        animation: false,
        sceneModePicker: true,
        navigationHelpButton: false
      });
    } catch (e) {
      viewer = new Cesium.Viewer("cesiumContainer", {
        imageryProvider: esriProvider,
        baseLayerPicker: false,
        geocoder: false,
        timeline: false,
        animation: false,
        sceneModePicker: true,
        navigationHelpButton: false
      });
    }

    // Application State
    let missiles = [];
    let filteredMissiles = [];
    let selectedMissile = null;
    let originPlace = null;
    let destPlace = null;
    let pickMode = "origin";
    let inRange = false;
    let currentDistance = 0;
    let lastImpactData = null;

    // Mouse Tracking State: Distinguish between Revolving Drag vs Stationary Click
    let mouseDownPos = null;
    let isDraggingPin = false;
    let pinDraggedRole = null;

    // Helper: Python API abstraction
    async function callPython(method, ...args) {
      if (window.pywebview && window.pywebview.api && typeof window.pywebview.api[method] === "function") {
        return await window.pywebview.api[method](...args);
      }
      try {
        const res = await fetch(`/api/${method}`, {
          method: "POST",
          headers: { "Content-Type": "application/json" },
          body: JSON.stringify(args)
        });
        return await res.json();
      } catch (err) {
        console.warn(`callPython failed for ${method}:`, err);
        return null;
      }
```

```
    }

    function showToast(title, message) {
      const toast = document.getElementById("toastNotification");
      document.getElementById("toastIcon").textContent = title.includes("⚠️") ? "⚠️" : (title.includes("❌") ? "❌" :
"ℹ️");
      document.getElementById("toastMsg").innerHTML = `<b>${title}:</b> ${message}`;
      toast.style.display = "flex";
      setTimeout(() => {
        toast.style.display = "none";
      }, 4500);
    }

    function showOutOfRangeModal(distKm, maxRangeKm, missileName) {
      document.getElementById("outOfRangeMsg").innerHTML = `
        <div style="margin-bottom: 10px;">The target is currently <b>${distKm.toLocaleString()} km</b> away.</div>
        <div style="margin-bottom: 10px; color: #fca5a5;">
          This exceeds <b>${missileName}</b>'s maximum operational range of <b>${maxRangeKm.toLocaleString()} km</b>.
        </div>
        <div style="font-size: 12px; color: #94a3b8; background: #1e293b; padding: 10px; border-radius: 6px;">
          💡 <b>Recommended Actions:</b>
          <ul style="margin-left: 20px; margin-top: 6px;">
            <li>Click or drag the Red Target pin inside the <b>Cyan Range Circle</b>.</li>
            <li>Or switch to an intercontinental missile (such as <b>Agni-V</b>, <b>Minuteman III</b>, or <b>RS-28 Sarm
at</b>).</li>
          </ul>
        </div>
      `;
      openModal("outOfRangeModal");
    }

    function toggleControlPanel() {
      const panel = document.getElementById("controlPanel");
      const btn = document.getElementById("btnPanelToggle");
      panel.classList.toggle("collapsed");
      btn.classList.toggle("collapsed");
      if (panel.classList.contains("collapsed")) {
        btn.textContent = "▶ Expand HUD";
      } else {
        btn.textContent = "◀ Minimise HUD";
      }
    }

    // Initialize application on load
    async function initApp() {
      const missileList = await callPython("get_missiles");
      if (missileList && missileList.length) {
        missiles = missileList;
      }

      // Dynamically populate country filter
      const countryCounts = {};
      missiles.forEach((m) => {
        countryCounts[m.country] = (countryCounts[m.country] || 0) + 1;
      });
      const cSel = document.getElementById("countryFilter");
      cSel.innerHTML = `<option value="ALL">All Countries (${missiles.length})</option>`;
      Object.keys(countryCounts).sort().forEach((c) => {
        const opt = document.createElement("option");
        opt.value = c;
        opt.textContent = `${c} (${countryCounts[c]})`;
        cSel.appendChild(opt);
      });

      // Dynamically populate warhead filter
      const nukeCount = missiles.filter((m) => m.nuclear_capable).length;
      const convCount = missiles.length - nukeCount;
      const wSel = document.getElementById("warheadFilter");
      wSel.innerHTML = `
        <option value="ALL">All Warhead Types (${missiles.length})</option>
        <option value="NUCLEAR">☢ Nuclear-Capable (${nukeCount})</option>
        <option value="CONVENTIONAL">💥 Conventional-Only (${convCount})</option>
      `;
```

```
      filterMissiles();

      // Set default Origin to New Delhi
      setOrigin({
        label: "New Delhi, India",
        longitude: 77.2090,
        latitude: 28.6139,
        attribution: "Default"
      });
    }

    // Filter missiles by search query, country, and warhead
    function filterMissiles() {
      const query = (document.getElementById("missileSearchQuery").value || "").trim().toLowerCase();
      const country = document.getElementById("countryFilter").value;
      const warhead = document.getElementById("warheadFilter").value;

      filteredMissiles = missiles.filter((m) => {
        if (country !== "ALL" && m.country !== country) return false;
        if (warhead === "NUCLEAR" && !m.nuclear_capable) return false;
        if (warhead === "CONVENTIONAL" && m.nuclear_capable) return false;
        if (query) {
          const matchName = m.name.toLowerCase().includes(query);
          const matchType = m.type.toLowerCase().includes(query);
          const matchCountry = m.country.toLowerCase().includes(query);
          if (!matchName && !matchType && !matchCountry) return false;
        }
        return true;
      });

      document.getElementById("missileCountBadge").textContent = `${filteredMissiles.length} of ${missiles.length} Miss
iles`;

      const sel = document.getElementById("missileSelect");
      sel.innerHTML = "";

      const groups = {};
      filteredMissiles.forEach((m) => {
        if (!groups[m.country]) groups[m.country] = [];
        groups[m.country].push(m);
      });

      for (const [cName, list] of Object.entries(groups)) {
        const optgroup = document.createElement("optgroup");
        optgroup.label = `── ${cName} (${list.length}) ──`;
        list.forEach((m) => {
          const opt = document.createElement("option");
          opt.value = m.id;
          const nukeSymbol = m.nuclear_capable ? "☢" : "💥";
          opt.textContent = `${nukeSymbol} ${m.name} — ${m.max_range_km.toLocaleString()} km (Mach ${m.speed_mach})`;
          optgroup.appendChild(opt);
        });
        sel.appendChild(optgroup);
      }

      if (filteredMissiles.length > 0) {
        sel.value = filteredMissiles[0].id;
        selectedMissile = filteredMissiles[0];
      } else {
        selectedMissile = missiles[0];
      }
      onMissileChanged();
    }

    function setPickMode(mode) {
      pickMode = mode;
      document.getElementById("btnPickOrigin").className =
        "btn-mode-toggle" + (mode === "origin" ? " active-origin" : "");
      document.getElementById("btnPickDest").className =
        "btn-mode-toggle" + (mode === "destination" ? " active-dest" : "");
    }
```

```
    function onMissileChanged() {
      const id = document.getElementById("missileSelect").value;
      selectedMissile = missiles.find((m) => m.id === id) || filteredMissiles[0] || missiles[0];

      // Update Spec Card
      document.getElementById("specCountry").textContent = selectedMissile.country;
      document.getElementById("specType").textContent = selectedMissile.type;
      document.getElementById("specRange").textContent = `${(selectedMissile.min_range_km || 0).toLocaleString()} km –
${selectedMissile.max_range_km.toLocaleString()} km`;
      document.getElementById("specSpeed").textContent = `Mach ${selectedMissile.speed_mach} (~${Math.round(selectedMis
sile.speed_mach * 1225).toLocaleString()} km/h)`;

      const nukeBadge = document.getElementById("specNukeBadge");
      const nukeToggle = document.getElementById("nuclearToggle");
      const nukeToggleRow = document.getElementById("nuclearToggleRow");
      const convNotice = document.getElementById("convNotice");

      if (!selectedMissile.nuclear_capable) {
        nukeBadge.className = "badge badge-conv";
        nukeBadge.textContent = "✴ Conventional-Only";
        nukeToggle.checked = false;
        nukeToggleRow.style.display = "none";
        convNotice.style.display = "block";
      } else {
        nukeBadge.className = "badge badge-nuke";
        nukeBadge.textContent = `☢ Nuclear Capable (Default ${selectedMissile.default_nuclear_yield_kt} kt)`;
        nukeToggle.checked = true;
        nukeToggleRow.style.display = "flex";
        convNotice.style.display = "none";
        document.getElementById("yieldSelect").value = String(selectedMissile.default_nuclear_yield_kt || 250);
      }

      onNuclearToggled();
      updateRangeCheck();
      renderGlobeEntities();
    }

    function onNuclearToggled() {
      const isNuke = document.getElementById("nuclearToggle").checked && selectedMissile.nuclear_capable;
      document.getElementById("yieldGroup").style.display = isNuke ? "flex" : "none";
    }

    // Coordinates conversion
    function cartesianToLonLat(cartesian) {
      if (!cartesian) return null;
      const carto = Cesium.Cartographic.fromCartesian(cartesian);
      return {
        lon: Cesium.Math.toDegrees(carto.longitude),
        lat: Cesium.Math.toDegrees(carto.latitude)
      };
    }

    // Cesium Mouse Events: Differentiate Revolving the Globe vs Clicking to Select
    const handler = new Cesium.ScreenSpaceEventHandler(viewer.scene.canvas);

    handler.setInputAction((movement) => {
      mouseDownPos = Cesium.Cartesian2.clone(movement.position);
      isDraggingPin = false;
      pinDraggedRole = null;

      // Check if clicking directly on an existing pin to drag it
      const picked = viewer.scene.pick(movement.position);
      if (Cesium.defined(picked) && picked.id && (picked.id.id === "origin_pin" || picked.id.id === "dest_pin")) {
        isDraggingPin = true;
        pinDraggedRole = picked.id.id === "origin_pin" ? "origin" : "destination";
        viewer.scene.screenSpaceCameraController.enableRotate = false;
      }
    }, Cesium.ScreenSpaceEventType.LEFT_DOWN);

    handler.setInputAction((movement) => {
      if (isDraggingPin && pinDraggedRole) {
        const ray = viewer.camera.getPickRay(movement.endPosition);
        const cartesian = viewer.scene.globe.pick(ray, viewer.scene);
```

```
        const coords = cartesianToLonLat(cartesian);
        if (coords) {
          const entityId = pinDraggedRole === "origin" ? "origin_pin" : "dest_pin";
          const entity = viewer.entities.getById(entityId);
          if (entity) {
            entity.position = Cesium.Cartesian3.fromDegrees(coords.lon, coords.lat);
          }
        }
      }
    }, Cesium.ScreenSpaceEventType.MOUSE_MOVE);

    handler.setInputAction((movement) => {
      // 1. If we were dragging an existing pin
      if (isDraggingPin && pinDraggedRole) {
        const role = pinDraggedRole;
        isDraggingPin = false;
        pinDraggedRole = null;
        viewer.scene.screenSpaceCameraController.enableRotate = true;
        const ray = viewer.camera.getPickRay(movement.position);
        const cartesian = viewer.scene.globe.pick(ray, viewer.scene);
        const coords = cartesianToLonLat(cartesian);
        if (coords) {
          handleGlobeClick(role, coords.lon, coords.lat);
        }
        mouseDownPos = null;
        return;
      }

      // 2. If we were clicking on the globe (Check if user revolved or just clicked)
      if (mouseDownPos) {
        const distMoved = Cesium.Cartesian2.distance(mouseDownPos, movement.position);
        mouseDownPos = null;

        // If mouse moved >= 6 pixels, the user was revolving the Earth! Do NOT place any pin!
        if (distMoved >= 6) {
          return;
        }

        // Mouse moved < 6 pixels: This was a deliberate click & release!
        const ray = viewer.camera.getPickRay(movement.position);
        const cartesian = viewer.scene.globe.pick(ray, viewer.scene);
        const coords = cartesianToLonLat(cartesian);
        if (coords) {
          handleGlobeClick(pickMode, coords.lon, coords.lat);
          if (pickMode === "origin") setPickMode("destination");
        }
      }
    }, Cesium.ScreenSpaceEventType.LEFT_UP);

    async function handleGlobeClick(role, lon, lat) {
      const res = await callPython("reverse_geocode", lon, lat);
      const place = res || {
        label: `Point (${lat.toFixed(3)}°, ${lon.toFixed(3)}°)`,
        longitude: lon,
        latitude: lat
      };
      if (role === "origin") {
        setOrigin(place);
      } else {
        setDestination(place);
      }
    }

    function setOrigin(place) {
      originPlace = place;
      document.getElementById("originLabel").textContent = `Selected: ${place.label}`;
      document.getElementById("originCoords").textContent = `Lon: ${place.longitude.toFixed(4)}° | Lat: ${place.latitud
e.toFixed(4)}°`;
      document.getElementById("originQuery").value = place.label;
      updateRangeCheck();
      renderGlobeEntities();
    }
```

```
    async function setDestination(place) {
      destPlace = place;
      document.getElementById("destLabel").textContent = `Selected: ${place.label}`;
      document.getElementById("destCoords").textContent = `Lon: ${place.longitude.toFixed(4)}° | Lat: ${place.latitude.
toFixed(4)}°`;
      document.getElementById("destQuery").value = place.label;

      // Auto-query live population from open database over Wi-Fi
      const popBox = document.getElementById("targetPopLive");
      if (popBox) {
        popBox.innerHTML = "<span>⌛</span> <span>Querying OpenDataSoft / GeoNames & OSM over Wi-Fi...</span>";
        callPython("get_population", place.longitude, place.latitude, place.label).then((pop) => {
          if (pop && pop.population !== undefined) {
            popBox.innerHTML = `
              <div style="font-size: 12px; color: #fff; font-weight: 700;">🌍 ${pop.place_name} (${pop.country})</div>
              <div style="color: var(--accent-cyan); font-weight: 600; margin-top: 2px;">
                Verified Population: <b>${pop.population.toLocaleString()}</b> &bull; Density: <b>${Math.round(pop.dens
ity_per_km2).toLocaleString()}/km²</b>
              </div>
              <div style="font-size: 10px; color: #94a3b8; margin-top: 2px;">Database: ${pop.data_source}</div>
            `;
          }
        });
      }

      updateRangeCheck();
      renderGlobeEntities();
    }

    // Great circle calculation (Haversine)
    function calculateDistance(lon1, lat1, lon2, lat2) {
      const R = 6371.0088;
      const dLat = (lat2 - lat1) * Math.PI / 180;
      const dLon = (lon2 - lon1) * Math.PI / 180;
      const a = Math.sin(dLat/2) * Math.sin(dLat/2) +
                Math.cos(lat1 * Math.PI / 180) * Math.cos(lat2 * Math.PI / 180) *
                Math.sin(dLon/2) * Math.sin(dLon/2);
      const c = 2 * Math.atan2(Math.sqrt(a), Math.sqrt(1 - a));
      return Math.round(R * c * 10) / 10;
    }

    function updateRangeCheck() {
      const banner = document.getElementById("rangeBanner");

      if (!originPlace || !destPlace) {
        banner.className = "range-banner pending";
        banner.innerHTML = "<span>ℹ</span><span>Select Origin and Target on the 3D globe or search above.</span>";
        inRange = true;
        return;
      }

      currentDistance = calculateDistance(
        originPlace.longitude, originPlace.latitude,
        destPlace.longitude, destPlace.latitude
      );

      const maxRange = selectedMissile.max_range_km;
      if (currentDistance > maxRange) {
        inRange = false;
        banner.className = "range-banner out-range";
        banner.innerHTML = `<span>⛔</span><span>OUT OF RANGE: Distance is <b>${currentDistance.toLocaleString()} km</
b> (Max: ${maxRange.toLocaleString()} km). Launch locked!</span>`;
      } else {
        inRange = true;
        banner.className = "range-banner in-range";
        banner.innerHTML = `<span>✓</span><span>TARGET IN RANGE: <b>${currentDistance.toLocaleString()} km</b> / ${max
Range.toLocaleString()} km (${selectedMissile.name})</span>`;
      }
    }

    // 3D Globe Render Entities
    function renderGlobeEntities(launched = false, impact = null) {
      viewer.entities.removeAll();
```

```
    if (originPlace) {
      viewer.entities.add({
        id: "origin_pin",
        position: Cesium.Cartesian3.fromDegrees(originPlace.longitude, originPlace.latitude),
        point: { pixelSize: 14, color: Cesium.Color.LIMEGREEN, outlineColor: Cesium.Color.WHITE, outlineWidth: 2 },
        label: {
          text: "ORIGIN: " + originPlace.label,
          font: "bold 13px Segoe UI",
          fillColor: Cesium.Color.LIMEGREEN,
          style: Cesium.LabelStyle.FILL_AND_OUTLINE,
          outlineWidth: 3,
          verticalOrigin: Cesium.VerticalOrigin.BOTTOM,
          pixelOffset: new Cesium.Cartesian2(0, -16)
        }
      });

      // Max range cyan circle
      if (selectedMissile && selectedMissile.max_range_km) {
        const visualRadius = Math.min(selectedMissile.max_range_km, 9500) * 1000.0;
        viewer.entities.add({
          position: Cesium.Cartesian3.fromDegrees(originPlace.longitude, originPlace.latitude),
          ellipse: {
            semiMajorAxis: visualRadius,
            semiMinorAxis: visualRadius,
            material: Cesium.Color.DEEPSKYBLUE.withAlpha(0.12),
            outline: true,
            outlineColor: Cesium.Color.CYAN,
            outlineWidth: 2,
            height: 0
          }
        });
      }
    }

    if (destPlace) {
      const pinColor = inRange ? Cesium.Color.ORANGERED : Cesium.Color.RED;
      const prefix = inRange ? "TARGET: " : "OUT OF RANGE: ";
      viewer.entities.add({
        id: "dest_pin",
        position: Cesium.Cartesian3.fromDegrees(destPlace.longitude, destPlace.latitude),
        point: { pixelSize: 14, color: pinColor, outlineColor: Cesium.Color.WHITE, outlineWidth: 2 },
        label: {
          text: prefix + destPlace.label,
          font: "bold 13px Segoe UI",
          fillColor: pinColor,
          style: Cesium.LabelStyle.FILL_AND_OUTLINE,
          outlineWidth: 3,
          verticalOrigin: Cesium.VerticalOrigin.BOTTOM,
          pixelOffset: new Cesium.Cartesian2(0, -16)
        }
      });
    }

    if (originPlace && destPlace) {
      const lineColor = inRange ? (launched ? Cesium.Color.GOLD : Cesium.Color.CYAN) : Cesium.Color.RED;
      viewer.entities.add({
        polyline: {
          positions: Cesium.Cartesian3.fromDegreesArray([
            originPlace.longitude, originPlace.latitude,
            destPlace.longitude, destPlace.latitude
          ]),
          width: launched ? 4 : 3,
          material: new Cesium.PolylineGlowMaterialProperty({
            glowPower: 0.3,
            color: lineColor
          }),
          clampToGround: false
        }
      });
    }

    // Render concentric blast rings upon impact
```

```
      if (launched && impact && destPlace) {
        const r = impact.radii_km;
        const rings = [
          { km: r.light_blast_1psi_km, color: Cesium.Color.YELLOW.withAlpha(0.20), border: Cesium.Color.YELLOW },
          { km: r.thermal_3rd_deg_km, color: Cesium.Color.DARKORANGE.withAlpha(0.28), border: Cesium.Color.ORANGE },
          { km: r.moderate_blast_5psi_km, color: Cesium.Color.RED.withAlpha(0.35), border: Cesium.Color.RED },
          { km: r.heavy_blast_20psi_km, color: Cesium.Color.DARKRED.withAlpha(0.50), border: Cesium.Color.CRIMSON },
          { km: r.fireball_km, color: Cesium.Color.WHITE.withAlpha(0.85), border: Cesium.Color.WHITE }
        ];

        rings.forEach((ring) => {
          if (ring.km > 0) {
            viewer.entities.add({
              position: Cesium.Cartesian3.fromDegrees(destPlace.longitude, destPlace.latitude),
              ellipse: {
                semiMajorAxis: ring.km * 1000.0,
                semiMinorAxis: ring.km * 1000.0,
                material: ring.color,
                outline: true,
                outlineColor: ring.border,
                height: 0
              }
            });
          }
        });

        // Smooth camera fly-to
        viewer.camera.flyTo({
          destination: Cesium.Cartesian3.fromDegrees(
            destPlace.longitude,
            destPlace.latitude,
            Math.max(r.light_blast_1psi_km * 6500, 30000)
          ),
          duration: 1.8
        });
      }
    }

    // City Search & Autocomplete Dropdown
    function normalizeRole(role) {
      return (role === "destination" || role === "dest") ? "dest" : "origin";
    }

    let searchTimeout = null;
    function onCityInput(role) {
      clearTimeout(searchTimeout);
      const prefix = normalizeRole(role);
      const input = document.getElementById(prefix + "Query") || document.getElementById(role + "Query");
      const suggestions = document.getElementById(prefix + "Suggestions") || document.getElementById(role + "Suggestion
s");
      if (!input || !suggestions) return;

      const query = input.value.trim();
      if (query.length < 2) {
        suggestions.style.display = "none";
        return;
      }
      searchTimeout = setTimeout(() => searchCity(prefix), 350);
    }

    async function searchCity(role) {
      const prefix = normalizeRole(role);
      const input = document.getElementById(prefix + "Query") || document.getElementById(role + "Query");
      const suggestions = document.getElementById(prefix + "Suggestions") || document.getElementById(role + "Suggestion
s");
      if (!input || !suggestions) return;

      const query = input.value.trim();
      if (!query) {
        suggestions.style.display = "none";
        return;
      }
```

```
      suggestions.innerHTML = `
        <div class="suggestion-status" style="color: var(--accent-cyan);">
          <div style="font-weight: 700;">⏳ Searching global database for "${query}"...</div>
          <div style="font-size: 10px; color: #94a3b8; margin-top: 3px;">Querying OpenStreetMap / GeoNames over Wi-Fi</
div>
        </div>
      `;
      suggestions.style.display = "block";

      try {
        const res = await callPython("search_city", query);
        if (res && res.success && res.candidates && res.candidates.length > 0) {
          suggestions.innerHTML = "";
          res.candidates.forEach((c) => {
            const item = document.createElement("div");
            item.className = "suggestion-item";
            item.innerHTML = `
              <div class="suggestion-header">
                <span class="sugg-name">📍 ${c.label}</span>
                <span class="sugg-badge">${c.attribution || "Global"}</span>
              </div>
              <div class="sugg-coords">
                <span>Lat: <b>${c.latitude.toFixed(4)}°</b></span>
                <span>Lon: <b>${c.longitude.toFixed(4)}°</b></span>
              </div>
            `;
            item.onmousedown = (e) => {
              e.preventDefault();
              suggestions.style.display = "none";
              if (prefix === "origin") {
                setOrigin(c);
              } else {
                setDestination(c);
              }
              if (viewer && viewer.camera) {
                viewer.camera.flyTo({
                  destination: Cesium.Cartesian3.fromDegrees(c.longitude, c.latitude, 350000.0),
                  duration: 1.5
                });
              }
            };
            suggestions.appendChild(item);
          });
          suggestions.style.display = "block";
        } else {
          const errText = (res && res.error) ? res.error : `No matching cities found for "${query}".`;
          suggestions.innerHTML = `
            <div class="suggestion-status" style="color: #fca5a5;">
              <div style="font-weight: 700;">⚠️ ${errText}</div>
              <div style="font-size: 10px; color: #cbd5e1; margin-top: 4px;">Try searching by alternative spelling, dis
trict, or country.</div>
            </div>
          `;
          suggestions.style.display = "block";
        }
      } catch (err) {
        suggestions.innerHTML = `
          <div class="suggestion-status" style="color: #fca5a5;">
            <div style="font-weight: 700;">⚠️ Geocoding search failed</div>
            <div style="font-size: 10px; color: #cbd5e1; margin-top: 4px;">${err}</div>
          </div>
        `;
        suggestions.style.display = "block";
      }
    }

    // Simulate Launch & Impact
    async function launchSimulation() {
      if (!originPlace || !destPlace) {
        showToast("⚠️ Target Required", "Please click on the 3D Earth (or search a city) to set the Target Point befor
e launching.");
        return;
      }
```

```
      if (!inRange) {
        showOutOfRangeModal(currentDistance, selectedMissile.max_range_km, selectedMissile.name);
        return;
      }

      const btn = document.getElementById("btnLaunch");
      const originalText = btn.innerHTML;
      btn.innerHTML = '<span>🚀</span><span>FETCHING POPULATION & SIMULATING...</span>';

      const isNuclear = document.getElementById("nuclearToggle").checked && selectedMissile.nuclear_capable;
      const yieldKt = parseFloat(document.getElementById("yieldSelect").value || selectedMissile.default_nuclear_yield_
kt || 250);

      try {
        const res = await callPython(
          "simulate_launch",
          originPlace,
          destPlace,
          selectedMissile.id,
          isNuclear,
          yieldKt
        );

        if (res && res.success) {
          lastImpactData = res.impact;
          renderGlobeEntities(true, res.impact);
          displayImpactModal(res.impact, res.distance_km, res.population_info);
        } else {
          showToast("❌ Simulation Notice", (res && res.error) || "Simulation calculation could not be completed.");
        }
      } catch (err) {
        showToast("❌ Error", "Simulation failed: " + err);
      } finally {
        btn.innerHTML = originalText;
      }
    }

    function displayImpactModal(impact, distKm, popInfo) {
      const r = impact.radii_km;
      const est = impact.estimates;

      document.getElementById("modalReportTitle").textContent =
        `Post-Impact Assessment: ${selectedMissile.name} (${selectedMissile.country}) → ${destPlace.label}`;

      document.getElementById("statFlightTime").textContent = `~${impact.flight_time_min} min`;
      document.getElementById("statDistance").textContent = `${distKm.toLocaleString()} km`;
      document.getElementById("statWarhead").textContent = impact.warhead_mode;

      // Real Population Metrics
      if (popInfo) {
        document.getElementById("modalPopSource").textContent = popInfo.data_source || "Open Data";
        document.getElementById("modalTargetCity").textContent = `${popInfo.place_name} (${popInfo.country})`;
        document.getElementById("modalCityPop").textContent = `${popInfo.population.toLocaleString()} people (Density:
${Math.round(popInfo.density_per_km2).toLocaleString()}/km²)`;
      } else {
        document.getElementById("modalTargetCity").textContent = destPlace.label;
        document.getElementById("modalCityPop").textContent = "Auto-Calculated";
      }

      document.getElementById("radFireball").textContent = `${(r.fireball_km * 1000).toLocaleString()} m (${r.fireball_
km} km)`;
      document.getElementById("radHeavy").textContent = `${r.heavy_blast_20psi_km} km`;
      document.getElementById("radModerate").textContent = `${r.moderate_blast_5psi_km} km`;
      document.getElementById("radThermal").textContent = `${r.thermal_3rd_deg_km} km`;
      document.getElementById("radLight").textContent = `${r.light_blast_1psi_km} km`;

      document.getElementById("valFatalities").textContent = `${est.estimated_fatalities.toLocaleString()} people`;
      document.getElementById("valInjuries").textContent = `${est.estimated_injuries.toLocaleString()} people`;
      document.getElementById("valStructures").textContent = `${est.structures_destroyed.toLocaleString()} structures`;

      // Animate chart bars
      const maxVal = Math.max(est.estimated_fatalities, est.estimated_injuries, est.structures_destroyed, 1);
      setTimeout(() => {
```

```
        document.getElementById("barFatalities").style.width = `${Math.min(100, (est.estimated_fatalities / maxVal) * 1
00)}%`;
        document.getElementById("barInjuries").style.width = `${Math.min(100, (est.estimated_injuries / maxVal) * 10
0)}%`;
        document.getElementById("barStructures").style.width = `${Math.min(100, (est.structures_destroyed / maxVal) * 1
00)}%`;
      }, 50);

      // Facts
      const factsUl = document.getElementById("factsList");
      factsUl.innerHTML = "";
      (selectedMissile.facts || []).forEach((f) => {
        const li = document.createElement("li");
        li.textContent = f;
        factsUl.appendChild(li);
      });

      openModal("impactModal");
    }

    function openModal(id) {
      document.getElementById(id).classList.add("active");
    }
    function closeModal(id) {
      document.getElementById(id).classList.remove("active");
    }

    // Save & Load Scenarios
    function openSaveScenarioModal() {
      if (!originPlace || !destPlace) {
        showToast("⚠️ Missing Selection", "Please set both Origin and Target before saving a scenario.");
        return;
      }
      document.getElementById("scenarioNameInput").value = `${selectedMissile.name} (${selectedMissile.country}) ${orig
inPlace.label} to ${destPlace.label}`;
      openModal("saveModal");
    }

    async function confirmSaveScenario() {
      const name = document.getElementById("scenarioNameInput").value.trim();
      if (!name) return;

      const isNuclear = document.getElementById("nuclearToggle").checked && selectedMissile.nuclear_capable;
      const yieldKt = parseFloat(document.getElementById("yieldSelect").value);

      const res = await callPython(
        "save_scenario",
        name,
        originPlace.label,
        originPlace.longitude,
        originPlace.latitude,
        destPlace.label,
        destPlace.longitude,
        destPlace.latitude,
        selectedMissile.id,
        isNuclear,
        yieldKt,
        0.0
      );

      closeModal("saveModal");
      showToast("💾 Saved", res.message || "Scenario saved successfully to SQLite!");
    }

    async function openLoadScenarioModal() {
      const list = await callPython("list_scenarios");
      const container = document.getElementById("savedScenariosList");
      container.innerHTML = "";

      if (!list || !list.length) {
        container.innerHTML = `<div style="color: #94a3b8; font-size: 13px; text-align: center; padding: 20px;">No save
d scenarios in SQLite database yet.</div>`;
      } else {
```

```
        list.forEach((s) => {
          const card = document.createElement("div");
          card.style.background = "#1e293b";
          card.style.border = "1px solid #334155";
          card.style.borderRadius = "8px";
          card.style.padding = "10px 14px";
          card.style.cursor = "pointer";
          card.innerHTML = `
            <div style="font-weight: 700; color: #fff; font-size: 13px;">${s.scenario_name}</div>
            <div style="font-size: 11px; color: #94a3b8; margin-top: 2px;">
              ${s.origin_city_label} ➔ ${s.destination_city_label} | Missile: ${s.selected_reference_record_id}
            </div>
          `;
          card.onclick = () => {
            loadScenarioObject(s);
            closeModal("loadModal");
          };
          container.appendChild(card);
        });
      }
      openModal("loadModal");
    }

    function loadScenarioObject(s) {
      setOrigin({
        label: s.origin_city_label,
        longitude: s.origin_longitude,
        latitude: s.origin_latitude
      });
      setDestination({
        label: s.destination_city_label,
        longitude: s.destination_longitude,
        latitude: s.destination_latitude
      });

      if (s.selected_reference_record_id) {
        document.getElementById("missileSelect").value = s.selected_reference_record_id;
        onMissileChanged();
      }

      if (s.hypothetical_assessment_zone_parameters) {
        try {
          const p = JSON.parse(s.hypothetical_assessment_zone_parameters);
          if (p.is_nuclear !== undefined) document.getElementById("nuclearToggle").checked = p.is_nuclear;
          if (p.yield_kt) document.getElementById("yieldSelect").value = p.yield_kt;
          onNuclearToggled();
        } catch(e) {}
      }

      updateRangeCheck();
      renderGlobeEntities();
    }

    function resetAll() {
      originPlace = null;
      destPlace = null;
      document.getElementById("originLabel").textContent = "Selected: None";
      document.getElementById("originCoords").textContent = "Click Earth to place Green Origin Pin";
      document.getElementById("originQuery").value = "";
      document.getElementById("destLabel").textContent = "Selected: None";
      document.getElementById("destCoords").textContent = "Click inside Cyan Circle for Red Target Pin";
      document.getElementById("destQuery").value = "";
      document.getElementById("rangeBanner").className = "range-banner pending";
      document.getElementById("rangeBanner").innerHTML = "<span>ℹ</span><span>Select Origin and Target on the 3D globe
or search above.</span>";
      document.getElementById("targetPopLive").innerHTML = "Auto-queried via OpenDataSoft / GeoNames & OSM when target
is selected";
      renderGlobeEntities();
    }

    // Close suggestions on outside click or Escape key
    window.addEventListener("click", (e) => {
      if (!e.target.closest(".input-row")) {
```

```
        const oS = document.getElementById("originSuggestions");
        const dS = document.getElementById("destSuggestions");
        if (oS) oS.style.display = "none";
        if (dS) dS.style.display = "none";
      }
    });

    window.addEventListener("keydown", (e) => {
      if (e.key === "Escape") {
        const oS = document.getElementById("originSuggestions");
        const dS = document.getElementById("destSuggestions");
        if (oS) oS.style.display = "none";
        if (dS) dS.style.display = "none";
      }
    });

    // Start
    window.addEventListener("DOMContentLoaded", initApp);
  </script>
</body>
</html>
```

app/data/reference_data.json — 1048 lines • 43,591 bytes • 58-Missile Technical Database (Complete JSON)


```
{
  "missiles": [
    {
      "id": "agni_v",
      "name": "Agni-V",
      "country": "India",
      "type": "Intercontinental Ballistic Missile (ICBM)",
      "min_range_km": 1500,
      "max_range_km": 5500,
      "speed_mach": 24.0,
      "conventional_yield_kt": 0.0015,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 250.0,
      "source_url": "https://missilethreat.csis.org/missile/agni-5/",
      "facts": [
        "Three-stage solid-fueled road-mobile ICBM developed by India's DRDO.",
        "Equipped with advanced ring-laser gyros and MIRV (Multiple Independently Targetable Reentry Vehicle) capabilit
y.",
        "Reaches terminal speeds of approximately Mach 24 (nearly 29,400 km/h)."
      ]
    },
    {
      "id": "agni_iv",
      "name": "Agni-IV",
      "country": "India",
      "type": "Intermediate-Range Ballistic Missile (IRBM)",
      "min_range_km": 900,
      "max_range_km": 4000,
      "speed_mach": 7.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 40.0,
      "source_url": "https://missilethreat.csis.org/missile/agni-4/",
      "facts": [
        "Two-stage solid-propellant ballistic missile bridging India's medium and intercontinental strike wings.",
        "Features composite rocket motor casings for significantly lighter launch weight.",
        "Re-entry heat shield withstands exterior friction temperatures above 4,000°C."
      ]
    },
    {
      "id": "agni_iii",
      "name": "Agni-III",
      "country": "India",
      "type": "Intermediate-Range Ballistic Missile (IRBM)",
      "min_range_km": 800,
      "max_range_km": 3500,
      "speed_mach": 5.0,
      "conventional_yield_kt": 0.002,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 200.0,
      "source_url": "https://missilethreat.csis.org/missile/agni-3/",
      "facts": [
        "Compact 17-meter two-stage solid-fuel missile designed for rapid deployment from rail launchers.",
        "High payload capacity capable of carrying heavy nuclear warhead packages.",
        "Forms the backbone of the Strategic Forces Command regional deterrence."
      ]
    },
    {
      "id": "agni_ii",
      "name": "Agni-II",
      "country": "India",
      "type": "Medium-Range Ballistic Missile (MRBM)",
      "min_range_km": 500,
      "max_range_km": 2000,
      "speed_mach": 4.5,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 150.0,
      "source_url": "https://missilethreat.csis.org/missile/agni-2/",
      "facts": [
```

```
        "Two-stage solid-propellant road and rail mobile ballistic missile.",
        "Features post-boost vehicle control fins for high-accuracy terminal trajectory correction.",
        "Tested extensively with high operational reliability under the SFC."
      ]
    },
    {
      "id": "agni_prime",
      "name": "Agni-Prime (Agni-P)",
      "country": "India",
      "type": "Medium-Range Ballistic Missile (MRBM)",
      "min_range_km": 700,
      "max_range_km": 2000,
      "speed_mach": 6.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 100.0,
      "source_url": "https://missilethreat.csis.org/missile/agni-p/",
      "facts": [
        "Next-generation canisterized solid-fuel missile that can be stored for years and launched on minutes' notic
e.",
        "Features dual-redundant navigation and guidance systems with thrust-vector control.",
        "Weighs 50% less than Agni-II despite having equivalent operational strike range."
      ]
    },
    {
      "id": "brahmos_er",
      "name": "BrahMos Block-III / ER",
      "country": "India",
      "type": "Supersonic Cruise Missile",
      "min_range_km": 10,
      "max_range_km": 800,
      "speed_mach": 2.8,
      "conventional_yield_kt": 0.0003,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 10.0,
      "source_url": "https://missilethreat.csis.org/missile/brahmos/",
      "facts": [
        "Joint Indo-Russian development and the world's fastest operational ramjet supersonic cruise missile.",
        "Flies sea-skimming trajectories as low as 3 to 10 meters before an aggressive terminal dive.",
        "Extended Range (ER) variant upgrades range to 800 km with precision radar seeker guidance."
      ]
    },
    {
      "id": "brahmos_ii",
      "name": "BrahMos-II (Hypersonic)",
      "country": "India",
      "type": "Hypersonic Cruise Missile",
      "min_range_km": 20,
      "max_range_km": 1000,
      "speed_mach": 7.0,
      "conventional_yield_kt": 0.0003,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://en.wikipedia.org/wiki/BrahMos-II",
      "facts": [
        "Scramjet-powered hypersonic cruise missile engineered to cruise at Mach 7 to Mach 8.",
        "Designed to penetrate dense anti-ballistic and air-defense radar umbrellas through pure velocity.",
        "Kinetic energy upon impact amplifies damage significantly beyond chemical explosives."
      ]
    },
    {
      "id": "nirbhay",
      "name": "Nirbhay",
      "country": "India",
      "type": "Subsonic Long-Range Cruise Missile",
      "min_range_km": 50,
      "max_range_km": 1000,
      "speed_mach": 0.75,
      "conventional_yield_kt": 0.00045,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 12.0,
      "source_url": "https://missilethreat.csis.org/missile/nirbhay/",
      "facts": [
```

```
      "All-weather stealth subsonic land-attack cruise missile developed by ADE/DRDO.",
      "Equipped with ring-laser gyro INS, GPS/NAVIC satellite guidance, and RF seeker for terminal accuracy.",
      "Loiters over target zone before executing precision strike."
    ]
  },
  {
    "id": "pralay",
    "name": "Pralay Tactical Ballistic",
    "country": "India",
    "type": "Quasi-Ballistic Tactical Missile",
    "min_range_km": 150,
    "max_range_km": 500,
    "speed_mach": 6.1,
    "conventional_yield_kt": 0.0007,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://en.wikipedia.org/wiki/Pralay_(missile)",
    "facts": [
      "Canisterized quasi-ballistic surface-to-surface missile designed for conventional battlefield strikes.",
      "Performs mid-course maneuvers using aerodynamic thrusters to defeat interceptor air-defense systems.",
      "Carries penetration, blast-fragmentation, and submunition warheads up to 1,000 kg."
    ]
  },
  {
    "id": "shaurya",
    "name": "Shaurya Hypersonic",
    "country": "India",
    "type": "Hypersonic Surface-to-Surface Missile",
    "min_range_km": 100,
    "max_range_km": 750,
    "speed_mach": 7.5,
    "conventional_yield_kt": 0.001,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 20.0,
    "source_url": "https://missilethreat.csis.org/missile/shaurya/",
    "facts": [
      "Land-based derivative of India's Sagarika (K-15) submarine-launched ballistic missile.",
      "Flies in the atmosphere at hypersonic speed, making radar detection and tracking exceedingly difficult.",
      "Stored in composite canisters mounted on all-terrain road trucks."
    ]
  },
  {
    "id": "k4_slbm",
    "name": "K-4 SLBM",
    "country": "India",
    "type": "Submarine-Launched Ballistic Missile (SLBM)",
    "min_range_km": 500,
    "max_range_km": 3500,
    "speed_mach": 5.5,
    "conventional_yield_kt": 0.001,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 200.0,
    "source_url": "https://missilethreat.csis.org/missile/k-4/",
    "facts": [
      "Nuclear-capable submarine-launched ballistic missile deployed aboard INS Arihant-class SSBNs.",
      "Equipped with advanced 3D thrust vectoring control for vertical underwater ejection.",
      "Provides India with a survivable, guaranteed second-strike nuclear deterrence capability."
    ]
  },
  {
    "id": "prithvi_ii",
    "name": "Prithvi-II",
    "country": "India",
    "type": "Short-Range Ballistic Missile (SRBM)",
    "min_range_km": 50,
    "max_range_km": 350,
    "speed_mach": 3.5,
    "conventional_yield_kt": 0.0005,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 10.0,
    "source_url": "https://missilethreat.csis.org/missile/prithvi-2/",
    "facts": [
      "First ballistic missile developed under India's Integrated Guided Missile Development Program (IGMDP).",
```

```
      "Uses twin liquid-fuel rocket engines with advanced inertial strap-down guidance.",
      "Capable of carrying conventional or nuclear warheads with CEP under 10 meters."
    ]
  },
  {
    "id": "minuteman_iii",
    "name": "LGM-30G Minuteman III",
    "country": "United States",
    "type": "Intercontinental Ballistic Missile (ICBM)",
    "min_range_km": 2000,
    "max_range_km": 13000,
    "speed_mach": 23.0,
    "conventional_yield_kt": 0.0005,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 335.0,
    "source_url": "https://missilethreat.csis.org/missile/minuteman-iii/",
    "facts": [
      "Forms the hardened silo-based land leg of the United States nuclear triad.",
      "Capable of launching within 60 seconds of receiving authenticated presidential launch codes.",
      "Carries the W78 (335 kt) or W87 (300 kt) thermonuclear warhead in a precision Mark 12A/21 RV."
    ]
  },
  {
    "id": "trident_ii_us",
    "name": "UGM-133A Trident II D5 (US)",
    "country": "United States",
    "type": "Submarine-Launched Ballistic Missile (SLBM)",
    "min_range_km": 2500,
    "max_range_km": 12000,
    "speed_mach": 24.0,
    "conventional_yield_kt": 0.0005,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 455.0,
    "source_url": "https://missilethreat.csis.org/missile/trident-ii-d5/",
    "facts": [
      "Deploys aboard Ohio-class ballistic missile submarines with extraordinary navigational accuracy.",
      "Each missile can deploy up to 8 MIRV thermonuclear warheads (W76-1 90kt or W88 455kt).",
      "Over 180 consecutive successful test flights, representing the gold standard of SLBM reliability."
    ]
  },
  {
    "id": "tomahawk_block_v",
    "name": "BGM-109 Tomahawk Block V",
    "country": "United States",
    "type": "Long-Range Subsonic Cruise Missile",
    "min_range_km": 50,
    "max_range_km": 1600,
    "speed_mach": 0.74,
    "conventional_yield_kt": 0.00045,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://missilethreat.csis.org/missile/tomahawk/",
    "facts": [
      "Premier US long-range all-weather precision strike cruise missile launched from cruisers and submarines.",
      "Uses GPS, TERCOM (Terrain Contour Matching), and optical DSMAC for sub-meter terminal accuracy.",
      "Block V includes multi-mode seekers capable of striking moving maritime targets at sea."
    ]
  },
  {
    "id": "jassm_er",
    "name": "AGM-158B JASSM-ER",
    "country": "United States",
    "type": "Air-Launched Stealth Cruise Missile",
    "min_range_km": 30,
    "max_range_km": 925,
    "speed_mach": 0.82,
    "conventional_yield_kt": 0.00045,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://missilethreat.csis.org/missile/jassm/",
    "facts": [
      "Low-observable radar-evading standoff missile carried by B-1B, B-52H, F-15E, F-16, and F-35.",
      "Equipped with a dual-mode penetrator warhead designed to shatter hardened underground command bunkers.",
```

```
        "Employs an imaging infrared (IIR) seeker that visually verifies the target prior to impact."
      ]
    },
    {
      "id": "hellfire",
      "name": "AGM-114 Hellfire",
      "country": "United States",
      "type": "Tactical Air-to-Surface Missile",
      "min_range_km": 0.5,
      "max_range_km": 11,
      "speed_mach": 1.3,
      "conventional_yield_kt": 9e-06,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://www.lockheedmartin.com/en-us/products/hellfire-tactical-missiles.html",
      "facts": [
        "Precision laser-guided anti-armor and counter-insurgency missile fired from Apache helicopters and MQ-9 Reaper
s.",
        "Carries an 8 kg shaped-charge tandem warhead designed to defeat explosive reactive armor.",
        "Originally stood for 'Heliborne Laser, Fire-and-Forget Missile'."
      ]
    },
    {
      "id": "atacms",
      "name": "MGM-140 ATACMS",
      "country": "United States",
      "type": "Tactical Ballistic Missile",
      "min_range_km": 25,
      "max_range_km": 300,
      "speed_mach": 3.0,
      "conventional_yield_kt": 0.00023,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/missile/atacms/",
      "facts": [
        "Fired from M142 HIMARS and M270 MLRS tracked and wheeled mobile launchers.",
        "Carries either a 227 kg unitary blast-frag warhead or APAM submunitions.",
        "Flies a semi-ballistic trajectory using GPS and ring-laser gyros to avoid air defense systems."
      ]
    },
    {
      "id": "prsm",
      "name": "Precision Strike Missile (PrSM)",
      "country": "United States",
      "type": "Next-Gen Tactical Ballistic Missile",
      "min_range_km": 60,
      "max_range_km": 500,
      "speed_mach": 4.2,
      "conventional_yield_kt": 0.00018,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/missile/prsm/",
      "facts": [
        "US Army successor to ATACMS fitting two missiles per HIMARS launcher pod instead of one.",
        "Compliant with the repealed INF Treaty limit, hitting pinpoint targets out to 500 km.",
        "Capable of attacking surface warships and air defense batteries in contested anti-access environments."
      ]
    },
    {
      "id": "alcm_agm86",
      "name": "AGM-86B ALCM",
      "country": "United States",
      "type": "Air-Launched Strategic Cruise Missile",
      "min_range_km": 100,
      "max_range_km": 2400,
      "speed_mach": 0.73,
      "conventional_yield_kt": 0.00045,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 150.0,
      "source_url": "https://missilethreat.csis.org/missile/alcm/",
      "facts": [
        "Primary nuclear standoff cruise missile of the US Air Force B-52H Stratofortress fleet.",
        "Carries the W80-1 variable-yield thermonuclear warhead (5 to 150 kt).",
```

```
        "Navigates via terrain-following radar at tree-top level to stay under Soviet and modern air radars."
      ]
    },
    {
      "id": "sm3_intercept",
      "name": "RIM-161 Standard Missile 3 (SM-3)",
      "country": "United States",
      "type": "Exoatmospheric Ballistic Missile Interceptor",
      "min_range_km": 100,
      "max_range_km": 2500,
      "speed_mach": 15.0,
      "conventional_yield_kt": 1e-06,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/defsys/sm-3/",
      "facts": [
        "Aegis Ballistic Missile Defense weapon capable of intercepting short to intermediate-range ballistic missiles
in space.",
        "Uses a Kinetic Warhead (hit-to-kill vehicle) with over 130 megajoules of structural kinetic impact energy.",
        "Has successfully intercepted and destroyed decaying satellites in low Earth orbit."
      ]
    },
    {
      "id": "harpoon_us",
      "name": "RGM-84 Harpoon Block II",
      "country": "United States",
      "type": "Anti-Ship Cruise Missile",
      "min_range_km": 10,
      "max_range_km": 280,
      "speed_mach": 0.71,
      "conventional_yield_kt": 0.00022,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/missile/harpoon/",
      "facts": [
        "Standard anti-ship missile used by the US Navy and over 30 allied nations for four decades.",
        "Employs active radar homing and low-altitude sea-skimming cruising profile.",
        "Block II upgrades added GPS guidance enabling precision strikes on land-based coastal batteries."
      ]
    },
    {
      "id": "sarmat_satan2",
      "name": "RS-28 Sarmat (Satan II)",
      "country": "Russia",
      "type": "Super-Heavy Thermonuclear ICBM",
      "min_range_km": 3000,
      "max_range_km": 18000,
      "speed_mach": 20.7,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 800.0,
      "source_url": "https://missilethreat.csis.org/missile/rs-28-sarmat/",
      "facts": [
        "World's largest liquid-fueled super-heavy ICBM weighing over 208 metric tons.",
        "Capable of flying fractional orbital trajectories over the South Pole to bypass northern radar arcs.",
        "Can carry up to 10 heavy MIRVs, 15 lighter MIRVs, or up to 3 Avangard hypersonic glide vehicles."
      ]
    },
    {
      "id": "yars_rs24",
      "name": "RS-24 Yars",
      "country": "Russia",
      "type": "Road-Mobile Intercontinental Ballistic Missile",
      "min_range_km": 2000,
      "max_range_km": 11000,
      "speed_mach": 20.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 500.0,
      "source_url": "https://missilethreat.csis.org/missile/rs-24-yars/",
      "facts": [
        "Core of the Russian Strategic Rocket Forces mobile deterrent, carried on 16-wheeled MZKT transports.",
        "Armed with 3 to 4 independently targetable MIRVs and advanced penetration decoy systems.",
```

```
      "Solid propellant design allows rapid cold-launch from hidden forest dispersal areas."
    ]
  },
  {
    "id": "voyevoda_r36m2",
    "name": "R-36M2 Voyevoda (SS-18 Satan)",
    "country": "Russia",
    "type": "Heavy Silo-Based ICBM",
    "min_range_km": 2500,
    "max_range_km": 16000,
    "speed_mach": 22.0,
    "conventional_yield_kt": 0.001,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 1000.0,
    "source_url": "https://missilethreat.csis.org/missile/ss-18/",
    "facts": [
      "Legendary Soviet heavy ICBM designed to eliminate hardened NATO missile silos and command bunkers.",
      "Can carry a massive single 20-megaton city-buster warhead or 10 heavy thermonuclear MIRVs.",
      "Housed in super-hardened silos rated to withstand direct near-miss nuclear overpressures."
    ]
  },
  {
    "id": "bulava_rsm56",
    "name": "RSM-56 Bulava",
    "country": "Russia",
    "type": "Submarine-Launched Ballistic Missile (SLBM)",
    "min_range_km": 1500,
    "max_range_km": 9300,
    "speed_mach": 18.0,
    "conventional_yield_kt": 0.001,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 150.0,
    "source_url": "https://missilethreat.csis.org/missile/bulava/",
    "facts": [
      "Primary armament of Russia's Borei-class fourth-generation nuclear ballistic missile submarines.",
      "Features low-trajectory flight capability and defensive decoys to confuse space tracking sensors.",
      "Carries 6 to 10 maneuverable nuclear warheads with autonomous celestial guidance."
    ]
  },
  {
    "id": "iskander_m",
    "name": "9M723 Iskander-M",
    "country": "Russia",
    "type": "Quasi-Ballistic Tactical Missile",
    "min_range_km": 50,
    "max_range_km": 500,
    "speed_mach": 5.9,
    "conventional_yield_kt": 0.00048,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 50.0,
    "source_url": "https://missilethreat.csis.org/missile/ss-26-iskander/",
    "facts": [
      "Road-mobile quasi-ballistic missile capable of pulling 30g evasive maneuvers in terminal descent.",
      "Employs optical and radar correlator seekers providing circular error probable (CEP) under 5 meters.",
      "Can be fitted with thermonuclear, bunker-buster, EMP, or cluster munitions."
    ]
  },
  {
    "id": "kinzhal_kh47",
    "name": "Kh-47M2 Kinzhal",
    "country": "Russia",
    "type": "Air-Launched Hypersonic Aeroballistic Missile",
    "min_range_km": 100,
    "max_range_km": 2000,
    "speed_mach": 10.0,
    "conventional_yield_kt": 0.0005,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 50.0,
    "source_url": "https://missilethreat.csis.org/missile/kinzhal/",
    "facts": [
      "Launched at high altitude from MiG-31K interceptors and Tu-22M3 strategic bombers.",
      "Accelerates to Mach 10 while retaining full aerodynamic control surface maneuvering.",
      "Used operationally in Ukraine against high-value underground ammunition depots and command centers."
```

```
    ]
  },
  {
    "id": "zircon_3m22",
    "name": "3M22 Zircon",
    "country": "Russia",
    "type": "Hypersonic Scramjet Cruise Missile",
    "min_range_km": 50,
    "max_range_km": 1000,
    "speed_mach": 9.0,
    "conventional_yield_kt": 0.0003,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 200.0,
    "source_url": "https://en.wikipedia.org/wiki/3M22_Zircon",
    "facts": [
      "Fires from shipboard UKSK vertical launch systems and Yasen-M nuclear submarines.",
      "Scramjet engine sustains Mach 8-9 flight within a plasma cloud that absorbs radar emissions.",
      "Leaves modern shipboard close-in weapon systems (CIWS) virtually zero reaction window."
    ]
  },
  {
    "id": "kalibr_3m54",
    "name": "3M-54 Kalibr",
    "country": "Russia",
    "type": "Land-Attack / Anti-Ship Cruise Missile",
    "min_range_km": 30,
    "max_range_km": 2500,
    "speed_mach": 0.8,
    "conventional_yield_kt": 0.00045,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 50.0,
    "source_url": "https://missilethreat.csis.org/missile/kalibr/",
    "facts": [
      "Russia's counterpart to the US Tomahawk cruise missile, launched from frigates, corvettes, and subs.",
      "Navigates around natural topographical contours to evade early warning radar networks.",
      "Anti-ship variant features a supersonic Mach 2.9 rocket booster for the final 20 km sprint."
    ]
  },
  {
    "id": "kh101_stealth",
    "name": "Kh-101 Stealth Cruise",
    "country": "Russia",
    "type": "Long-Range Air-Launched Stealth Cruise Missile",
    "min_range_km": 100,
    "max_range_km": 4500,
    "speed_mach": 0.77,
    "conventional_yield_kt": 0.0004,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://missilethreat.csis.org/missile/kh-101/",
    "facts": [
      "Strategic low-observable cruise missile with flattened radar-absorbent fuselage cross section.",
      "Carried internally by Tu-160 Blackjack and externally by Tu-95MS Bear heavy bombers.",
      "Employs Otblesk-U electro-optical scene matching system for final targeting accuracy."
    ]
  },
  {
    "id": "df41_china",
    "name": "DF-41 (Dongfeng-41)",
    "country": "China",
    "type": "Road-Mobile Intercontinental Ballistic Missile",
    "min_range_km": 3000,
    "max_range_km": 15000,
    "speed_mach": 25.0,
    "conventional_yield_kt": 0.001,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 1000.0,
    "source_url": "https://missilethreat.csis.org/missile/df-41/",
    "facts": [
      "China's most powerful road and rail mobile solid-fuel intercontinental ballistic missile.",
      "Operational strike range of 15,000 km covers the entire continental United States and Europe.",
      "Can carry up to 10 MIRV nuclear warheads along with sophisticated chaff and decoy suites."
    ]
```

```
    },
    {
      "id": "df31ag_china",
      "name": "DF-31AG",
      "country": "China",
      "type": "Road-Mobile Intercontinental Ballistic Missile",
      "min_range_km": 2000,
      "max_range_km": 11200,
      "speed_mach": 20.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 500.0,
      "source_url": "https://missilethreat.csis.org/missile/df-31/",
      "facts": [
        "Upgraded variant of DF-31 mounted on an 8-axle off-road all-terrain transporter-erector-launcher (TEL).",
        "Can launch from unpaved roads and remote wilderness, vastly increasing survivability.",
        "Equipped with MIRV technology and terminal maneuver capability."
      ]
    },
    {
      "id": "df26_guam_killer",
      "name": "DF-26B (Guam Killer)",
      "country": "China",
      "type": "Intermediate-Range Ballistic Missile (IRBM)",
      "min_range_km": 1000,
      "max_range_km": 4000,
      "speed_mach": 18.0,
      "conventional_yield_kt": 0.0012,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 300.0,
      "source_url": "https://missilethreat.csis.org/missile/df-26/",
      "facts": [
        "Hot-swappable dual-capable missile system supporting both conventional precision and nuclear warheads.",
        "Nicknamed the 'Guam Killer' due to its ability to strike major US military bases in the second island chain.",
        "Equipped with active radar terminal seeker capable of striking moving aircraft carriers."
      ]
    },
    {
      "id": "df21d_carrier_killer",
      "name": "DF-21D (Carrier Killer)",
      "country": "China",
      "type": "Anti-Ship Ballistic Missile (ASBM)",
      "min_range_km": 500,
      "max_range_km": 1500,
      "speed_mach": 10.0,
      "conventional_yield_kt": 0.0006,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/missile/df-21/",
      "facts": [
        "World's first operational anti-ship ballistic missile designed specifically to defeat aircraft carriers.",
        "Terminal radar and optical seekers correlate the target position as the reentry vehicle dives at Mach 10.",
        "Key pillar of China's Anti-Access/Area Denial (A2/AD) maritime strategy in the Western Pacific."
      ]
    },
    {
      "id": "df17_hgv",
      "name": "DF-17 Hypersonic Glide Vehicle",
      "country": "China",
      "type": "Hypersonic Boost-Glide Weapon System",
      "min_range_km": 500,
      "max_range_km": 2500,
      "speed_mach": 8.5,
      "conventional_yield_kt": 0.0005,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 50.0,
      "source_url": "https://missilethreat.csis.org/missile/df-17/",
      "facts": [
        "Boosted into high atmosphere by a ballistic rocket before detaching the DF-ZF hypersonic waverider.",
        "Glides at extreme speeds through the upper atmosphere, executing unpredictably shaped lateral turns.",
        "Renders traditional parabolic ballistic missile defense radars and interceptors largely ineffective."
      ]
    },
```

```
    {
      "id": "jl3_slbm",
      "name": "JL-3 (Julang-3)",
      "country": "China",
      "type": "Submarine-Launched Ballistic Missile (SLBM)",
      "min_range_km": 2000,
      "max_range_km": 10000,
      "speed_mach": 20.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 250.0,
      "source_url": "https://missilethreat.csis.org/missile/jl-3/",
      "facts": [
        "China's third-generation intercontinental SLBM deployed on Type 094 and Type 096 SSBNs.",
        "Allows Chinese submarines to strike targets in the continental United States from protected bastions in the So
uth China Sea.",
        "Carries up to 6 MIRV nuclear warheads."
      ]
    },
    {
      "id": "cj10_cruise",
      "name": "CJ-10 (Changjian-10)",
      "country": "China",
      "type": "Land-Attack Subsonic Cruise Missile",
      "min_range_km": 50,
      "max_range_km": 2000,
      "speed_mach": 0.75,
      "conventional_yield_kt": 0.0005,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 20.0,
      "source_url": "https://missilethreat.csis.org/missile/cj-10/",
      "facts": [
        "Long-range precision land-attack cruise missile developed by the Second Academy of CASIC.",
        "Uses inertial guidance combined with BeiDou satellite navigation and scene matching.",
        "Carries high-explosive unitary, thermobaric, or submunition warheads."
      ]
    },
    {
      "id": "m51_france",
      "name": "M51 SLBM",
      "country": "France",
      "type": "Submarine-Launched Ballistic Missile (SLBM)",
      "min_range_km": 2000,
      "max_range_km": 10000,
      "speed_mach": 25.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 150.0,
      "source_url": "https://missilethreat.csis.org/missile/m51/",
      "facts": [
        "Forms the primary sea-based component of France's independent nuclear deterrent (Force de frappe).",
        "Deployed aboard Triomphant-class nuclear ballistic submarines with 16 missiles per boat.",
        "Carries 6 to 10 TNO (Tête Nucléaire Océanique) thermonuclear warheads per missile."
      ]
    },
    {
      "id": "asmpa_france",
      "name": "ASMP-A",
      "country": "France",
      "type": "Air-Launched Supersonic Nuclear Cruise Missile",
      "min_range_km": 50,
      "max_range_km": 500,
      "speed_mach": 3.0,
      "conventional_yield_kt": 0.0003,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 300.0,
      "source_url": "https://missilethreat.csis.org/missile/asmp/",
      "facts": [
        "Airborne leg of the French nuclear deterrent, carried exclusively by Dassault Rafale fighters.",
        "Powered by an integral ramjet engine cruising at Mach 3 at high altitude or Mach 2 at sea level.",
        "Designed to deliver an 'ultime avertissement' (final nuclear warning) strike."
      ]
    },
```

```
  {
    "id": "storm_shadow_scalp",
    "name": "Storm Shadow / SCALP-EG",
    "country": "France",
    "type": "Air-Launched Low-Observable Cruise Missile",
    "min_range_km": 30,
    "max_range_km": 560,
    "speed_mach": 0.8,
    "conventional_yield_kt": 0.00045,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://missilethreat.csis.org/missile/storm-shadow-scalp-eg/",
    "facts": [
      "Joint UK-French long-range precision standoff weapon manufactured by MBDA.",
      "Equipped with the BROACH two-stage bunker-penetrating warhead to defeat reinforced bridges and bunkers.",
      "Used extensively by Ukraine with high interception resistance against Russian air defense systems."
    ]
  },
  {
    "id": "exocet_mm40",
    "name": "Exocet MM40 Block 3",
    "country": "France",
    "type": "Anti-Ship Cruise Missile",
    "min_range_km": 10,
    "max_range_km": 200,
    "speed_mach": 0.93,
    "conventional_yield_kt": 0.000165,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://en.wikipedia.org/wiki/Exocet",
    "facts": [
      "One of the world's most famous combat-proven anti-ship missile systems.",
      "Block 3 adds a turbojet engine extending range to 200 km and GPS waypoint coastal navigation.",
      "Flies just 1 to 2 meters above wave crests during terminal attack to stay hidden from radar."
    ]
  },
  {
    "id": "trident_ii_uk",
    "name": "Trident II D5 (United Kingdom)",
    "country": "United Kingdom",
    "type": "Submarine-Launched Ballistic Missile (SLBM)",
    "min_range_km": 2500,
    "max_range_km": 12000,
    "speed_mach": 24.0,
    "conventional_yield_kt": 0.0005,
    "nuclear_capable": true,
    "default_nuclear_yield_kt": 100.0,
    "source_url": "https://missilethreat.csis.org/missile/trident-ii-d5/",
    "facts": [
      "Sole nuclear weapons system in the British armed forces, carried aboard Vanguard-class SSBNs.",
      "Operated under Operation Relentless ensuring Continuous At-Sea Deterrence (CASD) since 1969.",
      "Carries British-assembled thermonuclear warheads developed at AWE Aldermaston."
    ]
  },
  {
    "id": "aster_30_uk",
    "name": "Sea Viper / Aster 30",
    "country": "United Kingdom",
    "type": "Naval Surface-to-Air / Anti-Missile",
    "min_range_km": 3,
    "max_range_km": 120,
    "speed_mach": 4.5,
    "conventional_yield_kt": 1.5e-05,
    "nuclear_capable": false,
    "default_nuclear_yield_kt": 0.0,
    "source_url": "https://en.wikipedia.org/wiki/Aster_(missile_family)",
    "facts": [
      "Primary anti-air and anti-missile defense weapon of the Royal Navy Type 45 Daring-class destroyers.",
      "Features PIF-PAF lateral thrusters in the warhead section for 60g terminal intercept maneuvers.",
      "Demonstrated successful combat intercepts against Houthi anti-ship ballistic missiles in the Red Sea."
    ]
  },
  {
```

```
      "id": "brimstone_uk",
      "name": "Brimstone 2",
      "country": "United Kingdom",
      "type": "Precision Ground-Attack Tactical Missile",
      "min_range_km": 1,
      "max_range_km": 60,
      "speed_mach": 1.3,
      "conventional_yield_kt": 6e-06,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://en.wikipedia.org/wiki/Brimstone_(missile)",
      "facts": [
        "Dual-mode millimeter-wave radar and semi-active laser guided anti-armor missile.",
        "Designed for salvo firing ('fire-and-forget') against moving armor formations with minimal collateral damag
e.",
        "Deployed from Eurofighter Typhoon, fast attack boats, and ground-based mobile launchers."
      ]
    },
    {
      "id": "jericho_iii",
      "name": "Jericho III",
      "country": "Israel",
      "type": "Intercontinental Ballistic Missile (ICBM)",
      "min_range_km": 1500,
      "max_range_km": 6500,
      "speed_mach": 20.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 400.0,
      "source_url": "https://missilethreat.csis.org/missile/jericho-3/",
      "facts": [
        "Three-stage solid-propellant ballistic missile forming the strategic backbone of Israel's nuclear deterrent.",
        "Based in hardened underground caves and silos at Sdot Micha Airbase.",
        "Capable of carrying a 1,000 kg thermonuclear warhead or 2-3 MIRVs across the Middle East, Europe, and Asia."
      ]
    },
    {
      "id": "popeye_turbo",
      "name": "Popeye Turbo SLCM",
      "country": "Israel",
      "type": "Submarine-Launched Long-Range Cruise Missile",
      "min_range_km": 50,
      "max_range_km": 1500,
      "speed_mach": 0.8,
      "conventional_yield_kt": 0.00035,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 200.0,
      "source_url": "https://en.wikipedia.org/wiki/Popeye_(missile)",
      "facts": [
        "Turbojet-powered strategic standoff missile deployed aboard Israeli Dolphin-class AIP submarines.",
        "Equipped with a sealed nuclear warhead for survivable second-strike deterrence in the Mediterranean.",
        "Fired through specially expanded 650 mm submarine torpedo tubes."
      ]
    },
    {
      "id": "delilah_israel",
      "name": "Delilah Standoff",
      "country": "Israel",
      "type": "Loitering Standoff Cruise Missile",
      "min_range_km": 15,
      "max_range_km": 250,
      "speed_mach": 0.7,
      "conventional_yield_kt": 3e-05,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://en.wikipedia.org/wiki/Delilah_(missile)",
      "facts": [
        "Precision loitering missile designed to hunt mobile surface-to-air missile radar systems.",
        "Features a man-in-the-loop electro-optical seeker allowing the operator to redirect or abort the attack.",
        "Can loiter over the target area for extended duration before initiating a dive attack."
      ]
    },
    {
```

```
      "id": "khorramshahr_4",
      "name": "Khorramshahr-4 (Kheibar)",
      "country": "Iran",
      "type": "Medium-Range Ballistic Missile (MRBM)",
      "min_range_km": 500,
      "max_range_km": 2000,
      "speed_mach": 16.0,
      "conventional_yield_kt": 0.0015,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/missile/khorramshahr/",
      "facts": [
        "Iran's most advanced liquid-fueled ballistic missile powered by hypergolic storable propellants.",
        "Reaches Mach 16 outside the atmosphere and Mach 8 inside the atmosphere during final dive.",
        "Carries a massive 1,500 kg warhead with mid-course steering engines that eliminate radar detection fins."
      ]
    },
    {
      "id": "fattah_1",
      "name": "Fattah-1 Hypersonic",
      "country": "Iran",
      "type": "Hypersonic Ballistic Missile",
      "min_range_km": 300,
      "max_range_km": 1400,
      "speed_mach": 13.0,
      "conventional_yield_kt": 0.0005,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://en.wikipedia.org/wiki/Fattah_(missile)",
      "facts": [
        "Unveiled by the IRGC Aerospace Force as Iran's first hypersonic missile with a movable nozzle reentry vehicl
e.",
        "Claims terminal maneuvering velocity of Mach 13 to defeat Arrow-3 and Patriot interceptor systems.",
        "Uses solid-propellant spherical rocket motor inside the warhead for high-altitude evasive bursts."
      ]
    },
    {
      "id": "sejjil_iran",
      "name": "Sejjil-2",
      "country": "Iran",
      "type": "Medium-Range Ballistic Missile (MRBM)",
      "min_range_km": 500,
      "max_range_km": 2000,
      "speed_mach": 14.0,
      "conventional_yield_kt": 0.0007,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://missilethreat.csis.org/missile/sejjil/",
      "facts": [
        "Two-stage solid-propellant MRBM offering vastly superior launch readiness compared to liquid-fueled Shahab sys
tems.",
        "Requires minutes to prepare for launch from mobile TELs, minimizing pre-launch vulnerability.",
        "High terminal velocity and steep reentry angle challenge regional missile defense systems."
      ]
    },
    {
      "id": "hwasong_17",
      "name": "Hwasong-17 (Monster ICBM)",
      "country": "North Korea",
      "type": "Heavy Intercontinental Ballistic Missile",
      "min_range_km": 3000,
      "max_range_km": 15000,
      "speed_mach": 22.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 500.0,
      "source_url": "https://missilethreat.csis.org/missile/hwasong-17/",
      "facts": [
        "World's largest road-mobile liquid-fueled ICBM, carried on an 11-axle heavy transport vehicle.",
        "Tested on lofted trajectories exceeding 6,000 km altitude, demonstrating full strike coverage of the United St
ates.",
        "Believed to be designed for carrying multiple nuclear warheads (MIRVs) and penetration aids."
      ]
```

```
    },
    {
      "id": "hwasong_15",
      "name": "Hwasong-15",
      "country": "North Korea",
      "type": "Intercontinental Ballistic Missile (ICBM)",
      "min_range_km": 2000,
      "max_range_km": 13000,
      "speed_mach": 20.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 300.0,
      "source_url": "https://missilethreat.csis.org/missile/hwasong-15/",
      "facts": [
        "Two-stage liquid-propellant ICBM first launched successfully in November 2017.",
        "Powered by twin gimballed combustion chamber rocket engines with vernier thrusters.",
        "Capable of delivering a super-large heavy thermonuclear warhead to any location in North America."
      ]
    },
    {
      "id": "kn23_nk",
      "name": "KN-23 (Hwasong-11Ga)",
      "country": "North Korea",
      "type": "Quasi-Ballistic Tactical Missile",
      "min_range_km": 50,
      "max_range_km": 690,
      "speed_mach": 6.0,
      "conventional_yield_kt": 0.0005,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 50.0,
      "source_url": "https://missilethreat.csis.org/missile/kn-23/",
      "facts": [
        "Solid-fueled quasi-ballistic missile strongly resembling the Russian Iskander-M and South Korean Hyunmoo-2B.",
        "Flies a depressed aero-ballistic trajectory with terminal pull-up maneuvers to escape radar tracking.",
        "Exported and fired in active combat operations during European theater warfare."
      ]
    },
    {
      "id": "taepodong_2",
      "name": "Taepodong-2 / Unha-3",
      "country": "North Korea",
      "type": "Multi-Stage Ballistic Missile / Space Launch",
      "min_range_km": 4000,
      "max_range_km": 10000,
      "speed_mach": 21.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 200.0,
      "source_url": "https://missilethreat.csis.org/missile/taepodong-2/",
      "facts": [
        "Three-stage liquid-fueled rocket based on clustered Nodong engine technology.",
        "Demonstrated satellite orbital insertion capability in 2012 and 2016.",
        "Serves as the structural design basis for early North Korean strategic ICBM development."
      ]
    },
    {
      "id": "hyunmoo_v",
      "name": "Hyunmoo-V (Monster Missile)",
      "country": "South Korea",
      "type": "Heavy Bunker-Busting Ballistic Missile",
      "min_range_km": 100,
      "max_range_km": 3000,
      "speed_mach": 10.0,
      "conventional_yield_kt": 0.009,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://en.wikipedia.org/wiki/Hyunmoo",
      "facts": [
        "World's heaviest conventional ballistic warhead carrying up to 8 to 9 metric tons of high explosive.",
        "Engineered to generate earth-penetrating kinetic shockwaves collapsing bunkers 100 meters underground.",
        "Nicknamed the 'Monster Missile' of the Republic of Korea Armed Forces."
      ]
    },
```

```
    {
      "id": "taurus_kepd",
      "name": "Taurus KEPD 350",
      "country": "Germany",
      "type": "Air-Launched Standoff Cruise Missile",
      "min_range_km": 30,
      "max_range_km": 500,
      "speed_mach": 0.95,
      "conventional_yield_kt": 0.00048,
      "nuclear_capable": false,
      "default_nuclear_yield_kt": 0.0,
      "source_url": "https://en.wikipedia.org/wiki/Taurus_KEPD_350",
      "facts": [
        "Joint German-Swedish precision standoff cruise missile developed by Taurus Systems.",
        "Equipped with MEPHISTO multi-stage penetrator warhead that counts void layers before detonation.",
        "Operated by Germany, Spain, and South Korea for hardened bridge and command center neutralisation."
      ]
    },
    {
      "id": "k15_sagarika",
      "name": "Sagarika (K-15) SLBM",
      "country": "India",
      "type": "Submarine-Launched Ballistic Missile (SLBM)",
      "min_range_km": 50,
      "max_range_km": 750,
      "speed_mach": 5.0,
      "conventional_yield_kt": 0.001,
      "nuclear_capable": true,
      "default_nuclear_yield_kt": 25.0,
      "source_url": "https://missilethreat.csis.org/missile/k-15_sagarika/",
      "facts": [
        "Underwater-launched ballistic missile providing India's sea-based nuclear deterrence aboard INS Arihant.",
        "Underwater gas booster launches the missile to the ocean surface before the rocket motor ignites.",
        "Compact two-stage solid-fuel motor designed and manufactured by DRDO."
      ]
    }
  ]
}
```

# 6. GEMINI PROMPT ENGINEERING GUIDE & EXTENSION TEMPLATES

This section is specifically formulated to assist you when uploading this PDF to **Google Gemini**. By providing Gemini with this PDF, Gemini will have the entire codebase, architecture, physics equations, and constraints in its context window. You can copy-paste any of the prompt templates below directly into Gemini.

## 6.1 System Prompt Context to Paste into Gemini

```
I have uploaded the complete technical dossier and source code of my desktop project:
"Real-World Missile Impact Simulator" (written in Python with Tkinter and PyView/CesiumJS).
Please read and internalize the architecture, specifically:
1. Tkinter (app/ui/main_window.py) is the MANDATORY primary GUI framework hosting the window, menus,
dialogs, and toolbar.
2. PyView / CesiumJS (app/visualization/globe/index.html) is embedded as a child window inside Tkinter
via Win32 SetParent.
3. Impact physics uses Glasstone-Dolan cube-root scaling (app/services/impact_physics.py).
4. Live geocoding and population lookups are handled over Wi-Fi without proprietary API keys
(OpenStreetMap & GeoNames).
5. All 58 missiles across 10 powers are defined in app/data/reference_data.json (Pakistani missiles
excluded).

Whenever I ask for modifications or features, ensure:
- The code you provide maintains Tkinter as the primary GUI.
- You provide exact diffs or complete drop-in replacement files.
- You keep all existing features (dropdown search, blast rings, live population, SQLite persistence)
intact.
```

## 6.2 Ready-to-Use Task Prompts for Gemini

### Template A: Adding Ballistic Trajectory Curve Animations

```
Gemini, based on the uploaded codebase, I want to add an animated 3D parabolic ballistic flight
trajectory arc on the Cesium globe when "SIMULATE LAUNCH & IMPACT" is pressed.
- In app/visualization/globe/index.html, calculate an apogee altitude based on missile range (e.g.,
ICBM apogee up to 1,200 km, cruise missiles low altitude 50 km).
- Animate a glowing projectile traveling along the geodesic arc from Origin to Target before triggering
the impact blast rings.
- Show an on-screen HUD flight countdown timer.
Please provide the exact JavaScript code modifications for index.html.
```

### Template B: Adding Anti-Ballistic Missile (ABM) Interception Mechanics

```
Gemini, based on the uploaded codebase, I want to introduce an Air Defense / Missile Interceptor
simulation (e.g. S-400, Patriot PAC-3, Iron Dome, Arrow 3, David's Sling).
- Extend app/data/reference_data.json to add an "interceptors" section with operational ranges,
```

```
intercept altitudes, and kill probability (Pk).
- Add an option in the Tkinter toolbar and HUD to place an Air Defense Battery.
- Calculate whether the incoming missile passes through the interception envelope and simulate
interception success vs failure.
Please outline the architectural changes and provide the code updates for impact_physics.py,
webview_api.py, and index.html.
```

### Template C: Nuclear Fallout Plume & Wind Vector Modeling

```
Gemini, based on the uploaded codebase, I want to model radioactive fallout plumes based on atmospheric
wind direction and speed.
- In impact_physics.py, add equations for cigar-shaped fallout dispersion ellipses (Early Fallout: 300
rad/hr, 100 rad/hr, 10 rad/hr).
- In index.html, render the asymmetric fallout plume extending downwind from the ground-zero
coordinates.
- Calculate prolonged radiation casualties in addition to immediate blast fatalities.
Please provide the physics formulas and code implementation.
```

### Template D: Exporting Detailed Mission Assessment Reports to PDF / CSV

```
Gemini, based on the uploaded codebase, I want to add an "Export Mission Report" button to both the
Tkinter toolbar and the Post-Impact Assessment modal.
- It should generate a detailed PDF report containing the scenario parameters, origin/target
coordinates, verified urban population, blast radii, estimated casualties, and missile technical
specifications.
- Please provide the Python backend function in webview_api.py and the Tkinter menu action in
main_window.py.
```