

# **Computer Programming**

Dr. Deepak B Phatak
Dr. Supratik Chakraborty
Department of Computer Science and Engineering
IIT Bombay

Session: More on Structures

# Quick Recap of Relevant Topics



- Brief introduction to object-oriented programming
- Structures as collections of variables of possibly different data types
- Accessing members of structures
- Programming using simple structures

#### Overview of This Lecture



- Common conventions when speaking of structures
- More features of structures
  - Structures as members of other structures
  - Initializing members of structures in structures
- Disallowed structure definitions
- Visibility of structure definitions in C++ programs

# Acknowledgment



- Some examples in this lecture are from An Introduction to Programming Through C++ by Abhiram G. Ranade McGraw Hill Education 2014
- All such examples indicated in slides with the citation
   AGRBook



```
struct MyStructType {
  int x;
  char y;
};

MyStructType myVariable;
```



```
struct MyStructType {
  int x;
  char y;
};
```

MyStructType myVariable;

"structure" refers to a specific structure type

The definition of structure MyStructType is given here.



```
struct MyStructType {
  int x;
  char y;
};

MyStructType myVariable;
```

"structure" refers to a specific object of a structure type

The structure myVariable is used in the program.



```
struct MyStructType {
  int x;
  char y;
};

MyStructType myVariable;
```

"structure" refers to a an arbitrary object of type MyStructType

A structure of type
MyStructType needs 5
bytes of storage



```
struct MyStructType {
  int x;
  char y;
};
```

MyStructType myVariable;

Member "x" of structure "myVariable" is like an object/variable of type int

myVariable.x = 12;

### Points and Disks in 2D space [Ref. AGRBook]



- We want to represent points and disks in 2-dimensional space
- Every point has an x-coordinate and a y-coordinate
- Every disk has a center (point) and a radius

```
struct Point {
   double x, y;
};

x
y
```

```
struct Disk {
   Point center;
   double radius;
};

center radius
```

### Points and Disks in 2D space [Ref. AGRBook]



- We want to represent points and disks in 2-dimensional space
- Every point has an x-coordinate and a y-coordinate
- Every disk has a center (point) and a radius

```
struct Point {
   double x, y;
};

x
y
```

```
struct Disk {
   Point center;
   double radius;
};

center
y
radius
```



```
p1
                                                  struct Point {
Point p1;
                                                    double x, y;
Disk d1;
                     d1
                                                struct Disk {
                                                  Point center;
                          center
                                      radius
                                                  double radius;
```



```
p1
Point p1;
                                                  struct Point {
                                                    double x, y;
Disk d1;
                                  0.5
                                          0.9
p1.x = 0.5; p1.y = 0.9;
                     d1
                                                 struct Disk {
                                                   Point center;
                          center
                                      radius
                                                   double radius;
```



```
p1
Point p1;
                                                  struct Point {
                                                    double x, y;
Disk d1;
                                 0.5
                                         0.9
p1.x = 0.5; p1.y = 0.9;
d1.center = p1;
                     d1
                                                struct Disk {
                                                  Point center;
                                      radius
                        0.5
                               0.9
                                                  double radius;
```



```
p1
                                                  struct Point {
Point p1;
                                                    double x, y;
Disk d1;
                                 0.5
                                         0.9
p1.x = 0.5; p1.y = 0.9;
d1.center = p1;
                    d1
                                                struct Disk {
d1.radius = 3.2;
                                                  Point center;
                                       3.2
                        0.5
                               0.9
                                                  double radius;
```



```
Disk d1;
```

```
struct Point {
  double x, y;
};
```

```
d1

center
y radius
```

```
struct Disk {
   Point center;
   double radius;
};
```



```
Disk d1;
                                                 struct Point {
                                                   double x, y;
d1.center.x = 0.5;
                    d1
                                               struct Disk {
                                                 Point center;
                         center
                                     radius
                                                 double radius;
  d1: Object of type Disk
```



```
Disk d1;
                                                struct Point {
                                                  double x, y;
d1.center_{x}x = 0.5;
                    d1
                                              struct Disk {
                                                Point center;
                         center
                                    radius
                                                double radius;
 d1.center: Member "center" of d1 can be used
              as an object of type Point
```



```
Disk d1;
                                               struct Point {
                                                double x, y;
d1.center.x = 0.5;
                   d1
                                             struct Disk {
                                               Point center;
                        center
                                   radius
                                               double radius;
  d1.center.x: Member "x" of d1.center can be
               used as an object of type double
```



```
Disk d1;
                                                  struct Point {
                                                    double x, y;
d1.center.x = 0.5;
d1.center.y = 0.9;
d1.radius = 3.2;
                     d1
                                                 struct Disk {
                                                  Point center;
                                       3.2
                               0.9
                                                  double radius;
```

# Initializing Members of Structures in Structures




```
Disk d1 = \{\{0.5, 0.9\}, 3.2\};
                                                     struct Point {
                                                       double x, y;
const Disk d2 = \{\{1.0, 2.0\}, 3.0\};
                      d1
                                                    struct Disk {
                                          3.2
                         0.5
                                 0.9
                                                     Point center;
                                                     double radius;
                      d2
                                          3.0
                                 2.0
```

#### **Disallowed Structure Construction**



 Structure type "StructType1" cannot have a member of the same structure type "StructType1"



Storage required for an object of type StructType1 would be infinite!

# Visibility of Structure Types



- Where should we define structure types?
- If a structure type is used only in one function, it can be defined in the body of the function

```
void doSomethingWithDisks()
{ struct Point { double x, y; };
   struct Disk {Point center; double radius};
   // Code that does something with points and disks
   return;
}
```

# Visibility of Structure Types



 If a structure data type is used in multiple functions, it must be defined outside and before the functions in program file.

```
struct Point {double x, y;};
struct Disk {Point center; double radius;};

void doOneThingWithPointsAndDisks() { ... return; }

void doAnotherThingWithPointsAndDisks() { ... return; }

void updatePointsAndDisks(Point &p, Disk &d) { ... return; }
```

### Summary



- Common conventions when speaking of structures
- Additional features of structures
  - Structures as members in other structures
  - Accessing and initializing members of structures in structures
- Illegal to have a structure with a member of the same structure type
- Visibility of structure types in a C++ program