

# Computer Programming

Dr. Deepak B Phatak

Dr. Supratik Chakraborty

Department of Computer Science and Engineering  
IIT Bombay

Session: Creating a Binary File

# Quick Recap

---



- We wrote a program to handle data in external files
  - We created a text file markdata.txt, using C++ functions
- We recall that a file on disk is like an array of bytes
  - Just as an array element can be accessed through an index value, one or more bytes can be directly accessed by giving the **position** of the starting byte
- There are file functions in C++ which can read or write a number of bytes at a specified position in the file

# Overview

---



- In this session, we will study a program to create a binary file, in which fixed length records are written
- Later, we will see how these records can be directly accessed, read, and updated

# Files, records, and fields



- Recall the format of the text file created (marksdata.txt)

10101                      Anil 112 12.50

10102                      Amit 111 15.00

10103                      Shefali 112 17.00

- Each line contains a **record** of one student's information
- A record has 4 **fields or attributes**
  - Roll number, name, batch number, marks
- Each field, and thus each record has a fixed length (in bytes)

# Fixed length records

- We know the record size (number of bytes in a record), say **S**
- If data for 10,000 students is written to a disk file, then the file will contain  $10,000 \times S$  bytes
- If we know which is the relative position **r**, of the record of a student in the file, then we can directly read the data for that student
  - $r * (S-1)$  will be the starting byte position of the record
  - Next **S** bytes will contain the record itself

# A record structure

---

- There is no need to store all values in a record in text format
  - We can directly store values in the internal format
- One good way is to define a structure for our record

```
struct studentinfo {  
    int roll;  
    char name[30];  
    int batch;  
    float marks;  
}
```

# Size and elements of a structure

---



- We define a structure variable `s`  
`struct studentinfo s;`
- Individual elements of `s` can now be accessed by  
`s.roll`, `s.name`, `s.batch`, and `s.marks`
- The size (in bytes) of a structure can be found by  
`int rec_size; rec_size = sizeof(struct studentinfo)`

# Size and elements of a structure



- Suppose we define a structure variable s  
`struct studentinfo s;`
- Individual elements of s can now be accessed by  
`s.roll, s.name, s.batch , and s.marks`
- The size (in bytes) of a structure can be found by  
`int rec_size; rec_size = sizeof(struct studentinfo)`
- Most compilers will count the size of our record as 44 bytes
  - Elements need to be allocated at **word** boundary (divisible by 4)



# Program logic for creating a database file



```
Open input text file, output binary file
Read one line from input text file, into four variables
While (not eof input file){
    assign values to elements of structure variable
    write the structure variable to output file
    Read next line from input text file
}
Close files
```

# Program logic for creating a database file



Open input text file, output binary file

Read one line from input text file, into four variables

While (**not** eof input file){

    assign values to elements of structure variable

    write the structure variable to output file

    Read next line from input text file


}

Close files

# Organizing records in a direct access file



- We can directly access data in a binary file giving position



- Current position can be found using a function `ftell()`  
`long POS; POS = ftell(fp);`
- Reading/writing happens at this position, which automatically advances after each such operation

# Program to create a binary file

---



```
/*Program create_student_db.cpp*/  
/* For creating a binary file containing records of students*/  
#include <iostream>  
#include <cstring>  
#include <cstdio>  
using namespace std;
```

# Program ...

---



```
struct studentinfo{  
    int roll;  
    char name[30];  
    int batch;  
    float marks;  
};
```

# Program ...

---



```
int main() {  
    struct studentinfo s;  
    int rec_size;  
    rec_size = sizeof(struct studentinfo);  
    cout << "Size of record is: "<<rec_size<<endl;  
    FILE *fp_input, *fp_output;
```

# Program ...

---



```
fp_input = fopen("markdata.txt", "r" );
if (fp_input == NULL){
    cout << "Could not open input file" << endl;
    return -1;
}
fp_output=fopen("studentdb","wb");
if (fp_output == NULL){
    cout << "Could not open output file"<< endl;
    return -1;
}
```

# Program ...

---



```
int r, b; char n[30]; float m;  
// attribute values for a record  
int count=0;
```



# Program ...

```
fscanf (fp_input, "%d %s %d %f",&r,n,&b,&m);
cout << endl;
while (!feof (fp_input)) {
    count++; s.roll=r, s.batch=b; s.marks=m; strcpy(s.name, n);
    fwrite(&s, rec_size, 1, fp_output);
    printf("%2d %5d %30s %3d %5.2f\n", count, s.roll, s.name,
           s.batch, s.marks);
    fscanf (fp_input, "%d %s %d %f",&r,n,&b,&m);
}
```

# Program ...

---

```
cout << "marks data file read and printed\n";  
cout << "Database created for student info\n";  
cout << "Total records written: "<<count<<endl;  
fclose(fp_input);  
fclose(fp_output);  
return 0;  
}
```

# Results of execution

```
M:\codeblocks\create_student_db\bin\Debug\create_student_db.exe  
Size of record is: 44  
  
1 10101 Anil 112 92.00  
2 10102 Amit 111 84.50  
3 10103 Shefali 112 78.00  
4 10104 Rajesh 111 39.00  
5 10105 Nandan 111 67.00  
6 10106 Avinash 112 65.00  
7 10107 Srikant 112 81.00  
8 10108 Nilmani 111 91.00  
9 10110 Rajesh 112 73.00  
10 10115 Ketan 111 54.00  
marks data file read and printed  
Database created for student info  
Total records written: 10  
  
Process returned 0 (0x0) execution time : 0.087 s  
Press any key to continue.
```

# Summary

---



- We studied how to create a binary file, to write fixed length records containing students' data
- In the next session, we will see how to access and update the records of this file