OFFICIAL BRAND CATALOGUE • POWER

WEIDMÜLLER

Weidmüller Interface GmbH & Co. KG

Industrial Switched Mode Power Supplies (SMPS) & DC Power Solutions

DEALER & SUPPLIER



ENGINEERING OVERVIEW & TECHNOLOGY HIGHLIGHTS

Weidmüller is a global technology leader in smart industrial connectivity and power supply systems. Weidmüller switch-mode power supply units deliver world-class efficiency, dynamic overload capabilities, and uninterrupted power for mission-critical automation.

- Peak energy efficiency up to 95.4% reducing panel heat dissipation
- Seamless communication interfaces (IO-Link / CANopen) for predictive maintenance
- Universal wide-range input AC (85-277V) and 3-Phase (320-575V)
- DCL (Dynamic Current Limit) technology for tripping breakers and starting heavy loads
- High MTBF > 1,000,000 hours and robust vibration resistance

INDUSTRIAL SWITCHED MODE POWER SUPPLIES (SMPS)



PROtop High-End Power Supplies

High-End PROtop

Flagship premium power supply with integrated ORing MOSFET for N+1 redundancy and DCL dynamic boost.

• Efficiency: up to 95.4% • Built-in IO-Link communication • Outputs: 24V / 48V DC (5A, 10A, 20A, 40A) • 1-Phase and 3-Phase models



PROmax High-Performance Power Supplies

PROmax Series

Designed for demanding continuous power requirements with continuous boost up to 120% and short boost up to 300%.

• Output: 5V, 12V, 24V, 48V DC • Currents: 3A to 40A • Slim width for high packing density in panels



PROeco Basic Switch Mode Power Supplies

Reliable, cost-effective standard power supplies with compact dimensions, tri-color LED status and basic diagnostics.

• Efficiency up to 93% • Output: 12V, 24V, 48V DC (3A to 40A) • High overload resistance • Universal AC/DC input



PRO-M Compact DIN Rail Power Units

Ultra-slim single-phase power supply units optimized for confined space in machine distribution boxes.

• Space-saving form factor • Wide operating temperature range -25°C to +70°C

POWER CONTINUITY, REDUNDANCY & PROTECTION



Diode & MOSFET Redundancy Modules

Decoupling modules to configure 100% fail-safe parallel power architecture for zero-downtime control panels.

• Current ratings: 20A, 40A, 80A • Minimal forward voltage drop • Built-in fault alarm contacts



Uninterruptible DC-UPS Systems & Buffers

Capacitor-based buffers and battery-backed DC-UPS to ride through grid dips and power interruptions.

• Buffer times from seconds to hours • Intelligent battery health monitoring



maxGUARD Electronic Load Monitoring

Combined terminal blocks and electronic fuses for precise selective 24V DC circuit protection.

• Integrated current adjustment 1A-12A • Remote reset & tripping indication

OFFICIAL COMMERCIAL QUOTATION & TECHNICAL SUPPORT

To request an instant pricing quotation, OEM warranty validation, or technical submittals for this brand:

Director: Mr. Pradeep Kulkarni
Mobile: +91 83085 02100 / +91 94220 12179
Email: info@speautomation.com | Online RFQ: www.speautomation.com/request-quote