OFFICIAL BRAND CATALOGUE • SENSORS

JUMO INDIA

JUMO India Pvt. Ltd. (JUMO GmbH & Co. KG)

Industrial Thermocouples, RTDs, Precision Pressure, Humidity & Liquid Analysis

OFFICIAL DEALER & PARTNER



ENGINEERING OVERVIEW & TECHNOLOGY HIGHLIGHTS

JUMO is a world-renowned German pioneer and manufacturer of industrial sensor and automation technology with over 50 years of experience in high-temperature measurement. JUMO's thermocouple portfolio is standardized according to DIN EN 60584, DIN 43710, and DIN 43732 covering thermocouple types K, J, N, S, R, and B for temperatures up to +1600°C. From screw-in, push-in, and mineral-insulated thermocouples to FDA 21 CFR Part 11 paperless recorders and sanitary transmitters, JUMO provides turnkey temperature instrumentation across all industrial processes.

- Standardized Thermocouples: Manufactured to DIN EN 60584, DIN 43710, and DIN 43732 for thermocouple types K, J, N, S, R, and B up to +1600°C
- Severe Duty & Safety Tested: DIN EN 14597 safety certified for boilers and furnaces, noble metal thermocouples with ceramic protection tubes (Alsint 99.7 / Pythagoras)
- Complete Measuring Chain: Compensating cables, polarized miniature/ standard connectors, head transmitters (dTRANS T01-T07 HART/SIL), and LOGOSCREEN recorders
- Flexible Mounting & Designs: Screw-in (Form B/J), push-in (Form A/B), bayonet spring-loaded, and mineral-insulated (MgO) cables with ultra-fast response (t0.5 from 0.15s)
- Specialized Industry Probes: Plastic melt thermocouples up to 2000 bar (Type 901090), steam-tight FOODtemp hygienic insertion probes (Type 901350)

INDUSTRIAL THERMOCOUPLES (DIN EN 60584 & DIN 43710)



JUMO Screw-in Thermocouples with Form B Head (Type 901020)

Type 901020

Industrial screw-in thermocouple with robust Form B terminal head designed for temperature acquisition in liquid and gaseous media, pipelines, boilers, and machinery.

• Temp. Range: -200 to +800 °C • Insertion Length: 160 to 600 mm • Thermocouple Types: J, K, and L • Connection: G 1/2, G 3/4, 1/2 NPT • SIL & Metrological Certified



JUMO Screw-in Thermocouples with Form J Head (Type 901030)

Type 901030

Compact screw-in thermocouple with space-saving Form J aluminum terminal head for tight machinery installations and heating systems.

• Temp. Range: -200 to +800 °C • Insertion Length: 50 to 300 mm • Thermocouple Types: J, K, and L • Protection Tube: Stainless steel 1.4571



JUMO Screw-in Thermocouples with Connecting Cable (Type 901050)

Type 901050

Screw-in thermocouple with integrated flexible compensating cable, stainless steel sheath, and strain-relief transition spring for machine building.

• Temp. Range: -200 to +600 °C • Sheath Material: Stainless steel 1.4571 • Thermocouple Types: K and L • Cable: Silicone, PTFE, or metal braiding



JUMO Push-in Thermocouples with Form A Head (Type 901110)

Type 901110

Heavy-duty push-in high-temperature thermocouple with heavy Form A terminal head and stop flange for furnaces, flue gas, incinerators, and thermal plants.

• Temp. Range: -200 to +1600 °C • Protection Tube Diameter: 15 mm or 22 mm • Thermocouple Types: B, J, K, L, and S • High-temperature ceramic or heat-resistant steel



JUMO Push-in Thermocouples with Form B Head (Type 901120)

Type 901120

Universal push-in thermocouple probe with Form B terminal head and adjustable compression fitting for duct and pipe temperature measurement.

• Temp. Range: -200 to +1200 °C • Insertion Length: 100 to 960 mm • Thermocouple Types: B, J, K, L, and S • Single or Duplex thermocouple elements



JUMO Push-in Bayonet Thermocouples (Type 901190)

Type 901190

Quick-mounting bayonet cap thermocouple with adjustable spring pressure for plastic injection molding machines, extruders, and hot runner tools.

• Temp. Range: 0 to 400 °C • Bayonet Cap: 12 mm / 15 mm dia • Thermocouple Types: J, K, and L • Compensating Cable: Metal braiding over glass fiber

JUMO Mineral-Insulated Thermocouples with Bare Wires (Type 901210)

Type 901210

Flexible, bendable mineral-insulated thermocouple cable with compacted MgO insulation according to DIN 43710 and DIN EN 60584 for high-vibration applications.

• Temp. Range: -200 to +1200 °C • Sheath Diameter: 0.5 mm to 6.0 mm • Fast Response: t0.5 from 0.15 s • Thermocouple Types: J, K, L, N • Vibration and pressure resistant




JUMO Mineral-Insulated Thermocouples with Tab Connector (Type 901240)

Type 901240

Mineral-insulated thermocouple probe terminated with miniature or standard polarized thermocouple connector plug for rapid tool disconnect.

• Temp. Range: -200 to +1200 °C • Connector: Standard / Miniature Tab Connector • Thermocouple Types: J, K, L, N • Inconel 600 / Stainless steel sheath



JUMO Safety Thermocouples DIN EN 14597 (Type 901006)

DIN EN 14597

Certified safety thermocouples for temperature control systems, heat transfer installations, and industrial furnaces tested according to DIN EN 14597.

• Temp. Range: -35 to +1500 °C • DIN EN 14597 Certified • Thermocouple Types: B, K, L, and S • Tested for thermal oil and boiler installations



JUMO Straight Thermocouples with Ceramic Protection Tube (Type 909744)

DIN 43 732

Severe-duty straight thermocouples with ceramic protection tube (Pythagoras / Alsint 99.7) for kilns, glass annealing, and molten non-ferrous metals.

• Temp. Range: -200 to +1600 °C • Length: 220 to 2040 mm • Thermocouple Types: L, K, S, or B • Noble metal PtRh-Pt thermocouples (Type S/B)



JUMO Screw-in Melt Thermocouples for Plastics Industry (Type 901090)

Type 901090

Specialized melt temperature thermocouple with ceramic-insulated sharp or flat probe tip for extrusion heads and plastic melt channels.

• Temp. Range: -40 to +600 °C • Process Connection: 1/2-20 UNF-2A, M18x1.5 • Thermocouple Types: J, K, and L • Pressure Resistant up to 2000 bar



JUMO FOODtemp Food Insertion Thermocouples (Type 901350)

FOODtemp

Hygienic penetration and insertion thermocouple probe with steam-tight ergonomic Teflon handle and penetration tip for meat, baking, and smoking chambers.

• Temp. Range: -100 to +260 °C • Food Grade Design • Thermocouple Type: K • Protection Type: IP67 steam-tight



JUMO Thermocouple Compensating Cables & Thermal Wire (Type 909735)

Type 909735

Standardized compensating cables and thermal wires for the electrical connection between thermocouples and transmitters according to DIN EN 60584 & DIN 43714.

• Temp. Range: -50 to +350 °C • Standards: DIN EN 60584 & DIN 43714 • Insulation: PVC, Silicone, Teflon PTFE, Glass fiber with steel braiding • Color-coded conductors for Type J, K, S, N



JUMO Polarized Plug Connectors for Thermocouples (Type 909760)

Type 909760

Miniature and standard thermocouple plug connectors with true thermoelectric alloy pins to prevent parasitic thermal EMF errors.

• Temp. Range: -60 to +200 °C • Thermocouple Types: J, K, T, E, N, S, R, B • Polarized flat and round pin versions • Glass-filled thermoplastic body

PRESSURE, HUMIDITY & LIQUID ANALYSIS



Industrial Pressure Transmitters (MIDAS / dTRANS p)

MIDAS Series

Piezoresistive and ceramic capacitive pressure transmitters for liquids, steam, gases, and sanitary hygienic lines.

• Ranges: 0-10 mbar to 0-1000 bar • Sanitary clamp, SMS, Varivent connections • Accuracy up to 0.05%



Level Probes & Melt Transmitters

Level & Melt

Hydrostatic submersible level probes for deep wells, boreholes, and tanks, plus melt pressure sensors.

• Submersible PUR/FEP cables • Overvoltage lightning protection



Humidity Transducers & Hygrostats

Humidity & Temp

Capacitive relative humidity and temperature transmitters for HVAC cleanrooms, chambers, and drying rooms.

• Range: 0 to 100% RH • Operating temp -40°C to +180°C



Liquid Analysis & TRON Controllers

Liquid Analysis

Sensors and transmitters for pH, ORP, conductivity, turbidity, and chlorine, alongside TRON multi-channel controllers.

• AQUIS touch multi-channel display • Flow measurement integration

OFFICIAL COMMERCIAL QUOTATION & TECHNICAL SUPPORT

To request an instant pricing quotation, OEM warranty validation, or technical submittals for this brand:

Director: Mr. Pradeep Kulkarni

Mobile: +91 83085 02100 / +91 94220 12179

Email: info@speautomation.com | Online RFQ: www.speautomation.com/request-quote