OFFICIAL BRAND CATALOGUE • SENSORS

GEFRAN

Gefran S.p.A. (Italy / India)

Linear TWIIST® Sensors, Melt Pressure Transducers, Controllers & Drives

DEALER & SUPPLIER



ENGINEERING OVERVIEW & TECHNOLOGY HIGHLIGHTS

Gefran is a premier European manufacturer specializing in industrial sensors, patented Linear TWIIST® contactless multivariable position transducers, linear displacement transducers (LVDT / magnetostrictive), melt pressure transmitters for polymer processing, digital process controllers, and variable frequency drives.

- Patented Linear TWIIST® contactless multivariable transducers measuring position, speed, tilt, and vibration
- High-precision LVDT and non-contact magnetostrictive linear transducers (Hyperwave technology)
- ADV200 high-performance vector inverters with closed-loop field-oriented control
- Industry-standard Melt Pressure Transducers for plastic extrusion up to 538°C
- Microprocessor controllers (Series 600, 800, 1200, 1600) with custom graphic displays
- Extreme measurement repeatability and durability in aggressive industrial environments

LINEAR TWIIST® CONTACTLESS POSITION TRANSDUCERS



LM-C Contactless Linear TWIIST Position Sensor (CANopen)

CANopen Multivariable

Contactless linear position transducer with TWIIST patented multi-variable technology. Measures position, velocity, triaxial tilt, vibration, and internal temperature over CANopen for Industry 4.0 preventive maintenance.

• Strokes: 100 to 1000 mm (1 µm resolution) • Multi-variable: Position, velocity, triaxial tilt, vibration & temp • Protocol: CANopen DS 301 / DSP 406 profile • Ingress & Temp: IP67 sealed, -40°C to +85°C, M12 5-pin



LM-L Contactless Linear TWIIST Position Sensor (IO-Link)

IO-Link Multivariable

Contactless multi-variable linear transducer featuring IO-Link v1.1 interface for smart factory integration, real-time condition monitoring, and edge diagnostics in industrial and mobile hydraulics.

• Strokes: 100 to 1000 mm (1 µm resolution) • Multi-variable: Position, speed, 3-axis inclination, vibration & temp • Protocol: IO-Link v1.1 (COM3 230.4 kBaud) & SIO mode • Ingress & Temp: IP67 sealed body, -40°C to +85°C, M12 5-pole



LS-A Contactless Linear TWIIST Position Sensor (Analog Output)

Analog Output

Patented contactless TWIIST position sensor with self-aligning mounting mechanism, available in single and redundant analog output configurations for machinery and mobile hydraulics.

• Strokes: 50 to 1000 mm • Outputs: 0-10 VDC, 4-20 mA, and ratiometric voltage • Configuration: Direct and reverse analog, single & redundant options • Mounting & Ingress: Self-aligning mechanism, IP67, -40°C to +85°C, M12

SENSORS & LINEAR DISPLACEMENT TRANSDUCERS



Melt Pressure Transducers & Transmitters

Melt Pressure

Mercury-filled, FDA-compliant Oil-filled, and Sodium-Potassium (NaK) impact fluid-free melt pressure sensors for extruders.

• Pressure range: 0-35 bar up to 0-2000 bar • Temp: up to 400°C / 538°C • Output: mV/V, 4-20mA, 0-10V, HART, CANopen, IO-Link



LVDT & Linear Displacement Transducers

LVDT & Linear

Potentiometric position transducers (LT, PK, PC series) and non-contact magnetostrictive sensors (WPG, MK4).

• Strokes from 10mm up to 4000mm • Resolution down to 0.005mm • Rod and profile types • IP67 protection



Temperature & Pressure Transducers

Industrial thermocouples, RTD Pt100 probes, and piezoresistive pressure sensors for hydraulic and pneumatic presses.

• Gauge & absolute pressure • High shock & vibration resistance

CONTROLLERS, INDICATORS & INDUSTRIAL DRIVES



Gefran Microprocessor Controllers (600, 800, 1200, 1600)

Series 600/800

Digital PID controllers with customizable bar-graphs, mathematical functions, timer alarms, and valve motor control.

• Dual 4-digit LED or LCD display • Universal configurable input • RS485 Modbus RTU communication



Gefran Inverters & Variable Frequency Drives (ADV200)

Field-oriented vector inverters engineered for extruders, cranes, metal processing, and high-speed precision spindles.

• Power range: 0.75kW to 1.65MW • Sensorless and closed loop encoder feedback • Integrated safe torque off (STO)

OFFICIAL COMMERCIAL QUOTATION & TECHNICAL SUPPORT

To request an instant pricing quotation, OEM warranty validation, or technical submittals for this brand:

Director: Mr. Pradeep Kulkarni

Mobile: +91 83085 02100 / +91 94220 12179

Email: info@speautomation.com | Online RFQ: www.speautomation.com/request-quote