OFFICIAL BRAND CATALOGUE • POWER

CERMET RESISTORS

Cermet Resistive Products

Industrial Power, Wirewound & Dynamic Braking Resistors

DEALER & SUPPLIER



ENGINEERING OVERVIEW & TECHNOLOGY HIGHLIGHTS

Cermet Resistors is a recognized manufacturer of heavy-duty industrial power resistors, dynamic braking resistors (DBR), and ceramic-encased wirewound resistors engineered to withstand high thermal shock and surge energy.

- Custom engineered wattage ratings from 5W up to multiple megawatts
- Non-inductive winding options for high-frequency switching
- High dielectric insulation resistance up to 3kVAC
- Exceptional surge energy absorption and pulse load capacity
- Corrosion-resistant aluminium enclosures and ceramic cored wirewound construction

DYNAMIC BRAKING & POWER RESISTORS



Dynamic Braking Resistors (DBR)

DBR for VFDs

Heavy-duty braking resistor banks engineered for Variable Frequency Drives (VFD), servo motors, cranes, and hoists.

• Wattage: 100W to 500kW+ • IP20 / IP23 / IP54 protective enclosures • High thermal mass resistor elements • Built-in thermal switch protection



Aluminium Housed Power Resistors

Aluminium Clad

Chassis-mount metal clad resistors encased in anodized extruded aluminium for rapid heat conduction.

• Ratings: 25W, 50W, 100W, 200W, 300W, 500W, 1000W • Compact footprint • Moisture and vibration sealed



Ceramic Encased Wirewound Resistors

Cement-coated and ceramic tubular wirewound power resistors with high pulse withstand capability.

• Wattage: 10W to 1000W • Flame-proof silicone / cement coating • Adjustable tapping options



Neutral Grounding Resistors (NGR) & Load Banks

Substation and generator protection grounding resistors to limit ground fault currents to safe values.

• Custom current / voltage ratings • Stainless steel grid or punched ribbon elements • Outdoor weatherproof enclosure



Precision Shunt Resistors & Current Sensors

Ultra-low resistance current-sensing manganin shunts for battery management, EV chargers, and DC panels.

• Current: 10A to 5000A • Millivolt output: 50mV, 60mV, 75mV, 100mV • High measurement accuracy Class 0.5/0.2

OFFICIAL COMMERCIAL QUOTATION & TECHNICAL SUPPORT

To request an instant pricing quotation, OEM warranty validation, or technical submittals for this brand:

Director: Mr. Pradeep Kulkarni

Mobile: +91 83085 02100 / +91 94220 12179 | Phone: 020-24336245

Email: sales@sahpl.com | info@speautomation.com | Online RFQ: www.speautomation.com/request-quote