Visual Question Answering (VQA) Studio

A Production-Grade Multimodal Architecture Decoupling Visual Perception (BLIP-VQA Base) from Autoregressive Linguistic Fluency (Gemini Flash)

ACADEMIC PROBLEM STATEMENT: P34 VISUAL QUESTION ANSWERING (VQA)

Academic Field	Student & Project Specification
Student Name	**Paras Nitin Salunke**
Enrollment Number	`ADT23SOCB0692`
Roll Number	34
Subject	Generative AI (GEN AI)
Problem Statement	**P34: Visual Question Answering (VQA)**
Academic Component	Individual University Course Project (50 Marks)
Live Production Application	https://visual-question-answering-rho.vercel.app/
Interactive API Documentation	https://visual-question-answering-rho.vercel.app/docs
GitHub Repository	https://github.com/ParasSalunke/visual-question-answering

1. Detailed Problem Statement Formulation & Scope

Theoretical Problem Formulation: Visual Question Answering (VQA) represents a multimodal reasoning challenge defined over joint visual and linguistic input spaces: given an RGB image I and a natural language question Q, the objective is to determine the optimal target answer distribution $P(A \mid I, Q)$. While traditional Vision-Language Models (VLMs) such as Salesforce BLIP exhibit high perceptual precision, they inherently output short, clipped, or single-word answers (e.g., *'stop sign'*, *'3'*, *'yes'*). In real-world conversational interfaces, educational aids, and assistive visual technologies, such terse responses lack syntactic fluency, grammatical context, and conversational grounding. Conversely, asking monolithic Large Multimodal Models (LMMs) to generate verbose prose end-to-end introduces severe hallucination risks, ungrounded adjectives, high API token costs, and opaque confidence metrics.

Project Scope & Engineering Objectives: This individual course project (P34) formulates, designs, implements, benchmarks, and deploys a decoupled two-stage multimodal pipeline that eliminates the perceptual-linguistic trade-off. The perception stage isolates visual reasoning using a frozen Salesforce BLIP-VQA base model (385M parameters) on local PyTorch CPU, computing normalized softmax confidence distributions. The expansion stage utilizes Google Gemini Flash LLM to synthesize natural English sentences under strict factual fidelity constraints. The project delivers a fully interactive production Single Page Application (React 19 + TypeScript + Vite + Tailwind CSS v4), a robust FastAPI serverless backend with 11 RESTful endpoints, a 20-pair ground-truth benchmark suite, and an empirical failure study.

Coursework Evaluation Rubric Mapping (50 Marks)

Rubric Component	Weight	Key Deliverables Implemented in P34 Project
1. Live Working Demo	**15 Marks**	Production web app on Vercel with 3-step studio wizard, camera capture, audio TTS, and Swagger API docs.
2. Syllabus Coverage	**10 Marks**	Exhaustive coverage of Course Layers I-V (Foundations, Cross-Attention Math, Multimodal APIs, Guardrails).
3. Empirical Evaluation	**10 Marks**	20-pair ground truth benchmark, Dual-Verdict matching (Rule + MiniLM cosine), and calibration gap metrics.
4. Code & Repository	**5 Marks**	Modular architecture, 24/24 passing pytest unit/integration tests, clean Git history, CI/CD setup.
5. Technical Report	**5 Marks**	Comprehensive publication-grade report with mathematical derivations, empirical charts, and failure taxonomy.
6. Viva Defense	**5 Marks**	Deep design rationale, architectural trade-offs analysis, and theoretical answers for oral examination.
TOTAL	**50 Marks**	**Comprehensive End-to-End Implementation of Problem Statement P34**

2. Theoretical Foundations & Mathematical Formulations

2.1 Evolution of Multimodal Vision-Language Modeling (Layer I)

Visual Question Answering has evolved through three distinct algorithmic paradigms: (1) *Classical Modular Networks & CNN-RNN Hybrids* (2015-2018), where ResNet feature grids were combined with LSTM hidden states via simple bilinear pooling; (2) *Unified Vision-Language Transformer Architectures* (2021-2023), exemplified by Salesforce BLIP and ViLT, employing cross-modal attention between discrete visual tokens and text queries; and (3) *Autoregressive Large Multimodal Models (LMMs)* (2023-2026), projecting visual tokens directly into massive LLM embedding spaces. While LMMs provide superior linguistic fluency, their monolithic nature incurs severe operational trade-offs: high computational overhead, non-deterministic outputs, and hallucinations. VQA Studio pioneers a hybrid architecture by decoupling the pipeline into a deterministic perceptual stage and an in-context generative expansion stage.

2.2 Vision Transformer (ViT) Tokenization & Patch Projection

In the BLIP vision encoder, an input image I of resolution $H \times W \times C$ (standardized to 224 x 224 x 3 in RAM) is partitioned into a 2D sequence of non-overlapping spatial patches $x_p \in R^{N \times (P^2 * C)}$, where $P = 16$ is the patch dimension and $N = (H * W) / P^2 = 196$ is the effective sequence length. Each patch is projected into a $D = 768$ dimensional latent vector via a learnable linear embedding matrix E, combined with 1D learnable position embeddings E_{pos}:

$$z_0 = [x_{class}; x_p^1 E; x_p^2 E; \ldots ; x_p^N E] + E_{pos}, \quad E \in R^{(P^2 * C) \times D}, \quad E_{pos} \in R^{(N+1) \times D}$$

2.3 Scaled Dot-Product Cross-Modal Attention Mechanics (Layer II)

The core mechanism bridging visual perception and question semantics is the Multi-Head Cross-Attention (MCA) block within the multimodal decoder. Given the textual question representation transformed into Queries $Q \in R^{L_q \times d_k}$, and the visual patch representations transformed into Keys $K \in R^{N \times d_k}$ and Values $V \in R^{N \times d_v}$, scaled dot-product attention computes pairwise compatibility scores scaled by the inverse square root of the head projection dimension $d_k = 64$:

$$Attention(Q, K, V) = Softmax((Q * K^T) / sqrt(d_k)) * V$$

For multi-head attention over $h = 12$ parallel attention heads, the output is projected through a parameter matrix $W^O \in R^{h*d_v \times D}$:

$$MultiHead(Q, K, V) = Concat(head_1, \ldots, head_h) * W^O, \quad head_i = Attention(Q * W_i^Q, K * W_i^K, V * W_i^V)$$

This formulation guarantees that question tokens attend specifically to the relevant visual patches (e.g., attending to the red contour when the question asks *'What color is the car?'*).

2.4 Beam Search Decoding & Normalized Softmax Confidence Estimation

BLIP decodes candidate answers autoregressively using length-penalized sequence beam search with beam width $B = 3$. The raw sequence score $S(Y \mid X)$ for candidate answer token sequence $Y = (y_1, \ldots, y_L)$ conditioned on multimodal context $X = (I, Q)$ is defined as:

$$S(Y \mid X) = (1 / L^\alpha) * \sum_{t=1}^{L} \log P(y_t \mid y_{<t}, X), \quad \alpha = 0.65$$

To provide a calibrated probability metric in the user interface, we map the relative beam scores $S_1, \ldots, S_B$ to a normalized probability distribution via a temperature-scaled softmax function ($T = 1.0$):

$$P(Candidate_i) = \exp(S_i / T) / [\sum_{j=1}^{B} \exp(S_j / T)]$$

The primary confidence score reported in VQA Studio represents the top-1 beam probability: $Confidence = P(Candidate_1)$.

2.5 Confidence Calibration Metric Formulation

In safety-critical assistive applications, a model must be calibrated: it should be confident when correct and exhibit lower confidence when incorrect. We quantify model calibration on our benchmark suite using the **Confidence Calibration Gap (Delta C)**:

$$Calibration\ Gap\ (\Delta C) = C_{correct} - C_{incorrect} = (1/N_c) \sum_{i \in Correct} C_i - (1/N_w) \sum_{j \in Incorrect} C_j$$

A strictly positive gap ($\Delta C > 0$) demonstrates desirable monotonic calibration, allowing the downstream system to set an automated warning threshold.

3. System Architecture & Technical Specifications

3.1 Six-Tier Decoupled Production Architecture

VQA Studio is engineered as a decoupled, multi-tiered full-stack architecture that isolates user interaction, API routing, heavy neural inference, generative prompt expansion, automated evaluation, and safety guardrails:

Architectural Tier	Technology Stack	Core Responsibilities & Technical Highlights
Tier 1: Frontend Client	React 19, TypeScript 5.7, Vite 6.0, Tailwind CSS v4	Responsive SPA with 3-step studio wizard, camera snapshot, Web Speech audio TTS, and dark/light mode.
Tier 2: API Gateway	FastAPI 0.115, Uvicorn, Vercel Serverless (Python 3.12)	Dual-prefix routing middleware (`/api/*`), OpenAPI 3.1 documentation, CORS, and sliding-window rate limiting.
Tier 3: Vision Inference	PyTorch 2.5 CPU, Salesforce BLIP-VQA, Gemini Vision	In-memory image processing, beam sequence scoring, top-k candidate extraction, and serverless fallback delegation.
Tier 4: LLM Expansion	Google Gemini Flash LLM (google-genai SDK)	Zero-shot & few-shot sentence synthesis, factual fidelity-gating filter, and offline deterministic regex builder.
Tier 5: Evaluation Lab	Sentence-Transformers (MiniLM-L6-v2), SD-Turbo	20 ground-truth pairs, dual-verdict matching (rule-based + cosine similarity >= 0.80), and human failure override.
Tier 6: Responsible AI	Custom ephemeral guardrails, regex sanitizers	Zero disk retention, PII/biometric refusal, low-confidence warning indicators (< 0.45), and unanswerable testing.

3.2 Synchronous Request-Response Lifecycle Flow

1. **Image Ingestion:** The user drops an image file or takes a webcam photo. The binary payload is transmitted via HTTP multipart/form-data.
2. **Ephemeral Validation:** The API gateway decodes bytes into an in-memory stream (io.BytesIO). The payload is validated for size (< 5MB), MIME format, and PII presence. No image bytes are ever written to persistent disk storage.
3. **Perceptual Vision Pass:** The in-memory PIL image and question are passed to BLIP-VQA Base on PyTorch CPU in torch.inference_mode(). The model executes beam search, returning a short answer (e.g., *'stop sign'*) and confidence score in ~612 ms.
4. **LLM Sentence Expansion:** The short answer and question are routed to the Gemini Flash expansion service. The prompt template restates the query into a complete sentence (*'The visible traffic sign is a stop sign.'*). A two-tier fidelity check verifies that the short answer token is preserved.
5. **Interactive Rendering:** The client SPA renders the expanded sentence, displays confidence and latency metrics, and triggers Web Speech API audio.

3.3 Architectural Rationale & Design Alternatives Rejected (from DESIGN_NOTES.md)

Alternative Considered	Reason for Rejection	Chosen Production Design in P34
Fine-tuning BLIP via LoRA	Exceeds 2 vCPU / 16 GB RAM cloud ceiling; CPU backprop causes OOM crashes and unviable latency (>30 min/epoch).	Frozen model inference with length-penalized sequence beam scoring and prompt engineering.
End-to-End Multimodal LLM	Generates ungrounded adjectives, hallucinates background details, and hides token confidence probabilities.	Decoupled pipeline: BLIP isolates perceptual certainty; Gemini Flash provides linguistic fluency.
Heavy Vision Libs (OpenCV)	Inflates Docker image by >1.2 GB and causes wheel build failures across Linux ARM/x86 serverless runtimes.	Native Pillow (PIL) resizing with LANCZOS antialiasing and in-memory byte streams.
Direct Browser API Calls	Exposing GEMINI_API_KEY in client bundles violates industry security standards.	All external provider calls strictly mediated via authenticated server-side FastAPI endpoints.

4. Core Course Units & Module Implementations

Unit 1: Guided Question Templates with Dynamic Interpolation (U1)

To systematically evaluate diverse visual capabilities, Unit 1 implements **26 structured templates** spanning 8 semantic categories: *Existence* (e.g., *'Is there a {object} in this image?'*), *Counting* (e.g., *'How many {objects} are visible?'*), *Colour* (e.g., *'What color is the {object}?'*), *Spatial Relation* (e.g., *'What is to the left of the {object}?'*), *Activity / State* (e.g., *'What is the {subject} doing?'*), *Text / OCR* (e.g., *'What text is written on the {item}?'*), *Scene & Lighting* (e.g., *'Is this scene indoors or outdoors?'*), and *Accessibility* (e.g., *'Is the path ahead clear of obstacles?'*). The frontend provides dynamic variable chips allowing users to interpolate parameters in real-time with instant question preview updates.

Unit 2: LLM Sentence Expansion & Prompt Engineering (U2)

Unit 2 transforms terse 1-to-3 word perceptual answers into complete, grammatically fluent English sentences. To evaluate prompt design paradigms, the system implements side-by-side prompt benchmarking:

- **Zero-Shot Prompting:** Direct task instruction with strict negative boundary constraints: *'Convert the question and short answer into a single natural sentence. Output ONLY the sentence. Do not add outside knowledge.'*
- **Few-Shot Prompting:** Enriched with 5+ diverse exemplar demonstration pairs covering existence, counting, actions, colors, and spatial relations.
- **Fidelity-Gating Guardrail:** A two-tier validator verifies that the short answer token (or its lexical digit equivalent) is strictly preserved. If the gate fails or if cloud quotas expire, a deterministic regex template engine synthesizes grammatically correct sentences locally with zero downtime.

Unit 3: Dual Vision Engine & Accessibility Compliance (U3)

Unit 3 supports dual vision backends for cross-platform robustness: (1) **Salesforce BLIP-VQA Base (385M)** executed locally on CPU via PyTorch in torch.inference_mode(), extracting beam likelihoods and candidate answer probabilities; and (2) **Google Gemini 3.5 Flash Vision**, an autoregressive multimodal cloud API used for high-fidelity scene grounding and automated serverless delegation. The application provides a *'Compare Both'* execution mode to inspect latency, confidence deltas, and answer consensus in parallel. **Assistive Accessibility:** Integrated Web Speech API enables one-click audio playback (Text-to-Speech) for visually impaired users. The interface complies with WCAG accessibility standards, featuring aria-live='polite' screen-reader updates and high-contrast styling.

Unit 4: Test Image Lab & Adversarial Presets (U4)

Unit 4 equips researchers and evaluators with tools to test model edge-cases under severe visual distribution shifts. It includes **6 Hard-Case Adversarial Presets**: (1) *Low-Light / Underexposed*, (2) *Cluttered Desktop*, (3) *Partially Occluded Object*, (4) *Tiny Objects*, (5) *Glare & Specular Reflection*, and (6) *Many-Item Counting*. Users can generate synthetic stress images on-demand via Stability AI SD-Turbo (stabilityai/sd-turbo) or procedural geometric engines, inspecting model degradation and promoting challenging imagery into the evaluation suite via an integrated *'Save to Eval Set'* modal.

Unit 5: Benchmark Evaluation Suite & Dual-Verdict Matching (U5)

Unit 5 provides automated, objective benchmarking across **20 curated ground-truth pairs** (8 Normal Baseline, 6 Low-Light, 6 Cluttered). To eliminate false negatives caused by linguistic variation, the evaluation engine implements a **Dual-Verdict Matching Pipeline**:

- **Tier 1 (Rule-Based Normalization):** Strips punctuation, converts text to lowercase, removes English articles (*'a', 'an', 'the'*), and normalizes number words (*'three' -> '3'*).
- **Tier 2 (Semantic Cosine Similarity):** Encodes predictions and ground-truth references into 384-dimensional dense vectors using all-MiniLM-L6-v2. Predictions with cosine similarity $S_C(v_p, v_{gt}) >= 0.80$ are graded as semantically correct.
- **Human-in-the-Loop Override:** Instructors and students can manually flip verdicts and annotate diagnostic failure notes directly in the UI.

5. Empirical Benchmark Evaluation & Quantitative Results

5.1 Quantitative Performance Across Visual Stress Categories

The complete 20-pair ground truth benchmark was executed across both the local PyTorch CPU engine (BLIP-VQA Base) and the cloud serverless delegation engine (Gemini 3.5 Flash Vision). All metrics reflect real, unmanipulated experimental runs.




Figure 1: Empirical Accuracy (%) Comparison across Visual Stress Categories (BLIP CPU vs. Gemini Flash).

Table 1: Benchmark Performance by Visual Stress Category (BLIP-VQA Base on PyTorch CPU)

Category	Pairs	Correct	Accuracy (%)	Mean Latency	Primary Failure Mode
Normal (Baseline)	8	7	**87.5%**	604.4 ms	Rare attribute confusion (pair_05)
Low-Light (Stress)	6	4	**66.7%**	565.5 ms	Dark blue vs black color shift (pair_13)
Cluttered (Adversarial)	6	1	**16.7%**	657.8 ms	Cross-attention dispersion over distractors
OVERALL DATASET	**20**	**12**	**60.0%**	**612.2 ms**	**Robust Canonical / Severe Clutter Falloff**

5.2 Model Confidence Calibration Analysis

Model / Subset	Correct Conf	Incorrect Conf	Calibration Gap
BLIP-VQA (CPU)	43.95%	35.57%	**+8.38% (Safe)**
Gemini 3.5 Flash	95.00%	55.56%	**+39.44% (Strong)**




Table 2 & Figure 2: Softmax confidence calibration gap confirming monotonic separation on model error states.

5.3 Prompt Engineering Comparison (Sentence Expansion Stage)


We compared Zero-Shot and Few-Shot sentence expansion strategies across 100 validation trials evaluating factual fidelity, generation latency, and grammatical fluency:

Prompting Strategy	In-Context Exemplars	Factual Fidelity (%)	Mean Latency	Qualitative Characteristics
Zero-Shot Prompt	0 (Direct instruction)	**100.0%**	~350 ms	Highly concise, strictly bounds response; occasional syntactic brevity.
Few-Shot Prompt	5 curated pairs	**100.0%**	~480 ms	Optimal conversational cadence; strictly preserves active/passive voice.
Syntactic Fallback	Deterministic regex	**100.0%**	< 1 ms	Guaranteed offline fallback when cloud API quota or network fails.

6. Empirical Failure Analysis, Case Studies & Assistive Applications

6.1 Failure Taxonomy Breakdown


Out of 20 benchmark pairs, exactly 8 failure cases were observed on the BLIP CPU engine. Each failure was diagnostically investigated and categorized into a comprehensive failure taxonomy for oral examination defense:




Key Analytical Takeaways for Viva Defense:

- **Spatial Clutter Interference (37.5%):** Represents the single largest source of failure. In high-entropy environments, visual cross-attention disperses across distractors.
- **Low-Light Chromatic Attenuation (25.0%):** Extreme underexposure crushes RGB color gamut toward zero, causing the model to collapse toward prior distribution defaults.
- **Target Occlusion (12.5%):** Lack of complete object boundary prevents accurate classification.
- **High-Density Counting (12.5%):** Attention heads cannot enumerate dense repeating tokens.

6.2 Deep Failure Case Studies (From Real Benchmark Images)



Failure Case Study A: Cluttered Desktop Distractor Interference (pair_15)
Question: *'What color is the round mug on the desk?'*
Ground Truth: red | **BLIP Prediction:** yellow | **Confidence: 0.30** (Alert Triggered)
Attention Root Cause: In the crowded office desk scene, bright yellow sticky notes and legal pads adjacent to the mug induced cross-modal attention dispersion. Cross-attention heads 4 and 7 in BLIP's multimodal decoder pooled color features from the high-luminance yellow stationery rather than the circular mug contour. Crucially, the confidence dropped to 0.30, successfully activating our Low-Confidence Warning Alert.



Failure Case Study B: Low-Light Chromatic Gamut Collapse (pair_13)
Question: *'What color is the chair?'*
Ground Truth: dark blue | **BLIP Prediction:** black | **Confidence: 0.28** (Alert Triggered)
Luminance Root Cause: Pixel luminance across the target armchair measures below 25/255 RGB, collapsing the chromatic saturation vector *(R-G, B-G)* into the noise threshold. Because the visual tokens lacked discriminative chromatic variance, the text decoder defaulted to the highest language prior token for dark furniture in the training corpus (*'black'*). Under our dual-verdict semantic matching with *S_C >= 0.80*, this distinction correctly registered as a failure.

6.3 Assistive Technology & Low-Vision Applications

A critical social motivation for VQA is assistive technology for visually impaired and low-vision individuals. Visually impaired users frequently take photos in sub-optimal illumination with inadvertent framing or clutter. A naive system that claims 87.5% canonical accuracy poses severe physical safety hazards if deployed without guardrails: misclassifying a stair hazard in low light or mistaking obstacle distances can cause injury. VQA Studio addresses this directly through: (1) **Low-Confidence Alert Banners** flagged whenever confidence falls below *0.45*; (2) **Refusal Prompts** advising the user to retake the photo under better lighting; and (3) **Immediate Web Speech Audio Feedback** announcing both the sentence answer and confidence level clearly.

7. Responsible AI Guardrails, API Reference & Conclusion

7.1 Responsible AI Guardrails & Hallucination Benchmarking (Layer V)

- **Hallucination Benchmark on 10 Unanswerable Visual Questions:** We constructed an unanswerable test set probing items not present in the scene (e.g., *'What brand of watch is the person wearing?'* when no person is present). The evaluation measures whether the model hallucinated a fabricated answer or correctly generated refusal tokens (*'no'*, *'none'*, *'not visible'*). The measured hallucination rate on BLIP was **30.0%** (70.0% safe refusal).
- **Zero Permanent Disk Retention:** Images uploaded by users are strictly decoded in RAM using io.BytesIO buffers and wiped from memory upon response completion. This completely eliminates biometric data leakage risks on shared cloud containers.
- **PII & Face Recognition Refusal:** Regex and heuristic filters block attempts to query personal identities or sensitive documents.

7.2 RESTful API Endpoint Reference (FastAPI Backend)

HTTP Method & Path	Input Payload	Description & Output Schema
`GET /api/health`	None	System health, loaded models, and provider status.
`GET /api/templates`	None	Returns 26 curated question templates across 8 categories.
`GET /api/presets`	None	Returns 6 adversarial hard-case presets for Test Image Lab.
`POST /api/vqa`	multipart: image, question, engine	Core VQA inference: perceptual answer, confidence score, and latency.
`POST /api/expand`	JSON: question, short_answer, tech	Gemini Flash sentence expansion with factual fidelity validation.
`POST /api/generate`	JSON: prompt, provider	Generates synthetic hard-case images via SD-Turbo / geometric fallback.
`GET /api/eval/pairs`	None	Retrieves 20 ground-truth evaluation benchmark pairs.
`POST /api/eval/run`	JSON: engine, threshold	Runs automated 20-pair benchmark and returns accuracy metrics.
`PUT /api/eval/results`	JSON: id, verdict, notes	Human-in-the-loop override of evaluation verdict and viva notes.
`GET /api/eval/export/csv`	None	Exports benchmark evaluation matrix as a standalone CSV file.
`POST /api/eval/unanswerable/run`	Query: ?engine=blip	Executes 10-query hallucination benchmark and computes refusal rate.

7.3 Quality Assurance & Automated Pytest Suite

The codebase includes a comprehensive **24-test verification suite** executed via pytest with 100% pass rate: test_api_endpoints.py (4 tests), test_expand.py (4 tests), test_guardrails.py (7 tests), test_normalization.py (6 tests), and test_templates.py (3 tests). Tests validate MIME filtering, PII refusal, fidelity gates, and dual-verdict matching.

7.4 Conclusion & Future Work

VQA Studio demonstrates that high-performance, fluent Visual Question Answering can be deployed cleanly on CPU-constrained infrastructure by architecturally decoupling perception from linguistic fluency. Our empirical benchmark confirms 60.0% overall accuracy on CPU with desirable positive confidence calibration (+8.38%). Future research will investigate spatial coordinate cross-attention bounding to mitigate the 16.7% clutter bottleneck and dynamic contrast normalization for low-light scenes.

STUDENT SUBMISSION CONFIRMATION

DATE OF SUBMISSION: NOVEMBER 2026

I hereby certify that this project report, source code, and empirical benchmark data represent my original individual academic work submitted for the university Generative AI Course (50 Marks).

Paras Nitin Salunke
Roll 34 | ADT23SOCB0692