

Week 1 — Assignment 2

"Build Your Home Lab & Security Audit"

Due: Alongside the Weekend Assignment | Time estimate: 2-3 hours

What you need: Your own laptop/PC, this document, internet

Why This Assignment Exists

The first assignment was about capturing and analyzing traffic. This one is about understanding your own environment — the machine you use every day. A security professional who does not understand their own system cannot protect anyone else's.

You will:

1. Audit your own computer's network configuration
2. Check what is running and listening on your machine
3. Analyze your own network topology
4. Write a mini security assessment of your home network

Task 1 — Your Machine's Network Identity (30 min)

Step 1: Gather your network information

On Windows: Open Command Prompt and run: `ipconfig /all`

On Linux/Mac: Open Terminal and run: `ifconfig` or `ip a`

Step 2: Record the following

Item	Your value
Your computer's hostname	kali
Your IPv4 address	192.168.59.134
Your subnet mask	255.255.255.0
Your default gateway (router IP)	192.168.59.2
Your DNS server(s)	192.168.59.2
Your MAC address	00:0c:29:b8:76:a4
Are you on Wi-Fi or Ethernet?	Ethernet (eth0)

Step 3: Answer these questions

1. What is your network's IP range? (Hint: if you are 192.168.1.105/24, your range is 192.168.1.0 – 192.168.1.255)

Ans. 192.168.59.0 – 192.168.59.255

2. How many devices could potentially be on your network?

Ans. 254

3. Is your DNS server your router or an external service?

Ans. Yes, my DNS server is my router. The DNS address (192.168.59.2) is the same as my default gateway, which means the router is providing DNS service instead of an external DNS provider

4. Why does the MAC address matter? (Hint: it is a Layer 2 identifier — visible even before IP communication)

Ans. It is a unique identifier for a device. It helps to identify a device in a LAN.

Task 2 — What Is Listening on Your Machine? (30 min)

Step 1: Check open ports

On Windows: `netstat -an`

On Linux/Mac: `ss -tlnp`

Step 2: Record what you find

Local Address	Port	State	What service do you think this is?
0.0.0.0	22	LISTENING	SSH service
:::	22	LISTENING	SSH service using IPV6
127.0.0.1		LISTENING	
			(add more rows as needed)

Step 3: Answer these questions

1. How many ports are in LISTENING state?

Ans. 1 port (SSH)

2. Are any of these ports from the Common Ports list in your cheat sheet?

Ans. YES Its SSH

3. Is port 3389 (RDP) open? If yes, what does that mean for security?

Ans. NO it's not open

4. Is port 23 (Telnet) open? If yes, why is that a problem?

Ans. No it's not open

5. What is the difference between 0.0.0.0:PORT and 127.0.0.1:PORT?

Ans. 0.0.0.0:PORT allows connections from all network interfaces, while 127.0.0.1:PORT only allows connections from the local machine itself.

Step 4: Check running processes

On Windows: `tasklist`

On Linux/Mac: `ps aux`

List the top 10 processes you see. Identify any you do not recognize.

Process	Purpose	Recognized?
/sbin/init splash	Starts and manages the Linux system (first process)	Yes
systemd-journald	Collects and manages system logs	Yes
NetworkManager	Manages network connections (Wi-Fi/Ethernet)	Yes
lightdm	Display/login manager for graphical interface	Yes
Xorg	Provides graphical display system	Yes
xfce4-session	Manages the XFCE desktop session	Yes

Process	Purpose	Recognized?
vmtoolsd	VMware tools service for virtual machine support	Yes
dbus-daemon	Handles communication between system applications	Yes
cron	Runs scheduled tasks automatically	Yes
sshd	SSH remote login service	Yes

Task 3 — Scan Your Home Network (30 min)

Step 1: Find your network range

From Task 1, you know your IP and subnet mask. Calculate your network range.

Example: If your IP is 192.168.1.105 and subnet mask is 255.255.255.0:

- Network: 192.168.1.0/24
- Range: 192.168.1.1 to 192.168.1.254

Step 2: Ping sweep your network

On Windows (PowerShell):

```
1..254 | ForEach-Object { ping -n 1 -w 100 192.168.1.$_ | Select-String "Reply from" }
```

On Linux/Mac (Terminal): `for i in {1..254}; do ping -c 1 -W 1 192.168.1.$i | grep "bytes from"; done`

Note: Replace 192.168.1 with YOUR network prefix. This scan is safe — ping only checks if a host responds.

Step 3: Record what you find

IP Address	Responds to ping?	Device type (if you know)
192.168.1.1	Yes	Router/Gateway
192.168.59.2	Yes	Router/Gateway
192.168.59.134	Yes	Kali Linux Machine

Step 4: Answer these questions

1. How many devices responded to your ping sweep?

Ans. 2 devices responded to the ping sweep.

2. Did you find any devices you did not expect?

Ans. No I did not.

3. If an attacker got onto your Wi-Fi, how many devices could they potentially reach?

Ans. An attacker could potentially reach up to 254 devices on the same network.

4. What is the security risk of having all devices on one flat network?

Ans. A flat network allows all devices to communicate with each other. If one device gets compromised, an attacker may move to other devices and access sensitive information

Task 4 — Your Home Network Security Assessment (30 min)

Write a mini security assessment of your own home network. Use everything you learned this week. Write in your own words. Minimum 300 words.

Structure your assessment like this:

1. Network Overview — What is your network range? How many devices? What types?
Ans. My home network uses the IP range 192.168.59.0/24 with my device IP as 192.168.59.134. The network can support up to 254 devices. The devices connected may include laptops, mobile phones, smart devices, and the router.
2. Open Ports & Services — What ports are open? Which services are running?
Ans. I checked open ports using network commands. Some ports were in a listening state, which means services were running on the system. For example, SSH service (port 22) may allow remote connections if enabled. Open ports should be monitored to reduce security risks.
3. Protocol Security — What protocols does your network use? Any unencrypted protocols?
Ans. My network uses protocols like TCP/IP, DNS, HTTPS, and Wi-Fi protocols for communication. HTTPS provides encryption, but unencrypted protocols like HTTP can expose information because the data is sent without protection.
4. CIA Triad Analysis — Confidentiality, Integrity, Availability of your network
Ans. Confidentiality: Protected by passwords and encryption, but can be at risk if weak security is used.
Integrity: Router security and updates help prevent unauthorized changes.
Availability: Keeping devices updated and maintaining the network helps ensure services remain available.
5. AAA Framework Analysis — Authentication, Authorization, Accounting on your network6. Recommendations — List 5 specific improvements you could make

#	Improvement	Why it matters	How to do it
1	Use a strong Wi-Fi password	Use a strong Wi-Fi password	Use a strong Wi-Fi password
2	Enable WPA3/WPA2 security	Protects wireless communication	Change router security settings
3	Keep software updated	Fixes known security vulnerabilities	Regularly update OS, apps, and router firmware
4			
5			

Week 1 Weekend Assignment

"Network Detective Challenge"

Due: End of Week 1 (before Day 5 test) | Time estimate: 3-4 hours across Saturday + Sunday

What you need: Your own laptop/PC, Wireshark (free), internet connection, this document

The Big Picture

Over the past 4 days you learned:

- Day 1: What cybersecurity is — CIA Triad, AAA, threats vs vulnerabilities vs risks
- Day 2: Networking basics — OSI model, TCP/IP, IP addressing, ports, protocols
- Day 3: Common protocols — HTTP/HTTPS, FTP/SFTP, SSH, SMTP, DNS, ICMP + subnetting
- Day 4: Linux & Windows security — permissions, users, hardening, event logs


Now it is time to combine all of that into one real-world mini-project.

This assignment has 3 parts. Do all 3. They build on each other.

Part 1 — Capture & Analyze HTTP Traffic (Day 2 + Day 3 skills)

What to do:

1. Install Wireshark (if not already): <https://www.wireshark.org/download.html>
2. Open Wireshark and start capturing on your active network interface (Wi-Fi or Ethernet).
3. While capturing, open a browser and visit 3 different websites:
 - One that uses HTTP (try <http://neverssl.com> — it deliberately uses HTTP)
 - One that uses HTTPS (try <https://www.google.com>)
 - One of your choice (any site you normally use)
4. Stop the capture after about 60 seconds of browsing.
5. Apply the display filter `http` in Wireshark — this shows only HTTP traffic.
6. Also try the filter `dns` to see DNS queries.
7. Also try the filter `tcp.port == 443` to see HTTPS traffic.



NeverSSL - helping you g... best bus strike mumbai - x YouTube

www.youtube.com

OffSec Kali Linux Kali Tools Kali Docs Kali Forums Kali NetHunter Exploit-DB Google Hacking DB

YouTube

Home Shorts Subscriptions You History

Try searching to get started

Start watching videos to help us build a feed of videos you'll love.

Sign in to like videos, comment, and subscribe.

Sign in

Explore

Shopping Music Movies Show more

More from YouTube

YouTube Premium YouTube Music

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http

No.	Time	Source	Destination	Protocol	Length	Info
328	27.398826643	192.168.59.134	34.107.221.82	HTTP	364	GET /success.txt?ip=1 HTTP/1.1
330	27.620497149	34.107.221.82	192.168.59.134	HTTP	270	HTTP/1.1 200 OK (text/plain)
2076	54.925453863	192.168.59.134	108.158.238.213	OCSP	494	Request
2119	55.215930962	108.158.238.213	192.168.59.134	OCSP	693	Response
3124	240.448615324	192.168.59.134	142.250.134.94	OCSP	481	Request
3139	240.525552209	192.168.59.134	142.250.134.94	OCSP	481	Request
3142	240.553478589	142.250.134.94	192.168.59.134	OCSP	1156	Response
3153	240.627919465	142.250.134.94	192.168.59.134	OCSP	1156	Response
3560	241.792522271	192.168.59.134	142.250.134.94	OCSP	480	Request
3562	241.793422044	192.168.59.134	142.250.134.94	OCSP	480	Request
3827	241.849903916	192.168.59.134	142.250.134.94	OCSP	481	Request
3946	241.883625961	192.168.59.134	142.250.134.94	OCSP	481	Request
3950	241.894732307	142.250.134.94	192.168.59.134	OCSP	1155	Response
3952	241.895233074	192.168.59.134	142.250.134.94	OCSP	481	Request
3960	241.897560351	142.250.134.94	192.168.59.134	OCSP	1155	Response
3976	241.913278533	192.168.59.134	142.250.134.94	OCSP	481	Request
4007	241.951889216	192.168.59.134	142.250.134.94	OCSP	481	Request
4009	241.957162405	142.250.134.94	192.168.59.134	OCSP	1156	Response
4016	241.983008469	142.250.134.94	192.168.59.134	OCSP	1156	Response


Frame 328: Packet, 364 bytes on wire (2912 bits), 364 bytes captured (2912 bits) on Interface
Ethernet II, Src: VMware_b8:76:14 (08:0c:29:b8:76:14), Dst: VMware_e5:8c:b0 (08:15:56:e5:8c:b0)
Internet Protocol Version 4, Src: 192.168.59.134, Dst: 34.107.221.82
Transmission Control Protocol, Src Port: 36286, Dst Port: 80, Seq: 1, Ack: 1, Len: 310
Hypertext Transfer Protocol

0000 00 50 50 e5 8c b0 00 00 20 b0 76 14 08 00 45 00 PV: ...) v: E
0010 01 5e 65 17 40 00 40 06 d8 96 c0 a0 3b 86 22 6b 'e @ : ; 'k
0020 dd 52 8d be 00 50 2a aa ed 76 05 a0 5f 58 50 18 R : P * v _ _ X P
0030 fa f0 fd 3c 00 00 47 45 54 20 2f 73 75 63 63 65 ... < . GE T /succe
0040 73 73 2e 7a 76 74 3f 69 70 70 3a 20 48 54 54 50 ss.txt?ip=1 HTTP
0050 2f 31 2e 31 0d 0a 48 6f 73 74 3a 20 64 65 74 65 /1.1 Ho st: dete
0060 63 74 70 6f 72 74 61 6c 2e 66 69 72 65 66 6f 78 ctportal .firefox
0070 2e 63 6f 6d 0d 0a 55 73 65 72 2d 41 67 65 6e 74 .com Us er-Agent
0080 3a 20 4d 6f 7a 69 6c 6c 61 2f 35 2e 36 20 28 58 : Mozilla/5.0 (X
0090 31 31 30 20 4c 69 6e 75 70 20 78 38 36 5f 36 34 11; Linu x x86_64
00a0 3b 20 72 76 3a 31 34 30 2e 30 29 20 47 65 63 6b ; rv:140 .0) Geck
00b0 6f 2f 32 30 31 30 30 31 30 31 20 46 69 72 65 66 o/201001 01 Firef
00c0 6f 78 2f 31 34 30 2e 30 0d 0a 41 63 63 65 70 74 ox/140.0 - Accept
00d0 3a 20 2a 2f 2a 0d 0a 41 63 63 65 70 74 2d 4c 61 - */* Accept-La
00e0 6e 67 75 61 67 65 3a 20 65 6e 2d 55 53 2c 65 6e nguage: en-US,en
00f0 3b 71 3d 30 2e 35 0d 0a 41 63 63 65 70 74 2d 45 ;q=0.5 - Accept-E
0100 6e 63 6f 64 69 6e 67 3a 20 67 7a 69 70 2c 20 64 ncoding: gzip, d
0110 65 66 6c 61 74 65 0d 0a 43 6f 6e 6e 65 63 74 69 eflate Connecti
0120 6f 6e 3a 20 6b 65 65 70 2d 61 6c 69 76 65 0d 0a on: keep -alive -
0130 50 72 69 6f 72 69 74 79 3a 20 75 3d 34 0d 0a 50 Priority : u=4 P

Hypertext Transfer Protocol: Protocol

Packets: 10777 - Displayed: 90 (0.8%) - Dropped: 0 (0.0%)

Profile: Default



What to write about (answer in your own words):

For each of the 3 websites, answer:

Question	Your answer
What website did you visit?	Neverssl, Google and Youtube
HTTP or HTTPS? How can you tell from the capture?	Neverssl – HTTP, google and youtube - HTTPS
What IP address did your computer connect to?	192.168.59.134
What was the destination port? (80 or 443?)	For neverssl it's 80 and for google and youtube it's 443
For HTTP sites: what information is visible in the packet?	HTTP packets are visible in Wireshark because they are not encrypted. Information like the website address, request details, headers, and webpage data can be seen directly in the packet.

For HTTPS sites: what information is visible vs hidden?	HTTPS packets show connection details like IP addresses, port 443, and TLS information, but the actual data being transferred is hidden because it is encrypted.	
What DNS queries did you see before the connection?	72	Standard query 0x405c A neverssl.com
	70	Standard query 0xf56b A google.com
	75	Standard query 0x7089 A www.youtube.com

Key concepts to connect:

- CIA Triad: When you visited the HTTP site, which part of CIA was violated? (Hint: no encryption = no Confidentiality) ---- When accessing an HTTP website, the main security principle affected is Confidentiality. HTTP does not encrypt the communication between the user and the server. During packet capture in Wireshark, the transmitted information such as website requests, headers, and other data can be viewed in plain text. This means an attacker monitoring the network can read the exchanged information.
- AAA: If the HTTP site had a login page, which AAA function would be exposed? (Hint: Authentication credentials in clear text) ---- When accessing an HTTP website, the main security principle affected is Confidentiality. HTTP does not encrypt the communication between the user and the server. During packet capture in Wireshark, the transmitted information such as website requests, headers, and other data can be viewed in plain text. This means an attacker monitoring the network can read the exchanged information.
- Subnetting: What is the IP range of your home network? (Check with ipconfig or ifconfig) What subnet mask is you using? ---- **IP Address:** 192.168.59.134

Subnet Mask: 255.255.255.0

CIDR Notation: /24

Network Address: 192.168.59.0

Network Range: 192.168.59.0 – 192.168.59.255

Usable Host Range: 192.168.59.1 – 192.168.59.254

Broadcast Address: 192.168.59.255

Where to get help / sources:

- Wireshark official docs: <https://www.wireshark.org/docs/>
- Wireshark 101 tutorial: <https://www.youtube.com/watch?v=TkCSr30UojM>
- How to filter HTTP traffic: In Wireshark, type http in the display filter bar

Part 2 — Subnetting Practice (Day 3 skills)

Using what you learned about subnetting in Day 3, solve these problems. Show your working.

Problem 1

Your home router gives you the network 192.168.1.0/24.

- How many total host addresses are available in this network?

Ans. 254 usable host addresses

- If you split it into 4 equal subnets, what is the new subnet mask in CIDR notation?

Ans. /26 (255.255.255.192)

- What are the network addresses of all 4 subnets?

Ans. 192.168.1.0

192.168.1.64
192.168.1.128
192.168.1.192

- What is the broadcast address of the third subnet?

Ans. 192.168.1.191

- How many usable hosts per subnet after splitting?

Ans. 62 usable hosts per subnet.

Problem 2

You are a network admin for a small office. You have these departments:

- Sales: needs 30 hosts
- Engineering: needs 50 hosts
- HR: needs 10 hosts
- Servers: needs 10 hosts

You are given the network 10.0.0.0/24.

- Design a subnetting scheme that gives each department enough addresses.
- For each department, write: network address, subnet mask (CIDR), usable host range, broadcast address.

Ans. Engineering (Needs 50 hosts)

Needs the largest subnet.

For 50 hosts:

- Required addresses = 64
- Subnet = /26
- Usable hosts = 62

Network Address: 10.0.0.0/26

Subnet Mask: 255.255.255.192

Usable Host Range:

10.0.0.1 – 10.0.0.62

Broadcast Address:

10.0.0.63

Sales (Needs 30 hosts)

For 30 hosts:

- Required addresses = 32
- Subnet = /27
- Usable hosts = 30

Network Address: 10.0.0.64/27

Subnet Mask: 255.255.255.224

Usable Host Range:

10.0.0.65 – 10.0.0.94

Broadcast Address:

10.0.0.95

HR (Needs 10 hosts)

For 10 hosts:

- Required addresses = 16
- Subnet = /28
- Usable hosts = 14

Network Address: 10.0.0.96/28
Subnet Mask: 255.255.255.240
Usable Host Range:
10.0.0.97 – 10.0.0.110
Broadcast Address:
10.0.0.111

Servers (Needs 10 hosts)

For 10 hosts:

- Required addresses = 16
- Subnet = /28
- Usable hosts = 14

Network Address: 10.0.0.112/28
Subnet Mask: 255.255.255.240
Usable Host Range:
10.0.0.113 – 10.0.0.126
Broadcast Address:
10.0.0.127

- Which department gets the largest subnet? Why?

Ans. Engineering requires 50 hosts, which is the highest requirement among all departments. A /26 subnet provides 62 usable host addresses, which is enough for all Engineering devices while avoiding unnecessary IP address wastage.

Problem 3 — Connect to Security

- Why would a security team want to put the Servers department on a different subnet from Sales? (Answer using CIA + AAA concepts)

Ans. A security team would separate the Servers department from Sales by placing them on different subnets to improve network security. This helps protect important server data and systems from unauthorized access.

From the CIA Triad perspective, subnet separation improves Confidentiality because Sales users should not have direct access to sensitive server information. It also improves Integrity by reducing the chance that a compromised Sales computer can modify or damage server data. Availability is improved because security issues in the Sales network are less likely to affect critical servers.

From the AAA framework, separating subnets helps with Authorization because users in Sales can be given only the access they actually need. Being connected to the company network does not mean every user should be allowed to access servers.

- If an attacker compromises a Sales PC, can they directly access a Server on a different subnet? Explain why or why not.

Ans. No, the attacker cannot directly access the Server subnet in most secure networks. When networks are divided into different subnets, communication between them must pass through a router or firewall.

The router/firewall checks the traffic and applies security rules. If the company has proper firewall rules, it can block Sales devices from accessing sensitive Server systems. This prevents attackers from easily moving from one part of the network to another after compromising a device.

- What device controls traffic between subnets? (Hint: think about Day 2 — routers/firewalls)

Ans. A router allows communication between different networks, while a firewall adds security by inspecting traffic and deciding what connections are allowed or blocked. In an organization, these devices help control access between departments and protect important systems like servers.

Part 3 — Connect Everything: CIA + AAA Across All 4 Days

This is the thinking part. Write short paragraphs (3-5 sentences each). No copy-paste — use your own words.

Question 1 — CIA Triad in Action

Pick one of the protocols you studied (HTTP, FTP, SMTP, DNS, SSH, or ICMP). For that protocol:

- How does it support one part of the CIA Triad?

Ans. HTTP supports Availability because it helps users access websites and communicate with web servers easily. It allows information and web pages to be delivered whenever users request them, making online services available.

- How does it fail to protect one part of the CIA Triad?

Ans. HTTP fails to protect Confidentiality because the data sent between the user and the website is not encrypted. This means an attacker who captures the traffic may be able to see the information being transferred.

- What would a security professional do to fix that weakness?

Ans. A security professional would replace HTTP with HTTPS, which uses encryption to secure the communication. They would also make sure websites use valid security certificates and follow secure communication practices.

Question 2 — AAA Framework in Action

Think about logging into a website (like Gmail or any site you use).

- Authentication: How does the site verify you are who you say you are?

Ans. Authentication.

- Authorization: After you log in, what are you allowed to do? What are you NOT allowed to do?

Ans. After logging in, authorization decides what actions you are allowed to perform. For example, you can read your own emails and send messages, but you cannot access another person's emails or change settings you do not have permission to modify.

- Accounting: What records might the site keep about your login? Why?

Ans. It may store information like login time, device details, IP address, and failed login attempts. These records help detect suspicious activity and improve security.

Now answer: What happens if an attacker captures your HTTP traffic from Part 1? Which part of AAA breaks first? Why?

Ans. If an attacker captures HTTP traffic, Authentication breaks first because HTTP does not encrypt data. The attacker may be able to see usernames, passwords, or login information sent between the user and the website. If they get these details, they can pretend to be the real user and access the account, which can later affect authorization and accounting as well.

Question 3 — The Full Attack Story

Imagine this scenario:

An employee at a company uses an unencrypted HTTP connection to log into the internal HR portal from a coffee shop. The company's network is poorly segmented — all departments are on the same subnet 192.168.1.0/24.

Using everything you learned this week, write a short attack story:

1. What can the attacker on the coffee shop Wi-Fi see? (Day 3 — HTTP, packet capture)

Ans. The attacker on the coffee shop Wi-Fi can capture the employee's network traffic using packet capture tools like Wireshark. Because the connection uses HTTP, the data is not encrypted, so the attacker may be able to see sensitive information such as the username, password, and details being sent between the employee and the HR portal.

2. What can the attacker do with those credentials? (Day 1 — Authentication broken, CIA violated)

Ans. Once the attacker gets the employee's login credentials, they can use them to log into the HR portal as that employee. This breaks Authentication because the system cannot tell the difference between the real user and the attacker. It also affects the Confidentiality of the CIA Triad because private employee information can be accessed.

3. Once inside the company network, what can the attacker reach? (Day 3 — subnetting, no segmentation)

Ans. Because the company uses one large subnet (192.168.1.0/24) for all departments, the attacker may be able to reach systems across the entire network. Without proper segmentation, a compromised employee device could allow the attacker to scan and access other departments like HR, Sales, Engineering, or servers more easily.

4. How could the company have prevented this? (Day 4 — hardening, Day 3 — segmentation, Day 1 — controls)

Ans. The company could prevent this by using HTTPS instead of HTTP so login details are encrypted. They should also separate departments into different subnets using network segmentation and apply firewall rules to control access. Additional security measures like multi-factor authentication, strong passwords, regular updates, and monitoring login activity would make it harder for attackers to gain access.

Question 4 — Linux/Windows Connection

- On Day 4 you learned about file permissions (Linux) and Event Viewer (Windows).

- How does the principle of least privilege (Day 4) connect to the AAA Authorization function (Day 1)?

Ans. The principle of least privilege means giving users only the permissions they actually need to do their work. This is connected to AAA Authorization because authorization decides what actions a user is allowed to perform after they log in. For example, a normal employee should not have administrator access because they do not need permission to change important system settings.

- If an attacker gets a shell on a Linux machine, what permission-related files would they look for?

Ans. If an attacker gets access to a Linux system, they may look at files like `/etc/passwd` and `/etc/shadow` to understand user accounts and password information. They may also check permission settings, ownership of files, and `sudo` configuration to find ways to gain higher privileges.

- On Windows, where would you look in Event Viewer to spot a brute-force login attempt?

Ans. On Windows, a security professional would check Event Viewer → Windows Logs → Security. They would look for repeated failed login events, especially Event ID 4625 (Failed login attempt), which can indicate a possible brute-force attack. Monitoring these logs helps identify suspicious login activity.

How to Submit

Create a single document (text file, markdown, or PDF) with:

1. Part 1: Your traffic analysis table + answers + at least 2 screenshots from Wireshark
2. Part 2: All subnetting answers with working shown
3. Part 3: All 4 written answers in your own words

Name it: Week1_Weekend_Assignment_YourName.md (or .txt or .pdf)

Grading Rubric (self-grade before submitting)

Criteria	Points	Your score
Part 1: Traffic captured and analyzed correctly	/25	
Part 1: CIA + AAA connections made	/10	
Part 2: Subnetting calculations correct	/25	
Part 2: Security reasoning about subnets	/10	
Part 3: Own words, no copy-paste	/15	
Part 3: Connections across all 4 days are accurate	/15	
Total	/100	

Tips for Doing This Well

- Do Part 1 first. It is the most hands-on and will make the theory in Parts 2 and 3 feel real.
- Use your notes from all 4 days. This assignment is designed to make you go back and review everything.
- If you get stuck on subnetting, re-read the Day 3 notes. The 192.168.1.0/24 example is your starting point.
- Screenshots matter. In cybersecurity, evidence matters. Show what you captured.
- Write like you are explaining to a friend. If you cannot explain it simply, you do not understand it yet.