



## DBMS EXPERIMENT 17:

High level language extension with cursors

Write a Cursor program using MySQL to retrieve the email-ids(build an email list) of employees from employeeestable.

## OUTPUT:

Program :-1

```
mysql> DELIMITER $$
mysql> CREATE PROCEDURE build_email_list (INOUT email_list varchar(4000))
-> BEGIN
-> DECLARE v_finished INTEGER DEFAULT 0;
-> DECLARE v_email varchar(100) DEFAULT "";
-> DECLARE email_cursor CURSOR FOR
-> SELECT email FROM employees;
-> DECLARE CONTINUE HANDLER FOR
-> NOT FOUND SET v_finished = 1;
-> OPEN email_cursor;
-> get_email:LOOP
-> FETCH email_cursor INTO v_email;
-> IF v_finished = 1 THEN
-> LEAVE get_email;
-> END IF;
-> SET email_list = CONCAT(v_email,";",email_list);
-> END LOOP get_email;
-> CLOSE email_cursor;
-> END $$
Query OK, 0 rows affected (0.00 sec)

mysql> DELIMITER ;
mysql> SET @email_list = "";
Query OK, 0 rows affected (0.00 sec)

mysql> CALL build_email_list(@email_list);
Query OK, 0 rows affected, 1 warning (0.00 sec)

mysql> select @email_list;
+-----+
| @email_list |
+-----+
| stony@marvel.com;kclark@deconics.com;pharry@warnerbros.com; |
+-----+
1 row in set (0.00 sec)
```

