

THE FORMAL THEORY OF REVERSIBLE BEHAVIORAL LEARNING: PATH FUNCTIONALS AND BEHAVIORAL GEOMETRY

Pardhu Sri Rushi Varma Konduru

Malla Reddy University
Hyderabad, Telangana, India
pardhuvarma.cs@gmail.com

ABSTRACT

Prior work established structural irreversibility as a fundamental property of weight-based neural adaptation and introduced Runtime Low-Rank Adaptive Environments (RLAE), a paradigm in which adaptive behavior is encoded in a separable parameter set ϕ , admitting deterministic rollback via an explicit unload operator $\mathcal{K}$, with recoverability validated empirically across model scales. That framework established *that* behavioral change can be structurally reversed—but left open *how* behavioral change evolves within the reversible setting.

This paper develops a geometric and variational theory of behavioral evolution within RLAE. We model adaptation as a continuous trajectory in behavioral parameter space Φ , introduce Behavioral Path Functionals (BPF) as cost functionals over such trajectories, and instantiate them via the Informational Geodesic Path Functional (IGPF), which assigns cost through information-theoretic divergence between successive behavioral states. Extending SVAR, we show that local behavioral sensitivity admits a quadratic approximation inducing a Riemannian metric over Φ , from which Geodesic Behavioral Distance (GBD) is defined as the minimal-cost transformation between behavioral states. Variational analysis of the IGPF yields the central result: optimal behavioral evolution follows geodesics, establishing a formal connection to natural gradient methods.

These results extend RLAE from a structural recoverability guarantee to a geometric theory of behavioral dynamics, establishing adaptation as a path-dependent process governed by information geometry over Φ .

1 INTRODUCTION

Modern neural systems increasingly rely on post-training adaptation to incorporate new tasks, align behavior, and operate under changing objectives. A central question in this setting is whether adaptive changes can be governed, audited, and reversed without compromising the integrity of the underlying model. In prior work [Konduru \(2026\)](#), we examined adaptation from a structural perspective and identified a fundamental limitation of weight-based approaches: modifications applied directly to shared model parameters θ introduce behavioral changes that are entangled with core model representations and cannot, in general, be deterministically undone. We formalized this as *structural irreversibility* and demonstrated empirically that rollback under direct weight mutation requires either explicit parameter checkpoints or retraining, with no guarantee of behavioral equivalence.

To address this limitation, we introduced *Runtime Low-Rank Adaptive Environments* (RLAE) in prior work, a paradigm in which adaptive behavior is represented exclusively in a separable behavioral parameter set ϕ , leaving the core parameter set θ frozen throughout adaptation. An explicit unload operator $\mathcal{K}$ removes the behavioral component entirely, restoring the model to its baseline identity without approximation or retraining. This establishes reversibility as a structural property of the adaptation mechanism itself, validated empirically via the Recoverability Factor (RF), Identity Leakage Score (ILS), and Structural Variance Analysis for Robustness (SVAR) across multiple model scales.

Earlier in prior work, we introduced RLAE as a structural framework for reversible behavioral adaptation, focusing on identity preservation and deterministic rollback under parameter isolation. The scope of that work was centered on the existence and reversibility of behavioral states, establishing recoverability as a first-class property of adaptive systems.

Building on this foundation, a natural next step is to examine not only whether behavioral states can be reached and reversed, but how transitions between such states are structured. In particular, the RLAE formulation treats adaptation as a sequence of discrete updates to ϕ , without explicitly modeling continuity, path dependence, or the geometry of behavioral change over Φ .

This motivates a shift from state-level reasoning to a path-based formalization of adaptation, in which behavioral evolution is treated as a continuous transformation with associated cost, structure, and optimality conditions. In this work, we develop this perspective through the introduction of Behavioral Path Functionals (BPF), which assign a scalar cost to trajectories in Φ , enabling adaptation to be formulated as an optimization problem over paths rather than over parameter values directly. We instantiate this general framework through the *Informational Geodesic Path Functional* (IGPF), in which trajectory cost is induced by information-theoretic divergence between successive behavioral states. This extends the KL-based divergence metrics introduced in prior work from static diagnostic tools into a variational structure governing behavioral transitions.

Geometric structure over Φ arises naturally from SVAR. The quadratic approximation of local behavioral sensitivity under bounded perturbations of ϕ defines a Riemannian metric over the behavioral parameter space, without modifying θ or the unload semantics of RLAE. This metric gives rise to *Geodesic Behavioral Distance* (GBD), the minimal-cost transformation between behavioral states under the induced geometry. Variational analysis of the IGPF then yields the central result of this paper: optimal behavioral evolution follows geodesics under this metric, establishing a formal and principled connection to natural gradient methods.

The contributions of this paper are as follows:

- We introduce *Behavioral Path Functionals* (BPF) as a general variational framework for modeling adaptation as a path-dependent process over the behavioral parameter space Φ .
- We define the *Informational Geodesic Path Functional* (IGPF), which grounds trajectory cost in information-theoretic divergence, extending the divergence metrics of prior work into a variational setting.
- We derive a Riemannian metric over Φ from SVAR, establishing a natural geometric structure over the behavioral parameter space that is consistent with the frozen-core constraint of RLAE.
- We formalize *Geodesic Behavioral Distance* (GBD) and establish through variational analysis that optimal behavioral evolution follows geodesics, connecting reversible adaptation to natural gradient methods.

Together, these results extend RLAE from a structural recoverability guarantee to a complete geometric theory of behavioral dynamics. Adaptation within the reversible setting is reframed as a path-dependent process governed by information geometry over Φ , providing a principled foundation for analyzing the efficiency, stability, and controllability of neural adaptation in modular and long-lived systems.

REFERENCES

Pardhu Sri Rushi Varma Konduru. On the structural limitations of weight-based neural adaptation and the role of reversible behavioral learning, 2026. URL <https://arxiv.org/abs/2603.02934>.

APPENDIX

A ADDITIONAL THEORETICAL DETAILS

For completeness, we restate the progress bound used in the main text.

Progress bound under projected updates. Let

$$\theta^+ = \theta - \eta P_S \nabla \mathcal{J}_t(\theta), \quad (1)$$

where P_S is the orthogonal projector associated with the fixed trainable subset S . Assume that $\mathcal{J}_t$ is L -smooth on a neighborhood containing both θ and θ^+ . Then

$$\mathcal{J}_t(\theta^+) \leq \mathcal{J}_t(\theta) - \eta \|P_S \nabla \mathcal{J}_t(\theta)\|^2 + \frac{L\eta^2}{2} \|P_S \nabla \mathcal{J}_t(\theta)\|^2. \quad (2)$$

Equivalently,

$$\mathcal{J}_t(\theta^+) \leq \mathcal{J}_t(\theta) - \eta \left(1 - \frac{L\eta}{2}\right) \|P_S \nabla \mathcal{J}_t(\theta)\|^2. \quad (3)$$

In particular, if $0 < \eta \leq 1/L$, then

$$\mathcal{J}_t(\theta^+) \leq \mathcal{J}_t(\theta) - \frac{\eta}{2} \|P_S \nabla \mathcal{J}_t(\theta)\|^2. \quad (4)$$

Proof. Since $\mathcal{J}_t$ is L -smooth, for any x, y in the neighborhood of interest,

$$\mathcal{J}_t(y) \leq \mathcal{J}_t(x) + \langle \nabla \mathcal{J}_t(x), y - x \rangle + \frac{L}{2} \|y - x\|^2. \quad (5)$$

Apply 5 with $x = \theta$ and $y = \theta^+$. Using 1,

$$\theta^+ - \theta = -\eta P_S \nabla \mathcal{J}_t(\theta). \quad (6)$$

Substituting into 5 gives

$$\mathcal{J}_t(\theta^+) \leq \mathcal{J}_t(\theta) + \langle \nabla \mathcal{J}_t(\theta), \theta^+ - \theta \rangle + \frac{L}{2} \|\theta^+ - \theta\|^2 \quad (7)$$

$$= \mathcal{J}_t(\theta) - \eta \langle \nabla \mathcal{J}_t(\theta), P_S \nabla \mathcal{J}_t(\theta) \rangle + \frac{L\eta^2}{2} \|P_S \nabla \mathcal{J}_t(\theta)\|^2. \quad (8)$$

Now use that P_S is an orthogonal projector. Hence it is symmetric and idempotent:

$$P_S^\top = P_S, \quad P_S^2 = P_S. \quad (9)$$

Therefore,

$$\langle \nabla \mathcal{J}_t(\theta), P_S \nabla \mathcal{J}_t(\theta) \rangle = \nabla \mathcal{J}_t(\theta)^\top P_S \nabla \mathcal{J}_t(\theta) \quad (10)$$

$$= \nabla \mathcal{J}_t(\theta)^\top P_S^\top P_S \nabla \mathcal{J}_t(\theta) \quad (11)$$

$$= \|P_S \nabla \mathcal{J}_t(\theta)\|^2. \quad (12)$$

Substituting 12 into 8 yields 2. Rearranging gives 3. Finally, if $0 < \eta \leq 1/L$, then

$$1 - \frac{L\eta}{2} \geq \frac{1}{2}, \quad (13)$$

which implies 4. $\square$

B NOTATION SUMMARY

In Tab. 1, we provide an overview of the mathematical notation.

Table 1: Notation used in the theoretical analysis

Symbol	Meaning
$\mathcal{T}_1, \dots, \mathcal{T}_T$	Sequence of tasks observed in continual learning.
T	Number of tasks in the continual learning sequence.
$\theta \in \mathbb{R}^d$	Full model parameter vector.
d	Total number of model parameters.
t	Task index.
m	Optimization-step index within task t .
θ_t	Parameters after completing training on task t .
$\theta_t^{(m)}$	Parameters after m optimization steps on task t .
$\mathcal{L}_t(\theta)$	Current-task loss at task t .
$\Omega_t(\theta; \theta_{1:t-1})$	Method-specific term that preserves previously acquired knowledge.
λ	Weight of the preservation term.
$\mathcal{J}_t(\theta)$	Full task- t objective, defined as $\mathcal{L}_t(\theta) + \lambda\Omega_t(\theta; \theta_{1:t-1})$.
$S \subseteq \{1, \dots, d\}$	Fixed subset of trainable parameter coordinates defining an adaptation regime.
P_S	Orthogonal projector that keeps coordinates in S and zeros out all others.
η	Step size used by the first-order optimizer.
$g_t^{(S)}(\theta)$	Projected current-task update signal, defined as $P_S \nabla \mathcal{L}_t(\theta)$.
$r_t^{(S)}(\theta)$	Projected preservation update signal, defined as $P_S \nabla \Omega_t(\theta; \theta_{1:t-1})$.
$\Gamma_t(S; \theta)$	Interaction term between projected current-task and preservation signals, defined as $\langle g_t^{(S)}(\theta), r_t^{(S)}(\theta) \rangle$.
$P_S \nabla \mathcal{J}_t(\theta)$	Projected gradient of the full task- t objective.
L	Smoothness constant of $\mathcal{J}_t$.
θ^+	One-step projected update from θ , defined in 1.
$\ \cdot\ $	Euclidean norm.
$\langle \cdot, \cdot \rangle$	Standard Euclidean inner product.

C ADDITIONAL EXPERIMENTAL VALUES

Tables 2, 3, 4, 5, and 6 report the numerical values underlying the results shown in Figures ?? and ??, listing average accuracy and average forgetting per training regime for each algorithm across CIFAR-100, MNIST, Fashion-MNIST, QMNIST, and KMNIST, together with standard deviations computed over task orderings.

Table 2: Average Accuracy and Average Forgetting per ordering $\pm$ std. across different training regimes on the CIFAR-100 dataset

Algorithm / Regime	Last Block		Last 2 Blocks		Last 3 Blocks		Last 6 Blocks		Full Finetune (8 Blocks)	
	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget
EWC	0.52 $\pm$ 0.009	0.02 $\pm$ 0.008	0.59 $\pm$ 0.010	0.02 $\pm$ 0.006	0.62 $\pm$ 0.013	0.02 $\pm$ 0.009	0.64 $\pm$ 0.017	0.03 $\pm$ 0.006	0.65 $\pm$ 0.016	0.03 $\pm$ 0.008
LwF	0.62 $\pm$ 0.008	0.05 $\pm$ 0.005	0.70 $\pm$ 0.006	0.08 $\pm$ 0.004	0.75 $\pm$ 0.004	0.08 $\pm$ 0.005	0.79 $\pm$ 0.008	0.07 $\pm$ 0.007	0.80 $\pm$ 0.008	0.07 $\pm$ 0.008
SI	0.57 $\pm$ 0.007	0.04 $\pm$ 0.006	0.61 $\pm$ 0.013	0.09 $\pm$ 0.012	0.62 $\pm$ 0.021	0.14 $\pm$ 0.019	0.62 $\pm$ 0.018	0.18 $\pm$ 0.015	0.63 $\pm$ 0.017	0.18 $\pm$ 0.017
GEM	0.52 $\pm$ 0.008	0.15 $\pm$ 0.010	0.55 $\pm$ 0.010	0.21 $\pm$ 0.011	0.57 $\pm$ 0.012	0.26 $\pm$ 0.011	0.61 $\pm$ 0.012	0.26 $\pm$ 0.014	0.71 $\pm$ 0.008	0.16 $\pm$ 0.011

Table 3: Average Accuracy and Average Forgetting per ordering $\pm$ std. across different training regimes on the MNIST dataset

Algorithm / Regime	Last Block		Last 2 Blocks		Last 3 Blocks		Last 6 Blocks		Full Finetune (8 Blocks)	
	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget
EWC	0.98 $\pm$ 0.012	0.02 $\pm$ 0.015	0.91 $\pm$ 0.082	0.11 $\pm$ 0.103	0.87 $\pm$ 0.083	0.16 $\pm$ 0.104	0.86 $\pm$ 0.060	0.18 $\pm$ 0.075	0.89 $\pm$ 0.078	0.14 $\pm$ 0.097
LwF	0.99 $\pm$ 0.002	0.01 $\pm$ 0.003	0.99 $\pm$ 0.007	0.01 $\pm$ 0.009	0.99 $\pm$ 0.007	0.01 $\pm$ 0.009	0.99 $\pm$ 0.004	0.01 $\pm$ 0.005	0.99 $\pm$ 0.011	0.01 $\pm$ 0.014
SI	0.96 $\pm$ 0.018	0.04 $\pm$ 0.021	0.86 $\pm$ 0.090	0.17 $\pm$ 0.113	0.84 $\pm$ 0.095	0.20 $\pm$ 0.119	0.80 $\pm$ 0.072	0.25 $\pm$ 0.090	0.80 $\pm$ 0.056	0.25 $\pm$ 0.070
GEM	0.96 $\pm$ 0.024	0.04 $\pm$ 0.030	0.94 $\pm$ 0.038	0.08 $\pm$ 0.047	0.92 $\pm$ 0.059	0.10 $\pm$ 0.075	0.93 $\pm$ 0.053	0.09 $\pm$ 0.067	0.95 $\pm$ 0.037	0.06 $\pm$ 0.047

Table 4: Average Accuracy and Average Forgetting per ordering $\pm$ std. across different training regimes on the Fashion MNIST dataset

Algorithm / Regime	Last Block		Last 2 Blocks		Last 3 Blocks		Last 6 Blocks		Full Finetune (8 Blocks)	
	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget
EWC	0.92 $\pm$ 0.043	0.09 $\pm$ 0.054	0.91 $\pm$ 0.057	0.10 $\pm$ 0.072	0.86 $\pm$ 0.063	0.16 $\pm$ 0.079	0.81 $\pm$ 0.082	0.23 $\pm$ 0.103	0.85 $\pm$ 0.041	0.17 $\pm$ 0.051
LwF	0.91 $\pm$ 0.042	0.10 $\pm$ 0.053	0.90 $\pm$ 0.059	0.12 $\pm$ 0.074	0.86 $\pm$ 0.084	0.17 $\pm$ 0.105	0.85 $\pm$ 0.077	0.17 $\pm$ 0.097	0.82 $\pm$ 0.049	0.21 $\pm$ 0.061
SI	0.92 $\pm$ 0.027	0.09 $\pm$ 0.035	0.93 $\pm$ 0.022	0.08 $\pm$ 0.027	0.88 $\pm$ 0.057	0.14 $\pm$ 0.071	0.89 $\pm$ 0.059	0.13 $\pm$ 0.075	0.87 $\pm$ 0.063	0.16 $\pm$ 0.080
GEM	0.97 $\pm$ 0.012	0.02 $\pm$ 0.013	0.96 $\pm$ 0.016	0.03 $\pm$ 0.019	0.95 $\pm$ 0.030	0.05 $\pm$ 0.041	0.91 $\pm$ 0.037	0.08 $\pm$ 0.051	0.94 $\pm$ 0.034	0.06 $\pm$ 0.042

Table 5: Average Accuracy and Average Forgetting per ordering $\pm$ std. across different training regimes on the QMNIST dataset

Algorithm / Regime	Last Block		Last 2 Blocks		Last 3 Blocks		Last 6 Blocks		Full Finetune (8 Blocks)	
	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget
EWC	0.98 $\pm$ 0.008	0.01 $\pm$ 0.010	0.91 $\pm$ 0.073	0.10 $\pm$ 0.090	0.90 $\pm$ 0.061	0.12 $\pm$ 0.076	0.92 $\pm$ 0.053	0.10 $\pm$ 0.067	0.85 $\pm$ 0.084	0.19 $\pm$ 0.104
LwF	0.99 $\pm$ 0.004	0.01 $\pm$ 0.005	0.99 $\pm$ 0.004	0.01 $\pm$ 0.004	0.99 $\pm$ 0.004	0.01 $\pm$ 0.005	0.98 $\pm$ 0.030	0.03 $\pm$ 0.036	0.98 $\pm$ 0.026	0.03 $\pm$ 0.033
SI	0.97 $\pm$ 0.025	0.03 $\pm$ 0.033	0.85 $\pm$ 0.095	0.18 $\pm$ 0.120	0.79 $\pm$ 0.127	0.25 $\pm$ 0.158	0.82 $\pm$ 0.068	0.23 $\pm$ 0.085	0.85 $\pm$ 0.101	0.18 $\pm$ 0.127
GEM	0.96 $\pm$ 0.014	0.04 $\pm$ 0.018	0.93 $\pm$ 0.047	0.08 $\pm$ 0.059	0.93 $\pm$ 0.045	0.08 $\pm$ 0.056	0.94 $\pm$ 0.052	0.08 $\pm$ 0.065	0.95 $\pm$ 0.049	0.06 $\pm$ 0.061

Table 6: Average Accuracy and Average Forgetting per ordering $\pm$ std. across different training regimes on the KMNIST dataset

Algorithm / Regime	Last Block		Last 2 Blocks		Last 3 Blocks		Last 6 Blocks		Full Finetune (8 Blocks)	
	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget	Acc	Forget
EWC	0.94 $\pm$ 0.010	-0.00 $\pm$ 0.009	0.95 $\pm$ 0.016	0.03 $\pm$ 0.022	0.93 $\pm$ 0.028	0.06 $\pm$ 0.037	0.92 $\pm$ 0.033	0.08 $\pm$ 0.045	0.93 $\pm$ 0.026	0.06 $\pm$ 0.033
LwF	0.95 $\pm$ 0.009	0.02 $\pm$ 0.008	0.97 $\pm$ 0.012	0.02 $\pm$ 0.014	0.97 $\pm$ 0.008	0.03 $\pm$ 0.010	0.96 $\pm$ 0.008	0.03 $\pm$ 0.010	0.97 $\pm$ 0.009	0.03 $\pm$ 0.010
SI	0.91 $\pm$ 0.025	0.05 $\pm$ 0.037	0.86 $\pm$ 0.035	0.14 $\pm$ 0.045	0.86 $\pm$ 0.050	0.15 $\pm$ 0.061	0.82 $\pm$ 0.047	0.20 $\pm$ 0.057	0.84 $\pm$ 0.081	0.17 $\pm$ 0.099
GEM	0.91 $\pm$ 0.014	0.07 $\pm$ 0.017	0.91 $\pm$ 0.016	0.10 $\pm$ 0.019	0.91 $\pm$ 0.016	0.10 $\pm$ 0.021	0.92 $\pm$ 0.014	0.09 $\pm$ 0.018	0.92 $\pm$ 0.020	0.09 $\pm$ 0.026