




Technical Parameters

Stroke	50	mm
Thread	M 64X2	
Energy capacity per cycle	1,200	Nm
Energy capacity per hour	174,000	Nm/h
Effective mass range (all codes)	22.0 - 14,000	kg
Impact velocity range	0.41 - 10.4	m/s
Return spring force	60 - 130	N
Damping codes	-0, -1, -2, -3, -4	
Rod end shown	PU cap (std)	
Weight (approx.)	3500	g

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker face at full stroke.
3. Rod end options: N no cap (length A less cap projection 32), PU cap shown, MC metallic cap.
4. Two lock nuts supplied. Accessories on request: FM foot mount, FN / SF flange, SC stop collar, CL clevis.
5. Self-compensating fixed damping - specify damping code at order; no rear adjuster.
6. Selection: [impactcal.netlify.app](#) | [www.adonitech.co.in](#)

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Black oxide	DEBUR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING		REVISION A	
				adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in			
	NAME	SIGNATURE	DATE	TITLE: AC 64-50-M SELF-COMPENSATING SHOCK ABSORBER - GA			
DRAWN	PARESH ADAVANI		24-11-22				
CHK'D				DWG NO. AT/GA/AC/64-50-M			
APPV'D	PARESH ADAVANI		26-11-22				
MFG				A4			
Q.A							
MATERIAL: Alloy steel body, HCP rod		WEIGHT: 3500 g		SCALE: 1:2		SHEET 1 OF 1	