


Technical Parameters

Stroke	13	mm
Thread	M 16X1.5	
Energy capacity per cycle	-	Nm
Energy capacity per hour	-	Nm/h
Effective mass range	-	kg
Return spring force	-	N
Damping	Adjustable (rear adjuster)	
Rod end shown	PU cap (std)	
Weight (approx.)	-	g

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker face at full stroke.
3. Rod end options: N no cap (length A less cap projection 12), PU cap shown, MC metallic cap.
4. Two lock nuts supplied. Accessories on request: FM foot mount, FN / SF flange, SC stop collar.
5. Damping set by rear adjuster at installation.
6. Selection: impactcal.netlify.app | www.adonitech.co.in

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Black oxide		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
						adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in TITLE: AD 16-13-M ADJUSTABLE SHOCK ABSORBER - GA DWG NO. AT/GA/AD/16-13-M A4			
	NAME	SIGNATURE		DATE					
DRAWN	PARESH ADAVANI			30-12-22					
CHK'D									
APPV'D	PARESH ADAVANI			01-01-23					
MFG									
Q.A									
MATERIAL: Alloy steel body, HCP rod		WEIGHT:		SCALE: 1:1					