





FRONT FLANGE MOUNT (FS)



VIEW FROM ROD END (SCALE 1:3)

Technical Parameters

Stroke	400	mm
Energy capacity per cycle	90	kJ
Energy capacity per hour	5,400	kJ/h
Max. buffer force	280	kN
Recoil force (extension)	2.4	kN
Recoil force (compression)	25	kN
Permitted side-load angle	2.5	°
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	49	kg

NOTES

- General arrangement for customer approval - not for manufacture.
- Shown fully extended; dashed line = striker cap face at full stroke.
- Mounting: FS front flange shown. Also available: RS rear flange, SS both flanges, RC rod clevis, TM, FM.
- Optional accessories: B rubber bellow over rod, U urethane striker cap.
- Working temperature 10 to 50 °C; SS construction and sensors on request.
- Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
		adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in							
	NAME		SIGNATURE		DATE		TITLE:		
DRAWN	PARESH ADAVANI				13-05-21		AKHG 100-400-FS HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT		
CHK'D									
APPV'D	PARESH ADAVANI				15-05-21		DWG NO.		A4
MFG							AT/GA/AKHG/100-400-FS		
Q.A									
MATERIAL: Steel body, hard-chrome rod			WEIGHT: 49 kg			SCALE: 1:10		SHEET 1 OF 1	