



REAR FLANGE MOUNT (RS)



VIEW FROM ROD END (SCALE 1:5)

Technical Parameters

Stroke	600	mm
Energy capacity per cycle	200	kJ
Energy capacity per hour	12,800	kJ/h
Max. buffer force	450	kN
Recoil force (extension)	3.5	kN
Recoil force (compression)	40	kN
Permitted side-load angle	2	°
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	95	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: RS rear flange shown. Also available: FS front flange, SS both flanges, RC rod clevis, TM, FM.
4. Optional accessories: B rubber bellow over rod, U urethane striker cap.
5. Working temperature 10 to 50 °C; SS construction and sensors on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

adoniTech

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS
GENERAL ARRANGEMENT - OUTLINE ONLY
DIMENSIONS SUBJECT TO CHANGE
WITHOUT PRIOR NOTICE
PROJECTION: FIRST ANGLE

FINISH: Painted yellow

DEBUR AND BREAK SHARP EDGES

DO NOT SCALE DRAWING

REVISION **A**

	NAME	SIGNATURE	DATE
DRAWN	PARESH ADAVANI		16-06-21
CHK'D			
APPV'D	PARESH ADAVANI		18-06-21
MFG			
Q.A			

MATERIAL: Steel body, hard-chrome rod

WEIGHT: 95 kg

ADONI TECH
Addl. MIDC, Kodoli, Satara 415004
www.adonitech.co.in

TITLE:

AKHG 120-600-RS

HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT

DWG NO. **AT/GA/AKHG/120-600-RS**

A4

SCALE: 1:12

SHEET 1 OF 1