





REAR FLANGE MOUNT (RS)



VIEW FROM ROD END (SCALE 1:4)

Technical Parameters

Stroke	1000	mm
Energy capacity per cycle	410	kJ
Energy capacity per hour	28,000	kJ/h
Max. buffer force	510	kN
Recoil force (extension)	6	kN
Recoil force (compression)	85	kN
Permitted side-load angle	2	°
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	253	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: RS rear flange shown. Also available: FS front flange, SS both flanges, RC rod clevis, TM, FM.
4. Optional accessories: B rubber bellow over rod, U urethane striker cap.
5. Working temperature 10 to 50 °C; SS construction and sensors on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
		adoniTech						ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in	
		NAME		SIGNATURE		DATE		TITLE:	
DRAWN		PARESH ADAVANI				10-09-21		AKHG 150-1000-RS HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT	
CHK'D									
APPV'D		PARESH ADAVANI				12-09-21		DWG NO.	
MFG								AT/GA/AKHG/150-1000-RS A4	
Q.A									
MATERIAL: Steel body, hard-chrome rod				WEIGHT: 253 kg		SCALE: 1:20		SHEET 1 OF 1	