




Technical Parameters

Stroke	600	mm
Energy capacity per cycle	323	kJ
Energy capacity per hour	21,000	kJ/h
Max. buffer force	670	kN
Recoil force (extension)	6	kN
Recoil force (compression)	85	kN
Permitted side-load angle	2.5	°
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	176	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: RS rear flange shown. Also available: FS front flange, SS both flanges, RC rod clevis, TM, FM.
4. Optional accessories: B rubber bellow over rod, U urethane striker cap.
5. Working temperature 10 to 50 °C; SS construction and sensors on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A			
		adoniTech						ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in			
	NAME		SIGNATURE		DATE		TITLE: AKHG 150-600-RS HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT DWG NO. AT/GA/AKHG/150-600-RS A4				
DRAWN	PARESH ADAVANI				02-09-21						
CHK'D											
APPV'D	PARESH ADAVANI				04-09-21						
MFG											
Q.A											
MATERIAL:		Steel body, hard-chrome rod		WEIGHT:		176 kg		SCALE: 1:12		SHEET 1 OF 1	