





FRONT FLANGE MOUNT (FS)

VIEW FROM ROD END

Technical Parameters

Stroke	75	mm
Energy capacity per cycle	6	kJ
Energy capacity per hour	300	kJ/h
Max. buffer force	100	kN
Recoil force (extension)	2.4	kN
Recoil force (compression)	5.3	kN
Permitted side-load angle	3	°
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	8	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: FS front flange shown. Also available: RS rear flange, SS both flanges, RC rod clevis, TM, FM.
4. Optional accessories: B rubber bellow over rod, U urethane striker cap.
5. Working temperature 10 to 50 °C; SS construction and sensors on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow	DEBUR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING		REVISION A			
				adoniTech		ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in			
	NAME		SIGNATURE		DATE		TITLE:		
DRAWN	PARESH ADAVANI				02-03-21		AKHG 65-75-FS		
CHK'D							HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT		
APPV'D	PARESH ADAVANI				04-03-21		DWG NO.		
MFG							AT/GA/AKHG/65-75-FS		
Q.A							A4		
MATERIAL: Steel body, hard-chrome rod			WEIGHT: 8 kg			SCALE: 1:2.5		SHEET 1 OF 1	