





FRONT FLANGE MOUNT (FS)



VIEW FROM ROD END (SCALE 1:2.5)

Technical Parameters

Stroke	150	mm
Energy capacity per cycle	24	kJ
Energy capacity per hour	1,800	kJ/h
Max. buffer force	200	kN
Recoil force (extension)	1.5	kN
Recoil force (compression)	17	kN
Permitted side-load angle	2	°
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	18	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: FS front flange shown. Also available: RS rear flange, SS both flanges, RC rod clevis, TM, FM.
4. Optional accessories: B rubber bellow over rod, U urethane striker cap.
5. Working temperature 10 to 50 °C; SS construction and sensors on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A		
						adoniTech		ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in		
	NAME		SIGNATURE		DATE		TITLE: AKHG 85-150-FS HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT			
DRAWN	PARESH ADAVANI				30-03-21					
CHK'D							DWG NO. AT/GA/AKHG/85-150-FS			
APPV'D	PARESH ADAVANI				01-04-21					
MFG							A4			
Q.A										
MATERIAL: Steel body, hard-chrome rod			WEIGHT: 18 kg			SCALE: 1:4		SHEET 1 OF 1		