





FRONT FLANGE MOUNT (FF)



VIEW FROM ROD END (SCALE 1:5)

Technical Parameters

Stroke	1830	mm
Energy capacity per cycle	238,000	Nm
Energy capacity per hour	6,242,000	Nm/h
Max. shock force	53,200	N
Nominal return force	2,895	N
Max. cycle rate	30	cycles/h
Body length Y / rod projection Z	2142 / 1895	mm
Operating temperature	-10 to +60	°C
Weight (approx.)	118	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker face at full stroke. Internal air/oil accumulator return.
3. Front flange (FF) shown. Also: FR rear flange (not for strokes > 300 mm), TF both flanges, TM, FM foot, CM clevis.
4. Flange and rod-end dimensions indicative - confirm with ADONI TECH before fixing the interface.
5. Custom-orificed: full application data required at order. Bellows, safety cable, sensor on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
								ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in	
NAME		SIGNATURE		DATE		TITLE:			
DRAWN		PARESH ADAVANI		08-05-22		ED 3.0 x 72 HEAVY-DUTY HYDRAULIC BUFFER - GA			
CHK'D									
APPV'D		PARESH ADAVANI		10-05-22		DWG NO. AT/GA/ED/3.0X72 A4			
MFG									
Q.A						SCALE: 1:25 SHEET 1 OF 1			
MATERIAL: Steel body, hard-chrome rod		WEIGHT: 118 kg							