





FRONT FLANGE MOUNT (FF)



VIEW FROM ROD END (SCALE 1:8)

Technical Parameters

Stroke	700	mm
Energy capacity per cycle	215,100	Nm
Energy capacity per hour	4,660,700	Nm/h
Max. shock force	355,900	N
Nominal return force	1,245	N
Max. cycle rate	30	cycles/h
Body length Y / rod projection Z	1098 / 771	mm
Operating temperature	-10 to +60	°C
Weight (approx.)	157	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker face at full stroke. Internal air/oil accumulator return.
3. Front flange (FF) shown. Also: FR rear flange (not for strokes > 300 mm), TF both flanges, TM, FM foot, CM clevis.
4. Flange and rod-end dimensions indicative - confirm with ADONI TECH before fixing the interface.
5. Custom-orificed: full application data required at order. Bellows, safety cable, sensor on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
		NAME		SIGNATURE		DATE		TITLE:	
DRAWN		PARESH ADAVANI				27-06-22		ED 4.0 x 28 HEAVY-DUTY HYDRAULIC BUFFER - GA	
CHK'D									
APPV'D		PARESH ADAVANI				29-06-22		DWG NO.	
MFG								AT/GA/ED/4.0X28	
Q.A								A4	
MATERIAL: Steel body, hard-chrome rod				WEIGHT: 157 kg		SCALE: 1:12		SHEET 1 OF 1	