





FRONT FLANGE MOUNT (FF)



VIEW FROM ROD END (SCALE 1:8)

Technical Parameters

Stroke	800	mm
Energy capacity per cycle	240,500	Nm
Energy capacity per hour	5,114,300	Nm/h
Max. shock force	355,900	N
Nominal return force	1,245	N
Max. cycle rate	30	cycles/h
Body length Y / rod projection Z	1200 / 873	mm
Operating temperature	-10 to +60	°C
Weight (approx.)	170	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker face at full stroke. Internal air/oil accumulator return.
3. Front flange (FF) shown. Also: FR rear flange (not for strokes > 300 mm), TF both flanges, TM, FM foot, CM clevis.
4. Flange and rod-end dimensions indicative - confirm with ADONI TECH before fixing the interface.
5. Custom-orificed: full application data required at order. Bellows, safety cable, sensor on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
						ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in			
	NAME	SIGNATURE		DATE		ED 4.0 x 32 HEAVY-DUTY HYDRAULIC BUFFER - GA			
DRAWN	PARESH ADAVANI			29-06-22					
CHK'D						DWG NO. AT/GA/ED/4.0X32			
APPV'D	PARESH ADAVANI			01-07-22					
MFG						A4			
Q.A									
MATERIAL: Steel body, hard-chrome rod		WEIGHT: 170 kg		SCALE: 1:15		SHEET 1 OF 1			