





FRONT FLANGE MOUNT (FF)



VIEW FROM ROD END (SCALE 1:4)

Technical Parameters

Stroke	800	mm
Energy capacity per cycle	156,000	Nm
Max. shock force	200	kN
Return force (extension)	1.65	kN
Return force (compression)	18	kN
Mounting bolts	4 x M16	
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	69	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: FF front flange shown. Also available: FR rear flange.
4. Optional: B protective bellows over rod, C safety cable, rod position sensor.
5. Nitrogen-charged return; working temperature 10 to 50 °C; SS construction on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A	
						adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in			
NAME		SIGNATURE		DATE		TITLE:			
DRAWN PARESH ADAVANI				01-12-21		EI 100x800-FF HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT			
CHK'D									
APPV'D PARESH ADAVANI				03-12-21		DWG NO.			
MFG						AT/GA/EI/100X800-FF A4			
Q.A									
MATERIAL: Steel body, hard-chrome rod				WEIGHT: 69 kg		SCALE: 1:15		SHEET 1 OF 1	