





REAR FLANGE MOUNT (FR)



VIEW FROM ROD END

Technical Parameters

Stroke	115	mm
Energy capacity per cycle	71,000	Nm
Max. shock force	645	kN
Return force (extension)	5	kN
Return force (compression)	65.7	kN
Mounting bolts	4 x M24	
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	65.7	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: FR rear flange shown. Also available: FF front flange.
4. Optional: B protective bellows over rod, C safety cable, rod position sensor.
5. Nitrogen-charged return; working temperature 10 to 50 °C; SS construction on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A		
						adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in				
	NAME		SIGNATURE		DATE		TITLE: EI 150x115-FR HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT			
DRAWN	PARESH ADAVANI				14-01-22					
CHK'D							DWG NO. AT/GA/EI/150X115-FR			
APPV'D	PARESH ADAVANI				16-01-22					
MFG							A4			
Q.A										
MATERIAL: Steel body, hard-chrome rod			WEIGHT: 65.7 kg			SCALE: 1:6		SHEET 1 OF 1		