





FRONT FLANGE MOUNT (FF)



VIEW FROM ROD END

Technical Parameters

Stroke	150	mm
Energy capacity per cycle	94,000	Nm
Max. shock force	645	kN
Return force (extension)	5	kN
Return force (compression)	65.7	kN
Mounting bolts	4 x M24	
Nitrogen charging pressure	10	bar
Working temperature	10 to 50	°C
Weight (approx.)	65.7	kg

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown fully extended; dashed line = striker cap face at full stroke.
3. Mounting: FF front flange shown. Also available: FR rear flange.
4. Optional: B protective bellows over rod, C safety cable, rod position sensor.
5. Nitrogen-charged return; working temperature 10 to 50 °C; SS construction on request.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A		
		adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in								
	NAME		SIGNATURE		DATE		TITLE: EI 150x150-FF HYDRAULIC CRANE BUFFER - GENERAL ARRANGEMENT			
DRAWN	PARESH ADAVANI				20-01-22					
CHK'D										
APPV'D	PARESH ADAVANI				22-01-22					
MFG										
Q.A							DWG NO.		A4	
MATERIAL: Steel body, hard-chrome rod							WEIGHT: 65.7 kg		AT/GA/EI/150X150-FF	