





SPRING BUFFER - BASE PLATE MOUNT



VIEW FROM STRIKER END

Technical Parameters

Stroke	75	mm
Energy capacity per stroke	390	Nm
Energy capacity per hour	117,000	Nm/h
Base plate	200 sq x 8 thk	mm
Front (striker) plate	Ø131 x 8 thk	mm
Mounting holes	4 x Ø17 on 160 sq	mm
Overall length	285	mm
Return	Helical spring	

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown free; dashed line = striker plate face at full stroke.
3. Base plate mounting, 4 bolts; 4 gusset stiffeners between base plate and housing are standard.
4. MS fabricated housing, painted yellow; spring steel helical spring.
5. Housing cylindrical, MS fabricated; front plate diameter per Adoni Tech design.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A		
						adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in TITLE: SB-1204B SPRING BUFFER - GENERAL ARRANGEMENT DWG NO. AT/GA/SB/1204B A4				
	NAME		SIGNATURE		DATE					
DRAWN	PARESH ADAVANI				09-07-22					
CHK'D										
APPV'D	PARESH ADAVANI				11-07-22					
MFG										
Q.A										
MATERIAL: MS housing, spring steel				WEIGHT:						SCALE: 1:5