





SPRING BUFFER - BASE PLATE MOUNT



Technical Parameters

Stroke	125	mm
Energy capacity per stroke	2,550	Nm
Energy capacity per hour	765,000	Nm/h
Base plate	300 sq x 8 thk	mm
Front (striker) plate	Ø191 x 8 thk	mm
Mounting holes	4 x Ø25 on 240 sq	mm
Overall length	445	mm
Return	Helical spring	

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown free; dashed line = striker plate face at full stroke.
3. Base plate mounting, 4 bolts; 4 gusset stiffeners between base plate and housing are standard.
4. MS fabricated housing, painted yellow; spring steel helical spring.
5. Housing cylindrical, MS fabricated; front plate diameter per Adoni Tech design.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A		
						adoniTech		ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in		
	NAME		SIGNATURE		DATE		TITLE: SB-1204D SPRING BUFFER - GENERAL ARRANGEMENT			
DRAWN	PARESH ADAVANI				13-07-22					
CHK'D							DWG NO. AT/GA/SB/1204D			
APPV'D	PARESH ADAVANI				15-07-22					
MFG							A4			
Q.A										
MATERIAL: MS housing, spring steel			WEIGHT:			SCALE: 1:8		SHEET 1 OF 1		