





SPRING BUFFER - BASE PLATE MOUNT

Technical Parameters

Stroke	250	mm
Energy capacity per stroke	12,500	Nm
Energy capacity per hour	3,750,000	Nm/h
Base plate	400 sq x 12 thk	mm
Front (striker) plate	Ø284 x 12 thk	mm
Mounting holes	4 x Ø26 on 300 sq	mm
Overall length	885	mm
Return	Helical spring	

NOTES

1. General arrangement for customer approval - not for manufacture.
2. Shown free; dashed line = striker plate face at full stroke.
3. Base plate mounting, 4 bolts; 4 gusset stiffeners between base plate and housing are standard.
4. MS fabricated housing, painted yellow; spring steel helical spring.
5. Housing cylindrical, MS fabricated; front plate diameter per Adoni Tech design.
6. Selection: www.cranebuffer.com | impactcal.netlify.app

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL ARRANGEMENT - OUTLINE ONLY DIMENSIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE PROJECTION: FIRST ANGLE		FINISH: Painted yellow		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION A		
						adoniTech ADONI TECH Addl. MIDC, Kodoli, Satara 415004 www.adonitech.co.in				
	NAME		SIGNATURE		DATE		TITLE: SB-1220-H SPRING BUFFER - GENERAL ARRANGEMENT			
DRAWN	PARESH ADAVANI				04-08-22					
CHK'D							DWG NO. AT/GA/SB/1220-H A4			
APPV'D	PARESH ADAVANI				06-08-22					
MFG										
Q.A										
MATERIAL: MS housing, spring steel			WEIGHT:			SCALE: 1:10		SHEET 1 OF 1		