

GIT Introduction:

- git branch: will display current branch in green with star and show other branches.
- git branch {branchname}: To create new branch.
- git checkout {branchname}: To go in particular branch.
- git status: show file list of new change done by you.
- git add {file_path}: To add file in git, after this command your file will track in git.
- git commit -m "{Jirald} - Crud Operation of Product"
- git push origin {branchname}: it will push all your code in cloud repo.
- git diff {file_path}: to check what code changed in particular file.
- Once task done, create Pull request.

1. Server Introduction

2. Virtual Host Setup

a. Go to : /etc/apache2/sites-available

b. Create test.conf

c. Add below code,

i. <VirtualHost *:80>

ii. ServerName pattern.localhost.com

iii. ServerAdmin webmaster@localhost

iv. DocumentRoot /var/www/html/Test

v. ErrorLog \${APACHE_LOG_DIR}/error.log

vi. CustomLog \${APACHE_LOG_DIR}/access.log combined

vii. </VirtualHost>

d. Enable configuration file: sudo a2ensite test.conf

e. Restart Apache: systemctl reload apache2

f. Host entry at the end of file: /etc/hosts:

i. 127.0.0.1 pattern.localhost.com

g. If got Forbidden error, we need to set permission to specific folder,

i. <Directory /home/kaushal/Downloads/Test>

ii. AllowOverride All

iii. Require all granted

iv. </Directory>

3. Magento Installation a. Create account in: <https://account.magento.com/> b. Go to : <https://commercemarketplace.adobe.com/customer/accessKeys/>

c. Create A New Access Key d. Check elasticsearch installed or not : <http://localhost:9200/>

e. sudo service elasticsearch start

f. composer create-project --repository-url=https://repo.magento.com/ magento/project-community-edition <install-directory-name>

g. Run Install Command

i. bin/magento setup:install \

ii. --base-url=http://magento2.localhost.com \

iii. --db-host=localhost \

iv. --db-name=magento2 \

v. --db-user=root \

vi. --db-password=toor1 \

vii. --admin-firstname=K \

viii. --admin-lastname=C \ ix. [--admin-email=k@c.com](mailto:k@c.com) \

x. --admin-user=kaushal \

xi. --admin-password=admin123 \

xii. --language=en_US \

xiii. --currency=USD \

xiv. --timezone=America/Chicago \

xv. --use-rewrites=1 \

xvi. --search-engine=opensearch \

xvii. --opensearch-host=localhost \

xviii. --opensearch-port=9200 \

xix. --opensearch-index-prefix=magento_local \

xx. --opensearch-timeout=15

h. Setup Virtual Host.

i. If admin need Two facto Auth, disable below module.

i. php bin/magento module:disable Magento_AdminAdobeImstwoFactorAuth

ii. php bin/magento module:disable Magento_TwoFactorAuth

1. Magento Admin
2. Setup Virtual Host

3. Magento installation
4. Configuration, category, product, home page, Static, Widget, insert widget.
5. Advance pricing

1. Magento2/generated : php classed of all module.
2. Pub/static: js and html

1. Create Custom Module in: **app/code**
 - a. Create vendor folder.
 - b. Inside vendor folder create custom module.
 - i. Create file: etc/module.xml and registration.php
2. Create Front controller:

- How to create table?
- How to get data?
- How to insert data?
- How to update data?

Deployment Commands:

php bin/magento setup:upgrade

- Clean up php classed, js and html
- Create Database Schema

php bin/magento setup:di:compile

- php classes, add it in generated/code

php bin/magento setup:static-content:deploy

- it ill js and html file in pub.static

php bin/magento c:c;php bin/magento c:f

What are modes in Magento 2?

Default mode is not used for the development and production environment. When in default mode, Magento 2:

- caches static files:

- does not display errors in the clipboard (on the screen), but in the log file (magento2_folder / var / log).

Developer mode is ideal for developers. When in developer mode Magento 2:

- does not cache static files;
- displays a detailed error log on the screen;
- automatically compiles the code;
- allows advanced code debugging.
- works slowly.

Production mode is used in the production environment. When in production mode, Magento 2:

- caches all view-files;
- doesn't change image size, when generating pages;
- stores all errors in the log file;
- allows integrating JavaScript into a bundle;
- works fast.

Database and other configuration will be in : app/etc/env.php

1. Use this command to check current deployment mode.

```
php bin/magento deploy:mode:show
```

2. How to change mode?

```
php bin/magento deploy:mode:set developer
```