

★ custom payment method

-----etc

-->system.xml

```
<section id="payment" type="text" sortOrder="400" showInDefault="1"
showInWebsite="1" showInStore="1">
```

```
    <group id="KitchenPayOffline" translate="label" type="text" sortOrder="30"
showInDefault="1" showInWebsite="1" showInStore="1">
```

```
        <label>Test to Pay Cash On Delivery </label>
```

```
        <field id="active" translate="label" type="select" sortOrder="1" showInDefault="1"
showInWebsite="1" showInStore="0" canRestore="1">
```

```
            <label>Enabled</label>
```

```
            <source_model>Magento\Config\Model\Config\Source\Yesno</source_model>
```

```
        </field>
```

```
        <field id="order_status" translate="label" type="select" sortOrder="20" showInDefault="1"
showInWebsite="1" showInStore="0" canRestore="1">
```

```
            <label>New Order Status</label>
```

```
            <source_model>Magento\Sales\Model\Config\Source\Order>Status\NewStatus</source_
model>
```

```
        </field>
```

```
        <field id="sort_order" translate="label" type="text" sortOrder="100" showInDefault="1"
showInWebsite="1" showInStore="0">
```

```
            <label>Sort Order</label>
```

```
            <frontend_class>validate-number</frontend_class>
```

```
        </field>
```

<field id="title" translate="label" type="text" sortOrder="10" showInDefault="1" showInWebsite="1" showInStore="1" canRestore="1">

<label>Title</label>

</field>

<field id="allowspecific" translate="label" type="allowspecific" sortOrder="50" showInDefault="1" showInWebsite="1" showInStore="0" canRestore="1">

<label>Payment from Applicable Countries</label>

<source_model>Magento\Payment\Model\Config\Source\Allspecificcountries</source_model>

</field>

<field id="specificcountry" translate="label" type="multiselect" sortOrder="51" showInDefault="1" showInWebsite="1" showInStore="0">

<label>Payment from Specific Countries</label>

<source_model>Magento\Directory\Model\Config\Source\Country</source_model>

<can_be_empty>1</can_be_empty>

</field>

<field id="min_order_total" translate="label" type="text" sortOrder="98" showInDefault="1" showInWebsite="1" showInStore="0">

<label>Minimum Order Total</label>

</field>

<field id="max_order_total" translate="label" type="text" sortOrder="99" showInDefault="1" showInWebsite="1" showInStore="0">

<label>Maximum Order Total</label>

</field>

<field id="model"></field>

</group>

</section>

--> config.xml

<payment>

<KitchenPayOffline>

<active>1</active>

<model>Kitchen\Payment\Model\KitchenPayOffline</model>

<order_status>pending</order_status>

<title>test Offline Cash On Delivery</title>

<allowspecific>0</allowspecific>

<group>offline</group>

</KitchenPayOffline>

</payment>

-----Model

-->KitchenPayOffline

<?php

namespace Kitchen\Payment\Model;

/**

* Class KitchenPayOffline

*

```

* @method \Magento\Quote\Api\Data\PaymentMethodExtensionInterface
getExtensionAttributes()
*

* @api
* @since 100.0.2
*/

class KitchenPayOffline extends \Magento\Payment\Model\Method\AbstractMethod
{
    const PAYMENT_METHOD_KITCHENPAYOFFLINE_CODE = 'KitchenPayOffline';

    /**
     * Payment method code
     *
     * @var string
     */
    protected $_code = self::PAYMENT_METHOD_KITCHENPAYOFFLINE_CODE;

    /**
     * Availability option
     *
     * @var bool
     */
    protected $_isOffline = true;
}

```

-----view/frontend/

--> layout/checkout_index_index.xml

```
<?xml version="1.0"?>
```

```
<page xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">
```

```
<body>
```

```
<referenceBlock name="checkout.root">
```

```
<arguments>
```

```
<argument name="jsLayout" xsi:type="array">
```

```
<item name="components" xsi:type="array">
```

```
<item name="checkout" xsi:type="array">
```

```
<item name="children" xsi:type="array">
```

```
<item name="steps" xsi:type="array">
```

```
<item name="children" xsi:type="array">
```

```
<item name="billing-step" xsi:type="array">
```

```
<item name="children" xsi:type="array">
```

```
<item name="payment" xsi:type="array">
```

```
<item name="children" xsi:type="array">
```

```
<item name="renders" xsi:type="array">
```

```
<!-- merge payment method renders here -->
```

```
<item name="children" xsi:type="array">
```

```

        <item name="kitchen-payment" xsi:type="array">

            <item name="component"
xsi:type="string">Kitchen_Payment/js/view/payment/KitchenPayOffline</item>

            <item name="methods" xsi:type="array">

                <item name="KitchenPayOffline" xsi:type="array">

                    <item name="isBillingAddressRequired"
xsi:type="boolean">true</item>

                </item>

                <!-- Add other payment methods as needed -->

            </item>

        </item>

        <!-- <item name="kitchen-payment-new" xsi:type="array">

            <item name="component"
xsi:type="string">Kitchen_Payment/js/view/payment/AllCustomerPayOffline</item>

            <item name="methods" xsi:type="array">

                <item name="AllCustomerPayOffline" xsi:type="array">

                    <item name="isBillingAddressRequired"
xsi:type="boolean">true</item>

                </item>

            </item>

        </item> -->

    </item>

</item>

```

```
        </item>
    </item>
</item>
</item>
</item>
</item>
</item>
</item>
</argument>
</arguments>
</referenceBlock>
</body>
</page>
```

--> js/view/payment/KitchenPayOffline.js

```
define(
    [
        'uiComponent',
        'Magento_Checkout/js/model/payment/renderer-list'
    ],
    function (
        Component,
        rendererList
```

```

){
    'use strict';
    rendererList.push(
    {
        type: 'KitchenPayOffline',
        component: 'Kitchen_Payment/js/view/payment/method-renderer/KitchenPayOffline-
method'
    }
    );
    /** Add view logic here if needed */
    return Component.extend({});
}
);

```

--> js/view/payment/method-renderer/KitchenPayOffline-method

```

define(
[
    'Magento_Checkout/js/view/payment/default'
],
function (Component) {
    'use strict';
    return Component.extend({
        defaults: {
            template: 'Kitchen_Payment/payment/KitchenPayOffline'
        },
    },

```

```

    /** Returns send check to info */
    getMailingAddress: function () {
        return window.checkoutConfig.payment.KitchenPayOffline.mailingAddress;
    },
    /** Returns payable to info */
    /**getPayableTo: function() {
        return window.checkoutConfig.payment.checkmo.payableTo;
    }*/
});
}
);

```

-->template/payment/KitchenPayOffline.html

```

<div
    class="payment-method"
    data-bind="css: {'_active': (getCode() == isChecked())}"
>
    <div class="payment-method-title field choice">
        <input
            type="radio"
            name="payment[method]"
            class="radio"
            data-bind="attr: {'id': getCode()}, value: getCode(), checked: isChecked, click:
selectPaymentMethod, visible: isRadioButtonVisible()"

```

```

/>

<label data-bind="attr: {'for': getCode()}" class="label"
    ><span data-bind="text: getTitle()"></span
></label>

</div>

<div class="payment-method-content">

    <!-- ko foreach: getRegion('messages') -->

    <!-- ko template: getTemplate() --><!-- /ko -->

    <!--/ko-->

    <div class="payment-method-billing-address">

        <!-- ko foreach: $parent.getRegion(getBillingAddressFormName()) -->

        <!-- ko template: getTemplate() --><!-- /ko -->

        <!--/ko-->

    </div>

    <div class="checkout-agreements-block">

        <!-- ko foreach: $parent.getRegion('before-place-order') -->

        <!-- ko template: getTemplate() --><!-- /ko -->

        <!--/ko-->

    </div>

    <div class="actions-toolbar">

        <div class="primary">

            <button

                class="action primary checkout"

                type="submit"

                data-bind=" click: placeOrder, attr: {title: $t('Place Order')}, css:
{disabled: !isPlaceOrderActionAllowed()}, enable: (getCode() == isChecked()) "

```

```
        disabled
    >
        <span data-bind="i18n: 'Place Order'"></span>
    </button>
</div>
</div>
</div>
</div>
```

```
=====
=====
=====
```

★ EventpluginName.xml

```
<?xml version="1.0"?>
```

```
<!--
```

```
/**
```

* Copyright © Magento, Inc. All rights reserved.

* See COPYING.txt for license details.

*/

-->

```
<page layout="3columns" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">
```

```
    <update handle="default_head_blocks"/>
```

```
    <body>
```

```
        <attribute name="id" value="html-body"/>
```

```
        <block name="require.js" class="Magento\Framework\View\Element\Template"
template="Magento_Theme::page/js/require_js.phtml" />
```

```
        <referenceContainer name="after.body.start">
```

```
            <block class="Magento\RequireJs\Block\Html\Head\Config" name="requirejs-
config"/>
```

```
            <block class="Magento\Framework\View\Element\Js\Cookie" name="js_cookies"
template="Magento_Theme::js/cookie.phtml">
```

```
                <arguments>
```

```
                    <argument name="session_config"
xsi:type="object">Magento\Theme\ViewModel\Block\SessionConfig</argument>
```

```
                </arguments>
```

```
            </block>
```

```
            <block class="Magento\Theme\Block\Html\Notices" name="global_notices"
template="Magento_Theme::html/notices.phtml"/>
```

```
        </referenceContainer>
```

```
        <referenceBlock name="top.links">
```

```
            <block class="Magento\Theme\Block\Html\Header" name="header" as="header"
before="-">
```

```
                <arguments>
```

```
                    <argument name="show_part" xsi:type="string">welcome</argument>
```

```
</arguments>

</block>

</referenceBlock>

<referenceContainer name="main.content">

    <block class="Magento\Framework\View\Element\Template"
name="skip_to_content.target" before="-"
template="Magento_Theme::html/skiptarget.phtml">

        <arguments>

            <argument name="target_id" xsi:type="string">contentarea</argument>

        </arguments>

    </block>

</referenceContainer>

<referenceContainer name="header.container">

    <container name="header.panel.wrapper" htmlClass="panel wrapper" htmlTag="div"
before="-">

        <container name="header.panel" label="Page Header Panel" htmlTag="div"
htmlClass="panel header">

            <block class="Magento\Framework\View\Element\Template"
name="skip_to_content" template="Magento_Theme::html/skip.phtml">

                <arguments>

                    <argument name="target" xsi:type="string">contentarea</argument>

                    <argument name="label" translate="true" xsi:type="string">Skip to
Content</argument>

                </arguments>

            </block>

            <block class="Magento\Store\Block\Switcher" name="store_language"
as="store_language" template="Magento_Store::switch/languages.phtml">

                <arguments>
```

```

        <argument name="view_model"
xsi:type="object">Magento\Store\ViewModel\SwitcherUrlProvider</argument>

    </arguments>

</block>

<block class="Magento\Customer\Block\Account\Navigation"
name="top.links">

    <arguments>

        <argument name="css_class" xsi:type="string">header links</argument>

    </arguments>

</block>

</container>

</container>

<container name="header-wrapper" label="Page Header" as="header-wrapper"
htmlTag="div" htmlClass="header content">

    <block class="Magento\Theme\Block\Html\Header\Logo" name="logo">

        <arguments>

            <argument name="logoPathResolver"
xsi:type="object">Magento\Theme\ViewModel\Block\Html\Header\LogoPathResolver</ar
gument>

            <argument name="logo_size_resolver"
xsi:type="object">Magento\Theme\ViewModel\Block\Html\Header\LogoSizeResolver</arg
ument>

        </arguments>

    </block>

</container>

</referenceContainer>

<referenceContainer name="page.top">

```

```

        <block class="Magento\Framework\View\Element\Template"
name="navigation.sections" before="-"
template="Magento_Theme::html/sections.phtml">

        <arguments>

            <argument name="group_name" xsi:type="string">navigation-
sections</argument>

            <argument name="group_css" xsi:type="string">nav-sections</argument>

        </arguments>

        <block class="Magento\Framework\View\Element\Template" name="store.menu"
group="navigation-sections" template="Magento_Theme::html/container.phtml">

            <arguments>

                <argument name="title" translate="true" xsi:type="string">Menu</argument>

            </arguments>

            <block class="Magento\Theme\Block\Html\Topmenu" name="catalog.topnav"
template="Magento_Theme::html/topmenu.phtml" ttl="3600" before="-"/>

        </block>

        <block class="Magento\Framework\View\Element\Text" name="store.links"
group="navigation-sections">

            <arguments>

                <argument name="title" translate="true"
xsi:type="string">Account</argument>

                <argument name="use_force" xsi:type="boolean">true</argument>

                <argument name="text" xsi:type="string"><![CDATA[<!-- Account links --
>]]></argument>

            </arguments>

        </block>

        <block class="Magento\Framework\View\Element\Template"
name="store.settings" group="navigation-sections"
template="Magento_Theme::html/container.phtml">

```

```

        <arguments>

            <argument name="title" translate="true"
xsi:type="string">Settings</argument>

        </arguments>

        <block class="Magento\Store\Block\Switcher" name="store.settings.language"
template="Magento_Store::switch/languages.phtml">

            <arguments>

                <argument name="id_modifier" xsi:type="string">nav</argument>

                <argument name="view_model"
xsi:type="object">Magento\Store\ViewModel\SwitcherUrlProvider</argument>

            </arguments>

        </block>

        <block class="Magento\Directory\Block\Currency"
name="store.settings.currency" template="Magento_Directory::currency.phtml">

            <arguments>

                <argument name="id_modifier" xsi:type="string">nav</argument>

            </arguments>

        </block>

    </block>

    </block>

    <container name="top.container" as="topContainer" label="After Page Header Top"
htmlTag="div" htmlClass="top-container"/>

        <block class="Magento\Theme\Block\Html\Breadcrumbs" name="breadcrumbs"
as="breadcrumbs"/>

    </referenceContainer>

    <referenceContainer name="columns.top">

        <block class="Magento\Theme\Block\Html\Title" name="page.main.title"
template="Magento_Theme::html/title.phtml"/>

```

```
<container name="page.messages" htmlTag="div" htmlClass="page messages">

    <block class="Magento\Framework\View\Element\Template"
name="ajax.message.placeholder" template="Magento_Theme::html/messages.phtml"/>

    <block class="Magento\Framework\View\Element\Messages" name="messages"
as="messages" template="Magento_Theme::messages.phtml"/>

</container>

</referenceContainer>

<referenceContainer name="main">

    <container name="content.top" label="Main Content Top">

        <block name="main_css_preloader" as="main_css_preloader"
template="Magento_Theme::html/main_css_preloader.phtml"
ifconfig="dev/css/use_css_critical_path"/>

    </container>

    <container name="content" label="Main Content Area"/>

    <container name="content.aside" label="Main Content Aside"/>

    <container name="content.bottom" label="Main Content Bottom"/>

</referenceContainer>

<referenceContainer name="page.bottom.container">

    <container name="page.bottom" label="Before Page Footer" htmlTag="div"
htmlClass="content"/>

</referenceContainer>

<referenceContainer name="footer-container">

    <container name="footer" as="footer" label="Page Footer" htmlTag="div"
htmlClass="footer content">

        <block class="Magento\Store\Block\Switcher" name="store_switcher"
as="store_switcher" template="Magento_Store::switch/stores.phtml"/>

        <block class="Magento\Framework\View\Element\Html\Links"
name="footer_links">
```

```
<arguments>

    <argument name="css_class" xsi:type="string">footer links</argument>

</arguments>

</block>

<block class="Magento\Theme\Block\Html\Footer" name="copyright"
template="Magento_Theme::html/copyright.phtml"/>

    <block class="Magento\Framework\View\Element\Template" name="report.bugs"
template="Magento_Theme::html/bugreport.phtml"
ifconfig="design/footer/report_bugs"/>

</container>

</referenceContainer>

<referenceContainer name="before.body.end">

    <block class="Magento\Theme\Block\Html\Footer" name="absolute_footer"
template="Magento_Theme::html/absolute_footer.phtml" />

</referenceContainer>

<referenceContainer name="content">

    <block class="Magento\Framework\View\Element\FormKey" name="formkey"/>

</referenceContainer>

</body>

</page>
```

```
=====
=====
=====
```

★ knockout thi grid show

without using php

===>

create controller

New/Index.php

```
<?php
```

```
// namespace Kitchen\KnockOut\Controller\Newpage;
```

```
// use Magento\Customer\Model\Session;
```

```
// class View extends \Magento\Framework\App\Action\Action
```

```
// {
```

```
//     protected $_pageFactory;
```

```
//     public function __construct(
```

```
//         \Magento\Framework\App\Action\Context $context,
```

```

//    Session $_session,
//    \Magento\Framework\View\Result\PageFactory $pageFactory)
// {
//    $this->_pageFactory = $pageFactory;
//    $this->_session = $_session;
//    return parent::__construct($context);
// }

// public function execute()
// {
//    echo "Knockout";
//    return $this->_pageFactory->create();
// }
//}

```

```

namespace Kitchen\KnockOut\Controller\NewIndex;

```

```

use Magento\Framework\App\Action\Action;
use Magento\Framework\App\Action\Context;
use Magento\Framework\View\Result\PageFactory;

```

```

class Index extends Action

```

```

{
    /**
     * @var PageFactory
     */

```

```
protected $resultPageFactory;
```

```
/**
```

```
 * View constructor.
```

```
 * @param Context $context
```

```
 * @param PageFactory $resultPageFactory
```

```
 */
```

```
public function __construct(
```

```
    Context $context,
```

```
    PageFactory $resultPageFactory
```

```
) {
```

```
    $this->resultPageFactory = $resultPageFactory;
```

```
    parent::__construct($context);
```

```
}
```

```
/**
```

```
 * Execute view action
```

```
 *
```

```
 * @return \Magento\Framework\Controller\ResultInterface
```

```
 */
```

```
public function execute()
```

```
{
```

```
    // echo "Knockout New Page";
```

```
    $resultPage = $this->resultPageFactory->create();
```

```
    return $resultPage;
```

```
}
```

```
}
```

```
===>
```

```
create layout
```

```
view/frontend/layout/kout_new_index.xml
```

```
<?xml version="1.0"?>
```

```
<page layout='1column' xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">
```

```
    <body>
```

```
        <referenceContainer name="content">
```

```
            <block class="Kitchen\KnockOut\Block\Grid\ViewAbstract" before="-"
cacheable="false" template="Kitchen_KnockOut::grid/knockoutview.phtml">
```

```
                <arguments>
```

```
                    <argument name="jsLayout" xsi:type="array">
```

```
                        <item name="components" xsi:type="array">
```

```
                            <item name="sample-grid" xsi:type="array">
```

```
                                <item name="component"
xsi:type="string">Kitchen_KnockOut/js/view/grid</item>
```

```
                            </item>
```

```
                        </item>
```

```
                    </argument>
```

```
                </arguments>
```

```
            </block>
```

```
</referenceContainer>

</body>

</page>
```

===>

create templates

view/frontend/templates/grid/knockoutView.phtml

```
<div id="block-sample-grid" data-bind="scope:'sample-grid'" class="block">

    <!-- ko template: getTemplate() --><!-- /ko -->

</div>

<script type="text/x-magento-init">

    {

        "#block-sample-grid": {

            "Magento_Ui/js/core/app": <?php /* @escapeNotVerified */ echo $block-
>getJsLayout();?>

        }

    }

</script>

<script>

    window.grid_data = <?= $block->getValues();?>

</script>
```

==>

create js

view/frontend/web/js/view/grid.js

```
define([
    'jquery',
    'ko',
    'uiComponent',
    'Kitchen_KnockOut/js/view/grid/price'
], function ($, ko, component, priceRender) {
    "use strict";
```

```
    return component.extend({
        items: ko.observableArray([]),
        columns: ko.observableArray([]),
        defaults: {
            template: 'Kitchen_KnockOut/grid',
        },
        initialize: function () {
            this._super();
            this._render();
        },
        _render: function () {
            this._prepareColumns();
            this._prepareItems();
        }
    });
});
```

```

},
_prepareItems: function () {
//  var data = window.grid_data;

    this.addItems(window.grid_data);
},
_prepareColumns: function () {
    this.addColumn({headerText: "ID", rowText: "entity_id", renderer: ""});
    this.addColumn({headerText: "First Name", rowText: "name", renderer: ""});
    this.addColumn({headerText: "Last Name", rowText: "sku", renderer: ""});
    this.addColumn({headerText: "Email", rowText: "price", renderer: ""});
    this.addColumn({headerText: "Gender", rowText: "sort_order", renderer: ""});
    this.addColumn({headerText: "Birth Date", rowText: "creation_time", renderer: ""});
    this.addColumn({headerText: "Profile Image", rowText: "update_time", renderer: ""});
},
addItem: function (item) {
    item.columns = this.columns;
    this.items.push(item);
},
addItems: function (items) {
    for (var i in items) {
        this.addItem(items[i]);
    }
},
addColumn: function (column) {
    this.columns.push(column);
}

```

```
});  
});
```

==>

create another js

view/frontend/web/js/view/grid/price.js

```
define(['jquery', 'ko', 'uiComponent'], function ($, ko, component) {  
    "use strict";  
    return component.extend({  
        render: function (item) {  
            return "$" + item.price.toFixed(2);  
        }  
    });  
});
```

==>

create html

view/frontend/web/template/grid.html

```
<table class="data table base list">
```

```

<thead>
    <tr data-bind="foreach: columns">
        <th data-bind="text: headerText"></th>
    </tr>
</thead>
<tbody data-bind="foreach: items">
    <tr data-bind="foreach: columns">
        <td><span data-bind="text: renderer ? renderer.render($parent) : $parent[rowText]
"></span></td>
    </tr>
</tbody>
</table>

```

==>

create block

Grid/ViewAbstract.php

```
<?php
```

```
namespace Kitchen\KnockOut\Block\Grid;
```

```
use Kitchen\Product\Model\GalleryFactory;
```

```
class ViewAbstract extends \Magento\Framework\View\Element\Template
```

```

{
    protected $configProvider;
    protected $customerFactory;
    protected $_layoutProcessors;

    public function __construct(
        \Magento\Framework\View\Element\Template\Context $context,
        \Magento\Checkout\Model\CompositeConfigProvider $configProvider,
        GalleryFactory $customerFactory,
        array $layoutProcessors = [],
        array $data = []
    ){
        parent::__construct($context, $data);
        $this->configProvider = $configProvider;
        $this->customerFactory = $customerFactory;
        $this->_layoutProcessors = $layoutProcessors;
    }

    public function getJsLayout()
    {
        foreach ($this->_layoutProcessors as $processor) {
            $this->jsLayout = $processor->process($this->jsLayout);
        }
        return parent::getJsLayout();
    }
}

```

```

public function getValues()
{
    $getGallery = $this->customerFactory->create();
    $getData = $getGallery->getCollection();
    $getArr = [];
    foreach ($getData as $row) {
        $getArr[] = $row->getData();
    }
    return json_encode($getArr);
}
}

```

==>

create model

self

dataprovider

<?php

```
namespace Kitchen\KnockOut\Model\Prod;
```

```
use Kitchen\KnockOut\Model\ResourceModel\Customer\CollectionFactory;
```

```
class DataProvider extends \Magento\Ui\DataProvider\AbstractDataProvider
{
    /**
     * @var Collection
     */
    protected $collection;

    /**
     * @var array
     */
    protected $loadedData;

    /**
     * @param string $name
     * @param string $primaryFieldName
     * @param string $requestFieldName
     * @param CollectionFactory $collectionFactory
     * @param array $meta
     * @param array $data
     */
    public function __construct(
        $name,
        $primaryFieldName,
        $requestFieldName,
        CollectionFactory $collectionFactory,
        array $meta = [],
```

```

        array $data = []
    ){
        $this->collection = $collectionFactory->create();
        parent::__construct($name, $primaryFieldName, $requestFieldName, $meta, $data);
    }

    /**
     * @return array
     */
    public function getData()
    {
        if (isset($this->loadedData)) {
            return $this->loadedData;
        }

        $items = $this->collection->getItems();

        /** @var Rule $rule */
        foreach ($items as $model) {
            $this->loadedData[$model->getId()] = $model->getData();
        }

        return $this->loadedData;
    }
}

```

=====

★ Normal Grid

https://www.rohanhapani.com/magento-2-create-admin-grid-and-form-without-ui-component/#google_vignette

1- etc/adminhtml/menu.xml

2- etc/acl.XML

3- controller/adminhtml/cust

----->index.php

4- block/adminhtml/Grid/Grid.php (addColumn)

5- view/adminhtml/layout/new_customer_index.xml

6- view/adminhtml/layout/new_customer_edit.xml

7- Controller/Adminhtml/cust

---->MassStatus.php

---->MassDelete.php

---->Save.php

---->Delete.php

---->Edit.php

---->Grid.php

---->NewAction.php

----->index.php(same as no-3)

8- Block

--->/Adminhtml/Grid.php

--->/Adminhtml/Grid/Grid.php (same as no- 4)

--->/Adminhtml/Grid/Edit.php

--->/Adminhtml/Grid/Edit/Form.php,Tabs.php

--->Adminhtml/Grid/Edit/Tab/Main.php

=====

=====

=====

★ New POPUP

--->

Block/Index

```
<?php
```

```
namespace Task\JsKo\Block;
```

```
class Index extends \Magento\Framework\View\Element\Template
```

```
{
```

```
}
```

--->

Controller/Index/Index

```
<?php
```

```
namespace Task\JsKo\Controller\Index;
```

```
class Index extends \Magento\Framework\App\Action\Action
```

```
{
```

```
protected $_pageFactory;
```

```
public function __construct(
```

```
\Magento\Framework\App\Action\Context $context,
```

```
\Magento\Framework\View\Result\PageFactory $pageFactory)
```

```
{
```

```
$this->_pageFactory = $pageFactory;
```

```
return parent::__construct($context);
```

```
}
```

```
public function execute()
```

```
{
```

```
    echo"ko";
```

```
return $this->_pageFactory->create();
```

```
}
```

```
}
```

```
-----  
-----
```


--->

view/frontend/layout/user12_index_index

<?xml version="1.0"?>

<page xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" layout="1column"
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">

<body>

<referenceContainer name="content">

<block class="Task\JsKo\Block\Index"

name="abcd_index_index"

template="Task_JsKo::test/index.phtml"/>

</referenceContainer>

</body>

</page>

--->
view/frontend/templates/test/index.phtml


```
<button id="custom-button">Open POPup</button>
```

```
<div id="custom-popup" style="display: none;">
```

```
  <p>This is the popup content.</p>
```

```
</div>
```

```
<script>
```

```
  require(['jquery', 'Magento_Ui/js/modal/modal'], function($, modal)
```

```
  {
```

```
    $(document).ready(function()
```

```
    {
```

```
      var options =
```

```
      {
```

```
        type: 'popup',
```

```
        responsive: true,
```

```
        innerScroll: true,
```

```
        title: 'Popup Title',
```

```
        buttons: []
```

```
      };
```

```
var popup = modal(options, $('#custom-popup'));

$('#custom-button').click(function()
{
    $('#custom-popup').modal('openModal');
});

});

});
</script>
```


add close button


```
<button id="custom-button">Open POPup</button>
<div id="custom-popup" style="display: none;">
    <p>This is the popup content.</p>
</div>
```

```
<script>
require(['jquery', 'Magento_Ui/js/modal/modal'], function($, modal)
{
    $(document).ready(function()
```

```
{
  var options =
  {
    type: 'popup',
    responsive: true,
    innerScroll: true,
    title: 'Popup Title',
    buttons: [
      {
        text: $.mage.__('Close'),
        class: 'action-primary',
        click: function(e)
        {
          this.closeModal();
        }
      }
    ]
  };

  var popup = modal(options, $('#custom-popup'));

  $('#custom-button').click(function()
  {
    $('#custom-popup').modal('openModal');
  });
});
```

```
});  
</script>
```

```
-----  
-----  
add save button  
-----  
-----
```

```
<button id="custom-button">Open POPup</button>  
<div id="custom-popup" style="display: none;">  
  <p>This is the popup content.</p>  
</div>
```

```
<script>  
  require(['jquery', 'Magento_Ui/js/modal/modal'], function($, modal)  
  {  
    $(document).ready(function()  
    {  
      var options =  
      {  
        type: 'popup',  
        responsive: true,  
        innerScroll: true,  
        title: 'Popup Title',
```

```
buttons: [  
  {  
    text: $.mage.__('Close'),  
    class: 'action-primary',  
    click: function(e)  
    {  
      this.closeModal();  
    }  
  },  
  {  
    text: $.mage.__('Save'),  
    class: 'action-secondary',  
    click: function(e)  
    {  
      this.closeModal();  
    }  
  }  
]
```

```
};
```

```
var popup = modal(options, $('#custom-popup'));
```

```
$('#custom-button').click(function()  
{  
  $('#custom-popup').modal('openModal');
```

```
    });  
    });  
    });  
</script>
```

```
-----  
-----  
-----  
-----
```

add save data

- name
- gender(radio)
- email(send to person)
- password(don't show)
- image(add)
- status(active & deactive)

when click save submit data

```
-----  
-----  
-----  
-----
```

```
<button id="custom-button">Open POPup</button>  
<div id="custom-popup">
```

```
<form id="registrationForm" action="#" method="post">

  <div>

    <label for="name">Name:</label>

    <input type="text" id="name" name="name" required>

  </div>

  <br/>

  <div>

    <label>Gender:</label>

    <label><input type="radio" name="gender" value="male"> Male</label>

    <label><input type="radio" name="gender" value="female"> Female</label>

    <label><input type="radio" name="gender" value="other"> Other</label>

  </div>

  <br/>

  <div>

    <label for="email">Email:</label>

    <input type="email" id="email" name="email" required>

  </div>

  <br/>

  <div>

    <label for="password">Password:</label>

    <input type="password" id="password" name="password" required>

  </div>

  <br/>

  <div>

    <label for="image">Image:</label>

    <input type="file" id="image" name="image">

  </div>

</form>
```

```
</div>

<br/>

<div>

  <label>Status:</label>

  <select id="status" name="status">

    <option value="active">Active</option>

    <option value="inactive">Inactive</option>

  </select>

</div>

<br/>

<button type="submit">Submit</button>

<br/>

</form>

</div>
```

```
-----
-----
---->
etc/db_schema.xml
-----
-----
```

```
<?xml version="1.0"?>
```

```
<schema xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
xsi:noNamespaceSchemaLocation="urn:magento:framework:Setup/Declaration/Schema/
etc/schema.xsd">
```

```
    <table name="user_ko_registration" resource="default" engine="innodb"
comment="User Registration Table">
```

```
        <column xsi:type="smallint" name="entity_id" unsigned="true" nullable="false"
identity="true"
```

```
            comment="Entity ID" />
```

```
        <column xsi:type="varchar" name="name" nullable="false" length="255"
comment="Name" />
```

```
        <column xsi:type="varchar" name="email" nullable="false" length="255"
comment="Email" />
```

```
        <column xsi:type="varchar" name="gender" nullable="false" length="10"
comment="Gender" />
```

```
        <column xsi:type="varchar" name="image" nullable="true" length="255"
comment="Image" />
```

```
        <column xsi:type="smallint" name="status" nullable="false" comment="Is Status" />
```

```
        <column xsi:type="timestamp" name="creation_time" on_update="false"
nullable="false" default="CURRENT_TIMESTAMP"
```

```
            comment="Creation Time" />
```

```
<column xsi:type="timestamp" name="update_time" on_update="true"
nullable="false" default="CURRENT_TIMESTAMP"
```

```
comment="Modification Time" />
```

```
<constraint xsi:type="primary" referencelId="PRIMARY">
```

```
<column name="entity_id" />
```

```
</constraint>
```

```
</table>
```

```
</schema>
```

```
-----
```

```
-----
```

```
--->
```

```
Controller\Index\Save
```

```
-----
```

```
-----
```

```
<?php
```

```
namespace Task\JsKo\Controller\Index;
```

```
use Magento\Framework\App\Action\Context;
```

```

use Magento\Framework\Controller\Result\JsonFactory;

use Task\JsKo\Model\UserFactory;

class Save extends \Magento\Framework\App\Action\Action
{
    protected $_jsonFactory;

    protected $_userFactory;

    public function __construct(
        Context $context,
        JsonFactory $jsonFactory,
        UserFactory $userFactory
    ){
        $this->_userFactory = $userFactory;
        $this->_jsonFactory = $jsonFactory;
        parent::__construct($context);
    }

    public function execute()
    {
        $result = $this->_jsonFactory->create();

        try{
            $jsonData = $this->getRequest()->getContent();
            $data = json_decode($jsonData, true);

```

```

// Validate the required fields
if (!isset($data['name']) || !isset($data['email'])) {
    throw new \InvalidArgumentException('Name and Email are required fields.');
```



```

}

$name = $data['name'];
$gender = isset($data['gender']) ? $data['gender'] : '';
$email = $data['email'];
$image = isset($data['image']) ? $data['image'] : '';
$status = isset($data['status']) ? $data['status'] : '';

$user = $this->_userFactory->create();
$user->setName($name);
$user->setEmail($email);
$user->setGender($gender); // Assuming you have a method like this in your model
$user->setImage($image); // Similarly, assuming methods for image and status
$user->setStatus($status);

$user->save();

// return $result->setData([
//     'success' => true,
//     'data' => $user->getData()
// ]);
} catch (\Exception $e) {
    return $result->setData([

```

```
        'success' => false,  
        'error' => $e->getMessage()  
    ]);  
}  
}  
}
```


--->

view/frontend/templates/test/index.phtml

FOR Save Data in data base

<button id="custom-button">Open POPup</button>

<div id="custom-popup">

```
<form id="registrationForm" action="#" method="post">

  <div>

    <label for="name">Name:</label>

    <input type="text" id="name" name="name" required>

  </div>

  <br/>

  <div>

    <label>Gender:</label>

    <label><input type="radio" name="gender" value="male"> Male</label>

    <label><input type="radio" name="gender" value="female"> Female</label>

    <label><input type="radio" name="gender" value="other"> Other</label>

  </div>

  <br/>

  <div>

    <label for="email">Email:</label>

    <input type="email" id="email" name="email" required>

  </div>

  <br/>

  <div>

    <label for="password">Password:</label>

    <input type="password" id="password" name="password" required>

  </div>

  <br/>

  <div>

    <label for="image">Image:</label>

    <input type="file" id="image" name="image">

  </div>

</form>
```

```
</div>

<br/>

<div>

    <label>Status:</label>

    <select id="status" name="status">

        <option value="1">Active</option>

        <option value="0">Inactive</option>

    </select>

</div>

<br/>

</form>

</div>


<script>

    require(['jquery', 'Magento_Ui/js/modal/modal', 'mage/storage'], function($, modal,
storage) {

        $(document).ready(function() {

            var options = {

                type: 'popup',

                responsive: true,

                innerScroll: true,

                title: 'User Registration',

                buttons: [

                    {
```

```

text: $.mage.__('Close'),
class: 'action-primary',
click: function(e) {
    this.closeModal();
}
},
{
text: $.mage.__('Submit'),
class: 'action-primary',
click: function() {

storage.post(
    'user12/index/save', // Adjust this URL to match your controller route
    JSON.stringify({
        name: $('#name').val(),
        gender: $('input[name=gender]:checked').val(),
        email: $('#email').val(),
        password: $('#password').val(),
        image: $('#image').val(),
        status: $('#status').val()
    }),
    true
).done(function(response) {
    $('#custom-popup').modal('closeModal');

}).fail(function(response) {

```

```
        });  
    }  
}  
]  
};
```

```
var popup = modal(options, $('#custom-popup'));
```

```
$('#custom-button').click(function() {  
    $('#custom-popup').modal('openModal');  
});
```

```
});
```

```
});
```

```
</script>
```

for send email....

save.php

```
<?php
```

```
namespace Task\JsKo\Controller\Index;
```

```
use Magento\Framework\App\Action\Context;
use Magento\Framework\Controller\Result\JsonFactory;
use Task\JsKo\Model\UserFactory;
use Magento\Framework\Mail\Template\TransportBuilder;
use Magento\Framework\Translate\Inline\StateInterface;
use Magento\Framework\App\Config\ScopeConfigInterface;
use Magento\Store\Model\ScopeInterface;
```

```
class Save extends \Magento\Framework\App\Action\Action
```

```
{
```

```
    protected $_jsonFactory;
```

```
    protected $_userFactory;
```

```
    protected $_transportBuilder;
```

```
    protected $_inlineTranslation;
```

```
    protected $_scopeConfig;
```

```
    public function __construct(
```

```
        Context $context,
```

```
        JsonFactory $jsonFactory,
```

```
        UserFactory $userFactory,
```

```
        TransportBuilder $transportBuilder,
```

```
        StateInterface $inlineTranslation,
```

```
        ScopeConfigInterface $scopeConfig
```

```
    ){
```

```
        $this->_userFactory = $userFactory;
```

```
        $this->_jsonFactory = $jsonFactory;
```

```
$this->_transportBuilder = $transportBuilder;
$this->_inlineTranslation = $inlineTranslation;
$this->_scopeConfig = $scopeConfig;
parent::__construct($context);
}
```

```
public function execute()
```

```
{
```

```
    $result = $this->_jsonFactory->create();
```

```
    try{
```

```
        $jsonData = $this->getRequest()->getContent();
```

```
        $data = json_decode($jsonData, true);
```

```
        // Validate the required fields
```

```
        if (!isset($data['name']) || !isset($data['email'])) {
```

```
            throw new \InvalidArgumentException('Name and Email are required fields.');
```

```
        }
```

```
        $name = $data['name'];
```

```
        $gender = isset($data['gender']) ? $data['gender'] : '';
```

```
        $email = $data['email'];
```

```
        $image = isset($data['image']) ? $data['image'] : '';
```

```
        $status = isset($data['status']) ? $data['status'] : '';
```

```
        $user = $this->_userFactory->create();
```

```

        $user->setName($name);
        $user->setEmail($email);
        $user->setGender($gender);
        $user->setImage($image);
        $user->setStatus($status);
        $user->save();

        // Send email
        $this->sendEmail($name, $email);

        return $result->setData([
            'success' => true,
            'data' => $user->getData()
        ]);
    } catch (\Exception $e) {
        return $result->setData([
            'success' => false,
            'error' => $e->getMessage()
        ]);
    }
}

private function sendEmail($name, $email)
{
    $sender = [

```

```

        'name' => $this->_scopeConfig->getValue('trans_email/ident_general/name',
ScopeInterface::SCOPE_STORE),

        'email' => $this->_scopeConfig->getValue('trans_email/ident_general/email',
ScopeInterface::SCOPE_STORE),

    ];

    $templateVars = [

        'name' => $name,

        'email' => $email,

    ];

    $templateOptions = ['area' => \Magento\Framework\App\Area::AREA_FRONTEND,
'store' => \Magento\Store\Model\Store::DEFAULT_STORE_ID];

    $transport = $this->_transportBuilder

        ->setTemplateIdentifier('Test_Email_template') // Specify your email template
identifier here

        ->setTemplateOptions($templateOptions)

        ->setTemplateVars($templateVars)

        ->setFrom($sender)

        ->addTo($email)

        ->getTransport();

    $transport->sendMessage();

}

}

```

etc/email_templates.xml

```
<?xml version="1.0"?>
```

```
<config xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="urn:magento:module:Magento_Email:etc/email_templates.xsd">
```

```
    <template id="Test_Email_template" label="Hello World" file="main1.html" type="html"
module="Task_JsKo" area="frontend"/>
```

```
</config>
```

--->

view/frontend/email/main1.html

```
<!--@subject Email Subject @-->
```

```
<!--@vars
```

```
{"store url=\"\"": "Store Url",
```

```
"skin url=\"images/logo_email.gif\" _area='frontend'": "Email Logo Image"}
```

```
@-->
```

```
<!--@styles
```

```
body,td { color:#2f2f2f; font:11px/1.35em Verdana, Arial, Helvetica, sans-serif; }
```

```
@-->
```

```
{{template config_path="design/email/header_template"}}
```

```
<table cellpadding="0" cellspacing="0" border="0" width="100%">
```

```
<tr>
```

```
<td align="center" valign="top" style="padding:20px 0 20px 0">
```

```
<table bgcolor="#FFFFFF" cellpadding="10" cellspacing="0" border="0"
width="650" style="border:1px solid #E0E0E0;">
```

```
<tr>
```

```
<td valign="top">
```

```
<h1 style="font-size:22px;font-weight:normal;line-height:22px;margin:0 0
11px 0;">{{trans "Hello"}},</h1>
```

```
</td>
```

```
</tr>
```

```
<tr>
```

```
<td>
```

```
<table cellpadding="0" cellspacing="0" border="0" width="650">
```

```
<tbody>
```

```
<tr>
```

```
<td colspan="2" valign="top" style="font-size:12px;padding:7px 9px
9px 9px;border:1px solid #EAEAEA;">
```

```
    {{var message}}
```

```
</td>
```

```
</tr>
```

```
</tbody>
```

```
</table>
```

```
</td>
```

```
</tr>
```

```
<tr>
```

```
<td bgcolor="#EAEAEA" align="center" style="background:#EAEAEA;text-align:center;">
```

```
<center>
```

```
<p style="font-size:12px;margin:0;">
```

```
<strong>{{trans "Thank you"}}</strong>
```

```
</p>
```

```
</center>
```

```
</td>
```

```
</tr>
```

```
</table>
```

```
</td>
```

```
</tr>
```

```
</table>
```

```
{{template config_path="design/email/footer_template"}}
```

```
=====
=====
=====
```

simple popup button

Block/Index

```
<?php

namespace Kitchen\Notice\Block;

class Index extends \Magento\Framework\View\Element\Template
{

    protected $customerSession;

    public function __construct(
        \Magento\Framework\View\Element\Template\Context $context,
        \Magento\Customer\Model\Session $customerSession
    ){
        parent::__construct($context);
        $this->customerSession = $customerSession;
    }

    public function sayHello()
    {
        return __('Hello World');
    }

    public function isLoggedIn()
    {
        return $this->customerSession->isLoggedIn();
    }
}
```

--->

view/frontend/layout/default.xml

```
<?xml version="1.0"?>
```

```
<page xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">
```

```
    <referenceContainer name="page.messages">
```

```
        <block class="Kitchen\Notice\Block\Index" name="messages"
template="Kitchen_Notice::messages.phtml"/>
```

```
    </referenceContainer>
```

```
</page>
```

view/frontend/templates/message.phtml

```
<div style="display: none;" id="modal-notification">
```

```
    <div id="popup">
```

```
        <label>Title:</label>
```

```
        <label>Description:</label>
```

```
    </div>
```

```
</div>
```

```
<script>
```

```
require([
    'jquery',
    'Magento_Ui/js/modal/modal'
], function($, modal) {
    var popupOptions = {
        type: 'popup',
        responsive: true,
        innerScroll: true,
        title: $.mage.__('Notification'),
        buttons: [{
            text: $.mage.__('Continue'),
            class: 'mymodal1',
            click: function () {
                $('#modal-notification').modal("closeModal");
            }
        }]
    };

    var popup = modal(popupOptions, $('#modal-notification'));

    $('#modal-notification').modal("openModal");
});
</script>
```

```
=====
=====
=====
```

simple popup button

Block/Index

```
<?php
```

```
namespace Kitchen\Notice\Block;
```

```
class Index extends \Magento\Framework\View\Element\Template
```

```
{
```

```
    protected $customerSession;
```

```
    public function __construct(
```

```
        \Magento\Framework\View\Element\Template\Context $context,
```

```
        \Magento\Customer\Model\Session $customerSession
```

```
    ){
```

```
        parent::__construct($context);
```

```
        $this->customerSession = $customerSession;
```

```
    }
```

```
public function sayHello()
{
    return __('Hello World');
}
```

```
public function isLoggedIn()
{
    return $this->customerSession->isLoggedIn();
}
}
```

--->

view/frontend/layout/default.xml

```
<?xml version="1.0"?>
```

```
<page xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">
```

```
    <referenceContainer name="page.messages">
```

```
        <block class="Kitchen\Notice\Block\Index" name="messages"
template="Kitchen_Notice::messages.phtml"/>
```

```
    </referenceContainer>
```

```
</page>
```

view/frontend/templates/message.phtml

```
<div style="display: none;" id="modal-notification">
```

```
    <div id="popup">
```

```
        <label>Title:</label>
```

```
        <label>Description:</label>
```

```
    </div>
```

```
</div>
```

```
<script>
```

```
    require([
```

```
        'jquery',
```

```
        'Magento_Ui/js/modal/modal'
```

```
    ], function($, modal) {
```

```
        var popupOptions = {
```

```
            type: 'popup',
```

```
            responsive: true,
```

```
            innerScroll: true,
```

```
            title: $.mage.__('Notification'),
```

```
            buttons: [{
```

```
                text: $.mage.__('Continue'),
```

```
                class: 'mymodal1',
```

```
                click: function () {
```

```
                    $('#modal-notification').modal("closeModal");
```

```
    }  
  }  
};
```

```
var popup = modal(popupOptions, $('#modal-notification'));
```

```
$('#modal-notification').modal("openModal");
```

```
});
```

```
</script>
```