

Effective Code Commenting

Code Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
  
    if criteria == "gaussian":  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        total = low+high  
        return low, high, total  
  
    elif criteria == 'whisker':  
        M_FACTOR = 1.5  
        QUART1 = 0.25  
        QUART3 = 0.75  
        low = len(data[data < data.quantile(QUART1)-(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        total = low+high  
        return low,high,total
```

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    avg,std = data.mean(),data.std  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    avg,std = data.mean(),data.std  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    avg,std = data.mean(),data.std  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

```
def removing_gaussian_outliers(data, n_std):  
    # calculating mean and standard deviation  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian emperical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    avg,std = data.mean(),data.std  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

```
def removing_gaussian_outliers(data, n_std):  
    # calculating mean and standard deviation  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian emperical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Redundant and time taking?

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    avg,std = data.mean(),data.std  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

```
def removing_gaussian_outliers(data, n_std):  
    # calculating mean and standard deviation  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian emperical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Redundant and time taking?

Yes and No

Code Commenting

When Writing Code:

- Code should be self explanatory and readable

Code Commenting

When Writing Code:

- Code should be self explanatory and readable
- If too complex, add comment

Code Commenting

When Writing Code:

- Code should be self explanatory and readable
- If too complex, add comment
- Comments increase length

Code Commenting

When Writing Code:

- Code should be self explanatory and readable
- If too complex, add comment
- Comments increase length
- Time taking

Code Commenting

When Writing Code:

- Code should be self explanatory and readable
- If too complex, add comment
- Comments increase length
- Time taking

Comments should be a last resort, but necessary if code is complex

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    # calculating mean and standard deviation  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian empirical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    # calculating mean and standard deviation  
    avg, std = data.mean(), data.std  
    # returning filtered data between left/right threshold by gaussian empirical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    # calculating mean and standard deviation  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian empirical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Code Commenting

```
def removing gaussian ouliers(data, n std):  
    # calculating mean and standard deviation  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian emperical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```


Code Commenting

```
def removing_gaussian_outliers(data, n_std):  
    avg,std = data.mean(),data.std  
    # returning filtered data between left/right threshold by gaussian emperical rule  
    return data[(data < (avg + (n_std*std))) & (data > (avg - (n_std*std)))]
```

Redundant Commenting

Redundant Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
    # if gaussian criteria is chosen  
    if criteria == "gaussian":  
        # number of outliers below n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        # number of outliers above n*std from the mean  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        # total outliers  
        total = low+high  
        return low, high, total  
    # if whisker criteria is chosen  
    elif criteria == 'whisker':  
        # multiplication factor to calculate whisker  
        M_FACTOR = 1.5  
        # first quatile of data  
        QUART1 = 0.25  
        # third quartile of data  
        QUART3 = 0.75  
        # number of outliers below lower whisker (median - 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # number of outliers above higher whisker (median + 1.5*IQR)  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # total outliers  
        total = low+high  
        return low, high, total
```

Redundant Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
    # if gaussian criteria is chosen  
    if criteria == "gaussian":  
        # number of outliers below n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        # number of outliers above n*std from the mean  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        # total outliers  
        total = low+high  
        return low, high, total  
    # if whisker criteria is chosen  
    elif criteria == 'whisker':  
        # multiplication factor to calculate whisker  
        M_FACTOR = 1.5  
        # first quatile of data  
        QUART1 = 0.25  
        # third quartile of data  
        QUART3 = 0.75  
        # number of outliers below lower whisker (median - 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        # number of outliers above higher whisker (median + 1.5*IQR)  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        # total outliers  
        total = low+high  
        return low, high, total
```

Redundant Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
    # if gaussian criteria is chosen  
    if criteria == "gaussian":  
        # number of outliers below n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        # number of outliers above n*std from the mean  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        # total outliers  
        total = low+high  
        return low, high, total  
    # if whisker criteria is chosen  
    elif criteria == 'whisker':  
        # multiplication factor to calculate whisker  
        M_FACTOR = 1.5  
        # first quatile of data  
        QUART1 = 0.25  
        # third quartile of data  
        QUART3 = 0.75  
        # number of outliers below lower whisker (median - 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # number of outliers above higher whisker (median + 1.5*IQR)  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # total outliers  
        total = low+high  
        return low, high, total
```

Redundant Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
    # if gaussian criteria is chosen  
    if criteria == "gaussian":  
        # number of outliers below n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        # number of outliers above n*std from the mean  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        # total outliers  
        total = low+high  
        return low, high, total  
    # if whisker criteria is chosen  
    elif criteria == 'whisker':  
        # multiplication factor to calculate whisker  
        M_FACTOR = 1.5  
        # first quatile of data  
        QUART1 = 0.25  
        # third quartile of data  
        QUART3 = 0.75  
        # number of outliers below lower whisker (median - 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1)-(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # number of outliers above higher whisker (median + 1.5*IQR)  
        high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # total outliers  
        total = low+high  
        return low, high, total
```


Redundant Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
    # if gaussian criteria is chosen  
    if criteria == "gaussian":  
        # number of outliers below n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        # number of outliers above n*std from the mean  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        # total outliers  
        total = low+high  
        return low, high, total  
    # if whisker criteria is chosen  
    elif criteria == 'whisker':  
        # multiplication factor to calculate whisker  
        M_FACTOR = 1.5  
        # first quatile of data  
        QUART1 = 0.25  
        # third quartile of data  
        QUART3 = 0.75  
        # number of outliers below lower whisker (median - 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1)-(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # number of outliers above higher whisker (median + 1.5*IQR)  
        high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        # total outliers  
        total = low+high  
        return low, high, total
```

Effective Commenting

```
def num_outliers(data, criteria='gaussian', n=3):  
    if criteria == "gaussian":  
        # number of outliers below/above n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        total = low+high  
        return low, high, total  
  
    elif criteria == 'whisker':  
        M_FACTOR = 1.5  
        QUART1 = 0.25  
        QUART3 = 0.75  
        # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))]])  
        total = low+high  
        return low, high, total
```


Thank You