

Code Decomposition and Modularity

Modularity

Modularity

- Modularity promotes bite-size code

Modularity

- Modularity promotes bite-size code
- Avoid complex nested constructs if possible (loops, if-else)

Modularity

- Modularity promotes bite-size code
- Avoid complex nested constructs if possible (loops, if-else)
- Each block should performs at-most one action

Modularity

- Modularity promotes bite-size code
- Avoid complex nested constructs if possible (loops, if-else)
- Each block should performs at-most one action
- Improves readability

Modularity

- Modularity promotes bite-size code
- Avoid complex nested constructs if possible (loops, if-else)
- Each block should performs at-most one action
- Improves readability
- Easier to resolve errors

Modularity


- Modularity promotes bite-size code
- Avoid complex nested constructs if possible (loops, if-else)
- Each block should performs at-most one action
- Improves readability
- Easier to resolve errors
- Easier to test and debug code

Modular Code


Modular Code

Very Complex Code


Modular Code



Modular Code



Modular Code



Decomposition of Code

```
def num_outliers(data, criteria='gaussian', n=3):  
    if criteria == "gaussian":  
        # number of outliers below/above n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        total = low+high  
        return low, high, total  
  
    elif criteria == 'whisker':  
        M_FACTOR = 1.5  
        QUART1 = 0.25  
        QUART3 = 0.75  
        # number of outliers below/above whiskers;(median - 1.5*IQR) and (median + 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        total = low+high  
        return low, high, total
```

Decomposition of Code

Trying to do too much at once

```
def num_outliers(data, criteria='gaussian', n=3):  
    if criteria == "gaussian":  
        # number of outliers below/above n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        total = low+high  
        return low, high, total  
  
    elif criteria == 'whisker':  
        M_FACTOR = 1.5  
        QUART1 = 0.25  
        QUART3 = 0.75  
        # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        total = low+high  
        return low, high, total
```

Decomposition of Code

Trying to do too much at once

```
def num_outliers(data, criteria='gaussian', n=3):  
    if criteria == "gaussian":  
        # number of outliers below/above n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        total = low+high  
        return low, high, total  
  
    elif criteria == 'whisker':  
        M_FACTOR = 1.5  
        QUART1 = 0.25  
        QUART3 = 0.75  
        # number of outliers below/above whiskers;(median - 1.5*IQR) and (median + 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1)-(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))])  
        total = low+high  
        return low,high,total
```


Decomposition of Code

```
def num_outliers(data, criteria='gaussian', n=3):  
    if criteria == "gaussian":  
        # number of outliers below/above n*std from the mean  
        low = len(data[data < (data.mean()-(n*data.std()))])  
        high = len(data[data > (data.mean()+(n*data.std()))])  
        total = low+high  
        return low, high, total  
  
    elif criteria == 'whisker':  
        M_FACTOR = 1.5  
        QUART1 = 0.25  
        QUART3 = 0.75  
        # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
        low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))] )  
        high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(data.quantile(QUART3) - data.quantile(QUART1)))] )  
        total = low+high  
        return low, high, total
```

Modular Code

```
def num_gaussian_outliers(data, n):  
    # number of outliers below/above n*std from the mean  
    low = len(data[data < (data.mean() - (n*data.std()))])  
    high = len(data[data > (data.mean() + (n*data.std()))])  
    total = low+high  
    return low, high, total
```

Modular Code

```
def num_gaussian_outliers(data, n):  
    # number of outliers below/above n*std from the mean  
    low = len(data[data < (data.mean()-(n*data.std()))])  
    high = len(data[data > (data.mean()+(n*data.std()))])  
    total = low+high  
    return low, high, total  
  
def num_whisker_outliers(data):  
    M_FACTOR = 1.5  
    QUART1 = 0.25  
    QUART3 = 0.75  
    IQR = data.quantile(QUART3) - data.quantile(QUART1)  
    # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
    low= len(data[data < data.quantile(QUART1)-(M_FACTOR*(IQR))])  
    high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(IQR))])  
    total = low+high  
    return low, high, total
```

Modular Code

```
def num_gaussian_outliers(data, n):  
    # number of outliers below/above n*std from the mean  
    low = len(data[data < (data.mean()-(n*data.std()))])  
    high = len(data[data > (data.mean()+(n*data.std()))])  
    total = low+high  
    return low, high, total  
  
def num_whisker_outliers(data):  
    M_FACTOR = 1.5  
    QUART1 = 0.25  
    QUART3 = 0.75  
    IQR = data.quantile(QUART3) - data.quantile(QUART1)  
    # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
    low = len(data[data < data.quantile(QUART1)-(M_FACTOR*(IQR))])  
    high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(IQR))])  
    total = low+high  
    return low, high, total
```

Modular Code

```
def num_gaussian_outliers(data, n):  
    # number of outliers below/above n*std from the mean  
    low = len(data[data < (data.mean()-(n*data.std()))])  
    high = len(data[data > (data.mean()+(n*data.std()))])  
    total = low+high  
    return low, high, total  
  
def num_whisker_outliers(data):  
    M_FACTOR = 1.5  
    QUART1 = 0.25  
    QUART3 = 0.75  
    IQR = data.quantile(QUART3) - data.quantile(QUART1)  
    # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
    low= len(data[data < data.quantile(QUART1)-(M_FACTOR*(IQR))])  
    high = len(data[data > data.quantile(QUART3)+(M_FACTOR*(IQR))])  
    total = low+high  
    return low,high,total  
  
def num_outliers(data, gaussian=True n=3):  
    return num_gaussian_outliers(data, n) if gaussian else num_whisker_outliers(data)
```

Modular Code

```
def num_gaussian_outliers(data, n):  
    # number of outliers below/above n*std from the mean  
    low = len(data[data < (data.mean() - (n*data.std()))])  
    high = len(data[data > (data.mean() + (n*data.std()))])  
    total = low+high  
    return low, high, total
```

```
def num_whisker_outliers(data):  
    M_FACTOR = 1.5  
    QUART1 = 0.25  
    QUART3 = 0.75  
    IQR = data.quantile(QUART3) - data.quantile(QUART1)  
    # number of outliers below/above whiskers; (median - 1.5*IQR) and (median + 1.5*IQR)  
    low = len(data[data < data.quantile(QUART1) - (M_FACTOR*(IQR))])  
    high = len(data[data > data.quantile(QUART3) + (M_FACTOR*(IQR))])  
    total = low+high  
    return low, high, total
```

```
def num_outliers(data, gaussian=True, n=3):  
    return num_gaussian_outliers(data, n) if gaussian else num_whisker_outliers(data)
```

Thank You