

Usability and the Lifecycle of Linked Open Data

A Thesis

Submitted to the Faculty of Graduate Studies and Research

In Partial Fulfillment of the Requirements

For the Degree of

Master of Science

in Computer Science

University of Regina

By

Parita Dipakkumar Amin

Regina, Saskatchewan

November, 2022

© Copyright 2022: Parita Amin

Abstract

The World Wide Web (WWW), as defined by the World Wide Web Consortium (W3C), is “the universe of network-accessible information, the embodiment of human knowledge”¹. With development over the years, the global web of linked documents has become the global web of linked data, which is popularly known as the Semantic Web.

The Semantic Web is now an established topic of research but there remain many unanswered questions. Data that are linked and open facilitate discovery and reuse. Likewise, vocabularies used to describe the semantic relationships amongst linked and open data facilitate discovery and reuse. Yet, it is not always a straightforward matter to take data that may be somehow accessible on a webpage written in Hyper Text Markup Language (HTML) and publish it as Linked Open Data (LOD). Many complementary technologies are used in handling LOD on the web, particularly the Resource Description Framework (RDF), the Web Ontology Language (OWL), and the Simple Protocol and RDF Query Language (SPARQL) to name a few.

Tim Berners-Lee’s vision for a global hypertext system continues to be fulfilled. This thesis work contributes to the practice of publishing by following the lifecycle of a particular dataset from spreadsheet to that is accessible on the web. As such, this thesis can become a resource for other researchers, and citizens at large, to contribute their data to the world.

¹<https://www.w3.org/WWW/>

Acknowledgements

I would like to take an opportunity to thank all the people who have supported me during my research period in some or the other way.

I would like to express my soulful gratitude to my supervisor Dr. Daryl H. Hepting for his valuable time, guidance, suggestions and comments throughout the course of the research. He was always open to all my questions and queries related to my research work as well as while writing this thesis. He provided me with the space required to make this study as my own work, at the same time he made sure that I am leading on the right path by giving constant feedback and suggestions whenever I was lost or stuck. I would also like to thank the Department of Computer Science and Faculty of Graduate Studies and Research for their academic as well as administrative support as and when required.

Lastly, I am grateful to my parents for always being there for me regardless of the distance and time-difference between the two different parts of the world. This would have been next to impossible for me if not for them. I would like to specially thank my brother Shivam for being the family here and for encouraging and motivating me during the times I was low. My special thanks to all my friends for all their support.

Post-Defense Acknowledgements

Table of Contents

Abstract	i
Acknowledgments	ii
Post-Defense Acknowledgments	iii
List of Figures	vi
List of Tables	viii
List of Abbreviations	ix
1 Introduction	1
1.1 Motivation	2
1.2 Contribution	3
1.3 Organization	3
2 Related Work	5
2.1 The Web	5
2.2 Semantic Web	5
2.2.1 The Semantic Web Stack	6
2.3 Linked Open Data	7
2.3.1 Linked Data	8
2.3.2 Linked (Open) Data	10
2.4 Resource Description Framework	10
2.4.1 Uniform Resource Identifier	19
2.5 Linked Data Life Cycle	20
2.6 Conversion of Data from CSV to RDF	21
2.7 Ontology Editors	23
2.8 Applications of Linked Open Data	24
2.8.1 Wikidata	24
2.8.2 DBpedia	29

3	Proof Of Concept	32
3.1	Ontology in Web Semantics	32
3.2	OWL Ontologies	33
3.2.1	Components of OWL Ontologies	33
3.3	OWL Ontology Inconsistencies and Reasoner	35
4	OWL Ontology for Survey	38
4.1	Development Tool for the Creation of New OWL Vocabularies	38
4.2	Protégé	39
4.2.1	Usability of Protégé	40
4.3	Procedure to Model the Survey Ontology in OWL Using Protégé Tools	43
4.3.1	Classes and Class Hierarchy	43
4.3.2	Object Properties and Object Property Hierarchy	50
4.3.3	Data Properties and Data Property Hierarchy	53
4.3.4	Individuals	57
4.4	Visualization Tools for OWL Ontology	59
4.4.1	OntoGraf	59
4.4.2	WebVOWL	60
5	Conclusion and Future Work	62
5.1	Conclusion	62
5.2	Future Work	63
A	Sample CSV Data	64
B	Expression of CSV Data in RDF	68
C	OWL Classes to be Used to Describe Surveys	72
	References	87

List of Figures

2.1	The Web to Semantic Web, according to Aghaei et al. [1]	6
2.2	Semantic Web Stack	7
2.3	An Illustration of Code in an RDF/XML Document	12
2.4	An Example of an RDF Triple	12
2.5	Graphical Representation of an RDF	13
2.6	Graphical Representation of an RDFS for a Comparatively Complex Illustration, after McBride [34]	14
2.7	English Statement for an Example of Actual RDF	15
2.8	RDF Triple for English Statement in Figure 2.7, after RDF Primer [33]	15
2.9	RDF Graph for English Statement in Figure 2.7, after RDF Primer [33]	16
2.10	RDF Graph for Two Relative Statements, after RDF Primer [33]	16
2.11	Graphical Representation of RDF with Details of the Respondent of the Survey, after RDF Primer [33]	17
2.12	RDF Representation in Figure 2.11 without a URI (blank node) for Address Entity, after RDF Primer [33]	18
2.13	Syntax Diagram of a Generic URI, after Berners-Lee et al. [12]	21
2.14	Components of an Example of URL, after Berners-Lee et al. [12]	21
2.15	Details of University of Regina, Regina, SK on Wikidata	26
2.16	Wikidata Entry (RDF/XML) for University of Regina, Regina, SK	27
2.17	Description of University of Regina, Regina, SK on DBpedia	30
2.18	DBpedia Data Architecture	31
3.1	Representation of Individuals in OWL	34
3.2	Representation of Properties in OWL	34
3.3	Representation of OWL Classes Consisting of Individuals and Properties	36
4.1	Five Es of Usability	40
4.2	The Student Feedback Form, from Hepting [28]	44
4.3	Protégé Home-screen for a New Project with an Ontology Name and an IRI	45
4.4	Class Hierarchy of Thing, Domain_Entity, Independent_Entity, and Value	46
4.5	Tools Menu to Create Class Hierarchy	46
4.6	“Enter hierarchy” Pop-up Window	47
4.7	Pop-up Window to Create Disjoint Sibling Classes	48

4.8	Class Hierarchy in Survey Ontology	49
4.9	Tools Menu to Create Object Property Hierarchy	51
4.10	Object Properties for Classes “Lady” and “Parita”	52
4.11	Domain and Range Classes for “hasName” and “isNameOf”	53
4.12	Object Property Hierarchies, Domain and Range for Classes	54
4.13	Tools Menu to Create Data Property Hierarchy	56
4.14	Data Property Hierarchies, Domain and Range for Classes	56
4.15	Class Hierarchy for the Final Version of Survey Ontology	58
4.16	Parent/Child Relation indicated by "Blue Back" Arrow	58
4.17	OntoGraf for Survey Ontology	60
4.18	WebVOWL for Survey Ontology	61

List of Tables

2.1	Commonly used Classes and Properties of RDFS	13
2.2	RDF Notations for Figure 2.10, after RDF Primer [33]	17
2.3	Definitions Used for Characterizing URI, by Berners-Lee et al. [11] . . .	20
2.4	Stages in Linked Data Life Cycle, after Ngomo et al. [35]	21
2.5	Statement Properties and Property IDs for the University of Regina on Wikidata	28
2.6	Identifier Properties and Property IDs for University of Regina on Wikidata	28
4.1	Degrees of Agreement for Likert-scale Questions	50
4.2	Object Properties and Their Domain and Range	53
4.3	Object Properties with Their Parent Nodes and Inverse Properties . . .	55
4.4	Data Properties and Their Domain and Range	57

List of Abbreviations

API	Application Programming Interface
CERN	Conseil Européen pour la Recherche Nucléaire
CSV	Comma Separated Value
DL	Description Logics
ER	Entity Relationship
GIF	Graphics Interchange Format
GREL	Google Refine Expression Language
GUI	Graphical User Interface
HTML	Hyper Text Markup Language
HTTP	Hyper Text Transfer Protocol
HTTPS	Hypertext Transfer Protocol Secure
IDE	Integrated Development Environment
IRI	Internationalized Resource Identifier
ISO	International Organization for Standardization
JPEG	Joint Photographic Experts Group
JSON	JavaScript Object Notation
LOD	Linked Open Data
N3	Notation3
OBDA	Ontology-Based Data Access
OWL	Web Ontology Language

PNG Portable Network Graphics
RDF Resource Description Framework
RDFS Resource Description Framework Schema
SPARQL Simple Protocol and RDF Query Language
SVG Scalable Vector Graphics
Turtle Terse RDF Triple Language
URI Uniform Resource Identifier
URL Uniform Resource Locator
VOWL Visual Web Ontology Language
W3C World Wide Web Consortium
WWW World Wide Web
XML eXtensible Markup Language

Chapter 1

Introduction

Tim Berners-Lee is the father of the WWW. He wrote *Information Management: A Proposal*¹ in 1989 and 1990 to present the need for a “global hypertext system” at the Conseil Européen pour la Recherche Nucléaire (CERN). In his conclusion to that document, he wrote:

“we should work toward a universal linked information system, in which generality and portability are more important than fancy graphics techniques and complex extra facilities. The aim would be to allow a place to be found for any information or reference which one felt was important and a way of finding it afterward. The result should be sufficiently attractive to use, that is, the information contained would grow past a critical threshold so that the usefulness of the scheme would, in turn, encourage its increased use.”

In the more than 30 years that have followed that initial proposal, a great deal of progress towards Berners-Lee’s vision has been realized. The original “web of documents” is becoming the “web of data” or the “semantic web”. Is this next web sufficiently attractive to use? This thesis will examine this question in the context of an example.

¹<https://www.w3.org/History/1989/proposal.html>, dated March 1989, May 1990

1.1 Motivation

In his teaching practise, my supervisor collects feedback from students in his classes each semester and makes the responses available on his website². Typically, student responses were collected on paper and then entered manually into computer-readable form. Data collection since the start of the COVID-19 pandemic has changed.

Although it is valuable to have this data available on the web, it is not published as LOD. The motivation for the research presented here was to examine the process by which existing data can be published as LOD and to consider whether that process is “sufficiently attractive to use”.

The published linked (structured) data which is available on the web can be efficiently retrieved and reused as, according to Ngomo et al. [35], linked data is “a set of best practices for publishing and connecting structured data on the web”. After the introduction of the semantic web and the four principles of linked data for publishing and connecting structured datasets on the web by Berners-Lee, the web of documents has been gradually moving towards the development of the web of data. With time, these principles have been accepted and considered as the standard to publish structured data on the semantic web [14, 16, 17, 27]. The four principles of linked data by Berners-Lee [8] are as follows:

- Use Uniform Resource Identifier (URI) as names for things
- Use Hyper Text Transfer Protocol (HTTP)³ URIs to look up those names
- Provide useful information, using the standards (RDF⁴, SPARQL)
- Include links to other URIs to discover more things

²<http://www2.cs.uregina.ca/hepting/teaching/evaluation.html>

³Both HTTP and Hypertext Transfer Protocol Secure (HTTPS)

⁴includes all the standards belonging to RDF family

After the development of Linked Data for the semantic web, Berners-Lee also contributed to web engineering by introducing a 5-star rating⁵ system for the rating of linked data implementations. In this system, using the linked data principles, the publishers of the data on the web link their data to the existing linked data to provide reference and make it available for lookup. The data on the web, according to the 5-star system, is accepted to be 5-star data if the data:

- is structured (machine-readable)
- has open-license for access
- is described and linked to other data using URIs

A query is used to retrieve information from a database that consists of multiple tables. According to the W3C recommendation, a semantic (web) query depicts the techniques and protocols that are “used to retrieve information from the web of data” using computer programs. Web (semantic) queries use the semantics and the constitution of data on the web to perform data retrieval operations. Various semantic web technologies have been developed for data retrieval on the web. SPARQL is one of the semantic web technologies used for web queries, where it gathers all the data from different domains and treats all those datasets as local.

1.2 Contribution

1.3 Organization

Following this introduction, the rest of the thesis is organized as follows. Chapter 2... Chapter 3... Chapter 4... Finally, Chapter 5 presents some conclusions and

⁵https://www.w3.org/2011/gld/wiki/5_Star_Linked_Data

opportunities for future work.

Chapter 2

Related Work

This Chapter provides the theoretical and conceptual information that is the foundation for this thesis, focusing on the semantic web and linked open data from the perspectives of technology and usability.

2.1 The Web

The idea of the Web, as described by Berners-Lee et al. [10], came from the positive experience of a small “home-brew” personal hypertext system. The Web can be used independently for multiple projects that can be later integrated with unique relationships among them using the newly shaped information to represent the new state of linked knowledge. The web was first designed by Berners-Lee in 1989¹ while working at the CERN. this sentence is not clear

2.2 Semantic Web

The web pages for the semantic web can be written using HTML and RDF as it is the web of data, contrary to the web of documents, where the web pages were written using HTML and the links were described using hyperlinks. In the web of data,

¹<https://www.w3.org/History/1989/proposal.html>

arbitrary things can be expressed using links to represent the relationship between two entities, as shown in Figure 2.1.




Figure 2.1: The Web to Semantic Web, according to Aghaei et al. [1]

The latest generation of web that is still at its research and development stage is Web 4.0 which is supposed to be read-write-execute with the property of concurrency [19]. This version of the web is intended to work with artificial intelligence to give users an exceptional quality of experience. While describing how Web 4.0 would be, Berners-Lee [13] stated “if HTML and the Web made all the online documents look like one huge book, RDF, schema, and inference languages will make all the data in the world look like one huge database”.

2.2.1 The Semantic Web Stack

The Semantic Web Stack ² is also known as Semantic Web Cake or Semantic Web Layer Cake. The stack represents the architecture of semantic web. Figure 2.2³ shows how semantic web principles are implemented in the layers of technologies.

²https://en.wikipedia.org/wiki/Semantic_Web_Stack

³<https://www.w3.org/2001/12/semweb-fin/w3csw>




Figure 2.2: Semantic Web Stack

The layers in the stack consist of different technologies. Going from the lowest level to the top level, the technologies are Unicode and URI; eXtensible Markup Language (XML), NS and xmlschema; RDF and rdfschema; Ontology vocabulary; Logic; Proof; and Trust. Digital signatures are used as security at different levels. The layers belong to three different groups, namely, self-descriptive document, data and rules.

2.3 Linked Open Data

According to Berners-Lee et al. [1], “Semantic web is not limited to publication of data on the web; it is about making links to connect related data.” The concept of Linked Open Data⁴ is an amalgamation of two technologies, Linked Data and Open Data. GraphDB⁵ by Ontotext, an RDF database, is an example of LOD. GraphDB promotes knowledge-discovery and efficient data-driven analytics by linking large datasets

⁴<https://www.ontotext.com/knowledgehub/fundamentals/linked-data-linked-open-data/>

⁵<https://www.ontotext.com/knowledgehub/fundamentals/linked-data-linked-open-data/>

from distinct sources to Open Data.

2.3.1 Linked Data

The relationships shared among the data from different sources on the web are equally important as the access to the data for efficient working of the semantic web. The technique used to manage these datasets and their relationships is referred to as Linked Data. In other words, Linked Data⁶ can be termed as a set of various techniques of publishing structured data on the web. The W3C standards and various semantic web technologies handle the distribution and engagement of the structured data across the web to aggregate the data available on the web into one huge database [13].

In 2006, Berners-Lee [15] framed four basic rules (mentioned in section 1.1) to publish and connect the structured datasets across the web. This set of rules was termed as Linked Data principles. A brief description of these principles is as follows:

1. Use URIs as names for things:

The web identifiers, the (URIs) should be used to give unique names to all the entities (or things) on the web. URI of an entity can be used to understand that the entity in this dataset is the same as the other entity in a disparate dataset.

2. Use HTTP⁷ URIs to look up for those names:

The HTTP/HTTPS protocols allow easy retrieval of resources. Hence, along with URIs, either of the protocols can be used to search things (entities) easily. This promotes the publication of data on the web and its addition to the global data space.

⁶<https://www.w3.org/wiki/LinkedData>

⁷Both HTTP and HTTPS

3. Provide useful information, using the standards (RDF⁸, SPARQL) to look up for a URI:

When an entity is searched using the URI associated with it, it is beneficial to use standards like RDF and SPARQL to query the datasets. RDF is a framework used for graphical representation of publication and distribution of data on the web, as described in detail in section 2.4. On the contrary, SPARQL is a query language used for retrieval and manipulation of data (in RDF format) on the web. It also helps with the information on relationships related to the data being searched.

4. Include links to other URIs to discover more thing:

In the semantic web, links between two entity defines the relationship using the basic entity-relationship model. Using links for URIs of the entities promotes interconnection of the data and search of things on the web. Connecting new data to already existing entities increases the reuse and interlinking within the domain and creates a computer-understandable network.

Publishing data on the web as per linked data principles can benefit the data providers by allowing them to use one global space to add all their data. An RDF data model and URIs are used by the linked data to name the things (entities). The linked datasets publish and locate the class-object data which in turn is accessed using the HTTP/HTTPS and maintains the connection among them [5].

A wide network of structured data, from a variety of domains, on the web has been formed obeying the principles of linked data by Berners-Lee. This has resulted in the formation of a huge database of structured linked data on the web which has further led to the concept of the LOD Cloud. The LOD cloud is a set of publicly [9]

⁸includes all the standards belonging to RDF family

accessible/available linked datasets.

2.3.2 Linked (Open) Data

According to a handbook⁹ by the Open Knowledge Foundation, “Open Data is data that can be freely used, re-used and redistributed by anyone - subject only, at most, to the requirement to attribute and share-alike”. To make open data available to everyone on the web, the data don’t need to be interlinked. Important features of open data are:

- Availability and access: the data should be available on the web. The users should be able to access the data easily by downloading them over the internet. It should be easy to access and modify the data.
- Re-use and redistribution: the data on the web must have permissions to re-use and redistribute in combination to other datasets.
- Universal participation: the data should be available to use, re-use, and redistribute for all the users without any discrimination to an individual or a group.

2.4 Resource Description Framework

The RDF, initially designed as a metadata data model, is a computer-understandable specification written in a particular format. According to a proposal by W3C¹⁰, RDF plays an important role in their “Semantic Web Vision”. RDF describes an entity (or resources) and the relationships among them on the web using basic data models like the Entity Relationship (ER) model.

⁹<https://opendatahandbook.org/guide/en/what-is-open-data/>

¹⁰<https://www.w3.org/TR/PR-rdf-syntax/Overview.html>

RDF is a W3C¹¹ specification for describing resources on the web. RDF uses “properties” and “property values” to describe the resource which is identified by web identifiers called URI (section 2.4.1). There are three types of objects in RDF, namely, resources, properties, and statements. Each data object in a dataset on the web is considered a resource and is named using a URI with an optional ID. To search for the resources on the web, the resources must be named using the HTTP/HTTPS URIs. The W3C has defined the “rdf:type” property to represent the “object of one or more classes” [21]. Resources are described by their characteristics, called “property”. The object of RDF that is used to combine a resource with a property of its value is a “statement”. A statement, in general terms, can be seen as building blocks of a statement in English, which are a subject, an object, and a predicate. An object in a statement can be either a property value, a resource, or a literal. RDF, according to Swick and Lassila [6], can be represented in three ways:

1. Using XML: an RDF/XML document
2. As triples: subject-predicate-object form
3. In graphical form

Figure 2.3 shows an example of an RDF/XML¹² document. The resource being described is “<https://www.semanticweb.org/pda324/ontologies/survey>” and “Survey Details” is the property value. The document consists of various XML tags enclosed between the angular brackets (“<” and “>”). An RDF/XML document starts and ends with <rdf : RDF> and </rdf : RDF> respectively. <rdf : Description> consists of the elements that are responsible for the creation of the statement. Description tag holds an identification for the resource.

¹¹https://www.w3schools.com/xml/xml_rdf.asp

¹²RDF written using XML

```
<rdf : RDF>  
  <rdf:Description rdf:about="https://www.semanticweb.org/pda324/ontologies/survey">  
    <s:istypeof>Survey Details</s:istypeof>  
  </rdf:Description>  
</rdf : RDF>
```

Figure 2.3: An Illustration of Code in an RDF/XML Document

Figure 2.4 shows an example of an RDF as a triple. An RDF triple, generally, follows subject-predicate-object format. For the illustration in the figure, the subject is “<https://www.semanticweb.org/pda324/ontologies/survey>”, predicate is “includes” and the object is “Survey Details”.

Subject : <https://www.semanticweb.org/pda324/ontologies/survey>
Predicate : includes
Object : Survey Details

Figure 2.4: An Example of an RDF Triple

Figure 2.5 show an RDF in graphical format. Resource is indicated using an oval shape and a rectangle is used to represent a property value. A connector (an arrow) is used to represent a property to show that property (predicate) connects the resource (subject) with the value (object).

The subject and object of the triples of RDF act as nodes in the graph. In addition to RDF/XML documentation, the RDF data model has a variety of serialization formats such as N-triples, which is a line base format where an RDF triple is used to represent each line [7]; Terse RDF Triple Language (Turtle); Notation3 (N3), which is a subset of Turtle and N-Quads, which is an extension of N-Triples (line based) and adds a graph label to each line that allows multiple graph encoding [20].

Resource Description Framework Schema (RDFS), according to McBride [34], was




Figure 2.5: Graphical Representation of an RDF

Class/Property	Description
<code>rdfs:Resource</code>	All things described by RDF are called resources
<code>rdfs:Class</code>	The class of resources that are RDF classes
<code>rdf:Property</code>	The class of RDF properties. It is an instance of <code>rdfs:Class</code>
<code>rdfs:Literal</code>	The class of literal values like integers and strings
<code>rdfs:Datatype</code>	The class of datatypes. All the objects of this class correspond to the RDF model of datatype
<code>rdf:HTML</code>	The class of HTML literal values and subclass of <code>rdfs:Literal</code>
<code>rdfs:range</code>	An instance of <code>rdf:Property</code> that is used to state that the values of a property are instances of one or more classes
<code>rdfs:domain</code>	An instance of <code>rdf:Property</code> that is used to state that any resource that has a given property is an instance of one or more classes.
<code>rdf:type</code>	An instance of <code>rdf:Property</code> that is used to state that a resource is an instance of a class
<code>rdfs:subClassOf</code>	An instance of <code>rdf:Property</code> that is used to state that all the instances of one class are instances of another
<code>rdfs:label</code>	an instance of <code>rdf:Property</code> that may be used to provide a human-readable version of a resource's name
<code>rdfs:subPropertyOf</code>	An instance of <code>rdf:Property</code> that is used to state that all resources related by one property are also related by another

Table 2.1: Commonly used Classes and Properties of RDFS

introduced by the W3C as a technique to define resource types and property names. The data publishers can use RDFS to define various vocabularies in an RDF model. Some of the commonly used RDFS classes and properties¹³ along with their description

¹³<https://www.w3.org/TR/rdf-schema/>

are listed in Table 2.1 [34].

Figure 2.6 shows a graph for the representation of RDFS for a comparatively complex and abstract example based on RDF Primer [33]. The graph has been drawn for the following statement:

Romeo and Juliet is written by William Shakespeare.

Figure 2.6 is the graphical representation of an RDF with schema as well as data. In the graph, the `rdf:type` of “Romeo and Juliet” is “Play” which in turn is an `rdf:subClassOf` “Literature”. Also, the `rdf:type` of “William Shakespeare” is “Person” which, further, is an `rdfs:range` of “is written by” of `rdfs:domain` “Literature”.




Figure 2.6: Graphical Representation of an RDFS for a Comparatively Complex Illustration, after McBride [34]

The actual RDF looks quite different from the previous example (Figures 2.3, 2.4, 2.5 and 2.6). For the representation of an actual RDF, consider Figure 2.7 for the corresponding English statement. “<http://www.semanticweb.org/survey.html>” is a subject URI with respondent and Robert James having URIs as “<http://xyz.org/1/respondent>”

and “<http://www.semanticweb.org/responseID/1234>” respectively. The example represents a survey system which has responses as well as respondents and related details as a part of the environment.

**<http://www.semanticweb.org/survey.html> has a respondent
whose value is Robert James**

Figure 2.7: English Statement for an Example of Actual RDF

In the form of RDF triple, the statement in Figure 2.7 can be represented as shown in Figure 2.8. URI is assigned to the subject [survey.html](http://www.semanticweb.org/survey.html) and to the object which is the response with responseID 1234 which corresponds to the property value Robert James. A URI is also assigned to the predicate (respondent).

SUBJECT - <http://www.semanticweb.org/survey.html>
PREDICATE - <http://xyz.org/1/respondent>
OBJECT - <http://www.semanticweb.org/responseID/1234>

Figure 2.8: RDF Triple for English Statement in Figure 2.7, after RDF Primer [33]

Figure 2.9 shows a graphical representation of the RDF triple in Figure 2.8. The subject and the object are two entities and the predicate being the third entity acts as a connector between them. Considering an entity-relationship data model, the predicate can be treated as a relationship shared by the subject and the object. There can be more details added to the system, that is, more statements can be added which are in relation to the one in Figure 2.7. Suppose the new statement added is:

<http://www.semanticweb.org/survey.html> has a date with value Sept. 08, 2020

and the URI for the date is “<http://www.semanticweb.org/respDetails/date>”.




Figure 2.9: RDF Graph for English Statement in Figure 2.7, after RDF Primer [33]

The new graph would be as shown in Figure 2.10 where as the set of statements in Table 2.2 shows the RDF triple notation for Figure 2.10. The first notation represents the entities, survey.html (subject) and Robert James (object), along with respondent (predicate) as the relation between them, using the URIs. The second notation is for the date, where instead of the URI, the value of the property, Sept. 08, 2020, is used. Here, survey.html is the subject and Sept. 08, 2020 is the object with date acting as the predicate.




Figure 2.10: RDF Graph for Two Relative Statements, after RDF Primer [33]

Consider a more complex system, where the details of respondent are collected. Suppose, one of the details is name and the other is address of the respondent. Figure 2.11

<http://www.semanticweb.org/survey.html> <http://xyz.org/1/respondent> <http://www.semanticweb.org/responseID/1234> .
<http://www.semanticweb.org/respDetails/date> “Sept. 08, 2020” .

Table 2.2: RDF Notations for Figure 2.10, after RDF Primer [33]

shows a graphical representation of this RDF system.




Figure 2.11: Graphical Representation of RDF with Details of the Respondent of the Survey, after RDF Primer [33]

For name, the respondent is subject and Robert James acts as object whereas respName is the predicate. The URI for respName is “http://www.semanticweb.org/respDetails/name” and the value, Robert James, is the object. On the other hand, respondent (subject) is connected to address (object) node, with URI “http://www.semanticweb.org/addressID/1234”, through respAddress (predicate) with URI “http://www.semanticweb.org/respDetails/address”. Further, the address node has multiple child nodes, namely, street, city, state and postal code. The address (subject) URI is connected to the values of four different object values, 49 University Drive (street), Regina (city), Saskatchewan (state) and S4S 5N2 (postalCode) where the URIs for the predicates are

“<http://www.semanticweb.org/respDetails/street>”, “<http://www.semanticweb.org/respDetails/city>”, “<http://www.semanticweb.org/respDetails/state>” and “<http://www.semanticweb.org/respDetails/postalCode>” respectively. Instead of using an unnecessary URI for the address entity, a blank node can be used to denote the entity, as shown in Figure 2.12. As the relationships of the node with other nodes give sufficient details without hindering the flow of the data tree, the node does not require a URIreference¹⁴.




Figure 2.12: RDF Representation in Figure 2.11 without a URI (blank node) for Address Entity, after RDF Primer [33]

In 2004, W3C recommended intended goals that are to be achieved whenever an RDF is to be designed. According to the W3CRecommendation¹⁵, the design should “have a simple data model; formal semantics and provable inference; should use an extensible URI-based vocabulary and an XML-based syntax; should support the use of XML schema datatypes; and should allow any one to make statements about any

¹⁴<https://lists.w3.org/Archives/Public/uri/2007Jul/0027.html>

¹⁵<https://www.w3.org/TR/rdf-concepts/>

resource”.

2.4.1 Uniform Resource Identifier

An abstract (a logical) or a physical resource on the web is identified by a unique set of ASCII characters which is referred to as a URI¹⁶. According to Berners-Lee et. al. [12] in RFC 3986, the unique string, on the web, follows a set of guidelines and security considerations while defining a syntax for the generic URI and determining a process for URI references’ resolution. As mentioned by W3C, for the operating systems on URIs, some specific “protocols are defined depending on the UriScheme¹⁷”. A system can perform multiple operations like “access”, “update”, “replace” and “find attributes” on the identified resources. In RFC 2396, Berners-Lee et al. [11] characterized URI using three definitions, as shown in Table 2.3.

2.4.1.1 Syntax of a URI

According to Berners-Lee et al. [12], the generic syntax of a URI comprises five components in a hierarchical sequence which are as follows:

$$\text{URI} = \text{scheme:} [//\text{authority}] \text{ path } [?\text{query}] [\#\text{fragment}]$$

where the authority component consists of three more components which are:

$$\text{authority} = [\text{userinfo}@] \text{ host } [:\text{port}]$$

A syntax diagram can be modelled to represent the components of Generic Syntax¹⁸ of URI along with their hierarchy as shown in Figure 2.13. Consider the following Uniform Resource Locator (URL). Figure 2.14 shows its components.

<https://parita@www.semanticweb.org:695/ontology/?tag=survey&order=newest#top>

¹⁶<https://www.w3.org/wiki/URI>

¹⁷<https://www.w3.org/2001/tag/doc/SchemeProtocols.html>

¹⁸<https://www.w3.org/Addressing/URL/uri-spec.html>

Term	Definition
Uniform	There are various benefits of achieving uniformity, like, it facilitates different procedures to access resources in the same environment using different types of resource identifiers; new types of resource identifiers can be introduced without modifying the actual usage of the existing identifiers; common syntactic conventions can be interpreted uniformly for a variety of resource identifiers on the semantic web; and the new applications or protocols can utilize the already existing large and widely-used resource identifiers as the identifiers can be reused in different contexts.
Resource	Anything on the web that can be uniquely identified is referred to as a resource. Some day-to-day examples of a resource are a computerized file or folder, weather-broadcasting service, an image, and a set of other resources. Some resources like books in a library, an animal, a human being, and a corporation are a set of resources that cannot be retrieved over the network. A resource is the “conceptual mapping” [11] to a set of entities independent of the corresponding entities at a particular time. Hence, if the conceptual mapping isn’t changed, a resource can remain constant irrespective of the changes in its content.
Identifier	An object which is used as a reference to a thing with unique identity on the web is termed as an identifier. In URI, a string of ASCII characters restricted by a specific syntax is object.

Table 2.3: Definitions Used for Characterizing URI, by Berners-Lee et al. [11]

2.5 Linked Data Life Cycle

The Linked Data Life Cycle includes multiple stages as described by Ngomo et al. [35] which are listed in Table 2.4. Each stage of this life cycle is independent yet linked to one another. So, it is not mandatory to go through all the stages sequentially to publish the data on the web. It is necessary to use a procedure that follows the life cycle to ensure the quality of data to be published as linked data. The first stage, generally, is data extraction along with conversion of the extracted data (in forms other than RDF) into RDF. Once the data is in RDF form, any or all of the other stages listed in Table 2.4 can be performed.




Figure 2.13: Syntax Diagram of a Generic URI, after Berners-Lee et al. [12]




Figure 2.14: Components of an Example of URL, after Berners-Lee et al. [12]

Stage	Description
Extraction	Extraction and conversion of unstructured and semi-structured data into RDF
Storage & Querying	Storing the RDF data in a format that supports data querying efficiently
Authoring	Allowing the users to create new data or to access and modify the existing data
Linking	Creating links the data belonging to various domains and users based on their entities
Enrichment	Data enrichment for efficient query support using various top-tier structures
Quality Analysis	Managing data using different strategies to ensure good quality of available data on the web
Browsing & Exploration	Making the structured data available on the web for the users to browse and explore effectively

Table 2.4: Stages in Linked Data Life Cycle, after Ngomo et al. [35]

2.6 Conversion of Data from CSV to RDF

The preferred format of the data published on the semantic web is RDF format. Many data scientists use tables and spreadsheets to store and publish data using Comma Separated Value (CSV) files over RDF format as conversion of data to RDF is com-

paratively difficult. The data used by Dr. Hepting has been stored in tabular format (Sample CSV data consisting of all responses is available in Appendix A). To convert tabular data into RDF (Appendix B consists of RDF code for the CSV data in Appendix A), W3C¹⁹ recommends the following open source tools [22],

- OpenRefine:

OpenRefine²⁰, an RDF extension of Google Refine, is a powerful java-based set of tools that work with messy data using Google Refine Expression Language (GREL)²¹. It allows the users to extract, transform, export, and convert CSV, Excel, spreadsheets and other tabular data into RDF where a Graphical User Interface (GUI) is used to define schema mapping.

- RDF123:

RDF123²² is a java application and servlet for the conversion of CSV and spreadsheets to RDF which uses arbitrary graphs to define schema mapping. According to Han et. al [26], it uses a graphical RDF123 template to allow users to convert the data from spreadsheets to RDF.

- csv2rdf4lod:

csv2rdf4lod²³ is a tool that is used for the conversion of tabular data into structured and linked RDF using specifications that are based on declarative RDF enhancement parameters. It forms default namespaces for URIs and provides VoID and original metadata for the conversion using identifiers for source organization, dataset and version.

¹⁹<https://www.w3.org/wiki/ConverterToRdf>

²⁰<https://openrefine.org>

²¹<https://libjohn.github.io/openrefine/grel.html>

²²<https://ebiquity.umbc.edu/resource/html/id/237/RDF123-java-application-v1-0>

²³<https://github.com/timrdf/csv2rdf4lod-automation/wiki>

- XLWrap:

XLWrap²⁴ is a graphical template based application that allows execution of various SPARQL queries [31]. The spreadsheets are wrapped to arbitrary RDF graphs which allows:

- Streamed processing of tabluar data like Excel, OpenDocument and CSV
- Loading Local/HTTP
- Expressions that include calculator operations for Excel and OpenDocument, and Custom functions
- Use of Application Programming Interface (API) and SPARQL endpoint

- Tarql:

Tarql²⁵ operates as a command-line application for the conversion of CSV to RDF using a user-defined mapping that is written in SPARQL standard 1.1.

2.7 Ontology Editors

Ontology editors are used by publishers to create new ontologies when the existing vocabulary is not suitable for their purpose. W3C²⁶ has recommended a list of ontology editors that can be used to edit, manage, organize and visualize ontology. The list of editors includes Protégé, NeOn Toolkit, SWOOP, Neologism, TopBraid Composer, Vitro, Knoodl, Anzo for Excel, OWLGrEd, Fluent Editor, Semantic Turkey, VocBench. The page does not include valid links to the editors' websites. Protégé is the most popular ontology editor among researchers. There exists negligible information about

²⁴<https://xlwrap.sourceforge.io>

²⁵<https://tarql.github.io>

²⁶https://www.w3.org/wiki/Ontology_editors

most of the editors in the list which has driven the decision of the use of Protégé for ontology development and OntoGraf and WebVOWL for visualization.

2.8 Applications of Linked Open Data

A variety of projects and websites, that use linked open data, have been developed. Wikidata and DBpedia are two major projects of linked open data that present structured data on the semantic web. This section consists of a brief description of both applications.

2.8.1 Wikidata

According to a report by Krotzsch and Vrandečić [38], Wikidata was introduced to the world of information engineering in 2012 by Wikimedia. Wikidata can be defined as “the community-created knowledge base of Wikipedia and the central data management platform for Wikipedia and most of its Sister Projects²⁷”, according to Erxleben et al. [23]. Wikidata was established for the collection and integration of data on the semantic web with Wikipedia. Wikidata is a free open-source tool that handles a large amount of structured data and maintains pages that store the data. Each entity on Wikidata represents the subject of a triple with a dedicated page. The properties of Wikidata are similar to that of RDF where the individuals and classes are indicated using items. As Wikidata is an open-source tool, the data on a page of the Wikidata is easily available for the users to access as well as edit.

For instance, the University of Regina, a university in the provincial capital of Saskatchewan—the city of Regina, has an item page allotted for it. Figure 2.15 shows the Wikidata item page of the University of Regina that can be accessed using the link:

²⁷Wikipedia, Wikivoyage, Wiktionary, Wikisource, and others

<https://www.wikidata.org/wiki/Q3104287>. Wikidata uses a method of automatically assigning unique identifiers to the entities, which are used as the labels of the item pages instead of the actual names of the entities. These identifiers are a string starting with a capital Q followed by a sequence of digits. The identifiers are assigned irrespective of the language as the Wikidata website supports multiple languages. For the University of Regina, the label used is “Q3104287”. The item page on Wikidata consists of multiple sections:

- label: The name of the subject that is treated as an entity. For the instance in Figure 2.15, the label is “University of Regina” along with the unique identifier “Q3104287”.
- description: This section consists of general introductory details about the subject. For the University of Regina, the description on wikidata is “university in Saskatchewan, Canada”.
- statements: This section consists of a list of subsections called “property”. The properties along with their property IDs for the University of Regina are listed in Table 2.5.
- identifiers: This section consists of various IDs belonging to the subject. For the University of Regina, the set of properties used for identifiers and their IDs are listed in Table 2.6.

The URI for an entity on Wikidata is “<https://www.wikidata.org/wiki/<id>>”, where `<id>` stands for the unique identifier. For the University of Regina, the `<id>` is the label identifier—Q3104287. Figure 2.16 shows the RDF/XML description of the University of Regina on Wikidata.

University of Regina (Q3104287)

university in Saskatchewan, Canada [edit](#)
Regina College | Regina Campus of the University of Saskatchewan

[- In more languages](#)
[Configure](#)

Language	Label	Description	Also known as
English	University of Regina	university in Saskatchewan, Canada	Regina College Regina Campus of the Universit...
Canadian English	No label defined	No description defined	
French	université de Regina	No description defined	Université de Régina Universite de Regina Université de regina
Italian	No label defined	No description defined	

[All entered languages](#)

Statements

instance of	university edit - 0 references + add reference
	open-access publisher edit - 1 reference stated in Directory of Open Access Journals + add reference
	+ add value
	+ add value

image	edit  University of Regina Library viewed from the Oval.jpg 3,222 × 2,250; 662 KB - 0 references + add reference
	+ add value

inception	1911 edit - 1 reference imported from Wikimedia project French Wikipedia

Figure 2.15: Details of University of Regina, Regina, SK on Wikidata

```

<?xml version="1.0" encoding="utf-8" ?>
  <rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema#"
    xmlns:ontolex="http://www.w3.org/ns/lemon/ontolex#"
    xmlns:wdt="http://www.wikidata.org/prop/direct/"
    xmlns:wdrn="http://www.wikidata.org/prop/direct-normalized/">
    <rdf:Description rdf:about="https://www.wikidata.org/wiki/Special:EntityData/Q3104287">
      <rdf:type rdf:resource="http://schema.org/Dataset"/>
      <schema:about rdf:resource="http://www.wikidata.org/entity/Q3104287"/>
      <cc:license rdf:resource="http://creativecommons.org/publicdomain/zero/1.0/">
      <rdf:Description rdf:about="https://en.wikipedia.org/wiki/University_of_Regina">
        <rdf:type rdf:resource="http://schema.org/Article"/>
        <schema:about rdf:resource="http://www.wikidata.org/entity/Q3104287"/>
        <schema:inLanguage>en</schema:inLanguage>
        <schema:isPartOf rdf:resource="https://en.wikipedia.org/">
        <schema:name xml:lang="en">University of Regina</schema:name>
        <schema:description xml:lang="en">university in Saskatchewan,
        Canada</schema:description>
        <wdt:P18
          rdf:resource="http://commons.wikimedia.org/wiki/Special:FilePath/University%20
            of%20Regina%20Library%20viewed%20from%20the%20Oval.jpg"/>
        </rdf:Description>
      </rdf:Description>
    </rdf:RDF>

```

Figure 2.16: Wikidata Entry (RDF/XML) for University of Regina, Regina, SK

Statement Property	Property ID
instance of	P31
image	P18
inception	P571
country	P17
located in the administrative territorial entity	P131
coordinate location	P625
subsidiary	P355
official website	P856
commons category	P373
topic's main category	P910
category for employees of the organization	P4195
category for alumni of educational institution	P3876
API endpoint	P6269
social media followers	P8687

Table 2.5: Statement Properties and Property IDs for the University of Regina on Wikidata

Identifier Property	Property ID
VIAF ID	P214
ISNI	P213
GND ID	P227
Library of Congress authority ID	P244
WorldCat Identities	P7859
ARWU university ID	P5242
Crossref funder ID	P3153
Facebook ID	P2013
Freebase ID	P646
Google Maps Customer ID	P3749
GRID ID	P2427
HAL structure ID	P6773
LittleSis organization ID	P3393
Microsoft Academic ID	P6366
Ringgold ID	P3500
ROR ID	P6782
Times Higher Education World University ID	P5586
Twitter username	P2002
U-Multirank university ID	P5600

Table 2.6: Identifier Properties and Property IDs for University of Regina on Wikidata

2.8.2 DBpedia

Jimmy Wales and Larry Sanger, in 2001, created the largest general reference work on the internet consisting of articles²⁸ in over 280 languages, the Wikipedia²⁹, which acts as a source of data for many web projects like DBpedia³⁰, one of the major linked open data projects. The main aim behind the development of DBpedia is the conversion of unstructured data on Wikipedia into structured datasets. DBpedia enables querying the Wikipedia data as well as the generation of links among the structured datasets, resulting in the establishment of a massive web of data.

Initially, the template of the page is discovered using a Template Extraction Algorithm³¹ which results in the identification of the structure of the template using various Pattern Matching Techniques³². Once the appropriate template is selected, the template data is parsed using a suitable algorithm and transformed into RDF triples. MediaWiki³³ links are identified and assigned specific URIs. On the other hand, the common units of data are recognized and assigned appropriate datatypes whereas RDF lists are created for the object lists. According to Auer et al. [4], DBpedia in 2007 was a platform that delivered information on “more than 1.95 million ‘things’ that includes at least 80,000 persons, 70,000 places, 35,000 music albums, 12,000 films”. The DBpedia semantic web services are handled using the GNU Free Documentation License terms and policies. The data on DBpedia is easily accessible in different ways like accessing the datasets as linked data; using SPARQL queries for data extraction and accessibility; and in the form of a downloadable RDF snippets [18]. Figure 2.17 shows DBpedia entry

²⁸include data comprising of templates, images, videos, categorizations, and links to other articles (pages) in multiple languages

²⁹https://en.wikipedia.org/wiki/Main_Page


³⁰<https://wiki.dbpedia.org/>

³¹like Principle Components Analysis, Linear Discriminant Analysis, Logically Linear Embedding

³²<https://www.dummies.com/programming/big-data/data-science/how-pattern-matching-works-in-data-science>

³³<https://www.mediawiki.org/wiki/MediaWiki>

for the “University of Regina, Regina, SK”. Like Wikidata, DBpedia also has a label, a description section and a set of important property-value pairs that give information related to the entity that has been described.



About: University of Regina
 An Entity of Type : جامعة عامة, from Named Graph : <http://dbpedia.org>, within Data Space : dbpedia.org

جامعة ريجينا هي جامعة عامة في كندا، تأسست عام 1911. تقع في مدن ريجينا، ساسكاتون، سوبفيل كورننت.

Property	Value
dbo:abstract	The University of Regina is a public research university located in Regina, Saskatchewan, Canada. Founded in 1911 as a private denominational high school of the Methodist Church of Canada, it began an association with the University of Saskatchewan as a junior college in 1925, and was disaffiliated by the Church and fully ceded to the University in 1934; in 1961 it attained degree-granting status as the Regina Campus of the University of Saskatchewan. It became an autonomous university in 1974. The University of Regina has an enrollment of over 15,000 full and part-time students. The university's student newspaper, The Carillon, is a member of CUP. The University of Regina is well-reputed for having a focus on experiential learning and offers internships, professional placements and practicums in addition to cooperative education placements in 41 programs. This experiential learning and career-preparation focus was further highlighted when, in 2009 the University of Regina launched the UR Guarantee Program, a unique program guaranteeing participating students a successful career launch after graduation by supplementing education with experience to achieve specific educational, career and life goals. Partnership agreements with provincial crown corporations, government departments and private corporations have helped the University of Regina both place students in work experience opportunities and help gain employment post-study. (en)
dbo:affiliation	dbr:University_of_the_Arctic dbr:Canadian_Association_of_Research_Libraries dbr:Canadian_Bureau_for_International_Education dbr:Canadian_University_Society_for_Intercollegiate_Debate dbr:International_Association_of_Universities dbr:L'Association_des_universités_de_la_francophonie_canadienne dbr:Canadian_University_Press dbr:Association_of_Universities_and_Colleges_of_Canada
dbo:athletics	dbr:U_Sports
dbo:city	dbr:Regina,_Saskatchewan
dbo:endowment	9.75E7
dbo:formerName	- Regina College (1911–1961) (en) - Regina Campus of theUniversity of Saskatchewan(1961–1974) (en)
dbo:motto	As one who serves
dbo:numberOfPostgraduateStudents	2027 (xsd:integer)
dbo:numberOfStudents	16501 (xsd:integer)

Figure 2.17: Description of University of Regina, Regina, SK on DBpedia

Figure 2.18 shows the data architecture of DBpedia. An open-link software, Virtuoso Universal Server³⁴, is a data virtualization tool used to host and publish RDF datasets on DBpedia, which can be easily accessed using SPARQL endpoint. The HTML or

³⁴https://dbpedia.org/page/Virtuoso_Universal_Server

RDF representation of the DBpedia resources is enabled by the data architecture using HTTP that supports the standard HTTP GET method calls from the web clients.




Figure 2.18: DBpedia Data Architecture

Chapter 3

Proof Of Concept

This chapter focuses on some fundamental concepts of OWL ontologies that were considered while developing the survey instrument for this research work.

3.1 Ontology in Web Semantics

Ontology is a branch of information science that encloses representation, nomenclature, and definition of various properties, categories, and relationships shared among the entities¹ that support any number of domains the user is interested in. In other words, Ontology is a form of defining a set of concepts for representing the subject properties and the relationships shared among them. According to Tom Gruber [25], ontology is “an explicit specification of a conceptualization”, where conceptualization is “an abstract, simplified view of the world (includes objects, concepts and other entities that are assumed to exist in some area of interest and the relationships that hold among them) that we wish to represent for some purpose”. In web semantics, an ontology is used to define the semantics of the resources briefly and methodically. The ontologies have have been used to “specify the physical as well as conceptual characteristics of resources, in the form of metadata schema on the semantic web, for a fixed set of

¹includes all types of data, concepts and entities

users” [30].

3.2 OWL Ontologies

W3C developed a standard ontology language called OWL² to define and describe concepts for ontology using different facilities and operations like intersection, union and negation. It is based on a logical model due to which a reasoner³ can be used to check the mutual consistency among the statements and definitions in the ontology. The reasoner is also responsible for the identification of a suitable concept for particular definitions [29].

3.2.1 Components of OWL Ontologies

An OWL ontology consists of a set of components that define and describe the concepts collectively. The basic components of any OWL ontology, Individuals, Properties and Classes, are briefly explained in this section.

- Individuals:

According to Horridge et al. [29], “Individuals represent objects in the domain in which we are interested”. Individuals are the objects of classes. Figure 3.1 shows the representation of different individuals in various domains. The triangles are used here to denote the individuals in free space.

- Properties:

The Binary Relationships⁴ between the individuals (things) are called properties.

For instance, the individuals “Max” and “Kieron” from Figure 3.1 are linked to

²<http://www.w3.org/TR/owl-guide/>

³maintains hierarchy accurately

⁴links shared by two individuals



Figure 3.1: Representation of Individuals in OWL

each other by the property “hasSibling”. Each property can have its inverse. For instance, “hasSibling” can have an inverse property “isSiblingOf”. The properties can be symmetric or transitive. It is possible to have functional properties where the properties can be restricted to having only one value. Figure 3.2 shows representation of properties between the individuals “Max” and “India”, and “Max” and “Kieron”. The relation between “Max” and “India” is “livesIn”. The arrow between two individuals in the figure denotes the property (relationship) between them.




Figure 3.2: Representation of Properties in OWL

- Classes:

In OWL, the sets consisting of individuals are called OWL classes. Mathematical (formal) descriptions are used to describe the OWL classes. These descriptions

include accurate statements on the requirements for the class membership. For instance, the class “Country” consists of all the individuals that are countries in the Domain of Discourse⁵. Inheritance in OWL classes (Class Hierarchy) may exist with the classes having subclasses and/or super-classes which is technically termed as taxonomy. “Subclasses specialise (‘are subsumed by’) their super-classes” [29]. For instance, consider the classes “Lady” and “Human”, where “Lady” is a subclass of “Human”. This implies the following statements:

- All ladies are humans
- All members of class “Lady” are members of class “Human”
- Being a “Lady” implies that individual is “Human”
- “Lady” is subsumed by “Human”

Figure 3.3 shows the representation of the classes for the individuals and properties that are shown in Figure 3.2.

3.3 OWL Ontology Inconsistencies and Reasoner

A Reasoner⁶ is used in Protégé to address and solve the inconsistencies. The current version of the Protégé Integrated Development Environment (IDE) offers support for some built-in semantic reasoners which are listed below:

- ELK 0.4.3⁷ : A Java-based fast reasoner for lightweight OWL2 EL which is available under Apache License 2.0

⁵can contain one or more classes

⁶https://en.wikipedia.org/wiki/Semantic_reasoner

⁷<https://www.w3.org/2001/sw/wiki/ELK>




Figure 3.3: Representation of OWL Classes Consisting of Individuals and Properties

- FaCT++ 1.6.5⁸ : A Tableaux-based reasoner for expressive OWL Description Logics (DL) which is implemented using C++
- Hermit 1.4.3.456⁹ : A Java-based reasoner, written using OWL, that can be used to determine consistency of the ontology as well as for the identification of relationships among the classes of the ontology
- Mastro DL-Lite¹⁰ : An Ontology-Based Data Access (OBDA) management system in which the DL-Lite family of languages for lightweight DL are used for ontology specifications
- Ontop 4.1.0¹¹ : A reasoner which uses SPARQL for querying datasets as Virtual RDF Graphs

⁸<https://www.w3.org/2001/sw/wiki/Fact>

⁹<https://www.w3.org/2001/sw/wiki/Hermit>

¹⁰https://protegewiki.stanford.edu/wiki/Mastro_DL-Lite_Reasoner

¹¹<https://www.w3.org/2001/sw/wiki/OnTop>

- Pellet and Pellet (incremental)¹² : A Java-based OWL2 reasoner for the optimization of nominals, conjunctive query answering, and incremental reasoning

¹²<https://www.w3.org/2001/sw/wiki/Pellet>

Chapter 4

OWL Ontology for Survey

4.1 Development Tool for the Creation of New OWL Vocabularies

In data science, for a fresh and developing branch like ontology engineering, it is difficult to find enough knowledge that can be reused. The field is still growing with research and development in progress as well as a lot still required to be explored in the future. As a result of this, linked open vocabularies are limited currently, and hence, the data publishers will have to create a vocabulary in case they do not find the required vocabulary from the already existing vocabularies.

There are editors available today that help the publishers to create their own linked open vocabularies. Alatrish at the University of Belgrad [2], in 2013, compared the most used ontology editors, namely, Apollo, OntoStudio, Protégé, Swoop, and TopBraid Composer. The editors were compared based on the following features:

- General description: developers' details, and accessibility on the internet (open source or software licensed)
- Software architecture and tools evaluation: semantic web architecture, support for plug-ins, backup management, and ontology storage

- Interoperability: interoperability with other ontology tools, support and translation for other languages
- Knowledge representation: Knowledge Representation (KR) paradigm of knowledge model, axiom language, and methodological support
- Inference services: built-in inference engine, other attached inference engines, and constraint/consistency checking
- Usability: graphical taxonomy, graphical views, zooms, collaborative working, and ontology libraries

After studying the details and comparison among the most used editors based on the above features by Alatrish [2], Protégé has been used for the development of the instrument to support this research and thesis work.

4.2 Protégé

Stanford University developed a free, open-source ontology development platform, Protégé¹, that offers a set of substantial tools² to build ontologies for knowledge-based applications and to implement various “knowledge-modeling structures and actions that support the creation, visualization and manipulation of ontologies in various representation formats” [2]. Protégé offers customization options to build knowledge models and to add data.

¹<https://protege.stanford.edu>

²along with various plug-ins and Java-based API

4.2.1 Usability of Protégé

The International Organization for Standardization (ISO) standard 9241³ defines usability as “the extent to which a product can be used by specified users to achieve specified goals with effectiveness, efficiency, and satisfaction in a specified context of use”. In usability engineering, Jacob Neilson [36] suggested five qualities of a usable product: “learnability, efficiency, memorability, errors (low rate, easy to recover), and satisfaction”. These were the original five dimensions of usability which were then retermed as all five words starting with “E” by Quesenbery [37], and they became popular as the five Es of usability [37]. The new terms are as shown in Figure 4.1.




Figure 4.1: Five Es of Usability

- Effective: The task is completed accurately

³<https://www.iso.org/standard/63500.html>

The user must be able to complete the desired task accurately using the design. If the user is unable to complete the task, irrespective of the time spent and efforts made to complete the task, the design is said to have failed to reach meet the design's goals. To measure effectiveness in a design, it is necessary to know users' perspectives of success and accuracy.

- Efficient: The task is completed quickly

The user must be able to complete the task easily. The interface should be designed to allow the users to complete the desired tasks with the least complexity and within the minimum possible time. If a simple task takes more than the required time for completion, the design is not feasible and would be said to not meet the goals.

- Engaging: The look and feel of the design is interactive and engaging

The look and feel of the interface must be interactive so that the user finds it interesting and continues using it. The user of the interface should be able to connect with the presentation and the organization of the components of the interface and hence should be satisfied by using the design to complete the desired task.

- Error-tolerant: Error prevention and data recovery in case any error is committed

The interface should be able to easily handle errors. This means in case the user commits mistakes, the interface should be helpful enough to not lose the work done by the user along with providing the error correction options.

- Easy to learn: The interface should be easy to learn

The user should get the feeling of familiarity and adaption while using the interface. The names of the components and tools in the design must be appropriate

so that the user can understand their purpose from the name itself. For instance, in a banking application, using the keyword “balance owed” to denote the debit amount might confuse the user by not giving a clear idea about who owes the money, that is, whether the customer owes the amount to the bank or vice versa.

The five dimensions of usability can be considered while designing as well as for evaluation. While designing, the engineers consider the five dimensions as goals to be achieved whereas while testing and evaluation, they are considered as the requirements necessary for the designed model. The five dimensions of usability were used to assess the usability of Protégé and the report of the evaluation is as follows:

- **Effective:** Protégé is an effective design as it allows the users to build ontologies and use other tools precisely. The users can complete the desired tasks accurately using the set of facilities available.
- **Efficient:** It is easy and straightforward to describe the vocabularies and build ontologies. All the desired tasks in Protégé can be completed quickly (without wasting much time) as it is easy to look for the facilities using the menus and tools available. Hence, Protégé is an efficient ontology builder.
- **Engaging:** The tools and menus in Protégé are interactive which leads to a better experience for the user. Also, the layout and the components are attractive and decent for the user to use this ontology builder whenever necessary. Overall, Protégé gives an engaging and satisfactory user experience.
- **Error-tolerant:** Protégé provides options for modifications, additions, and deletions of classes, objects, and properties, which allow the users to correct the errors that were committed. Also, the deleted classes can be recovered using “Undo” from the edit menu resulting in proving Protégé as an error-tolerant design.

- Easy to learn: Protégé is easy to learn as it has a familiar look and commonly used names for the tools and menus making it easy for the users to adapt and know them nicely. Also, the “Help” document along with a list of some frequently asked questions is available which helps the users in the correct direction whenever they are lost.

4.3 Procedure to Model the Survey Ontology in OWL Using Protégé Tools

This section focuses on a step-wise methodology that has been followed to create new OWL vocabularies for a survey using Protégé. Figure 4.2 shows the student feedback form for which the new vocabularies are described. Protégé is available for use as a web application. Protégé can also be downloaded⁴ to use as a desktop application for ontology construction and visualization.

To commence with the process of building the survey ontology, a new project needs to be created with a unique Internationalized Resource Identifier (IRI)⁵ and the ontology version. Figure 4.3 shows the Protégé home-screen with a new project created and an IRI with the name and version of ontology.

4.3.1 Classes and Class Hierarchy

The next step is to create classes and build the hierarchy for the class nodes. Each entity in Protégé is directly or indirectly a child node of the “Thing” class. Also, each object has a name-value pair, which generally are the nodes of the “Domain_Entity” class, an inherited class of Thing. Initially, four classes, “Thing”, “Domain_Entity”,

⁴<https://protege.stanford.edu/products.php#desktop-protege>

⁵<https://www.w3.org/2011/rdf-wg/wiki/IRIs/RDFConceptsProposal>

Student Feedback Form

(adapted from <http://cft.vanderbilt.edu/teaching-guides/reflecting/student-feedback/#inclass>)

Course: _____ **Instructor:** Daryl Hepting **Date:** _____

1 = Never; 5 = Always

- | | | | | | | |
|---|---|---|---|---|---|---|
| 1 | The instructor is well-prepared for class. | 1 | 2 | 3 | 4 | 5 |
| 2 | The instructor clearly communicates his expectations for student preparation and participation. | 1 | 2 | 3 | 4 | 5 |
| 3 | The instructor uses class time effectively. | 1 | 2 | 3 | 4 | 5 |
| 4 | The instructor has clear expectations for assigned work. | 1 | 2 | 3 | 4 | 5 |
| 5 | The instructor encourages student participation. | 1 | 2 | 3 | 4 | 5 |
| 6 | The instructor clearly answers questions. | 1 | 2 | 3 | 4 | 5 |
| 7 | The instructor treats students with respect. | 1 | 2 | 3 | 4 | 5 |
| 8 | The instructor effectively directs and stimulates discussion. | 1 | 2 | 3 | 4 | 5 |
| 9 | The instructor effectively encourages students to ask questions and give answers. | 1 | 2 | 3 | 4 | 5 |

What do you like best about this course?

What would you like to change about this course?

What do you think the instructor's greatest strengths are?

Figure 4.2: The Student Feedback Form, from Hepting [28]




Figure 4.3: Protégé Home-screen for a New Project with an Ontology Name and an IRI

“Independent_Entity”, and “Value” are created using class hierarchy, as shown in Figure 4.4. To create a class hierarchy for the classes that represent entities in the survey, there are three steps to be followed:

1. Select “owl:Thing” in the Class Hierarchy View of the Classes tab from the Windows menu followed by selecting “Create class hierarchy...” from the Tools menu, as shown in Figure 4.5 to open a “Enter hierarchy” pop-up window which allows the users to add classes to the ontology.
2. Enter the class names in the pop-up window starting from the left. For the child nodes, leave some spaces before writing the class name. Each horizontal line consists of one class name, as shown in Figure 4.6.
3. On clicking “Continue” on the pop-up window in Figure 4.6, it opens up a new pop-up window. Here, it is important to state whether one wants the sibling classes to be disjoint or not. The checkbox needs to be checked accordingly.




Figure 4.4: Class Hierarchy of Thing, Domain_Entity, Independent_Entity, and Value




Figure 4.5: Tools Menu to Create Class Hierarchy




Figure 4.6: “Enter hierarchy” Pop-up Window

Usually, it is recommended to create disjoint sibling classes which can be changed later as necessary, as shown in Figure 4.7.

Once the classes are added, the next step is to describe the classes. Descriptions of classes like “Equivalent to”, “SubClass Of”, “Instances”, “Disjoint With” and so on can be added using the Description view of the Class tab (shown in Figure 4.4). Each class can be described individually by selecting a particular class and adding details to the description view.

All the classes can be created and described using the above steps. In the end, the class hierarchy for the survey ontology would be as shown in Figure 4.8. The survey can have “Respondent”, “Response Date”, “Type of Survey”, “Survey Questions”, “Survey Answers”, and “Likert Scale”, which are considered for this ontology as well. Here, the type of survey used is “feedback survey”. The survey questions and survey answers would further have entities corresponding to various forms of question-answer.




Figure 4.7: Pop-up Window to Create Disjoint Sibling Classes

Generally, feedback surveys consist of two types of questions, namely, “Likert Questions” and “Open-ended Questions”. The type of questions might differ depending on the designer of the survey, some of which, as stated on the *SurveyMonkey*⁶ website, are listed below.

- Multiple Choice Questions
- Rating Scale Questions
- Likert Scale Questions
- Matrix Questions
- Dropdown Questions
- Open-ended Questions
- Demographic Questions
- Ranking Questions
- Image Choice Questions
- Click Map Questions
- File Upload Questions
- Slider Questions
- Benchmarkable Questions

⁶<https://www.surveymonkey.com/mp/survey-question-types/>




Figure 4.8: Class Hierarchy in Survey Ontology

For this research, the feedback survey that has been considered has Likert and Open-ended questions. The entities described for the questions and answers are “LikertScaleQuestions”, and “OpenEndedQuestions” as sub-classes of “SurveyQuestions”, and “LikertScaleAnswers”, and “OpenEndedAnswers” as sub-classes of “SurveyAnswers”.

For all the survey questions, there would be a question and an answer, where both of them would be considered as distinct entities. Likert questions are the questions for which the answers are from the preset list of answers. For the Likert questions, the questions can be either of type “Never-Always-4” or “Never-Always-5” or “Never-Always-7” or “Never-Always-*”, of which Never-Always-5 has been used by Hepting [28]. In a Never-Always-5 type of survey, 5 degrees of agreement are used as shown in Table 4.1. In addition to these degrees, this ontology also considers the instances where the question wouldn’t be answered. In this case, the field corresponding to the answer is left blank. On the other hand, Open-ended questions have unpredictable answers and hence there cannot be any degree of measurement for Open-ended questions.

Number	Agreement
1	Never
2	[Rarely]
3	[Sometimes]
4	[Often]
5	Always

Table 4.1: Degrees of Agreement for Likert-scale Questions

4.3.2 Object Properties and Object Property Hierarchy

The next step in building the ontology, after describing the classes, is describing the “Object Properties”. Object properties are used to link the entities (classes in Protégé). The “owl:topObjectProperty” is the root node of the object properties’ hierarchy. The

hierarchy for object properties can be built by selecting a property in the Object Property Hierarchy view of the Object Property Views tab and then going to the tools menu as shown in Figure 4.9. The remaining steps are similar to the ones that are followed for building class hierarchy (Figure 4.5, 4.6, and 4.7).




Figure 4.9: Tools Menu to Create Object Property Hierarchy

Also, the description view of object properties hierarchy allows the user to describe the object properties. The details that can be added or modified using the description view are “Equivalent To”, “SubProperty Of”, “Inverse Of”, “Domains (intersection)”, “Ranges (intersection)”, “Disjoint With”, and “SuperProperty Of (Chain)”.

The names of the object properties usually start with an “is” or a “has”. For instance, consider two classes: “Lady” (class 1) and “Parita” (class 2). To describe the link between class 1 (Lady) and class 2 (Parita) such that class 1 has value class 2 and class 2 is value of class 1, the properties “hasName” and “isNameOf” would be used

respectively, as shown in Figure 4.10.




Figure 4.10: Object Properties for Classes “Lady” and “Parita”

Each object property might have a corresponding inverse property. For the above instance, it can be said that:

Lady hasName Parita **is equivalent to** Parita isNameOf Lady

Here, “hasName” is inverse of “isNameOf” and “isNameOf” is inverse of “hasName”. Apart from inverse, domain and range⁷ are two other important parts of description of object properties. According to Horridge et al. [29], in OWL, “domain and range are not constraints to be checked. They are axioms which are used by the reasoner to make inferences”. As shown in Figure 4.11, “Lady” acts as the “Domain” and “Parita” acts as the “Range” for “hasName” whereas for “isNameOf”, “Parita” is the “Domain” and “Lady” is the “Range”.

Using the above method of naming and building object properties, some of the primary object properties are described for the survey ontology as shown in Figure 4.12 where as Table 4.2 shows the list of the object properties along with their domain and range classes (entities). Table 4.3 consists of the parent nodes and inverse properties of the object properties. The three parent nodes involved in object property hierarchy

⁷<http://protegeproject.github.io/protege/views/object-property-description/>




Figure 4.11: Domain and Range Classes for “hasName” and “isNameOf”

are “owl:TopObjectProperty”, “hasContent”, and “isContentOf”. Protégé has a built-in “Reasoner” that allows the users to determine inconsistencies of a class as well as to discover implicit information.

Object Property	Domain	Range
hasSurveyQuestion	Survey	SurveyQuestions
hasLikertScale	LikertScaleQuestions	LikertScale
hasLikertScaleAnswer	Respondent	LikertScale
hasRespondedOn	Respondent	ResponseDate
respondedToSurvey	Respondent	Survey
hasOEAnswer_Change	OpenEndedQuestions	OpenEndedAnswers
hasOEAnswer_LikeBest	OpenEndedQuestions	OpenEndedAnswers
hasOEAnswer_Strengths	OpenEndedQuestions	OpenEndedAnswers

Table 4.2: Object Properties and Their Domain and Range

4.3.3 Data Properties and Data Property Hierarchy

Furthermore, the “Data Properties” can also be described for ontology. “An ontology data property provides a relation to attach an entity instance to some literal datatype




Figure 4.12: Object Property Hierarchies, Domain and Range for Classes

Object Property	Parent Node	Inverse Property
hasContent	owl:TopObjectProperty	isContentOf
isContentOf	owl:TopObjectProperty	hasContent
hasLikertScale	owl:TopObjectProperty	
hasLikertScaleAnswer	owl:TopObjectProperty	
hasOEAnswer_Change	owl:TopObjectProperty	
hasOEAnswer_LikeBest	owl:TopObjectProperty	
hasOEAnswer_Strengths	owl:TopObjectProperty	
hasRespondedOn	owl:TopObjectProperty	
respondedByRespondent	owl:TopObjectProperty	respondedToSurvey
respondedToSurvey	owl:TopObjectProperty	respondedByRespondent
hasSurveyQuestion	hasContent	isSurveyQuestionOf
hasSurveyAnswer	hasContent	isSurveyAnswerOf
isSurveyQuestionOf	isContentOf	hasSurveyQuestion
isSurveyAnswerOf	isContentOf	hasSurveyAnswer

Table 4.3: Object Properties with Their Parent Nodes and Inverse Properties

value (an RDF number, string or data for example) that is a measure or estimate of what that data property is about.”⁸ In Protégé, the “owl:topDataProperty” is the root node of the data properties’ hierarchy. The data property hierarchy can be built by selecting a property in the Data Property Hierarchy view of the Data Property Views tab and then going to the tools menu as shown in Figure 4.13. The remaining steps are similar to the ones that are followed for building class and object property hierarchy (Figure 4.5, 4.6, and 4.7).

Data properties can be described using the description view of data properties of hierarchy which included details like “Equivalent To”, “SubProperty Of”, “Domains (intersection)”, “Ranges”, and “Disjoint With”. Figure 4.14 shows the data properties described for the survey ontology. The parent node of all the data properties is “owl:topDataProperty” and the domain and range for all the data properties are “Respondent” and “xsd:positiveInteger” respectively. Table 4.4 consists of list of data properties along with their domain and range classes (entities).

⁸<https://ddooley.github.io/docs/data-properties/>




Figure 4.13: Tools Menu to Create Data Property Hierarchy




Figure 4.14: Data Property Hierarchies, Domain and Range for Classes

Data Property	Domain	Range
hasLikertAns_is_well-prepared_for_class	Respondent	xsd:positiveInteger
hasLikertAns_clearly_communicates_his_expectations_for_student_preparation_and_participation	Respondent	xsd:positiveInteger
hasLikertAns_uses_class_time_effectively	Respondent	xsd:positiveInteger
hasLikertAns_has_clear_expectations_for_assigned_work	Respondent	xsd:positiveInteger
hasLikertAns_encourages_student_participation	Respondent	xsd:positiveInteger
hasLikertAns_clearly_answers_questions	Respondent	xsd:positiveInteger
hasLikertAns_treats_students_with_respect	Respondent	xsd:positiveInteger
hasLikertAns_effectively_directs_and_stimulates_discussion	Respondent	xsd:positiveInteger
hasLikertAns_effectively_encourages_students_to_ask_questions_and_give_answers	Respondent	xsd:positiveInteger

Table 4.4: Data Properties and Their Domain and Range

4.3.4 Individuals

After describing the classes, object properties, data properties, and individuals, the next step is to determine and fix the errors and inconsistencies in the ontology using a Reasoner. The final class hierarchy of the OWL ontology in Protégé, after using the HermiT 1.4.3.456 reasoner, would be as shown in Figure 4.15.

The grey (all entities) and blue (“Survey” entity) back arrows in front of the yellow solid dot, which indicates class, show parent/child relationship other than that of SubClassOf. This feature can be enabled and disabled by selecting “Display relationship in class hierarchy” option from the “View” menu of Protégé. Figure 4.16 shows the relation indicated by the blue back arrow.




Figure 4.15: Class Hierarchy for the Final Version of Survey Ontology




Figure 4.16: Parent/Child Relation indicated by "Blue Back" Arrow

4.4 Visualization Tools for OWL Ontology

The next step is visualization of the built OWL ontology using various visualization tools. Protégé supports plug-ins for some visualization tools like OntoGraf and OWLViz whereas tools like WebVOWL, RelFinder and OWLGrEd are available for use as web-based tools. This section focuses on the two tools, OntoGraf and WebVOWL, used for the visualization of the survey ontology in this research.

4.4.1 OntoGraf

Falconer [24] introduced OntoGraf as a Protégé plug-in for the visualization of the OWL ontologies. This tool helps the users to represent the ontologies, built using Protégé, by repetitively allowing and restricting the desired classes. OntoGraf offers various graph layout options for visualization like Grid Layout⁹, Spring Layout, and Tree Layout¹⁰. Antoniazzi and Viola [3] stated that the “individuals of a class can be visualized in its tooltip, but this is uncomfortable when dealing with a high number of assertional statements”. The graphs generated using OntoGraf can be exported as image files of various formats such as Portable Network Graphics (PNG), Joint Photographic Experts Group (JPEG), Graphics Interchange Format (GIF) and as a dot file¹¹.

Figure 4.17 shows the graph generated using OntoGraf for the survey ontology. To start with the graph formation, the classes “Thing”, “Domain_entity”, “Independent_entity” and “Value” were selected followed by expansion of “Independent_entity” and “Value” classes by double-clicking them. This expansion adds all the classes that are connected to the classes. The classes connected includes both the subclasses as well as the ones linked through the object properties. Solid blue lines are used to denote the

⁹classes are arranged in a grid alphabetically

¹⁰both horizontal and vertical

¹¹a Microsoft Word Template with the details of default settings

relationships between the classes and their subclasses whereas dashed lines are used to represent the object properties.




Figure 4.17: OntoGraf for Survey Ontology

4.4.2 WebVOWL

WebVOWL [32], the Web-based Visual Web Ontology Language (VOWL), one of the variety of forms in which the VOWL visualization tool is available, represents the “ontologies graphically using a force-directed graph layout” [3]. VOWL follows some ground rules for the representation of OWL ontologies which are:

1. Circles are used to denote classes. Also, different types are assigned different colors. For instance, OWL classes are denoted using “light blue circles”.
2. Black solid lines are used to represent OWL object and datatype properties. The object properties use light blue labels whereas the datatype properties are labelled in green.
3. The relationships between the classes and their subclasses are represented using dashed lines.

Figure 4.18 shows the graphical representation of the survey ontology using WebVOWL. The figure focuses on only some of the class-subclass relationships and some of the object properties. The metadata and the statistics of the node (circle) or the edge (line) can be retrieved by clicked on them. The entities (classes) and their relationships (object and datatype properties) can be presented or restricted using filters. The VOWL graph can be exported as an Scalable Vector Graphics (SVG) image file or a JavaScript Object Notation (JSON) code file.




Figure 4.18: WebVOWL for Survey Ontology

Chapter 5

Conclusion and Future Work

This Chapter focuses on the prime offerings of this research work where one of the sections includes the conclusions drawn from the work done and the other discusses future work that can be done to succeed in this research.

5.1 Conclusion

This thesis work describes a new attempt on developing a linked open data instrument for feedback surveys. It focuses on the issues encountered and the user experience of various tools and references used for the modelling of the instrument and for data visualization. The thesis revolves around some fundamental topics like Semantic Web, Linked Open Data, RDF, and OWL ontologies. It also describes how and why Protégé has been used over other ontology development tools to describe survey vocabularies. The thesis can be considered as a guide for the researchers who are interested in exploring this lesser known aspect of semantic web.

The thesis includes a detailed background study on the fundamental topics, the usability of Protégé, and discussion on some tools for linked open data visualizations. Chapter 4 describes the steps involved in building the survey ontology using Protégé, various parts and facilities offered by Protégé, and the visual representation of the

ontology toward the end.

5.2 Future Work

This thesis also offers a number of future development options like building a real-time linked open data application for feedback surveys that follows the linked data life cycle. Web Scraping (or Web Extraction) is a method of extracting desired data from the resources on the WWW into a separate file for data retrieval and data analysis. Data Extraction is one of the steps in the linked data life cycle that can be explored in future research to facilitate use of data that has already been published to the web with HTML tables.

Versioning of the survey ontology is a topic of interest. The ontology vocabularies (available in Appendix C) can be reused for appropriate applications but they may need to be updated over time. Hence, ontology versioning and version management of the survey instrument for this feedback survey, as well as for other types of surveys is an aspect of this research that can be explored.

Developing a data entry form for the feedback survey instrument that can be defined, in part, directly from the survey ontology would facilitate recording of survey responses collected offline.

Appendix A

Sample CSV Data

Likert Item	5	Always	4	[Mostly]	3	[Sometimes]	2	[Rarely]	1	Never	Total		
1. The instructor is well-prepared for class	29	16	8	0	0	53							
2. The instructor clearly communicates his expectations for student preparation and participation	33	15	4	1	0	53							
3. The instructor uses class time effectively	26	18	7	2	0	53							
4. The instructor has clear expectations for assigned work	34	10	8	1	0	53							
5. The instructor encourages student participation	45	6	2	0	0	53							
6. The instructor clearly answers questions	31	16	5	1	0	53							
7. The instructor treats students with respect	49	3	1	0	0	53							
8. The instructor effectively directs and stimulates discussion	38	10	4	1	0	53							
9. The instructor effectively encourages students to ask questions and give answers	43	8	2	0	0	53							
Total	328	102	41	6	0	477							
Weighted Average:	91%	'Always'											
Response	Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Avg	SD	Mode	Median
1	5	5	5	5	5	5	5	5	5	5.00	0.00	5	5
2	4	3	3	2	3	4	5	3	4	3.44	0.88	3	3

3,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 4,5,5,4,5,5,5,5,5,5,4.89,0.33,5,5
 5,5,5,4,5,5,5,5,4,5,4.78,0.44,5,5
 6,3,4,4,3,5,4,5,5,5,4.22,0.83,5,4
 7,3,4,4,4,4,4,5,3,3,3.78,0.67,4,4
 8,4,4,4,4,5,5,5,5,5,4.56,0.53,5,5
 9,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 10,4,5,4,5,5,5,4,4,5,4.56,0.53,5,5
 11,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 12,5,5,5,4,5,4,5,5,5,4.78,0.44,5,5
 13,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 14,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 15,4,5,4,4,5,5,5,5,5,4.67,0.50,5,5
 16,5,5,4,5,5,5,5,5,5,4.89,0.33,5,5
 17,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 18,3,4,5,3,3,2,3,4,4,3.44,0.88,3,3
 19,3,3,3,3,5,3,5,4,5,3.78,0.97,3,3
 20,4,4,4,5,5,5,5,5,5,4.67,0.50,5,5
 21,4,4,3,5,5,4,5,5,5,4.44,0.73,5,5
 22,3,3,3,3,5,3,5,4,5,3.78,0.97,3,3
 23,4,4,4,3,5,4,5,5,5,4.33,0.71,4,4
 24,4,4,5,5,5,4,5,5,5,4.67,0.50,5,5
 25,3,2,2,3,4,3,5,3,4,3.22,0.97,3,3
 26,3,3,2,3,4,3,4,2,3,3.00,0.71,3,3
 27,5,5,4,5,5,5,5,4,4,4.67,0.50,5,5
 28,5,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5

29,4,4,4,3,5,4,5,5,4,4.22,0.67,4,4
 30,4,5,4,5,5,4,5,5,4,4.56,0.53,5,5
 31,5,5,5,5,5,4,5,5,5,4.89,0.33,5,5
 32,5,5,5,5,4,5,5,4,5,4.78,0.44,5,5
 33,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 34,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 35,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 36,4,4,3,4,5,5,5,5,5,4.44,0.73,5,5
 37,5,5,5,5,5,5,5,4,5,4.89,0.33,5,5
 38,4,4,3,4,5,3,5,4,5,4.11,0.78,4,4
 39,5,5,5,4,5,4,5,5,4,4.67,0.50,5,5
 40,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 41,5,4,5,5,5,5,5,5,5,4.89,0.33,5,5
 42,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 43,4,5,4,5,5,5,5,5,5,4.78,0.44,5,5
 44,4,5,4,5,4,4,5,4,5,4.44,0.53,4,4
 45,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 46,3,4,4,4,4,4,5,3,4,3.89,0.60,4,4
 47,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 48,4,4,4,5,5,4,4,5,5,4.44,0.53,4,4
 49,4,4,3,4,5,5,5,5,5,4.44,0.73,5,5
 50,5,5,4,4,5,4,5,5,5,4.67,0.50,5,5
 51,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 52,5,5,5,5,5,5,5,5,5,5.00,0.00,5,5
 53,5,5,5,5,5,4,5,5,5,4.89,0.33,5,5
 Avg,4.40,4.51,4.28,4.45,4.81,4.45,4.91,4.60,4.77,4.58,0.21

SD,0.74 ,0.72 ,0.84 ,0.82 ,0.48 ,0.75 ,0.35 ,0.72 ,0.51

Mode,5 ,5 ,5 ,5 ,5 ,5 ,5 ,5 ,5

Median ,5 ,5 ,4 ,5 ,5 ,5 ,5 ,5 ,5

Appendix B

Expression of CSV Data in RDF

```
<?xml version="1.0" encoding="UTF-8"?>
2 <rdf:RDF
    xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
4    xmlns:owl="http://www.w3.org/2002/07/owl#"
    xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
6    xmlns:foaf="http://xmlns.com/foaf/0.1/">
    <rdf:Description rdf:about="http://survey.org/Question_1.
8 %20The%20instructor%20is%20well-prepared%20for%20class">
        <Always xmlns="http://survey.org/likert/" rdf:datatype=
10 "http://www.w3.org/2001/XMLSchema#int">29</Always>
        <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
12 "http://www.w3.org/2001/XMLSchema#int">16</Mostly>
        <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
14 "http://www.w3.org/2001/XMLSchema#int">8</Sometimes>
        <Rarely xmlns="http://survey.org/likert/">0</Rarely>
16 <Never xmlns="http://survey.org/likert/">0</Never>
    </rdf:Description>
18
    <rdf:Description rdf:about="http://survey.org/likert/Total">
20 <Responses xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">53</Responses>
22 </rdf:Description>

24 <rdf:Description rdf:about="http://survey.org/Question_2.
    %20The%20instructor%20clearly%20communicates%20his%20expectations
26 %20for%20student%20preparation%20and%
    20participation">
28 <Always xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">33</Always>
30 <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">15</Mostly>
32 <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">4</Sometimes>
34 <Rarely xmlns="http://survey.org/likert/">1</Rarely>
    <Never xmlns="http://survey.org/likert/">0</Never>
36 </rdf:Description>
```

```

38 <rdf:Description rdf:about="http://survey.org/likert/Total">
    <Responses xmlns="http://survey.org/likert/" rdf:datatype=
40   "http://www.w3.org/2001/XMLSchema#int">53</Responses>
    </rdf:Description>
42
    <rdf:Description rdf:about="http://survey.org/Question_3.
44 %20The%20instructor%20uses%20class%20time%20effectively">
    <Always xmlns="http://survey.org/likert/" rdf:datatype=
46   "http://www.w3.org/2001/XMLSchema#int">26</Always>
    <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
48   "http://www.w3.org/2001/XMLSchema#int">18</Mostly>
    <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
50   "http://www.w3.org/2001/XMLSchema#int">7</Sometimes>
    <Rarely xmlns="http://survey.org/likert/">2</Rarely>
52   <Never xmlns="http://survey.org/likert/">0</Never>
    </rdf:Description>
54
    <rdf:Description rdf:about="http://survey.org/likert/Total">
56   <Responses xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">53</Responses>
58 </rdf:Description>

60 <rdf:Description rdf:about="http://survey.org/Question_4.
    %20The%20instructor%20has%20clear%20expectations%20for
62 %20assigned%20work">
    <Always xmlns="http://survey.org/likert/" rdf:datatype=
64   "http://www.w3.org/2001/XMLSchema#int">34</Always>
    <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
66   "http://www.w3.org/2001/XMLSchema#int">10</Mostly>
    <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
68   "http://www.w3.org/2001/XMLSchema#int">8</Sometimes>
    <Rarely xmlns="http://survey.org/likert/">1</Rarely>
70   <Never xmlns="http://survey.org/likert/">0</Never>
    </rdf:Description>
72
    <rdf:Description rdf:about="http://survey.org/likert/Total">
74   <Responses xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">53</Responses>
76 </rdf:Description>

78 <rdf:Description rdf:about="http://survey.org/Question_5.%20The
    %20instructor%20encourages%20student%20participation">
80   <Always xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">45</Always>
82   <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">6</Mostly>
84   <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">2</Sometimes>
86   <Rarely xmlns="http://survey.org/likert/">0</Rarely>
    <Never xmlns="http://survey.org/likert/">0</Never>
88 </rdf:Description>

```



```

90 <rdf:Description rdf:about="http://survey.org/likert/Total">
    <Responses xmlns="http://survey.org/likert/" rdf:datatype=
92   "http://www.w3.org/2001/XMLSchema#int">53</Responses>
    </rdf:Description>
94
    <rdf:Description rdf:about="http://survey.org/Question_6.%20The
96 %20instructor%20clearly%20answers%20questions">
    <Always xmlns="http://survey.org/likert/" rdf:datatype=
98   "http://www.w3.org/2001/XMLSchema#int">31</Always>
    <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
100  "http://www.w3.org/2001/XMLSchema#int">16</Mostly>
    <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
102  "http://www.w3.org/2001/XMLSchema#int">5</Sometimes>
    <Rarely xmlns="http://survey.org/likert/">1</Rarely>
104  <Never xmlns="http://survey.org/likert/">0</Never>
    </rdf:Description>
106
    <rdf:Description rdf:about="http://survey.org/likert/Total">
108  <Responses xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">53</Responses>
110 </rdf:Description>

112 <rdf:Description rdf:about="http://survey.org/Question_7.%20The
    %20instructor%20treats%20students%20with%20respect">
114  <Always xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">49</Always>
116  <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">3</Mostly>
118  <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">1</Sometimes>
120  <Rarely xmlns="http://survey.org/likert/">0</Rarely>
    <Never xmlns="http://survey.org/likert/">0</Never>
122 </rdf:Description>

124 <rdf:Description rdf:about="http://survey.org/likert/Total">
    <Responses xmlns="http://survey.org/likert/" rdf:datatype=
126  "http://www.w3.org/2001/XMLSchema#int">53</Responses>
    </rdf:Description>
128
    <rdf:Description rdf:about="http://survey.org/Question_8.%20The
130 %20instructor%20effectively%20directs%20and%20stimulates
    %20discussion">
132  <Always xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">38</Always>
134  <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">10</Mostly>
136  <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
    "http://www.w3.org/2001/XMLSchema#int">4</Sometimes>
138  <Rarely xmlns="http://survey.org/likert/">1</Rarely>
    <Never xmlns="http://survey.org/likert/">0</Never>
140 </rdf:Description>

```

```

142 <rdf:Description rdf:about="http://survey.org/likert/Total">
    <Responses xmlns="http://survey.org/likert/" rdf:datatype=
144   "http://www.w3.org/2001/XMLSchema#int">53</Responses>
    </rdf:Description>
146
    <rdf:Description rdf:about="http://survey.org/Question_9.%20The
148 %20instructor%20effectively%20encourages%20students%20to
    %20ask%20questions%20and%20give%20answers">
150   <Always xmlns="http://survey.org/likert/" rdf:datatype=
        "http://www.w3.org/2001/XMLSchema#int">43</Always>
152   <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
        "http://www.w3.org/2001/XMLSchema#int">8</Mostly>
154   <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
        "http://www.w3.org/2001/XMLSchema#int">2</Sometimes>
156   <Rarely xmlns="http://survey.org/likert/">0</Rarely>
        <Never xmlns="http://survey.org/likert/">0</Never>
158 </rdf:Description>

160 <rdf:Description rdf:about="http://survey.org/likert/Total">
    <Responses xmlns="http://survey.org/likert/" rdf:datatype=
162   "http://www.w3.org/2001/XMLSchema#int">53</Responses>
    </rdf:Description>
164
    <rdf:Description rdf:about="http://survey.org/likert/Question_Total">
166   <Always xmlns="http://survey.org/likert/" rdf:datatype=
        "http://www.w3.org/2001/XMLSchema#int">328</Always>
168   <Mostly xmlns="http://survey.org/likert/" rdf:datatype=
        "http://www.w3.org/2001/XMLSchema#int">102</Mostly>
170   <Sometimes xmlns="http://survey.org/likert/" rdf:datatype=
        "http://www.w3.org/2001/XMLSchema#int">41</Sometimes>
172   <Rarely xmlns="http://survey.org/likert/">6</Rarely>
        <Never xmlns="http://survey.org/likert/">0</Never>
174 </rdf:Description>

176 <rdf:Description rdf:about="http://survey.org/likert/Total">
    <Responses xmlns="http://survey.org/likert/" rdf:datatype=
178   "http://www.w3.org/2001/XMLSchema#int">477</Responses>
    </rdf:Description>
180
    </rdf:RDF>

```

Appendix C

OWL Classes to be Used to Describe Surveys

```
<?xml version="1.0"?>
2 <Ontology xmlns="http://www.w3.org/2002/07/owl#"
  xml:base="http://www.semanticweb.org/pda324/ontologies/survey"
4   xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:xml="http://www.w3.org/XML/1998/namespace"
6   xmlns:xsd="http://www.w3.org/2001/XMLSchema#"
  xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
8   ontologyIRI="http://www.semanticweb.org/pda324/ontologies/survey"
  versionIRI="http://www.semanticweb.org/pda324/ontologies/survey/1.10"
  ">
10  <Prefix name="" IRI="http://www.semanticweb.org/pda324/
  ontologies/survey"/>
12  <Prefix name="owl" IRI="http://www.w3.org/2002/07/owl#" />
  <Prefix name="rdf" IRI="http://www.w3.org/1999/02/22-rdf-syntax-ns#" /
  >
14  <Prefix name="xml" IRI="http://www.w3.org/XML/1998/namespace" />
  <Prefix name="xsd" IRI="http://www.w3.org/2001/XMLSchema#" />
16  <Prefix name="rdfs" IRI="http://www.w3.org/2000/01/rdf-schema#" />
  <Declaration>
18    <Class IRI="#Always" />
  </Declaration>
20  <Declaration>
    <Class IRI="#Domain_entity" />
22  </Declaration>
  <Declaration>
24    <Class IRI="#Independent_entity" />
  </Declaration>
26  <Declaration>
    <Class IRI="#Likert_NeverAlways5" />
28  </Declaration>
  <Declaration>
30    <Class IRI="#Likert_NeverAlways5_names" />
  </Declaration>
```

```

32    <Declaration>
33        <Class IRI="#Likert_NeverAlways5_numbers"/>
34    </Declaration>
35    <Declaration>
36        <Class IRI="#Likert_question"/>
37    </Declaration>
38    <Declaration>
39        <Class IRI="#Never"/>
40    </Declaration>
41    <Declaration>
42        <Class IRI="#Open_Ended_question"/>
43    </Declaration>
44    <Declaration>
45        <Class IRI="#Respondents"/>
46    </Declaration>
47    <Declaration>
48        <Class IRI="#Sample_Detail"/>
49    </Declaration>
50    <Declaration>
51        <Class IRI="#Survey"/>
52    </Declaration>
53    <Declaration>
54        <Class IRI="#Survey_Question"/>
55    </Declaration>
56    <Declaration>
57        <Class IRI="#Value"/>
58    </Declaration>
59    <Declaration>
60        <Class IRI="#feedback_survey"/>
61    </Declaration>
62    <Declaration>
63        <Class IRI="#sample_courseID"/>
64    </Declaration>
65    <Declaration>
66        <Class IRI="#sample_course_name"/>
67    </Declaration>
68    <Declaration>
69        <Class IRI="#sample_max_responses"/>
70    </Declaration>
71    <Declaration>
72        <Class IRI="#sample_name"/>
73    </Declaration>
74    <Declaration>
75        <Class IRI="#sample_number"/>
76    </Declaration>
77    <Declaration>
78        <Class IRI="#sample_semester"/>
79    </Declaration>
80    <Declaration>
81        <Class IRI="#0"/>
82    </Declaration>
83    <Declaration>

```

```

84     <Class IRI="#1"/>
      </Declaration>
86 <Declaration>
      <Class IRI="#1_The_instructor_is_well-prepared_for_class"/>
88 </Declaration>
      <Declaration>
90     <Class IRI="#1_What_do_you_like_the_best_about_this_course?"/>
      </Declaration>
92 <Declaration>
      <Class IRI="#2"/>
94 </Declaration>
      <Declaration>
96     <Class IRI="#2_The_instructor_clearly_communicates_his
      _expectations_for_student_preparation_and_participation"/>
98 </Declaration>
      <Declaration>
100    <Class IRI="#2_What_would_you_like_to_change_about_this_course?"/
    >
      </Declaration>
102 <Declaration>
      <Class IRI="#3"/>
104 </Declaration>
      <Declaration>
106     <Class IRI="#3_The_instructor_uses_class_time_effectively"/>
      </Declaration>
108 <Declaration>
      <Class IRI="#3_What_do_you_think_the_instructor's_greatest
110     _strengths_are?"/>
      </Declaration>
112 <Declaration>
      <Class IRI="#4"/>
114 </Declaration>
      <Declaration>
116     <Class IRI="#4_The_instructor_has_clear_expectations_for
      _assigned_work"/>
118 </Declaration>
      <Declaration>
120     <Class IRI="#5"/>
      </Declaration>
122 <Declaration>
      <Class IRI="#5_The_instructor_encourages_student_participation"/>
124 </Declaration>
      <Declaration>
126     <Class IRI="#6_The_instructor_clearly_answers_questions"/>
      </Declaration>
128 <Declaration>
      <Class IRI="#7_The_instructor_treats_students_with_respect"/>
130 </Declaration>
      <Declaration>
132     <Class IRI="#8_The_instructor_easily_directs_and_simulates
      _discussion"/>
134 </Declaration>

```

```

136     <Declaration>
137         <Class IRI="#9_The_instructor_effectively_encourages_students
138             _to_ask_questions_and_give_answers"/>
139     </Declaration>
140     <Declaration>
141         <Class IRI="#[No_Answer]"/>
142     </Declaration>
143     <Declaration>
144         <Class IRI="#[Often]"/>
145     </Declaration>
146     <Declaration>
147         <Class IRI="#[Rarely]"/>
148     </Declaration>
149     <Declaration>
150         <Class IRI="#[Sometimes]"/>
151     </Declaration>
152     <Declaration>
153         <ObjectProperty IRI="#hasCourseID"/>
154     </Declaration>
155     <Declaration>
156         <ObjectProperty IRI="#hasCourseName"/>
157     </Declaration>
158     <Declaration>
159         <ObjectProperty IRI="#hasMaxResponses"/>
160     </Declaration>
161     <Declaration>
162         <ObjectProperty IRI="#hasName"/>
163     </Declaration>
164     <Declaration>
165         <ObjectProperty IRI="#hasNumber"/>
166     </Declaration>
167     <Declaration>
168         <ObjectProperty IRI="#hasRespondent"/>
169     </Declaration>
170     <Declaration>
171         <ObjectProperty IRI="#hasSampleDetail"/>
172     </Declaration>
173     <Declaration>
174         <ObjectProperty IRI="#hasSemester"/>
175     </Declaration>
176     <Declaration>
177         <ObjectProperty IRI="#hasSurveyQuestion"/>
178     </Declaration>
179     <Declaration>
180         <ObjectProperty IRI="#isCourseIDOf"/>
181     </Declaration>
182     <Declaration>
183         <ObjectProperty IRI="#isCourseNameOf"/>
184     </Declaration>
185     <Declaration>
186         <ObjectProperty IRI="#isMaxResponseOf"/>
187     </Declaration>

```

```

188     <Declaration>
189         <ObjectProperty IRI="#isNameOf" />
190     </Declaration>
191 <Declaration>
192     <ObjectProperty IRI="#isNumberOf" />
193 </Declaration>
194 <Declaration>
195     <ObjectProperty IRI="#isRespondentOf" />
196 </Declaration>
197 <Declaration>
198     <ObjectProperty IRI="#isSampleDetailOf" />
199 </Declaration>
200 <Declaration>
201     <ObjectProperty IRI="#isSemesterOf" />
202 </Declaration>
203 <Declaration>
204     <ObjectProperty IRI="#isSurveyQuestionOf" />
205 </Declaration>
206 <EquivalentClasses>
207     <Class IRI="#Always" />
208     <Class IRI="#5" />
209 </EquivalentClasses>
210 <EquivalentClasses>
211     <Class IRI="#Never" />
212     <Class IRI="#1" />
213 </EquivalentClasses>
214 <EquivalentClasses>
215     <Class IRI="#0" />
216     <Class IRI="#[No_Answer]" />
217 </EquivalentClasses>
218 <EquivalentClasses>
219     <Class IRI="#2" />
220     <Class IRI="#[Rarely]" />
221 </EquivalentClasses>
222 <EquivalentClasses>
223     <Class IRI="#3" />
224     <Class IRI="#[Sometimes]" />
225 </EquivalentClasses>
226 <EquivalentClasses>
227     <Class IRI="#4" />
228     <Class IRI="#[Often]" />
229 </EquivalentClasses>
230 <SubClassOf>
231     <Class IRI="#Always" />
232     <Class IRI="#Likert_NeverAlways5_names" />
233 </SubClassOf>
234 <SubClassOf>
235     <Class IRI="#Independent_entity" />
236     <Class IRI="#Domain_entity" />
237 </SubClassOf>
238 <SubClassOf>
239     <Class IRI="#Likert_NeverAlways5" />

```

```

240     <Class IRI="#Likert_question"/>
    </SubClassOf>
    <SubClassOf>
242     <Class IRI="#Likert_NeverAlways5_names"/>
        <Class IRI="#Likert_NeverAlways5"/>
244    </SubClassOf>
    <SubClassOf>
246     <Class IRI="#Likert_NeverAlways5_numbers"/>
        <Class IRI="#Likert_NeverAlways5"/>
248    </SubClassOf>
    <SubClassOf>
250     <Class IRI="#Likert_question"/>
        <Class IRI="#Survey_Question"/>
252    </SubClassOf>
    <SubClassOf>
254     <Class IRI="#Likert_question"/>
        <Class IRI="#Value"/>
256    </SubClassOf>
    <SubClassOf>
258     <Class IRI="#Never"/>
        <Class IRI="#Likert_NeverAlways5_names"/>
260    </SubClassOf>
    <SubClassOf>
262     <Class IRI="#Open_Ended_question"/>
        <Class IRI="#Survey_Question"/>
264    </SubClassOf>
    <SubClassOf>
266     <Class IRI="#Open_Ended_question"/>
        <Class IRI="#Value"/>
268    </SubClassOf>
    <SubClassOf>
270     <Class IRI="#Respondents"/>
        <Class IRI="#Independent_entity"/>
272    </SubClassOf>
    <SubClassOf>
274     <Class IRI="#Sample_Detail"/>
        <Class IRI="#Independent_entity"/>
276    </SubClassOf>
    <SubClassOf>
278     <Class IRI="#Survey"/>
        <Class IRI="#Independent_entity"/>
280    </SubClassOf>
    <SubClassOf>
282     <Class IRI="#Survey_Question"/>
        <Class IRI="#Independent_entity"/>
284    </SubClassOf>
    <SubClassOf>
286     <Class IRI="#Value"/>
        <Class IRI="#Domain_entity"/>
288    </SubClassOf>
    <SubClassOf>
290     <Class IRI="#feedback_survey"/>

```



```

292     <Class IRI="#Survey" />
    </SubClassOf>
    <SubClassOf>
294         <Class IRI="#sample_courseID" />
        <Class IRI="#Sample_Detail" />
296    </SubClassOf>
    <SubClassOf>
298         <Class IRI="#sample_course_name" />
        <Class IRI="#Sample_Detail" />
300    </SubClassOf>
    <SubClassOf>
302         <Class IRI="#sample_max_responses" />
        <Class IRI="#Sample_Detail" />
304    </SubClassOf>
    <SubClassOf>
306         <Class IRI="#sample_name" />
        <Class IRI="#Sample_Detail" />
308    </SubClassOf>
    <SubClassOf>
310         <Class IRI="#sample_number" />
        <Class IRI="#Sample_Detail" />
312    </SubClassOf>
    <SubClassOf>
314         <Class IRI="#sample_semester" />
        <Class IRI="#Sample_Detail" />
316    </SubClassOf>
    <SubClassOf>
318         <Class IRI="#0" />
        <Class IRI="#Likert_NeverAlways5_numbers" />
320    </SubClassOf>
    <SubClassOf>
322         <Class IRI="#1" />
        <Class IRI="#Likert_NeverAlways5_numbers" />
324    </SubClassOf>
    <SubClassOf>
326         <Class IRI="#1_The_instructor_is_well-prepared_for_class" />
        <Class IRI="#Likert_NeverAlways5" />
328    </SubClassOf>
    <SubClassOf>
330         <Class IRI="#1_What_do_you_like_the_best_about_this_course?" />
        <Class IRI="#Open_Ended_question" />
332    </SubClassOf>
    <SubClassOf>
334         <Class IRI="#2" />
        <Class IRI="#Likert_NeverAlways5_numbers" />
336    </SubClassOf>
    <SubClassOf>
338         <Class IRI="#2_The_instructor_clearly_communicates_his
            _expectations_for_student_preparation_and_participation" />
340         <Class IRI="#Likert_NeverAlways5" />
    </SubClassOf>
342    <SubClassOf>

```

```

    <Class IRI="#2_What_would_you_like_to_change_about_this_course?"/>
344 >
    <Class IRI="#Open_Ended_question"/>
    </SubClassOf>
346 <SubClassOf>
    <Class IRI="#3"/>
348 <Class IRI="#Likert_NeverAlways5_numbers"/>
    </SubClassOf>
350 <SubClassOf>
    <Class IRI="#3_The_instructor_uses_class_time_effectively"/>
352 <Class IRI="#Likert_NeverAlways5"/>
    </SubClassOf>
354 <SubClassOf>
    <Class IRI="#3_What_do_you_think_the_instructor's_greatest
356 _strengths_are?"/>
    <Class IRI="#Open_Ended_question"/>
358 </SubClassOf>
    <SubClassOf>
360 <Class IRI="#4"/>
    <Class IRI="#Likert_NeverAlways5_numbers"/>
362 </SubClassOf>
    <SubClassOf>
364 <Class IRI="#4_The_instructor_has_clear_expectations_for
    _assigned_work"/>
366 <Class IRI="#Likert_NeverAlways5"/>
    </SubClassOf>
368 <SubClassOf>
    <Class IRI="#5"/>
370 <Class IRI="#Likert_NeverAlways5_numbers"/>
    </SubClassOf>
372 <SubClassOf>
    <Class IRI="#5_The_instructor_encourages_student
374 _participation"/>
    <Class IRI="#Likert_NeverAlways5"/>
376 </SubClassOf>
    <SubClassOf>
378 <Class IRI="#6_The_instructor_clearly_answers_questions"/>
    <Class IRI="#Likert_NeverAlways5"/>
380 </SubClassOf>
    <SubClassOf>
382 <Class IRI="#7_The_instructor_treats_students_with_respect"/>
    <Class IRI="#Likert_NeverAlways5"/>
384 </SubClassOf>
    <SubClassOf>
386 <Class IRI="#8_The_instructor_easily_directs_and_simulates
    _discussion"/>
388 <Class IRI="#Likert_NeverAlways5"/>
    </SubClassOf>
390 <SubClassOf>
    <Class IRI="#9_The_instructor_effectively_encourages_students
392 _to_ask_questions_and_give_answers"/>
    <Class IRI="#Likert_NeverAlways5"/>

```

```

394     </SubClassOf>
395     <SubClassOf>
396         <Class IRI="#[No_Answer]" />
397         <Class IRI="#Likert_NeverAlways5_names" />
398     </SubClassOf>
399     <SubClassOf>
400         <Class IRI="#[Often]" />
401         <Class IRI="#Likert_NeverAlways5_names" />
402     </SubClassOf>
403     <SubClassOf>
404         <Class IRI="#[Rarely]" />
405         <Class IRI="#Likert_NeverAlways5_names" />
406     </SubClassOf>
407     <SubClassOf>
408         <Class IRI="#[Sometimes]" />
409         <Class IRI="#Likert_NeverAlways5_names" />
410     </SubClassOf>
411     <DisjointClasses>
412         <Class IRI="#Always" />
413         <Class IRI="#Never" />
414         <Class IRI="#[No_Answer]" />
415         <Class IRI="#[Often]" />
416         <Class IRI="#[Rarely]" />
417         <Class IRI="#[Sometimes]" />
418     </DisjointClasses>
419     <DisjointClasses>
420         <Class IRI="#Independent_entity" />
421         <Class IRI="#Value" />
422     </DisjointClasses>
423     <DisjointClasses>
424         <Class IRI="#Likert_NeverAlways5_names" />
425         <Class IRI="#Likert_NeverAlways5_numbers" />
426     </DisjointClasses>
427     <DisjointClasses>
428         <Class IRI="#Likert_NeverAlways5_names" />
429         <Class IRI="#Likert_NeverAlways5_numbers" />
430         <Class IRI="#1_The_instructor_is_well-prepared_for_class" />
431         <Class IRI="#2_The_instructor_clearly_communicates_his
432             _expectations_for_student_preparation_and_participation" />
433         <Class IRI="#3_The_instructor_uses_class_time_effectively" />
434         <Class IRI="#4_The_instructor_has_clear_expectations_for
435             _assigned_work" />
436         <Class IRI="#5_The_instructor_encourages_student
437             _participation" />
438         <Class IRI="#6_The_instructor_clearly_answers_questions" />
439         <Class IRI="#7_The_instructor_treats_students_with_respect" />
440         <Class IRI="#8_The_instructor_easily_directs_and_simulates
441             _discussion" />
442         <Class IRI="#9_The_instructor_effectively_encourages_students
443             _to_ask_questions_and_give_answers" />
444     </DisjointClasses>
445     <DisjointClasses>

```

```

446         <Class IRI="#Likert_question"/>
447         <Class IRI="#Open_Ended_question"/>
448     </DisjointClasses>
449     <DisjointClasses>
450         <Class IRI="#Respondents"/>
451         <Class IRI="#Sample_Detail"/>
452         <Class IRI="#Survey"/>
453         <Class IRI="#Survey_ Question"/>
454     </DisjointClasses>
455     <DisjointClasses>
456         <Class IRI="#Sample_Detail"/>
457         <Class IRI="#Survey"/>
458         <Class IRI="#Survey_ Question"/>
459     </DisjointClasses>
460     <DisjointClasses>
461         <Class IRI="#sample_courseID"/>
462         <Class IRI="#sample_course_name"/>
463         <Class IRI="#sample_max_responses"/>
464         <Class IRI="#sample_name"/>
465         <Class IRI="#sample_number"/>
466         <Class IRI="#sample_semester"/>
467     </DisjointClasses>
468     <DisjointClasses>
469         <Class IRI="#sample_courseID"/>
470         <Class IRI="#sample_max_responses"/>
471         <Class IRI="#sample_name"/>
472         <Class IRI="#sample_number"/>
473         <Class IRI="#sample_semester"/>
474     </DisjointClasses>
475     <DisjointClasses>
476         <Class IRI="#0"/>
477         <Class IRI="#1"/>
478         <Class IRI="#2"/>
479         <Class IRI="#3"/>
480         <Class IRI="#4"/>
481         <Class IRI="#5"/>
482     </DisjointClasses>
483     <DisjointClasses>
484         <Class IRI="#1_What_do_you_like_the_best_about_this_course?"/>
485         <Class IRI="#2_What_would_you_like_to_change_about_this
486         _course?"/>
487         <Class IRI="#3_What_do_you_think_the_instructor's_greatest
488         _strengths_are?"/>
489     </DisjointClasses>
490     <SubObjectPropertyOf>
491         <ObjectProperty IRI="#hasCourseID"/>
492         <ObjectProperty IRI="#hasSampleDetail"/>
493     </SubObjectPropertyOf>
494     <SubObjectPropertyOf>
495         <ObjectProperty IRI="#hasCourseName"/>
496         <ObjectProperty IRI="#hasSampleDetail"/>
497     </SubObjectPropertyOf>

```

```

498     <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasMaxResponses"/>
500     <ObjectProperty IRI="#hasSampleDetail"/>
    </SubObjectPropertyOf>
502 <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasName"/>
504     <ObjectProperty IRI="#hasSampleDetail"/>
    </SubObjectPropertyOf>
506 <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasNumber"/>
508     <ObjectProperty IRI="#hasSampleDetail"/>
    </SubObjectPropertyOf>
510 <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasRespondent"/>
512     <ObjectProperty abbreviatedIRI="owl:topObjectProperty"/>
    </SubObjectPropertyOf>
514 <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasSampleDetail"/>
516     <ObjectProperty abbreviatedIRI="owl:topObjectProperty"/>
    </SubObjectPropertyOf>
518 <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasSemester"/>
520     <ObjectProperty IRI="#hasSampleDetail"/>
    </SubObjectPropertyOf>
522 <SubObjectPropertyOf>
        <ObjectProperty IRI="#hasSurveyQuestion"/>
524     <ObjectProperty abbreviatedIRI="owl:topObjectProperty"/>
    </SubObjectPropertyOf>
526 <SubObjectPropertyOf>
        <ObjectProperty IRI="#isCourseIDOf"/>
528     <ObjectProperty IRI="#isSampleDetailOf"/>
    </SubObjectPropertyOf>
530 <SubObjectPropertyOf>
        <ObjectProperty IRI="#isCourseNameOf"/>
532     <ObjectProperty IRI="#isSampleDetailOf"/>
    </SubObjectPropertyOf>
534 <SubObjectPropertyOf>
        <ObjectProperty IRI="#isMaxResponseOf"/>
536     <ObjectProperty IRI="#isSampleDetailOf"/>
    </SubObjectPropertyOf>
538 <SubObjectPropertyOf>
        <ObjectProperty IRI="#isNameOf"/>
540     <ObjectProperty IRI="#isSampleDetailOf"/>
    </SubObjectPropertyOf>
542 <SubObjectPropertyOf>
        <ObjectProperty IRI="#isNumberOf"/>
544     <ObjectProperty IRI="#isSampleDetailOf"/>
    </SubObjectPropertyOf>
546 <SubObjectPropertyOf>
        <ObjectProperty IRI="#isRespondentOf"/>
548     <ObjectProperty abbreviatedIRI="owl:topObjectProperty"/>
    </SubObjectPropertyOf>

```

```

550     <SubObjectPropertyOf>
551         <ObjectProperty IRI="#isSampleDetailOf"/>
552         <ObjectProperty abbreviatedIRI="owl:topObjectProperty"/>
553     </SubObjectPropertyOf>
554     <SubObjectPropertyOf>
555         <ObjectProperty IRI="#isSemesterOf"/>
556         <ObjectProperty IRI="#isSampleDetailOf"/>
557     </SubObjectPropertyOf>
558     <SubObjectPropertyOf>
559         <ObjectProperty IRI="#isSurveyQuestionOf"/>
560         <ObjectProperty abbreviatedIRI="owl:topObjectProperty"/>
561     </SubObjectPropertyOf>
562     <InverseObjectProperties>
563         <ObjectProperty IRI="#hasCourseID"/>
564         <ObjectProperty IRI="#isCourseIDOf"/>
565     </InverseObjectProperties>
566     <InverseObjectProperties>
567         <ObjectProperty IRI="#hasCourseName"/>
568         <ObjectProperty IRI="#isCourseNameOf"/>
569     </InverseObjectProperties>
570     <InverseObjectProperties>
571         <ObjectProperty IRI="#hasMaxResponses"/>
572         <ObjectProperty IRI="#isMaxResponseOf"/>
573     </InverseObjectProperties>
574     <InverseObjectProperties>
575         <ObjectProperty IRI="#hasName"/>
576         <ObjectProperty IRI="#isNameOf"/>
577     </InverseObjectProperties>
578     <InverseObjectProperties>
579         <ObjectProperty IRI="#hasNumber"/>
580         <ObjectProperty IRI="#isNumberOf"/>
581     </InverseObjectProperties>
582     <InverseObjectProperties>
583         <ObjectProperty IRI="#hasRespondent"/>
584         <ObjectProperty IRI="#isRespondentOf"/>
585     </InverseObjectProperties>
586     <InverseObjectProperties>
587         <ObjectProperty IRI="#hasSampleDetail"/>
588         <ObjectProperty IRI="#isSampleDetailOf"/>
589     </InverseObjectProperties>
590     <InverseObjectProperties>
591         <ObjectProperty IRI="#hasSemester"/>
592         <ObjectProperty IRI="#isSemesterOf"/>
593     </InverseObjectProperties>
594     <InverseObjectProperties>
595         <ObjectProperty IRI="#hasSurveyQuestion"/>
596         <ObjectProperty IRI="#isSurveyQuestionOf"/>
597     </InverseObjectProperties>
598     <ObjectPropertyDomain>
599         <ObjectProperty IRI="#hasCourseID"/>
600         <Class IRI="#Sample_Detail"/>
601     </ObjectPropertyDomain>

```

```

602 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasCourseName"/>
604 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyDomain>
606 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasMaxResponses"/>
608 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyDomain>
610 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasName"/>
612 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyDomain>
614 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasNumber"/>
616 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyDomain>
618 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasRespondent"/>
620 <Class IRI="#Survey"/>
    </ObjectPropertyDomain>
622 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasSampleDetail"/>
624 <Class IRI="#Survey"/>
    </ObjectPropertyDomain>
626 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasSemester"/>
628 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyDomain>
630 <ObjectPropertyDomain>
        <ObjectProperty IRI="#hasSurveyQuestion"/>
632 <Class IRI="#Survey"/>
    </ObjectPropertyDomain>
634 <ObjectPropertyDomain>
        <ObjectProperty IRI="#isRespondentOf"/>
636 <Class IRI="#Respondents"/>
    </ObjectPropertyDomain>
638 <ObjectPropertyDomain>
        <ObjectProperty IRI="#isSampleDetailOf"/>
640 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyDomain>
642 <ObjectPropertyDomain>
        <ObjectProperty IRI="#isSurveyQuestionOf"/>
644 <Class IRI="#Survey_Question"/>
    </ObjectPropertyDomain>
646 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasCourseID"/>
648 <Class IRI="#sample_courseID"/>
    </ObjectPropertyRange>
650 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasCourseName"/>
652 <Class IRI="#sample_course_name"/>
    </ObjectPropertyRange>

```

```

654 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasMaxResponses"/>
656 <Class IRI="#sample_max_responses"/>
    </ObjectPropertyRange>
658 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasName"/>
660 <Class IRI="#sample_name"/>
    </ObjectPropertyRange>
662 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasNumber"/>
664 <Class IRI="#sample_number"/>
    </ObjectPropertyRange>
666 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasRespondent"/>
668 <Class IRI="#Respondents"/>
    </ObjectPropertyRange>
670 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasSampleDetail"/>
672 <Class IRI="#Sample_Detail"/>
    </ObjectPropertyRange>
674 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasSemester"/>
676 <Class IRI="#sample_semester"/>
    </ObjectPropertyRange>
678 <ObjectPropertyRange>
        <ObjectProperty IRI="#hasSurveyQuestion"/>
680 <Class IRI="#Survey_Question"/>
    </ObjectPropertyRange>
682 <ObjectPropertyRange>
        <ObjectProperty IRI="#isRespondentOf"/>
684 <Class IRI="#Survey"/>
    </ObjectPropertyRange>
686 <ObjectPropertyRange>
        <ObjectProperty IRI="#isSampleDetailOf"/>
688 <Class IRI="#Survey"/>
    </ObjectPropertyRange>
690 <ObjectPropertyRange>
        <ObjectProperty IRI="#isSurveyQuestionOf"/>
692 <Class IRI="#Survey"/>
    </ObjectPropertyRange>
694 <DisjointObjectProperties>
        <ObjectProperty IRI="#hasCourseID"/>
696 <ObjectProperty IRI="#hasCourseName"/>
        <ObjectProperty IRI="#hasMaxResponses"/>
698 <ObjectProperty IRI="#hasName"/>
        <ObjectProperty IRI="#hasNumber"/>
700 <ObjectProperty IRI="#hasSemester"/>
    </DisjointObjectProperties>
702 <DisjointObjectProperties>
        <ObjectProperty IRI="#hasRespondent"/>
704 <ObjectProperty IRI="#hasSampleDetail"/>
        <ObjectProperty IRI="#hasSurveyQuestion"/>

```



```

706      <ObjectProperty IRI="#isRespondentOf"/>
      <ObjectProperty IRI="#isSampleDetailOf"/>
708      <ObjectProperty IRI="#isSurveyQuestionOf"/>
    </DisjointObjectProperties>
710  <DisjointObjectProperties>
    <ObjectProperty IRI="#isCourseIDOf"/>
712    <ObjectProperty IRI="#isCourseNameOf"/>
    <ObjectProperty IRI="#isMaxResponseOf"/>
714    <ObjectProperty IRI="#isNameOf"/>
    <ObjectProperty IRI="#isNumberOf"/>
716    <ObjectProperty IRI="#isSemesterOf"/>
  </DisjointObjectProperties>
718 </Ontology>

720 <!-- Generated by the OWL API (version 4.5.9.2019-02-01T07:24:44Z)
      https://github.com/owlcs/owlapi -->

```

Bibliography

- [1] Sareh Aghaei, Mohammad Ali Nematbakhsh, and Hadi Khosravi Farsani. Evolution of the World Wide Web: From WEB 1.0 TO WEB 4.0. *International Journal of Web and Semantic Technology*, 3(1):1–10, 2012.
- [2] Emhimed Alatrish. Comparison Some of Ontology Editors. *Management Information Systems*, 8(2):18–24, 2013.
- [3] Francesco Antoniazzi and Fabio Viola. RDF Graph Visualization Tools: A Survey. In *Proceedings of the 23rd Conference of Open Innovations Association (FRUCT)*, pages 25–36, 2018.
- [4] Sören Auer, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. DBpedia: A Nucleus for a Web of Open Data. In *Proceedings of the 6th International Conference on the Semantic Web and 2nd Asian Conference on Asian Semantic Web Conference*, pages 722–735. Springer-Verlag, Berlin, Heidelberg, 2007.
- [5] Florian Bauer and Martin Kaltenböck. Linked Open Data: The Essentials - A Quick Start Guide for Decision Makers. *Edition Mono/Monochrom*, Vienna, 2011.
- [6] Dave Beckett and Brian McBride. RDF/XML Syntax Specification (Revised). *W3C Recommendation*, 2004. <https://www.w3.org/TR/REC-rdf-syntax/> , accessed August 14, 2019.
- [7] David Beckett. RDF 1.1 N-Triples. *W3C Recommendation*, 2014. <https://www.w3.org/TR/2014/REC-n-triples-20140225/> , accessed October 29, 2019.
- [8] Tim Berners-Lee. Linked Data. *W3C Recommendation*, 1996. <https://www.w3.org/DesignIssues/LinkedData> , accessed January 23, 2019.
- [9] Tim Berners-Lee. Universal Resource Identifiers in WWW: A Unifying Syntax for the Expression of Names and Addresses of Objects on the Network as used in the World-Wide Web. *RFC 1630*, June 1998. <https://www.rfc-editor.org/info/rfc1630> , accessed September 24, 2020.

- [10] Tim Berners-Lee, Robert Cailliau, Ari Luotonen, Henrik Frystyk Nielsen, and Arthur Secret. The World Wide Web. *Communications of the ACM*, 37(8):76–83, 1994.
- [11] Tim Berners-Lee, Roy Fielding, and Larry Masinter. Uniform Resource Identifiers (URI): Generic Syntax. *Internet Engineering Task Force, RFC 2396*, August 1998. <https://www.rfc-editor.org/info/rfc2396> , accessed October 01, 2020.
- [12] Tim Berners-Lee, Roy Fielding, and Larry Masinter. Uniform Resource Identifiers (URI): Generic Syntax. *RFC 3986*, January 2005. <https://www.rfc-editor.org/info/rfc3986> , accessed October 02, 2020.
- [13] Tim Berners-Lee and Mark Fischetti. *Weaving the Web: The Original Design and Ultimate Destiny of the World Wide Web by Its Inventor*. Harper San Francisco, 1999.
- [14] Christian Bizer. The Emerging Web of Linked Data. *IEEE Intelligent Systems*, 24(5):87–92, 2009.
- [15] Christian Bizer, Tom Heath, and Tim Berners-Lee. Linked Data - The Story So Far. *International Journal of Semantic Web Information Systems*, 5:1–22, 2009.
- [16] Christian Bizer, Tom Heath, and Tim Berners-Lee. Linked Data: The Story So Far. In *Semantic Services, Interoperability and Web Applications: Emerging Concepts*, pages 205–227. IGI global, USA, 2011.
- [17] Christian Bizer, Tom Heath, Kingsley Idehen, and Tim Berners-Lee. Linked Data on the Web (LDOW2008). In *Proceedings of the 17th International Conference on World Wide Web*, pages 1265–1266. ACM, 2008.
- [18] Christian Bizer, Jens Lehmann, Georgi Kobilarov, Sören Auer, Christian Becker, Richard Cyganiak, and Sebastian Hellmann. DBpedia-A Crystallization Point for the Web of Data. *Web Semantics: Science, Services and Agents on the World Wide Web*, 7(3):154–165, 2009.
- [19] Nupur Choudhury. World Wide Web and Its Journey from Web 1.0 to Web 4.0. *International Journal of Computer Science and Information Technologies*, 5(6):8096–8100, 2014.
- [20] Richard Cyganiak, Andreas Harth, and Aidan Hogan. N-Quads: Extending N-Triples with Context. *W3C Recommendation*, pages 1–41, 2008.
- [21] Richard Cyganiak, David Wood, Markus Lanthaler, Graham Klyne, Jeremy J Carroll, and Brian McBride. RDF 1.1 Concepts and Abstract Syntax. *W3C Recommendation*, 25(02):1–22, January 2014. <http://hdl.handle.net/10421/2427> , accessed January 05, 2020.

- [22] Ivan Ermilov, Sören Auer, and Claus Stadler. CSV2RDF: User-Driven CSV to RDF Mass Conversion Framework. In *Proceedings of the International Symposium on Applied Electromagnetics and Mechanics*, volume 13, pages 4–6. ACM, 2013.
- [23] Fredo Erxleben, Michael Günther, Markus Krötzsch, Julian Mendez, and Denny Vrandečić. Introducing Wikidata to the Linked Data Web. In *Proceedings of the International Semantic Web Conference*, pages 50–65. Springer, 2014.
- [24] Sean Falconer. Ontograf Protege Plugin. Available at: <http://protegewiki.stanford.edu/wiki/OntoGraf>, 2010.
- [25] Thomas R Gruber. Toward Principles for the Design of Ontologies used for Knowledge Sharing? *International Journal of Human-Computer Studies*, 43(5):907–928, 1995.
- [26] Lushan Han, Tim Finin, Cynthia Parr, Joel Sachs, and Anupam Joshi. RDF123: From Spreadsheets to RDF. In *Proceedings of the International Semantic Web Conference*, pages 451–466. Springer, 2008.
- [27] Tom Heath and Christian Bizer. Linked Data: Evolving the Web into a Global Data Space. *Synthesis Lectures on the Semantic Web: Theory and Technology*, 1(1):1–136, 2011.
- [28] Daryl Hepting. Student Feedback Instrument. Available at: <http://www2.cs.uregina.ca/~hepting/assets/teaching/pdf/feedback-instrument.pdf>, 2020.
- [29] Matthew Horridge, Simon Jupp, Georgina Moulton, Alan Rector, Robert Stevens, and Chris Wroe. A Practical Guide to Building OWL Ontologies using Protégé 4 and CO-ODE Tools Edition 1.3. *The University of Manchester*, March 2011.
- [30] Elin K Jacob. Ontologies and the Semantic Web. *Bulletin of the American Society for Information Science and Technology*, 29(4):19–19, 2003.
- [31] Andreas Langeegger and Wolfram Web. XLWrap–Querying and Integrating Arbitrary Spreadsheets with SPARQL. In *Proceedings of the International Semantic Web Conference*, pages 359–374. Springer, 2009.
- [32] Steffen Lohmann, Vincent Link, Eduard Marbach, and Stefan Negru. WebVOWL: Web-based Visualization of Ontologies. In *International Conference on Knowledge Engineering and Knowledge Management*, pages 154–158. Springer, 2014.
- [33] Frank Manola, Eric Miller, and Brian McBride. RDF Primer. *W3C Recommendation*, 10(1):1–6, 2004. <https://www.w3.org/TR/2004/REC-rdf-primer-20040210/> , accessed December 2017.

- [34] Brian McBride. The Resource Description Framework (RDF) and Its Vocabulary Description Language RDFS. In *Handbook on Ontologies*, pages 51–65. Springer, Berlin, 2004.
- [35] Axel-Cyrille Ngonga Ngomo, Sören Auer, Jens Lehmann, and Amrapali Zaveri. Introduction to Linked Data and Its Life Cycle on the Web. In *Proceedings of Reasoning Web 2014: Reasoning on the Web in the Big Data Era*, pages 1–99, Cham. Springer International, September 2014.
- [36] Jakob Nielsen. Usability Engineering. *Morgan Kaufmann Publishers Inc., San Francisco, USA*, pages 23–48, 1994.
- [37] Whitney Quesenbery and Whitney Interactive Design. Dimensions of Usability: Defining the Conversation, Driving the Process. In *UPA 2003 Conference*, pages 23–27, 2003.
- [38] Denny Vrandečić and Markus Krötzsch. Wikidata: A Free Collaborative Knowledgebase. *Communications of the ACM*, 57(10):78–85, 2014.