

PRINCIPALES UTILISATIONS

Eau de mer dans zone non immergée et zone non explosive

DOCUMENTS DE REFERENCE

-

FOURNISSEUR FABRICANT

FUTURE PIPE INDUSTRIES Gamme Wavistrong Pipes systems

ETAT DE LIVRAISON

-

DOCUMENTS DE CONTROLE

Document de contrôle suivant NF EN 10-204 type 2.1, type 2.2, type 3.1, type 3.2 si spécifié sur la commande.

MATERIEL AVEC APPROBATION

Certificat d'Approbation de type BV N° 5583 et DNV N° K-5924

MATIERE TRAITEMENT DE SURFACE

STRATIFIE VERRE RESINE

Paroi interne riche en résine époxy renforcée par un voile de verre ou de polyester 0,5mm. Paroi effective:fibres de verre imprégné de résine époxy, épaisseur en fonction de la pression Paroi extérieure:couche de résine époxy 0,3mm

CHARACTERISTIQUES

Tuyauterie en GRP répondant à la résolution IMO A.753(18) L3.

Résistance au feu pendant 1/2h à l'état plein.

Standard utilisable pour les classes PN10 uniquement du DN 40 au DN150 (plage à ajuster en fonction des DN présents dans ce standard).

MAIN USES

Sea water pipes in no submerged spaces and no explosive spaces

REFERENCE DOCUMENTS

-

SUPPLIER MANUFACTURER

FUTURE PIPE INDUSTRIES Gamme Wavistrong Pipes systems

DELIVERY STATUS

-

CONTROL DOCUMENTS

Certificate according to NF EN 10204 type 2.1, type 2.2, type 3.1, type 3.2 if specified on the order

MATERIAL WITH APPROVAL

Certificate of Type Approval : BV N° 5583 / DNV N°K-5924

MATERIAL SURFACE TREATMENT

STRATIFY GLASS RESIN


Wall structure:resin-rich inner layer reinforced with glass or linear polyester non-woven Th0,5mm. Reinforced wall:glass reinforcement with amine cured EPOXY resin, Th depends on pressure. Wall has epoxy resin topcoat 0,3mm

CHARACTERISTICS

Pipe in GRP answered resolution A.753(18) L3.

Fire endurance for 1/2h full of water.

Standard used for PN10 classes only from DN 40 to DN 150 (range adjust for DN present in this standard).



Embout femelles Coniques TB/TB/TB

Pour assemblage conique/conique par collage TJ

Référence Objet	DN1 (mm)	DN3 (mm)	TH1 (mm)	TH3 (mm)	Weight (kg)	Water Weight (kg)	Work Diam 1 WD1 (mm)	Work Diam 3 WD3 (mm)	Pipe Length (mm)	F1 TO C (mm)	F3 TO C (mm)	SCH1 (-)	Pressure (-)	L (mm)	Length 1 (mm)
5000006358	450	350	5.3	4.3	43	160.63	470	370	850	425	395	10	12.5	660	330
5000006359	450	400	5.3	4.8	43	207.35	470	420	850	425	405	10	12.5	660	330
5000006660	500	400	5.9	4.8	57	279.13	522	422	930	465	365	11	12.5	730	365
5000006661	500	450	5.9	5.3	58	285.3	522	472	930	465	472	11	12.5	730	365
5000006662	600	450	6.9	5.3	95	481.9	626	472	1110	555	435	13	12.5	870	435
5000006663	600	500	6.9	5.9	96	484.1	626	526	1110	555	435	13	12.5	870	435