

- 1 Functional Programming 101
  - Short intro
  - Arrows
- 2 Parallel Arrows
  - Introduction to Parallelism
  - Generalization to Arrows
  - ArrowParallel Implementations
- 3 Usability
  - Skeletons
  - Syntactic Sugar
- 4 Benchmarks

## 1 Functional Programming 101

- Short intro
- Arrows

## 2 Parallel Arrows

- Introduction to Parallelism
- Generalization to Arrows
- ArrowParallel Implementations

## 3 Usability

- Skeletons
- Syntactic Sugar

## 4 Benchmarks

# Functions

```

1 public static int fib(int x) {
2     if (x<=0)
3         return 0;
4     else if (x==1)
5         return 1;
6     else
7         return fib(x-2) + fib(x-1);
8 }

```

```

1 fib :: Int -> Int
2 fib x
3   | x <= 0 = 0
4   | x == 1 = 0
5   | otherwise =
6     ( fib (x - 2))
7     + (fib (x - 1))

```

- Functional programming equally powerful as imperative programming
- focused on the "what?" instead of the "how?"  
⇒ more concise ⇒ easier to reason about
- based on Lambda Calculus

# Arrow Definition (1)

Another way to think about computations:





# Arrow Definition (2)

```
class Arrow arr where
  arr :: (a -> b) -> arr a b
```

```
(>>>) :: arr a b -> arr b c -> arr a c
```

```
first :: arr a b -> arr (a,c) (b,c)
```



# Functions $\in$ Arrows

Functions  $(\rightarrow)$  are arrows:

```
1 instance Arrow ( $\rightarrow$ ) where
2   arr f = f
3   f >>> g = g . f
4   first f = \ (a, c)  $\rightarrow$  (f a, c)
```

# The Kleisli Type

## The Kleisli type

```
1 data Kleisli m a b = Kleisli { run :: a -> m b }
```

is also an arrow:

```
1 instance Monad m => Arrow (Kleisli m) where
2   arr f = Kleisli $ return . f
3   f >>> g = Kleisli $ \a -> f a >>= g
4   first f = Kleisli $ \(a,c) -> f a >>= \b -> return (b,c)
```

# Combinators (1)

```

1 second :: arr a b -> arr (c, a) (c, b)
2 second f = arr swap >>>
3   first f >>> arr swap
4   where swap (x, y) = (y, x)


```



```

1 (***) :: arr a b -> arr c d -> arr (a, c) (b, d)
2 f *** g = first f >>> second g


```





# Combinators (2)


```
1 (&&&) :: arr a b -> arr a c -> arr a (b, c)
2 f &&& g = arr (\a -> (a, a)) >>> (f *** g)
```



# Arrow Example

Arrow usage example:


```
1 add :: Arrow arr => arr a Int -> arr a Int -> arr a Int
2 add f g = (f &&& g) >>> arr \(u, v) -> u + v
```



- 1 Functional Programming 101
  - Short intro
  - Arrows
- 2 Parallel Arrows
  - Introduction to Parallelism
  - Generalization to Arrows
  - ArrowParallel Implementations
- 3 Usability
  - Skeletons
  - Syntactic Sugar
- 4 Benchmarks

In general, Parallelism can be looked at as:

1  $\text{parEvalN} :: [a \rightarrow b] \rightarrow [a] \rightarrow [b]$




```
1 parEvalN :: [a -> b] -> [a] -> [b]
```

## Roadmap:

- Implement using existing Haskells
  - Multicore
  - ParMonad
  - Eden
- Generalize to Arrows
- Adapt Implementations
- Profit


# Multicore Haskell

```
1 parEvalN :: (NFData b) => [a -> b] -> [a] -> [b]
2 parEvalN fs as = zipWith ($) fs as 'using' parList rdeepseq
```



# ParMonad

```
1 parEvalN :: (NFData b) => [a -> b] -> [a] -> [b]
2 parEvalN fs as = runPar $
3   (sequence $ map (spawnP) $ zipWith ($) fs as) >>= mapM get
```




# ParMonad

```


1 parEvalN :: (NFData b) => [a -> b] -> [a] -> [b]
2 parEvalN fs as = runPar $
3   (sequence $ map (spawnP) $ zipWith ($) fs as) >>= mapM get

```






# ParMonad



# Eden

```
1 parEvalN :: (Trans a, Trans b) => [a -> b] -> [a] -> [b]
2 parEvalN fs as = spawnF fs as
```



# The ArrowParallel typeclass

Now, let's generalize:

```
1 parEvalN :: [a -> b] -> [a] -> [b]
```

# The ArrowParallel typeclass

Now, let's generalize:

```
1 parEvalN :: [a -> b] -> [a] -> [b]
```

```
1 parEvalN :: (Arrow arr) => [arr a b] -> arr [a] [b]
```

# The ArrowParallel typeclass

Now, let's generalize:

```
1 parEvalN :: [a -> b] -> [a] -> [b]
```

```
1 parEvalN :: (Arrow arr) => [arr a b] -> arr [a] [b]
```

```
1 class Arrow arr => ArrowParallel arr a b where  
2   parEvalN :: [arr a b] -> arr [a] [b]
```

# The ArrowParallel typeclass

Now, let's generalize:

```
1 parEvalN :: [a -> b] -> [a] -> [b]
```


```
1 parEvalN :: (Arrow arr) => [arr a b] -> arr [a] [b]
```

```
1 class Arrow arr => ArrowParallel arr a b where  
2   parEvalN :: [arr a b] -> arr [a] [b]
```

```
1 class Arrow arr => ArrowParallel arr a b conf where  
2   parEvalN :: conf -> [arr a b] -> arr [a] [b]
```

# Multicore

```
1 instance (NFData b, ArrowApply arr, ArrowChoice arr) =>
2   ArrowParallel arr a b conf where
3     parEvalN _ fs = listApp fs >>>
4       arr (flip using $ parList rdeepseq)
```




# ParMonad

```

1 instance (NFData b, ArrowApply arr, ArrowChoice arr) =>
2   ArrowParallel arr a b conf where
3     parEvalN _ fs =
4       (arr $ \as -> (fs, as)) >>>
5       zipWithArr (app >>> arr spawnP) >>>
6       ...


```





# ParMonad

```
1      ...  
2      arr sequence >>>  
3      arr (>>= mapM get) >>>  
4      arr runPar
```



# Eden (1)

For Eden we need separate implementations.

This is because of `spawnF`'s

```
1 spawnF :: (Trans a, Trans b) => [a -> b] -> [a] -> [b]
```

and `app`'s signature

```
1 app :: (ArrowApply arr) => arr (arr a b, a) b
```

which don't fit together.

# Eden (1)

For Eden we need separate implementations.

This is because of `spawnF`'s

```
1 spawnF :: (Trans a, Trans b) => [a -> b] -> [a] -> [b]
```

and `app`'s signature

```
1 app :: (ArrowApply arr) => arr (arr a b, a) b
```

which don't fit together.


Hacky alternative:

```
1 class (Arrow arr) => ArrowUnwrap arr where  
2   arr a b -> (a -> b)
```

# Eden (2)

## Implementation for Functions


```
1 instance (Trans a, Trans b) => ArrowParallel (->) a b conf where
2   parEvalN _ fs as = spawnF fs as
```



# Eden (3)

Implementation for the Kleisli Type:

```
1 instance (Monad m, Trans a, Trans b, Trans (m b)) =>
2   ArrowParallel (Kleisli m) a b conf where
3   parEvalN conf fs =
4     (arr $ parEvalN conf (map (\(Kleisli f) -> f) fs)) >>>
5     (Kleisli $ sequence)
```



- 1 Functional Programming 101
  - Short intro
  - Arrows
- 2 Parallel Arrows
  - Introduction to Parallelism
  - Generalization to Arrows
  - ArrowParallel Implementations
- 3 Usability
  - Skeletons
  - Syntactic Sugar
- 4 Benchmarks

# Skeletons... (1)


parEvalN, but **chunky**:

```
1 parEvalNLazy :: conf -> ChunkSize -> [arr a b] -> (arr [a] [b])
```



parallel evaluation of **different typed functions**:


```
1 parEval2 :: conf -> arr a b -> arr c d -> (arr (a, c) (b, d))
```



# Skeletons... (2)

map, but in **parallel**:

```
1 parMap :: conf -> (arr a b) -> (arr [a] [b])
```



parMap, but **chunky**:

```
1 parMapStream :: conf -> ChunkSize -> arr a b -> arr [a] [b]
```






# Skeletons... (3)

`parMap`, but with **workload distribution**:

```
1 farm :: conf -> NumCores -> arr a b -> arr [a] [b]
```



`farm`, but **chunky**:

```
1 farmChunk ::  
2   conf -> ChunkSize -> NumCores -> arr a b -> arr [a] [b]
```




# Parallel Operators (1)

```

1 ( $|>>>|$ ) :: [arr a b] -> [arr b c] -> [arr a c]
2 ( $|>>>|$ ) = zipWith (>>>)

```



On all Elements:



```

1 ( $|***|$ ) :: arr a b -> arr c d -> arr (a, c) (b, d)
2 ( $|***|$ ) = parEval2 ()

```





# Parallel Operators (2)

```

1 (|&&&|) :: arr a b -> arr a c -> arr a (b, c)
2 (|&&&|) f g = (arr $ \a -> (a, a)) >>> f |***| g

```





# Parallelism made easy

Parallel Evaluation made easy:

```


1 add :: Arrow arr => arr a Int -> arr a Int -> arr a Int
2 add f g = (f |&&&| g) >>> arr \(u, v) -> u + v


```




- 1 Functional Programming 101
  - Short intro
  - Arrows
- 2 Parallel Arrows
  - Introduction to Parallelism
  - Generalization to Arrows
  - ArrowParallel Implementations
- 3 Usability
  - Skeletons
  - Syntactic Sugar
- 4 Benchmarks

- Run on: Core i7-3970X CPU @ 3.5GHz / 6C/12T
- compiled with ParMonad backend
- used Sudoku Benchmark from ParMonad examples









- 1 Functional Programming 101
  - Short intro
  - Arrows
- 2 Parallel Arrows
  - Introduction to Parallelism
  - Generalization to Arrows
  - ArrowParallel Implementations
- 3 Usability
  - Skeletons
  - Syntactic Sugar
- 4 Benchmarks