

❖ **Name:-Parth Rajaram Gathadi**

❖ **Div:-CS5**

❖ **Roll.No:-CS3-33**

❖ **PRN.No:-202401100077**

🔗 Import necessary libraries

```
import pandas as pd
import numpy as np
```

🔗 Load datasets

```
movies = pd.read_csv('/content/drive/MyDrive/Dataset/movies.csv')
ratings = pd.read_csv('/content/drive/MyDrive/Dataset/ratings.csv')
tags = pd.read_csv('/content/drive/MyDrive/Dataset/tags.csv')
links = pd.read_csv('/content/drive/MyDrive/Dataset/links.csv')
```

🔗 Problem 1: Find the total number of movies in the dataset.

```
total_movies = movies.shape[0]
print(f"Total number of movies: {total_movies}")
```

↻ Total number of movies: 9742

🔗 Problem 2: Find the number of unique users who have rated movies.

```
unique_users = ratings['userId'].nunique()
print(f"Number of unique users: {unique_users}")
```

↻ Number of unique users: 610

🔗 Problem 3: Find the average rating given by users.

```
average_rating = ratings['rating'].mean()
print(f"Average rating: {average_rating:.2f}")
```

Average rating: 3.50

🔗 Problem 4: Find the movie with the highest average rating (minimum 50 ratings).

```
avg_rating_movie = ratings.groupby('movieId').agg({'rating': ['mean', 'count']})
avg_rating_movie.columns = ['mean_rating', 'rating_count']
high_avg_movie = avg_rating_movie[avg_rating_movie['rating_count'] >= 50].sort_values(by='mean_rating', ascending=False)
highest_rated_movie_id = high_avg_movie.index[0]
highest_rated_movie_title = movies[movies['movieId'] == highest_rated_movie_id]['title'].values[0]
print(f"Highest rated movie (min 50 ratings): {highest_rated_movie_title}")
```

↻ Highest rated movie (min 50 ratings): Shawshank Redemption, The (1994)

Problem 5: Find the number of movies belonging to the "Comedy" genre.

```
comedy_movies = movies[movies['genres'].str.contains('Comedy', na=False)]
print(f"Number of Comedy movies: {comedy_movies.shape[0]}")
```

Number of Comedy movies: 3756

Problem 6: Find the most common genre among all movies.

```
all_genres = movies['genres'].str.split('|').explode()
most_common_genre = all_genres.value_counts().idxmax()
print(f"Most common genre: {most_common_genre}")
```

Most common genre: Drama

Problem 7: Find the number of users who have given a rating of 5.0.

```
users_5_star = ratings[ratings['rating'] == 5.0]['userId'].nunique()
print(f"Number of users who gave 5-star ratings: {users_5_star}")
```

Number of users who gave 5-star ratings: 573

Problem 8: Find the movie that received the most ratings.

```
most Rated movie_id = ratings['movieId'].value_counts().idxmax()
most Rated movie_title = movies[movies['movieId'] == most Rated movie_id]['title'].values[0]
print(f"Movie with most ratings: {most Rated movie_title}")
```

Movie with most ratings: Forrest Gump (1994)

Problem 9: Find the user who has rated the most number of movies.

```
top_user_id = ratings['userId'].value_counts().idxmax()
print(f"User who rated most movies: UserID {top_user_id}")
```

User who rated most movies: UserID 414

Problem 10: Calculate the standard deviation of ratings.

```
rating_std = ratings['rating'].std()
print(f"Standard deviation of ratings: {rating_std:.2f}")
```

Standard deviation of ratings: 1.04

Problem 11: List the top 5 movies with the most 5-star ratings.

```
five_star_ratings = ratings[ratings['rating'] == 5.0]
top5_five_star_movies = five_star_ratings['movieId'].value_counts().head(5)
print("Top 5 movies with most 5-star ratings:")
for movie_id in top5_five_star_movies.index:
    title = movies[movies['movieId'] == movie_id]['title'].values[0]
    print(f"{title}")
```

Top 5 movies with most 5-star ratings:
Star Wars: Episode IV - A New Hope (1977)

Problem 12: Find how many movies have no genre listed.

```
no_genre_movies = movies[movies['genres'] == '(no genres listed)']
print(f"Movies with no genres listed: {no_genre_movies.shape[0]}")
```

↳ Movies with no genres listed: 34

Problem 13: Find the oldest movie in the dataset.

```
movies['year'] = movies['title'].str.extract(r'\((\d{4})\)').dropna()
movies['year'] = pd.to_numeric(movies['year'], errors='coerce') oldest_movie
= movies.sort_values('year').iloc[0]['title'] print(oldest_movie)
```

↳ Trip to the Moon, A (Voyage dans la lune, Le) (1902)

Problem 14: Find the newest movie in the dataset.

```
newest_movie = movies.sort_values('year', ascending=False).iloc[0]['title']
print(f"Newest movie: {newest_movie}")
```

↳ Newest movie: SuperFly (2018)

Problem 15: Find the percentage of movies tagged by users.

```
movies_tagged = tags['movieId'].nunique() percentage_tagged =
(movies_tagged / total_movies) * 100 print(f"Percentage of
movies tagged: {percentage_tagged:.2f}%")
```

↳ Percentage of movies tagged: 16.14%

Problem 16: Find the average number of ratings per movie.

```
avg_ratings_per_movie = ratings.groupby('movieId').size().mean()
print(f"Average number of ratings per movie: {avg_ratings_per_movie:.2f}")
```

↳ Average number of ratings per movie: 10.37

Problem 17: Find the number of unique tags used.

```
unique_tags = tags['tag'].nunique() print(f"Number
of unique tags used: {unique_tags}")
```

↳ Number of unique tags used: 1589

Problem 18: Find the top 5 most commonly used tags.

```
top5_tags = tags['tag'].value_counts().head(5)
print("Top 5 most common tags:") print(top5_tags)
```

↳ Top 5 most common tags: tag

In Netflix queue	131 atmospheric	36 thought-provoking
24 superhero	24 surreal	23 Name: count, dtype:

int64 #Problem 19: Check if there are any missing (null) values in each file.

```
print("\nMissing values in movies.csv:") print(movies.isnull().sum())
print("\nMissing values in ratings.csv:") print(ratings.isnull().sum())

print("\nMissing values in tags.csv:") print(tags.isnull().sum())

print("\nMissing values in links.csv:") print(links.isnull().sum())
```



```
Missing values in movies.csv:
movieId      0
title        0
genres       0
year         13
dtype: int64
```

```
Missing values in ratings.csv:
userId       0
movieId      0
rating       0
timestamp    0
dtype: int64
```

```
Missing values in tags.csv:
userId       0
movieId      0
tag          0
timestamp    0
dtype: int64
```

```
Missing values in links.csv:
movieId      0 imdbId      0
tmdbId       8 dtype: int64
```

```
#Problem 20: Merge movies and ratings datasets and find the average rating per genre.
```

```
ratings_movies = pd.merge(ratings, movies, on='movieId') ratings_movies =
ratings_movies.dropna(subset=['genres']) ratings_movies['genres_split'] =
ratings_movies['genres'].str.split('|') ratings_exploded = ratings_movies.explode('genres_split')
genre_avg_rating = ratings_exploded.groupby('genres_split')['rating'].mean().sort_values(ascending=False)
print("\nAverage rating per genre:") print(genre_avg_rating)
```



```
Average rating per genre:
genres_split
Film-Noir      3.920115
War            3.808294
Documentary    3.797785
Crime          3.658294
Drama          3.656184
Mystery        3.632460
Animation      3.629937
IMAX           3.618335
Western        3.583938
Musical        3.563678
Adventure      3.508609
Romance        3.506511
Thriller       3.493706
Fantasy        3.491001
(no genres listed) 3.489362
Sci-Fi         3.455721
Action         3.447984
Children       3.412956
Comedy         3.384721
Horror         3.258195
Name: rating, dtype: float64
```