Strife: A Secure Distributed Payment Gateway

Two-phase commit over gRPC with durable logs, crash recovery and mutual TLS

October 2026

Abstract

Strife moves money between accounts held at independent bank servers. A payment gateway authenticates users and coordinates each transfer with the two-phase commit (2PC) protocol, so a payment either happens at both banks or at neither. Every component talks over mutually authenticated TLS, users hold revocable JWT sessions, and every 2PC vote and decision is written to a SQLite log before it is acted on, so the system recovers from a crash of the gateway or of any bank at any point. A chaos experiment that hard-killed components 15 times during 2,747 payments ended with every payment atomic and the total money unchanged; 33 automated tests cover payments, security and recovery. This report describes the design, argues its correctness, and presents the measurements.

1 Project Overview

Strife simulates the core of a payment processor such as Stripe: clients ask a gateway to transfer money, and the gateway debits one bank and credits another. Because the two banks are separate processes with separate storage, the transfer is a distributed transaction. The system meets the following requirements:

- Bank servers, clients and a payment gateway implemented with gRPC.
- Mutual TLS on every connection, with identities checked on both sides.
- Authentication, authorization and logging implemented with gRPC interceptors.
- Idempotent payments: retrying a payment never charges twice.
- Offline payments: queued by the client and sent once the gateway is reachable again.
- Atomic transfers via 2PC with timeouts.
- Fault tolerance: durable state at every participant and automatic recovery after crashes.

2 System Architecture




Figure 1: Components and their durable state. Banks also call `RegisterBank` on the gateway at start-up.

2.1 Payment Gateway (`server/payment_gateway.py`)

- Central coordinator: validates requests, runs 2PC and answers queries.
- Persists payments, the bank directory and revoked tokens in `gateway.db` (SQLite, WAL mode, `fsync` on every commit).
- Runs a *recovery worker* that drives in-doubt payments to a final state (Section 4.5).
- gRPC methods: `AuthenticateClient`, `LogoutClient`, `CheckBalance`, `ProcessPayment`, `GetPaymentStatus`, `ViewTransactionHistory` and `RegisterBank`.

2.2 Bank Servers (`server/bank_server.py`)

- Each bank is an independent process with its own SQLite ledger (`<bank>.db`) holding account balances and the 2PC state of every transaction it has seen.
- Opening balances are loaded from `bank_data.json` the first time a bank starts; afterwards the ledger is the source of truth.
- gRPC methods: `GetBalance`, `PrepareTransaction`, `CommitTransaction` and `AbortTransaction`. Only the gateway's certificate may call them.
- On start-up the bank registers its host and port with the gateway, retrying until the gateway is reachable.

2.3 Client (`client/client.py`)

- Interactive command-line interface for login, payments, balances, history and logout.
- Parses rupee amounts exactly (as decimals) and sends integer paise.
- Queues payments on disk while the gateway is unreachable and sends them automatically when it returns (Section 6).

2.4 Shared modules

`auth.py` (password hashing, login throttling, JWT sessions), `interceptor.py` (authorization, certificate identity, access logging), `tls.py` (mTLS credentials), `storage.py` (serialised SQLite transactions) and `config.py` (settings from environment variables).

2.5 Money representation

All amounts are 64-bit integers in *paise*. Floating point is never used for money, so balances cannot drift through rounding (for example $0.1 + 0.2 \neq 0.3$ in binary floating point).

3 Authentication & Security

3.1 Mutual TLS and component identity

A local certificate authority, created by `scripts/gen_certs.py`, issues one certificate per component. Keys are generated locally (or inside Docker and the test suite) and are never committed to the repository. Both sides of every connection verify the other's certificate (`require_client_auth=True`), and the certificate's common name (CN) is then used for authorization:

Component	Certificate CN	May call
Gateway	`gateway`	bank RPCs (the only identity banks accept)
Bank	`<bank>.bank`, e.g. `hdfc.bank`	`RegisterBank` for *its own* name only
Client	`client`	user RPCs (plus a valid JWT)

Because a bank may only register under the name in its own certificate, a client or a different bank cannot redirect HDFC's traffic to an address it controls. Because banks accept only the gateway's certificate, nobody can call `PrepareTransaction` or `CommitTransaction` directly to create or move money.

3.2 User authentication

- Passwords are stored as salted scrypt hashes ($N = 2^{14}, r = 8, p = 1$) and compared in constant time. A login for an unknown user verifies against a dummy hash, so response time does not reveal which usernames exist.
- Five failed logins within five minutes lock the username for 60 seconds (`RESOURCE_EXHAUSTED`).
- A successful login returns an HS256 JWT with subject, issue time, 15-minute expiry and a unique id (`jti`). The signing key comes from `PG_JWT_SECRET` and must be at least 32 characters.
- Logout revokes the token's `jti`. The revocation list is stored in `gateway.db`, so a revoked token stays invalid across restarts.

3.3 Authorization

`AuthorizationInterceptor` rejects every call without a valid, unexpired, unrevoked token (except `AuthenticateClient` and `RegisterBank`) with `UNAUTHENTICATED`. The service then enforces ownership: a user may only check balances of, and pay from, accounts linked to them (`PERMISSION_DENIED` otherwise), and may only see the status of payments they sent or received.

3.4 Input validation

The server validates every payment independently of the client:

- the amount must be between 1 paisa and Rs. 10,00,000 (banks additionally refuse non-positive amounts);
- the receiver account must exist (`NOT_FOUND`);

- sender and receiver accounts must differ;
- the transaction id must be 1–64 characters from `[A-Za-z0-9_-]`.

Each failure returns a specific gRPC status code (`INVALID_ARGUMENT`, `NOT_FOUND`, `PERMISSION_DENIED`) rather than a generic error.

4 Transaction Processing (2PC)




Figure 2: Payment states in the coordinator log. Every transition is a compare-and-set on the stored status.

4.1 Phase 0: log the payment

After validation the gateway inserts the payment into `gateway.db` with status Preparing. The client-generated transaction id is the primary key.

4.2 Phase 1: prepare

The gateway asks the sender's bank to prepare a Debit and the receiver's bank to prepare a Credit. Each bank votes inside one serialised SQLite transaction (`BEGIN IMMEDIATE`):

- **Debit:** vote yes only if balance − reserved ≥ amount, where *reserved* is the sum of the account's other prepared debits; the vote itself records a reservation of *amount*.
- **Credit:** vote yes if the account exists.

The vote is written to disk before the reply is sent. A repeated prepare for the same transaction returns the original vote.

4.3 Decision

If both banks vote yes, the gateway changes the status from Preparing to Committing; otherwise to Aborting, storing the reason (for example "Insufficient funds"). The decision is durable *before* any bank is told about it.

4.4 Phase 2: commit or abort

The gateway sends the decision to both banks. Both operations are idempotent:

- **Commit** applies the debit or credit and marks the entry committed; repeating it is a no-op.
- **Abort** releases the reservation. An abort for a transaction the bank never saw writes a *tombstone*, so a delayed prepare that arrives afterwards is refused.

When both banks acknowledge, the status becomes COMMITTED or ABORTED. If a bank cannot be reached, the payment stays in COMMITTING/ABORTING and the recovery worker retries. A client whose payment is COMMITTING is told it succeeded: the decision is final and will be applied.

4.5 Timeouts and recovery

Every gateway-to-bank call has a 3-second deadline. The recovery worker runs every 2 seconds, and immediately when the gateway starts:

- COMMITTING/ABORTING: resend the decision to both banks until both acknowledge.
- PREPARING for longer than 30 seconds: the coordinator crashed or stalled before deciding. No commit decision exists, so the payment is moved to ABORTING (*presumed abort*) and the reservations are released.

Both the request thread and the recovery worker change state only by compare-and-set, so exactly one decision is ever recorded, even if they race.

5 Idempotent Payment Processing

5.1 Implementation

The client generates a random 128-bit transaction id for each payment and reuses it for every retry, including retries from the offline queue. The id is the primary key of the coordinator log:

- a new id starts a new payment;
- an id seen before *with the same user and parameters* returns the stored outcome (COMMITTED, ABORTED, or "in progress") without touching the banks;
- an id seen before with a different user or different parameters is rejected with `ALREADY_EXISTS`, so ids cannot be hijacked.

5.2 Correctness arguments

We assume the gateway and every bank eventually restart after a crash with their disks intact, and that the network eventually delivers messages between live processes.

Exactly-once (no double charge). Inserting a payment and checking for an existing id happen in one SQLite transaction, and the id is a primary key, so at most one payment record exists per id. The banks key their ledger entries on (transaction id, operation), so even a prepare or commit retried by the gateway affects each account at most once. Therefore a payment is applied at most once however often the client retries.

Atomicity. The decision is a single compare-and-set from PREPARING, so it is recorded exactly once and never changes. A bank applies a commit only for an entry it prepared, and only when the gateway sends COMMIT, which it does only after logging COMMITTING; a bank releases a reservation only on ABORT. Hence the two banks can never apply different outcomes. Because votes and decisions are durable, a crash of either side loses neither; and because phase 2 is idempotent and retried until acknowledged, both banks eventually apply the logged decision.

No overdraft or double spend. Each bank maintains the invariant balance $-$ reserved ≥ 0 for every account. Prepare checks it and adds the reservation in one serialised transaction, so two concurrent debits cannot both pass the check against the same funds. A committed debit

subtracts an amount that was already reserved, so the balance never goes negative. A database `CHECK` constraint enforces this as well.

Conservation of money. Every committed payment applies a debit and a credit of the same amount, and by atomicity they are applied together or not at all. The total money across all banks is therefore constant. The chaos experiment (Section 8.2) checks exactly this.

Liveness and its limit. Under the assumptions above, every payment reaches COMMITTED or ABORTED. 2PC is, however, a *blocking* protocol: while the gateway is down, a bank that voted yes must keep its reservation, because it cannot know the decision. The funds are safe but unavailable until the gateway returns.

6 Offline Payments & Retry Mechanism

6.1 Client-side queuing

- Each RPC is retried up to three times while the gateway reports `UNAVAILABLE` or the deadline expires.
- If the gateway is still unreachable, the payment, with its transaction id, is appended to `offline_payments.json` and survives client restarts.

6.2 Automatic resending

A background thread checks the channel's connectivity every 10 seconds (without sending fake requests) and, once the gateway is reachable and the user is logged in, resends queued payments. A payment leaves the queue once the gateway gives any final answer: completed, aborted for insufficient funds, or rejected as invalid. Because the transaction id is unchanged, a payment that had reached the gateway before the connection dropped is not applied a second time.

6.3 Failure handling

Failure	Behaviour
Gateway down	Client queues the payment; it is sent once the gateway returns.
Response lost after the gateway processed it	Resend returns the stored outcome; no second charge.
Bank down during prepare	Payment aborts; the other bank's reservation is released; the unreachable bank's abort is delivered when it returns.
Bank down during commit	Payment stays COMMITTING; recovery commits when the bank returns (its yes vote is on disk).
Gateway crash after the decision	On restart, recovery delivers the logged decision.
Gateway crash before the decision	After the prepare timeout, presumed abort releases the reservations.
Delayed prepare after an abort	Refused because of the abort tombstone.

7 Logging & Monitoring

- `LoggingInterceptor` records every RPC with its method, final status code, latency and peer address.

- `AuthorizationInterceptor` and `PeerIdentityInterceptor` log each rejected call and its reason.
- The coordinator logs each payment's progress (prepare votes, decision, phase-2 retries, recoveries). Banks log every vote, commit and abort.
- The authoritative history is the coordinator log in `gateway.db`, which `ViewTransactionHistory` and `GetPaymentStatus` query. Users see the sender's account number only on their own outgoing payments.

8 Evaluation

8.1 Automated tests

33 pytest tests start a gateway and three banks in-process on free ports:

- **Payments (7):** cross-bank transfer; insufficient funds; server-side rejection of zero, negative and oversized amounts; specific error codes; idempotent retries; a double-spend attempt with 40 concurrent Rs. 100 payments against a Rs. 1,500 balance (exactly 15 succeed); 120 random concurrent transfers that must conserve money.
- **Security (7):** missing, forged, expired and revoked tokens; revocation surviving a restart; login lock-out; access to another user's account; bank impersonation; non-gateway callers at a bank.
- **Recovery (7):** receiver commit failure; bank down during prepare; gateway crash after the decision; gateway crash before the decision; bank crash after voting yes; late prepare after abort; malformed operation.
- **Client (12):** exact rupee parsing, and an offline payment sent exactly once after the gateway returns.

8.2 Chaos experiment

`scripts/chaos_demo.py` runs the gateway and the three banks as separate operating-system processes. Eight client threads send random payments while, every 1–3 seconds, a random component is hard-killed (`SIGKILL`/`TerminateProcess`, so no clean-up code runs) and restarted. After the load stops and recovery settles, an audit compares the coordinator log with every bank ledger. Result of a 40-second run:

Measure	Value
Components killed (gateway / HDFC / ICICI / SBI)	15 (4 / 5 / 2 / 4)
Payments logged	2,747
committed / aborted	2,264 / 483
Client calls that failed with `UNAVAILABLE`	32
In-doubt payments settled by the recovery worker	158 (117 committed, 41 aborted)
of which presumed aborted after a gateway crash	10
Payments left in doubt, or reservations left held	0
Payments where the two banks disagree	0
Money before / after	Rs. 23,000.00 / Rs. 23,000.00

The aborts combine insufficient-funds outcomes (the workload draws random amounts against small balances) with payments that a kill interrupted before a commit decision.

8.3 Throughput and latency

`scripts/benchmark.py` runs the same multi-process deployment (mTLS on every hop) and measures completed payments per second at several client concurrencies (8 seconds per level, Windows laptop). Each payment performs four gateway-to-bank calls and seven durable writes: three at the gateway and two at each bank.




Figure 3: Throughput with SQLite `synchronous=FULL` (fsync on every commit, the default) and `NORMAL`.

	`FULL` (default)		`NORMAL`	
Clients	TPS	p50 / p99 (ms)	TPS	p50 / p99 (ms)
1	57	16 / 29	118	8 / 21
4	77	42 / 328	187	20 / 40
16	49	319 / 489	208	72 / 134
32	67	391 / 713	226	134 / 221

Discussion. With full durability, throughput is limited by disk flushes, not by gRPC or TLS. Every commit waits for an fsync, and each process issues its writes one at a time, so adding clients mostly adds queueing delay. Relaxing to `NORMAL`, which in WAL mode still survives process crashes but may lose the last commits on an operating-system crash or power loss, gives 2–4× the throughput and much lower tail latency. The usual way to keep full durability at higher throughput is *group commit*: one fsync shared by the writes of many concurrent payments.

9 Assumptions

1. Users are predefined in `users.json` (with hashed passwords); there is no self-registration. New users are added with `scripts/hash_password.py`.
2. A user has at most one account per bank, so a bank name identifies the account unambiguously.
3. Every component has a certificate issued by the deployment's CA before it starts.
4. Banks and clients know the gateway's address (`PG_GATEWAY_ADDRESS`); banks tell the gateway their own address when they register.

5. Crashed processes eventually restart with their disks intact.

10 Deployment

`docker compose up` generates certificates into a shared volume and starts the gateway and the three banks, each with its own data volume; the client runs with `docker compose run client`. GitHub Actions runs the test suite, the chaos experiment, a check that the generated protobuf code is up to date, and a Docker Compose smoke test.

11 Limitations & Future Enhancements

- **Coordinator availability.** The gateway is a single coordinator, and 2PC blocks while it is down. Replicating the coordinator log with a consensus protocol (Raft or Paxos), as Spanner does, would let another replica finish in-doubt payments.
- **Storage.** SQLite with one connection per process serialises writes. PostgreSQL with group commit would raise throughput while keeping full durability.
- **Latency.** The two prepares run one after the other; running them in parallel would remove one round trip from every payment.
- **Identity.** Users come from a JSON file, and tokens are signed with one shared HS256 key. A production system would use a user database and asymmetric signing keys (RS256 or EdDSA) with rotation.
- **Operations.** Metrics such as Prometheus counters for payment outcomes and recovery backlog, and an admin view of in-doubt payments.