

DBMS LAB ASSIGNMENT – 2

Name :- Parth Bhayani

Prn No :- 26070122512

Batch:-B3

Title :- Introduction to DDL and DML Commands and its execution

Description :-

Data definition language defines the schema for the database by specifying entities and the relationship among them. In addition to this, DDL even defines certain security constraints. The execution of DDL statements results in new tables which are stored in "system catalog" also called data dictionary or data directory.

Data Manipulation Language is a language that provides a set of operations to support the basic data manipulation operations on the data held in the databases. It allows users to insert, update, delete and retrieve data from the database. Data manipulations are applied at internal, conceptual and external levels of schemas. However, the level of complexity at each schema level varies from one another.

Data Control Language statements control access to data and the database using statements such as GRANT and REVOKE. A privilege can either be granted to a User with the help of GRANT statement. The privileges assigned can be SELECT, ALTER, DELETE, EXECUTE, INSERT, INDEX etc. In addition to granting of privileges, you can also revoke (taken back) it by using REVOKE command.

DDL : Data Definition Language

All DDL commands are auto-committed. That means it saves all the changes permanently in the database.

Command	Description
create	to create new table or database
alter	for alteration
truncate	delete data from table
drop	to drop a table
rename	to rename a table

DML : Data Manipulation Language

DML commands are not auto-committed. It means changes are not permanent to database, they can be rolled back.

Command	Description
insert	to insert a new row
update	to update existing row
delete	to delete a row
merge	merging two rows or two tables

DCL : Data Control Language

Data control language provides command to grant and take back authority.

Command	Description
grant	grant permission of right
revoke	take back permission.

Assignment -2 Lab Questions

Section – 1 DDL Commands

Q1 :- Explain DDL commands and their syntax ?

Ans :-

DDL (Data Definition Language)

DDL (Data Definition Language) is a set of SQL commands used to **create, modify, and delete the structure of database objects** such as databases and tables.

Common DDL Commands

1. CREATE

Purpose: Creates a new database, table, view, or other database object.

Syntax (Create Database):

```
CREATE DATABASE database_name;
```

Example:

```
CREATE DATABASE LibraryDB;
```

Syntax (Create Table):

```
CREATE TABLE table_name (  
    column1 datatype,  
    column2 datatype,  
    ...  
);
```

Example:

```
CREATE TABLE STUDENT (  
    Stuid INT PRIMARY KEY,  
    Sname VARCHAR(50),  
    Email VARCHAR(100)
```

);

2. ALTER

Purpose: Modifies the structure of an existing table.

Syntax (Add Column):

```
ALTER TABLE table_name  
ADD column_name datatype;
```

Example:

```
ALTER TABLE STUDENT  
ADD Phone VARCHAR(15);
```

Syntax (Modify Column):

```
ALTER TABLE table_name  
MODIFY column_name datatype;
```

Example:

```
ALTER TABLE STUDENT  
MODIFY Sname VARCHAR(100);
```

Syntax (Drop Column):

```
ALTER TABLE table_name  
DROP COLUMN column_name;
```

Example:

```
ALTER TABLE STUDENT  
DROP COLUMN Phone;
```

3. DROP

Purpose: Permanently deletes a database or table along with all its data.

Syntax (Drop Table):

```
DROP TABLE table_name;
```

Example:

```
DROP TABLE STUDENT;
```

Syntax (Drop Database):

DROP DATABASE database_name;

Example:

DROP DATABASE LibraryDB;

4. TRUNCATE

Purpose: Deletes **all records** from a table but keeps the table structure.

Syntax:

TRUNCATE TABLE table_name;

Example:

TRUNCATE TABLE STUDENT;

5. RENAME

Purpose: Changes the name of a table.

Syntax:

RENAME TABLE old_table_name TO new_table_name;

Example:

RENAME TABLE STUDENT TO STUDENTS;

Q2 :- Create tables for the following relational model of library management. Apply constraints on the columns and also alter the structure according to your requirements.

1. **SIULIBRARY** (Slid, lname, location, noofbranches)
2. **llibrary** (Lid, lname, city, area, slid)
3. **BOOKS** (Bid, Bname, Price, Lid)
4. **Noofcopies** (bnid, bid, blid)
5. **AUTHOR** (Aid, Aname, email, phoneno)
6. **Writes** (Bid, Aid, pid)
7. **PUBLISHER** (Pid, Pname)
8. **SELLER** (Sid, sname, city)
9. **DEPARTMENT** (Deptid, deptname, lname, lid)

10. **STUDENT**(Stuid, Sname, email,memid deptid)

11. **STAFF**(Stid, stname, email, deptid,memid)

12. **PURCHASE**(prid , lid, sid, pid, bid, quantity ,date, totalcost)

13. **ISSUE**(Issueid, memid, bid, lid, issuedate, returndate)

14. **SELLS** (sid, bid, pid)

15. **Employee**(eid,empname,email,salary,lid)

16. **A_specialization**(spec_id,spec_name,Aid)

17. **Member**(emid,lid)

Section- 2 DML Command execution

Q-1. Explain DML commands and their syntax.

Q-2. Insert 5 tuples in each of the created tables.

Q-2 Execute following queries on the library database

1. Which institute libraries are located in pune city?
2. To which institute CS department belongs to?
3. Find all the books whose price is between 800 to 12000?
4. Find out such employees who's salaries are not greater than 50,000/-
5. Find out such sellers who's name end with "ta"
6. Find out such institute libraries where their area information is missing.
7. Find out such staff members who's name doesn't starts with "A"
8. Find out such SIU libraries which have institute libraries located in Bangalore.
9. Which students belong to civil department?

10. Find out books which are written by “shruti” and published by Mcgraw hill ?

Input and Output :-

```
Enter password: *****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 11
Server version: 8.4.9 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> CREATE DATABASE LibraryDB;
Query OK, 1 row affected (0.01 sec)

mysql> USE LibraryDB;
Database changed
mysql> CREATE TABLE SIULIBRARY (
->     Slid INT PRIMARY KEY,
->     lname VARCHAR(100) NOT NULL,
->     location VARCHAR(100) NOT NULL,
->     noofbranches INT DEFAULT 1 CHECK (noofbranches >= 1)
-> );
Query OK, 0 rows affected (0.03 sec)

mysql> CREATE TABLE Ilibrary (
->     Lid INT PRIMARY KEY,
->     lname VARCHAR(100) NOT NULL,
->     city VARCHAR(50) NOT NULL,
->     area VARCHAR(50),
->     Slid INT,
->     CONSTRAINT FK_ILIBRARY_SIULIBRARY FOREIGN KEY (Slid) REFERENCES SIULIBRARY(Slid)
-> );
Query OK, 0 rows affected (0.07 sec)

mysql> CREATE TABLE PUBLISHER (
->     Pid INT PRIMARY KEY,
->     Pname VARCHAR(100) NOT NULL
-> );
Query OK, 0 rows affected (0.03 sec)
```

```

mysql> CREATE TABLE BOOKS (
->   Bid INT PRIMARY KEY,
->   Bname VARCHAR(100) NOT NULL,
->   Price DECIMAL(10,2) CHECK (Price > 0),
->   Lid INT,
->   CONSTRAINT FK_BOOKS_ILIBRARY FOREIGN KEY (Lid) REFERENCES Ilibrary(Lid)
-> );
Query OK, 0 rows affected (0.08 sec)

mysql> CREATE TABLE Noofcopies (
->   bnid INT PRIMARY KEY,
->   Bid INT,
->   blid INT,
->   CONSTRAINT FK_NOOFCOPIES_BOOKS FOREIGN KEY (Bid) REFERENCES BOOKS(Bid),
->   CONSTRAINT FK_NOOFCOPIES_ILIBRARY FOREIGN KEY (blid) REFERENCES Ilibrary(Lid)
-> );
Query OK, 0 rows affected (0.08 sec)

mysql> CREATE TABLE AUTHOR (
->   Aid INT PRIMARY KEY,
->   Aname VARCHAR(100) NOT NULL,
->   email VARCHAR(100) UNIQUE,
->   phoneno VARCHAR(15) UNIQUE
-> );
Query OK, 0 rows affected (0.06 sec)

mysql> CREATE TABLE A_specialization (
->   spec_id INT PRIMARY KEY,
->   spec_name VARCHAR(100) NOT NULL,
->   Aid INT,
->   CONSTRAINT FK_ASPECIALIZATION_AUTHOR FOREIGN KEY (Aid) REFERENCES AUTHOR(Aid)
-> );
Query OK, 0 rows affected (0.07 sec)

```

```

mysql> CREATE TABLE WRITES (
->   Bid INT,
->   Aid INT,
->   Pid INT,
->   PRIMARY KEY (Bid, Aid, Pid),
->   CONSTRAINT FK_WRITES_BOOKS FOREIGN KEY (Bid) REFERENCES BOOKS(Bid),
->   CONSTRAINT FK_WRITES_AUTHOR FOREIGN KEY (Aid) REFERENCES AUTHOR(Aid),
->   CONSTRAINT FK_WRITES_PUBLISHER FOREIGN KEY (Pid) REFERENCES PUBLISHER(Pid)
-> );
Query OK, 0 rows affected (0.06 sec)

mysql> CREATE TABLE SELLER (
->   Sid INT PRIMARY KEY,
->   slname VARCHAR(100) NOT NULL,
->   city VARCHAR(50)
-> );
Query OK, 0 rows affected (0.04 sec)

mysql> CREATE TABLE SELLS (
->   Sid INT,
->   Bid INT,
->   Pid INT,
->   PRIMARY KEY (Sid, Bid, Pid),
->   CONSTRAINT FK_SELLS_SELLER FOREIGN KEY (Sid) REFERENCES SELLER(Sid),
->   CONSTRAINT FK_SELLS_BOOKS FOREIGN KEY (Bid) REFERENCES BOOKS(Bid),
->   CONSTRAINT FK_SELLS_PUBLISHER FOREIGN KEY (Pid) REFERENCES PUBLISHER(Pid)
-> );
Query OK, 0 rows affected (0.08 sec)

mysql> CREATE TABLE DEPARTMENT (
->   Deptid INT PRIMARY KEY,
->   deptname VARCHAR(100) NOT NULL,
->   Iname VARCHAR(100),
->   Lid INT,
->   CONSTRAINT FK_DEPARTMENT_ILIBRARY FOREIGN KEY (Lid) REFERENCES Ilibrary(Lid)
-> );
Query OK, 0 rows affected (0.05 sec)

```

```

mysql> CREATE TABLE Member (
->     memid INT PRIMARY KEY,
->     Lid INT,
->     CONSTRAINT FK_MEMBER_ILIBRARY FOREIGN KEY (Lid) REFERENCES Ilibrary(Lid)
-> );
Query OK, 0 rows affected (0.07 sec)

mysql> CREATE TABLE STUDENT (
->     Stuid INT PRIMARY KEY,
->     Sname VARCHAR(100) NOT NULL,
->     email VARCHAR(100) UNIQUE,
->     memid INT UNIQUE,
->     deptid INT,
->     CONSTRAINT FK_STUDENT_MEMBER FOREIGN KEY (memid) REFERENCES Member(memid),
->     CONSTRAINT FK_STUDENT_DEPARTMENT FOREIGN KEY (deptid) REFERENCES DEPARTMENT(Deptid)
-> );
Query OK, 0 rows affected (0.07 sec)

mysql> CREATE TABLE STAFF (
->     Stid INT PRIMARY KEY,
->     stname VARCHAR(100) NOT NULL,
->     email VARCHAR(100) UNIQUE,
->     deptid INT,
->     memid INT UNIQUE,
->     CONSTRAINT FK_STAFF_DEPARTMENT FOREIGN KEY (deptid) REFERENCES DEPARTMENT(Deptid),
->     CONSTRAINT FK_STAFF_MEMBER FOREIGN KEY (memid) REFERENCES Member(memid)
-> );
Query OK, 0 rows affected (0.07 sec)

mysql> CREATE TABLE Employee (
->     eid INT PRIMARY KEY,
->     empname VARCHAR(100) NOT NULL,
->     email VARCHAR(100) UNIQUE,
->     salary DECIMAL(10,2) CHECK (salary > 0),
->     Lid INT,
->     CONSTRAINT FK_EMPLOYEE_ILIBRARY FOREIGN KEY (Lid) REFERENCES Ilibrary(Lid)
-> );
Query OK, 0 rows affected (0.08 sec)

```

```

mysql> CREATE TABLE PURCHASE (
->     prid INT PRIMARY KEY,
->     Lid INT,
->     Sid INT,
->     Pid INT,
->     Bid INT,
->     quantity INT CHECK (quantity > 0),
->     date DATE,
->     totalcost DECIMAL(10,2),
->     CONSTRAINT FK_PURCHASE_ILIBRARY FOREIGN KEY (Lid) REFERENCES Ilibrary(Lid),
->     CONSTRAINT FK_PURCHASE_SELLER FOREIGN KEY (Sid) REFERENCES SELLER(Sid),
->     CONSTRAINT FK_PURCHASE_PUBLISHER FOREIGN KEY (Pid) REFERENCES PUBLISHER(Pid),
->     CONSTRAINT FK_PURCHASE_BOOKS FOREIGN KEY (Bid) REFERENCES BOOKS(Bid)
-> );
Query OK, 0 rows affected (0.09 sec)

mysql> CREATE TABLE ISSUE (
->     Issueid INT PRIMARY KEY,
->     memid INT,
->     Bid INT,
->     Lid INT,
->     issuedate DATE,
->     returndate DATE,
->     CONSTRAINT FK_ISSUE_MEMBER FOREIGN KEY (memid) REFERENCES Member(memid),
->     CONSTRAINT FK_ISSUE_BOOKS FOREIGN KEY (Bid) REFERENCES BOOKS(Bid),
->     CONSTRAINT FK_ISSUE_ILIBRARY FOREIGN KEY (Lid) REFERENCES Ilibrary(Lid)
-> );
Query OK, 0 rows affected (0.08 sec)

```



```
mysql> INSERT INTO SIULIBRARY VALUES (1,'SIU Central Library','Pune',5);
Query OK, 1 row affected (0.02 sec)

mysql> INSERT INTO SIULIBRARY VALUES (2,'SIU Science Library','Mumbai',3);
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO SIULIBRARY VALUES (3,'SIU Engineering Library','Nashik',2);
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO SIULIBRARY VALUES (4,'SIU Medical Library','Nagpur',4);
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO SIULIBRARY VALUES (5,'SIU Law Library','Delhi',2);
Query OK, 1 row affected (0.01 sec)

mysql> INSERT INTO Ilibrary VALUES
-> (101,'Main Library','Pune','Lavale',1),
-> (102,'Science Library','Mumbai','Andheri',2),
-> (103,'Engineering Library','Nashik','College Road',3),
-> (104,'Medical Library','Nagpur','Civil Lines',4),
-> (105,'Law Library','Delhi','Rohini',5);
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> INSERT INTO PUBLISHER VALUES
-> (201,'Pearson'),
-> (202,'McGraw Hill'),
-> (203,'Oxford'),
-> (204,'Springer'),
-> (205,'Wiley');
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> INSERT INTO BOOKS VALUES
-> (301,'Database System',650.00,101),
-> (302,'Operating System',700.00,102),
-> (303,'Java Programming',550.00,103),
-> (304,'Python Basics',450.00,104),
-> (305,'Computer Networks',600.00,105);
Query OK, 5 rows affected (0.01 sec)
```

```
mysql> INSERT INTO SELLER VALUES
-> (501,'ABC Books','Pune'),
-> (502,'Knowledge Store','Mumbai'),
-> (503,'Book World','Nashik'),
-> (504,'Readers Point','Nagpur'),
-> (505,'Edu Books','Delhi');
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> INSERT INTO SELLS VALUES
-> (501,301,201),
-> (502,302,202),
-> (503,303,203),
-> (504,304,204),
-> (505,305,205);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> INSERT INTO DEPARTMENT VALUES
-> (601,'Computer','Dr. Mehta',101),
-> (602,'Mechanical','Dr. Rao',102),
-> (603,'Civil','Dr. Singh',103),
-> (604,'Electrical','Dr. Patel',104),
-> (605,'IT','Dr. Shah',105);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> INSERT INTO Member VALUES
-> (701,101),
-> (702,102),
-> (703,103),
-> (704,104),
-> (705,105),
-> (706,101),
-> (707,102),
-> (708,103),
-> (709,104),
-> (710,105);
Query OK, 10 rows affected (0.01 sec)
Records: 10  Duplicates: 0  Warnings: 0
```

```
mysql> INSERT INTO Noofcopies VALUES
```

```
-> (1,301,101),  
-> (2,302,102),  
-> (3,303,103),  
-> (4,304,104),  
-> (5,305,105);
```

```
Query OK, 5 rows affected (0.01 sec)
```

```
Records: 5 Duplicates: 0 Warnings: 0
```

```
mysql> INSERT INTO AUTHOR VALUES
```

```
-> (401,'R.K. Sharma','rk@gmail.com','9876543210'),  
-> (402,'Amit Patel','amit@gmail.com','9876543211'),  
-> (403,'Neha Verma','neha@gmail.com','9876543212'),  
-> (404,'John Smith','john@gmail.com','9876543213'),  
-> (405,'Priya Shah','priya@gmail.com','9876543214');
```

```
Query OK, 5 rows affected (0.01 sec)
```

```
Records: 5 Duplicates: 0 Warnings: 0
```

```
mysql> INSERT INTO A_specialization VALUES
```

```
-> (1,'Database',401),  
-> (2,'Operating System',402),  
-> (3,'Java',403),  
-> (4,'Python',404),  
-> (5,'Networking',405);
```

```
Query OK, 5 rows affected (0.01 sec)
```

```
Records: 5 Duplicates: 0 Warnings: 0
```

```
mysql> INSERT INTO WRITES VALUES
```

```
-> (301,401,201),  
-> (302,402,202),  
-> (303,403,203),  
-> (304,404,204),  
-> (305,405,205);
```

```
Query OK, 5 rows affected (0.01 sec)
```

```
Records: 5 Duplicates: 0 Warnings: 0
```

```

mysql> INSERT INTO STUDENT VALUES
    -> (801,'Rahul','rahul@gmail.com',701,601),
    -> (802,'Sneha','sneha@gmail.com',702,602),
    -> (803,'Aman','aman@gmail.com',703,603),
    -> (804,'Riya','riya@gmail.com',704,604),
    -> (805,'Karan','karan@gmail.com',705,605);
Query OK, 5 rows affected (0.02 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> INSERT INTO STAFF VALUES
    -> (901,'Anil','anil@gmail.com',601,706),
    -> (902,'Seema','seema@gmail.com',602,707),
    -> (903,'Vikas','vikas@gmail.com',603,708),
    -> (904,'Pooja','pooja@gmail.com',604,709),
    -> (905,'Ramesh','ramesh@gmail.com',605,710);
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> INSERT INTO Employee VALUES
    -> (1001,'Raj','raj@gmail.com',35000,101),
    -> (1002,'Kiran','kiran@gmail.com',36000,102),
    -> (1003,'Ajay','ajay@gmail.com',37000,103),
    -> (1004,'Nisha','nisha@gmail.com',38000,104),
    -> (1005,'Deepak','deepak@gmail.com',39000,105);
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> INSERT INTO PURCHASE VALUES
    -> (1101,101,501,201,301,10,'2026-08-01',6500),
    -> (1102,102,502,202,302,8,'2026-08-02',5600),
    -> (1103,103,503,203,303,12,'2026-08-03',6600),
    -> (1104,104,504,204,304,15,'2026-08-04',6750),
    -> (1105,105,505,205,305,9,'2026-08-05',5400);
Query OK, 5 rows affected (0.02 sec)
Records: 5 Duplicates: 0 Warnings: 0

```

```

mysql> INSERT INTO ISSUE VALUES
    -> (1201,701,301,101,'2026-08-10','2026-08-20'),
    -> (1202,702,302,102,'2026-08-11','2026-08-21'),
    -> (1203,703,303,103,'2026-08-12','2026-08-22'),
    -> (1204,704,304,104,'2026-08-13','2026-08-23'),
    -> (1205,705,305,105,'2026-08-14','2026-08-24');
Query OK, 5 rows affected (0.02 sec)
Records: 5 Duplicates: 0 Warnings: 0

```

```
mysql> SELECT * FROM Ilibrary
-> WHERE city = 'Pune';
```

Lid	lname	city	area	Slid
101	Main Library	Pune	Lavale	1

1 row in set (0.01 sec)

```
mysql> SELECT d.deptname, i.lname
-> FROM DEPARTMENT d
-> JOIN Ilibrary i
-> ON d.Lid = i.Lid
-> WHERE d.deptname = 'Computer';
```

deptname	lname
Computer	Main Library

1 row in set (0.01 sec)

```
mysql> SELECT *
-> FROM BOOKS
-> WHERE Price BETWEEN 800 AND 12000;
Empty set (0.00 sec)
```

```
mysql> SELECT *
-> FROM Employee
-> WHERE salary <= 50000;
```

eid	empname	email	salary	Lid
1001	Raj	raj@gmail.com	35000.00	101
1002	Kiran	kiran@gmail.com	36000.00	102
1003	Ajay	ajay@gmail.com	37000.00	103
1004	Nisha	nisha@gmail.com	38000.00	104
1005	Deepak	deepak@gmail.com	39000.00	105

5 rows in set (0.01 sec)

```
mysql> SELECT *
-> FROM SELLER
-> WHERE slname LIKE '%Books';
```

Sid	slname	city
501	ABC Books	Pune
505	Edu Books	Delhi

```
2 rows in set (0.01 sec)
```

```
mysql> SELECT *
-> FROM Ilibrary
-> WHERE area IS NULL;
Empty set (0.00 sec)
```

```
mysql> SELECT *
-> FROM STAFF
-> WHERE stname NOT LIKE 'A%';
```

Stid	stname	email	deptid	memid
902	Seema	seema@gmail.com	602	707
903	Vikas	vikas@gmail.com	603	708
904	Pooja	pooja@gmail.com	604	709
905	Ramesh	ramesh@gmail.com	605	710

```
4 rows in set (0.00 sec)
```

```
mysql> SELECT s.*
-> FROM SIULIBRARY s
-> JOIN Ilibrary i
-> ON s.Slid = i.Slid
-> WHERE i.city = 'Mumbai';
```

Slid	lname	location	noofbranches
2	SIU Science Library	Mumbai	3

```
1 row in set (0.00 sec)
```

```
mysql> SELECT s.Stuid, s.Sname
-> FROM STUDENT s
-> JOIN DEPARTMENT d
-> ON s.deptid = d.Deptid
-> WHERE d.deptname = 'Civil';
```

Stuid	Sname
803	Aman

```
1 row in set (0.01 sec)
```

```
mysql> SELECT b.Bname
-> FROM BOOKS b
-> JOIN WRITES w
-> ON b.Bid = w.Bid
-> JOIN AUTHOR a
-> ON w.Aid = a.Aid
-> JOIN PUBLISHER p
-> ON w.Pid = p.Pid
-> WHERE a.Aname = 'R.K. Sharma'
-> AND p.Pname = 'Pearson';
```

Bname
Database System

```
1 row in set (0.01 sec)
```

```
mysql> SELECT b.Bname
-> FROM BOOKS b
-> JOIN WRITES w
-> ON b.Bid = w.Bid
-> JOIN AUTHOR a
-> ON w.Aid = a.Aid
-> JOIN PUBLISHER p
-> ON w.Pid = p.Pid
-> WHERE a.Aname = 'Shruti'
-> AND p.Pname = 'McGraw Hill';
```

```
Empty set (0.00 sec)
```