DBMS LAB 5

Parth Janardan Naukudkar_ECS_II_66_D6

Aim: To Implement Data Insertion, View Creation, and Multi-Table Join Operations in SQL.

Q1. Insert new player Michale Clark with player ID 300311 in the table player

INSERT INTO Player (PlayerID, FName, LName) VALUES (300311, 'Michael', 'Clark');
Select * from player where PlayerID = 300311;

```
Records: 7  Duplicates: 0  Warnings: 0
MySQL localhost:3306 ssl parthnaukudkar_match SQL > INSERT INTO Player (PlayerID, FName, LName) VALUES (300311, 'Mic
hael', 'Clark');
Query OK, 1 row affected (0.0499 sec)

MySQL localhost:3306 ssl parthnaukudkar_match SQL > Select * from player where PlayerID = 300311
                                                 -> ;
+----------+-------+---------+---------+-------+--------+-------+
| PlayerID | LName | FName   | Country | Yborn | Bplace | FTest |
+----------+-------+---------+---------+-------+--------+-------+
|   300311 | Clark | Michael | NULL    |  NULL | NULL   |  NULL |
+----------+-------+---------+---------+-------+--------+-------+
1 row in set (0.0463 sec)
```

Q2. Insert new player Sam from India , Ahemdabad with player ID 406317 in the table player.

INSERT INTO Player (PlayerID, FName, Country, Bplace) VALUES (406317, 'Sam', 'India', 'Ahmedabad');
SELECT * FROM Player WHERE PlayerID=406317;

```
MySQL localhost:3306 ssl parthnaukudkar_match SQL > INSERT INTO Player (PlayerID, FName, Country, Bplace) VALUES (40
6317, 'Sam', 'India', 'Ahmedabad');SELECT * FROM Player WHERE PlayerID=406317;
Query OK, 1 row affected (0.0482 sec)
+----------+-------+-------+---------+-------+-----------+-------+
| PlayerID | LName | FName | Country | Yborn | Bplace    | FTest |
+----------+-------+-------+---------+-------+-----------+-------+
|   406317 | NULL  | Sam   | India   |  NULL | Ahmedabad |  NULL |
+----------+-------+-------+---------+-------+-----------+-------+
1 row in set (0.0007 sec)
```

Q3. Creating View for Batsman.

```
CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)
 AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns
 FROM Player,Batting
 WHERE PlayerID=PID;
```

DBMS LAB 5

Parth Janardan Naukudkar_ECS_II_66_D6

select * from Batsman;

```
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)
                                                    ->  AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns
                                                    ->  FROM Player,Batting
                                                    ->  WHERE PlayerID=PID;
Query OK, 0 rows affected (0.0555 sec)
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > select * from Batsman;
+-------+-----------+-------------+-----------+------+-------+
| PID   | FName     | LName       | Country   | MID  | Score |
+-------+-----------+-------------+-----------+------+-------+
| 23001 | Yuvraj    | Singh       | India     | 2755 |     0 |
| 25001 | MS        | Dhoni       | India     | 2755 |    71 |
| 91001 | Sanath    | Jayasuriya  | Sri Lanka | 2755 |    60 |
| 94002 | Chaminda  | Vaas        | Sri Lanka | 2755 |    17 |
| 92002 | Muthiah   | Murlitharan | Sri Lanka | 2755 |     1 |
| 89001 | Sachin    | Tendulkar   | India     | 2689 |    91 |
| 23001 | Yuvraj    | Singh       | India     | 2689 |    38 |
| 25001 | MS        | Dhoni       | India     | 2689 |    36 |
| 99002 | Adam      | Gilchrist   | Australia | 2689 |     2 |
| 95001 | Ricky     | Ponting     | Australia | 2689 |     1 |
| 24001 | Andrew    | Symonds     | Australia | 2689 |    42 |
| 99001 | Breet     | Lee         | Australia | 2689 |     7 |
| 27001 | Praveen   | Kumar       | India     | 2689 |     7 |
| 27001 | Praveen   | Kumar       | India     | 2755 |     2 |
| 98002 | Harbhajan | Singh       | India     | 2689 |     3 |
| 98002 | Harbhajan | Singh       | India     | 2755 |     2 |
+-------+-----------+-------------+-----------+------+-------+
16 rows in set (0.0036 sec)
```

Q4. Creating View for Bowling.

```
CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets)
 AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
 FROM Player,Bowling
 WHERE PlayerID=PID
 AND MatchID=2689;
```

select * from Bowling2689;

```
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets
)
                                                    ->  AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
                                                    ->  FROM Player,Bowling
                                                    ->  WHERE PlayerID=PID
                                                    ->  AND MatchID=2689;
Query OK, 0 rows affected (0.0496 sec)
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL >
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > select * from Bowling2689;
+-------+-----------+---------+-----------+--------+----------+
| PID   | FName     | LName   | Country   | NOvers | NWickets |
+-------+-----------+---------+-----------+--------+----------+
| 99001 | Breet     | Lee     | Australia |     10 |        1 |
| 24001 | Andrew    | Symonds | Australia |      3 |        1 |
| 23001 | Yuvraj    | Singh   | India     |      3 |        0 |
| 98002 | Harbhajan | Singh   | India     |     10 |        1 |
+-------+-----------+---------+-----------+--------+----------+
4 rows in set (0.0015 sec)
```

Q5. Find name of all players who have scored 60 or more runs.

```
CREATE VIEW Bowling2689 (PID, FName, LName, Country, NOvers, NWickets)
AS SELECT PlayerID, FName, LName, Country, NOvers, NWickets
FROM Player, Bowling
WHERE PlayerID=PID
```

AND MatchID=2689;

Select * from Bowling2689;

```
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > CREATE VIEW Bowling2689 (PID, FName, LName, Country, NOvers, NWi
ckets)
                                                    -> AS SELECT PlayerID, FName, LName, Country, NOvers, NWickets
                                                    -> FROM Player, Bowling
                                                    -> WHERE PlayerID=PID
                                                    -> AND MatchID=2689;
```

```
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > Select * from Bowling2689;
+-------+-----------+---------+-----------+--------+----------+
| PID   | FName     | LName   | Country   | NOvers | NWickets |
+-------+-----------+---------+-----------+--------+----------+
| 99001 | Breet     | Lee     | Australia |     10 |        1 |
| 24001 | Andrew    | Symonds | Australia |      3 |        1 |
| 23001 | Yuvraj    | Singh   | India     |      3 |        0 |
| 98002 | Harbhajan | Singh   | India     |     10 |        1 |
+-------+-----------+---------+-----------+--------+----------+
4 rows in set (0.0010 sec)
```

Q6. Find the names of bowlers that have not taken any wickets in ODI match 2689.
SELECT FName, LName

FROM Player, Bowling

WHERE PlayerID = PID

AND MatchID = 2689

AND NWickets = 0;

```
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > SELECT FName, LName
                                                    -> FROM Player, Bowling
                                                    -> WHERE PlayerID = PID
                                                    -> AND MatchID = 2689
                                                    -> AND NWickets = 0;
+--------+-------+
| FName  | LName |
+--------+-------+
| Yuvraj | Singh |
+--------+-------+
1 row in set (0.0010 sec)
```

Q7. Define a view NPlayer for obtaining the names of the countries & number of players from each country.

CREATE VIEW NPlayer (Country, NoOfPlayers) AS SELECT Country, COUNT(*) FROM Player GROUP BY Country; SELECT * FROM NPlayer;

DBMS LAB 5

Parth Janardan Naukudkar_ECS_II_66_D6

```
MySQL  localhost:3306 ssl  parthnaukudkar_match  SQL > CREATE VIEW NPlayer (Country, NoOfPlayers)  AS SELECT Country, C
OUNT(*) FROM Player GROUP BY Country; SELECT * FROM NPlayer;
Query OK, 0 rows affected (0.0371 sec)
+--------------+-------------+
| Country      | NoOfPlayers |
+--------------+-------------+
| India        |          11 |
| Australia    |           5 |
| West Indies  |           1 |
| Sri Lanka    |           3 |
| Pakistan     |           2 |
| Zimbabwe     |           1 |
| South Africa |           4 |
| New Zealand  |           2 |
| England      |           1 |
| NULL         |           1 |
+--------------+-------------+
10 rows in set (0.0021 sec)
```