LAB EXP 8: LEADING AND TRAILING

EX. NO. 8 Parth Langalia RA201103301003

AIM: A program to implement Leading and Trailing

ALGORITHM:

- 1. For Leading, check for the first non-terminal.
- 2. If found, print it.
- 3. Look for next production for the same non-terminal.
- 4. If not found, recursively call the procedure for the single non-terminal present before the comma or End Of Production String.
- 5. Include it's results in the result of this non-terminal.
- 6. For trailing, we compute same as leading but we start from the end of the production to the beginning.
- 7. Stop

CODE:

```
}gram[50];
void get()
{ cout<<"\n-----\n";
      cout<<"\nEnter the no. of variables : "; cin>>vars;
      cout<<"\nEnter the variables : \n";</pre>
      for(i=0;i<vars;i++)
      { cin>>gram[i].lhs;
             var[i]=gram[i].lhs;
      }
      cout << "\nEnter the no. of terminals : ";
      cin>>terms;
      cout<<"\nEnter the terminals : ";</pre>
      for(j=0;j<terms;j++)
      cin>>term[i];
      cout<<"\n----- PRODUCTION DETAILS -----\n";
      for(i=0;i<vars;i++)
      { cout<<"\nEnter the no. of production of "<<gram[i].lhs<<":";
             cin>>gram[i].prodno; for(j=0;j<gram[i].prodno;j++)
             { cout<<gram[i].lhs<<"->";
                    cin>>gram[i].rhs[j];
              }
      } }
void leading()
for(i=0;i<vars
;i++)
      { for(j=0;j<gram[i].prodno;j++)
              { for(k=0;k< terms;k++)
                    { if(gram[i].rhs[j][0]==term[k])
                           lead[i][k]=1;
```

```
else
                               { if(gram[i].rhs[j][1]==term[k])
                                       lead[i][k]=1;
                               }
                       }
               }
        }
       for(rep=0;rep<vars;rep++)</pre>
       { for(i=0;i<vars;i++)
               \{ for(j=0;j < gram[i].prodno;j++) \}
                       { for(m=1;m<vars;m++)
                               \{ if(gram[i].rhs[j][0]==var[m]) \}
                                       { temp=m; goto
                                               out;
                                       }
                               }
                               out:
                               for(k=0;k<terms;k++)</pre>
                               { if(lead[temp][k]==1)
                                       lead[i][k]=1;
                               }
                       }
        }
}
void trailing()
{ for(i=0;i<vars;i++)
       { for(j=0;j < gram[i].prodno;j++)
               { count=0;
```

```
while(gram[i].rhs[j][count]!='\xspace')
                              count++;
                       for(k=0;k<terms;k++)
                       { if(gram[i].rhs[j][count-1]==term[k])
                              trail[i][k]=1;
                              else
                              { if(gram[i].rhs[j][count-2]==term[k])
                                      trail[i][k]=1;
                              }
                       }
               }
       for(rep=0;rep<vars;rep++)</pre>
       { for(i=0;i<vars;i++)
               { for(j=0;j<gram[i].prodno;j++)
                       { count=0;
                              while(gram[i].rhs[j][count]!='\xspace')
                                      count++;
                              for(m=1;m<vars;m++)
                              { if(gram[i].rhs[j][count-1]==var[m])
                                      temp=m;
                              }
                              for(k=0;k< terms;k++)
                              {
                                      if(trail[temp][k]==1)
                                              trail[i][k]=1;
                              }
                       }
               }
       } }
void display()
```

```
{ for(i=0;i<vars;i++)
       { cout<<"\nLEADING("<<gram[i].lhs<<") = ";
              for(j=0;j<terms;j++)
              {
                     if(lead[i][j]==1)
                             cout<<term[j]<<",";
              } }
       cout<<endl;
       for(i=0;i<vars;i++)
       { cout<<"\nTRAILING("<<gram[i].lhs<<") = ";
              for(j=0;j<terms;j++)
              {
                     if(trail[i][j]==1)
                             cout<<term[j]<<",";
               }
       } }
void main()
{
       clrscr();
       get();
       leading();
       trailing();
       display();
       getch();
}
```

OUTPUT:

```
----- LEADING AND TRAILING -----
Enter the no. of variables: 3
Enter the variables:
T
F
Enter the no. of terminals: 5
Enter the terminals : )
i
----- PRODUCTION DETAILS ------
Enter the no. of production of E:2
E->E+T
E->T
Enter the no. of production of T:2
T->T*F
T->F
Enter the no. of production of F:2
F\rightarrow (E)
F->i
LEADING(E) = (,*,+,i,
LEADING(T) = (,*,i,
LEADING(F) = (,i,
TRAILING(E) = ), *, +, i,
TRAILING(T) = ),*,i,
TRAILING(F) = ),i,
```

RESULT:

The program was successfully compiled and run.