

select_city_screen.dart

```
List<String> cities = ['Ahmedabad',  
  'Surat', 'Vadodara'];  
  
ListTile(  
  title: Text(city),  
  onTap: () {  
    Navigator.push(  
      context,  
      MaterialPageRoute(  
        builder: (context) => WeatherScreen(  
          cityName: city,  
        ),  
      ),  
    );  
  },  
);
```

We pass city name using constructor.

weather_screen.dart

```
class WeatherScreen extends StatelessWidget {  
  final String? cityName;  
  const WeatherScreen({Key? key, this.cityName})  
    : super(key: key);  
  
  @override  
  Widget build(BuildContext context) {  
    return Scaffold(  
      appBar: AppBar(title: Text('Weather')),  
      body: Center(  
        child: Text(  
          'Weather in $cityName',  
          style: TextStyle(fontSize: 24),  
        ),  
      ),  
    );  
  }  
}
```

We receive city name and display it.



Passing both values

```
Navigator.push(
  context,
  MaterialPageRoute(
    builder: (context) => WeatherScreen(
      cityName: city,
      temperature: temp,
    ),
  ),
);
```

WeatherScreen (updated)

```
final String? cityName;
final int? temperature;

const WeatherScreen({this.cityName, this.temperature, Key? key})
  : super(key: key);

...
Text('Weather in $cityName', style: TextStyle(fontSize: 24)),
SizedBox(height: 10),
Text('Temperature: $temperature°C',
  style: TextStyle(fontSize: 20, color: Colors.orange)),
...
```



```
class Product {
    final String name;
    final double price;
    Product({required this.name, required this.price});
}
```

Navigate with Product object

```
Navigator.push(
  context,
  MaterialPageRoute(
    builder: (context) =>
      ProductDetailScreen(
        product: product,
      ),
  ),
);
```

ProductDetailScreen

```
final Product? product;
const ProductDetailScreen({this.product,
  Key? key}) : super(key: key);

...
Text(product?.name ?? 'No Product',
  style: TextStyle(fontSize: 24)),
SizedBox(height: 10),
Text('₹ ${product?.price ?? 0}',
  style: TextStyle(fontSize: 20, color: Colors.green(70))),
...

```

WeatherScreen (No data)



If no city or temperature is passed, we show a default message instead of crashing.

of calling without data

```
.push(  
t,  
alPageRoute(  
der: (context) => WeatherScreen(), // no arguments
```

```
weather_screen.dart (safe handling)  
  
class WeatherScreen extends StatelessWidget {  
  final String? cityName;  
  final int? temperature;  
  
  const WeatherScreen({this.cityName, this.temperature, Key? key})  
    : super(key: key);  
  
  @override  
  Widget build(BuildContext context) {  
    final String name = (cityName == null || cityName!.isEmpty)  
      ? 'No city selected'  
      : 'Weather in $cityName';  
  
    final String tempText = (temperature == null)  
      ? ''  
      : 'Temperature: $temperature°C';  
    ...  
    return Scaffold(  
      appBar: AppBar(title: Text('Weather')),  
      body: Center(  
        child: Column(  
          mainAxisAlignment: MainAxisAlignment.center,  
          children: [  
            Icon(cityName == null || cityName!.isEmpty ? Icons.help_outline : Icons.cloud,  
              size: 60, color: Colors.grey),  
            SizedBox(height: 16),  
            Text(name, style: TextStyle(fontSize: 22)),  
            if (tempText.isNotEmpty) ...[  
              SizedBox(height: 10),  
              Text(tempText, style: TextStyle(fontSize: 18, color: Colors.orange)),  
            ],  
          ],  
        ),  
      ),  
    );  
  }  
}
```

