



```

1 class UserInfoScreen extends StatefulWidget {
2   @override
3   State<UserInfoScreen> createState() => _UserInfoScreenState();
4 }
5
6 class _UserInfoScreenState extends State<UserInfoScreen> {
7   final TextEditingController _nameController = TextEditingController();
8   final TextEditingController _emailController = TextEditingController();
9   String _name = '';
10  String _email = '';
11
12  void _showValues() {
13    setState(() {
14      _name = _nameController.text;
15      _email = _emailController.text;
16    });
17  }
18
19  @override
20  Widget build(BuildContext context) {
21    return Scaffold(
22      appBar: AppBar(title: Text('User Info')),
23      body: Padding(
24        padding: EdgeInsets.all(16),
25        child: Column(
26          children: [
27            TextField(
28              controller: _nameController,
29              decoration: InputDecoration(labelText: 'Username'),
30            ),
31            SizedBox(height: 12),
32          ],
33        ),
34      ),
35    );
36  }
37 }

```



```

1 class LoginFormScreen extends StatefulWidget {
2   @override
3   State<LoginFormScreen> createState() => _LoginFormScreenState();
4 }
5
6 class _LoginFormScreenState extends State<LoginFormScreen> {
7   final _phoneController = TextEditingController();
8   final _otpController = TextEditingController();
9   final _referralController = TextEditingController();
10  final FocusNode _phoneFocus = FocusNode();
11  final FocusNode _otpFocus = FocusNode();
12  final FocusNode _referralFocus = FocusNode();
13
14  @override
15  Widget build(BuildContext context) {
16    return Scaffold(
17      appBar: AppBar(title: Text('Login')),
18      body: Padding(
19        padding: EdgeInsets.all(16),
20        child: Column(
21          children: [
22            TextField(
23              controller: _phoneController,
24              focusNode: _phoneFocus,
25              textInputAction: TextInputAction.next,
26              keyboardType: TextInputType.phone,
27              decoration: InputDecoration(labelText: 'Phone Number'),
28              onSubmitted: (_) => FocusScope.of(context).requestFocus(_otpFocus),
29            ),
30            SizedBox(height: 12),
31          ],
32        ),
33      ),
34    );
35  }
36 }

```

Recent

- main.dart
- screen1_user_info.dart
- screen2_login_form.dart
- screen3_password_screen.dart
- screen4_search_screen.dart

Run: main.dart

I/flutter (19930):
D/EGL_emulation(19930):
sync_submit: 0xebb40000:
episode 0x0



```

1 class PasswordScreen extends StatefulWidget {
2   @override
3   State<PasswordScreen> createState() => _PasswordScreenState();
4 }
5 class _PasswordScreenState extends State<PasswordScreen> {
6   final _passController = TextEditingController();
7   final _confirmController = TextEditingController();
8
9   @override
10  Widget build(BuildContext context) {
11    return Scaffold(
12      appBar: AppBar(title: Text('Set Password')),
13      body: Padding(
14        padding: EdgeInsets.all(16),
15        child: Column(
16          children: [
17            TextField(
18              controller: _passController,
19              obscureText: true,
20              decoration: InputDecoration(labelText: 'Password'),
21            ),
22            SizedBox(height: 12),
23            TextField(
24              controller: _confirmController,
25              obscureText: true,
26              textInputAction: TextInputAction.done,
27              decoration: InputDecoration(labelText: 'Confirm Password'),
28              onSubmitted: (_) {
29                FocusScope.of(context).unfocus();
30                ScaffoldMessenger.of(context).showSnackBar(
31                  SnackBar(content: Text('Passwords entered!')),
32                );
33              },
34            ),
35          ],
36        ),
37      ),
38    );
39  }
40 }

```



```

1 class SearchScreen extends StatefulWidget {
2   @override
3   State<SearchScreen> createState() => _SearchScreenState();
4 }
5 class _SearchScreenState extends State<SearchScreen> {
6   final TextEditingController _searchController = TextEditingController();
7   final List<String> _allRestaurants = [
8     'Domino's',
9     'McDonald's',
10    'Pizzeria Hut',
11    'La Pino's Pizza',
12    'KFC',
13    'Chicago Pizza',
14    'Oven Story Pizza',
15  ];
16  List<String> _filteredList = [];
17
18  @override
19  void initState() {
20    super.initState();
21    _filteredList = _allRestaurants;
22    _searchController.addListener(_filterSearchResults);
23  }
24  void _filterSearchResults() {
25    String query = _searchController.text.toLowerCase();
26    setState(() {
27      _filteredList = _allRestaurants
28        .where((item) => item.toLowerCase().contains(query))
29        .toList();
30    });
31  }
32 }

```

```

1 @override
2 void dispose() {
3   _searchController.dispose();
4   _searchFocus.dispose();
5   super.dispose();
6 }
7
8 FocusNode _searchFocus = FocusNode();
9
10 TextField(
11   controller: _searchController,
12   focusNode: _searchFocus,
13   decoration: InputDecoration(
14     hintText: 'Search Restaurants...',
15     prefixIcon: Icon(Icons.search),
16     border: OutlineInputBorder(
17       borderRadius: BorderRadius.circular(8),
18     ),
19     contentPadding: EdgeInsets.symmetric(horizontal: 12, vertical: 8),
20   ),
21 )

```

- ✓ All TextEditingController
- ✓ and FocusNode instances
- ✓ are properly disposed
- ✓ to avoid memory leaks.

```

1 void main() {
2   runApp(const MyApp());
3 }
4
5 class MyApp extends StatelessWidget {
6   const MyApp({super.key});
7
8   @override
9   Widget build(BuildContext context) {
10    return MaterialApp(
11      debugShowCheckedModeBanner: false,
12      home: UserInfoScreen(),
13    );
14  }
15 }

```